Technical MCQ - Pseudo Codes Based on PYQ With Video Sol

🎯 Infosys Systems Engineer (SE) | 🗓️ 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

Total Questions: 30 | **Total Marks:** 30 | **Duration:** 30 Minutes

Section: Technical

Problem 1 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q1 | Source: Infosys PYQ | Level: Infosys SE Standard

```
1.    #include
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];

cout<< Test::getX();     }
```

A 0 0

B 5 5

C 0 5

D a) Run time error

✓ **Verified Answer:** ✅ **(C) 0 5** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 2 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q2 Source: Infosys PYQ Level: Infosys SE Standard

```
1.    #include
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main(){
Point t1;
return 0;
}
```

A Constructor called	B Compile time error
C Run time error	D Blank line

✓ **Verified Answer:** ✅ **(B) Compile time error** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 3 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q3 Source: Infosys PYQ Level: Infosys SE Standard

```
1.    #include
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }

}
```

A 7 6 3	B 7 5 4
C 6 7 8	D 6 5 4

✓ **Verified Answer:** ✅ **(A) 7 6 3** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 4 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q4 Source: Infosys PYQ Level: Infosys SE Standard

1. Where are placed the list of processes that are prepared to be executed and waiting?

A Job queue	B Ready queue
C Execution queue	D Process queue

✓ **Verified Answer:** ✅ **(B) Ready queue** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 5 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q5 Source: Infosys PYQ Level: Infosys SE Standard

1. Who among the following can block the running process?

A Fork	B Read
C Down	D All of these

✓ **Verified Answer:** ✅ **(D) All of these** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 6 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q6 Source: Infosys PYQ Level: Infosys SE Standard

1. Which of the following does not interrupt the running process?

A Timer interrupt	B Device
C Power failure	D Scheduler process

✓ **Verified Answer:** ✅ **(D) Scheduler process** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 7 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q7 Source: Infosys PYQ Level: Infosys SE Standard

1. The \u0021 article referred to as a

A Unicode escape sequence	B Octal escape
C Hexadecimal	D Line feed

✓ **Verified Answer:** ✅ **(A) Unicode escape sequence** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 8 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q8 Source: Infosys PYQ Level: Infosys SE Standard

1. Which of the following is a valid declaration of a char?

A char ch = '\utea';	B char ca = 'tea';
C char cr = \u0223;	D char cc = '\itea';

✓ **Verified Answer:** ✅ **(A) char ch = '\utea';** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 9 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q9 Source: Infosys PYQ Level: Infosys SE Standard

1. Which of the following is a valid long literal?

A ABH8097	B L990023
C 904423	D 0xnf029L

✓ **Verified Answer:** ✅ **(D) 0xnf029L** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 10 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q10 Source: Infosys PYQ Level: Infosys SE Standard

1. What does the expression float a = 35 / 0 return?

A 0	B Not a Number
C Infinity	D Run time exception

✓ **Verified Answer:** ✅ **(C) Infinity** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 11 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q11 Source: Infosys PYQ Level: Infosys SE Standard

1. Which option is false about the final keyword?
   a) A) A final method cannot be overridden in its subclasses.
   b) B) A final class cannot be extended.
   c) C) A final class cannot extend other classes.
   d) D) A final method can be inherited.

A A&B	B B&C
C C&D	D None of these

✓ **Verified Answer:** ✅ **(C) C&D** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 12 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q12 Source: Infosys PYQ Level: Infosys SE Standard

1. Construct post order Transversal for the constructed tree with the given In-Order and Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8

A 9 10 7 8 6	B 9 7 6 10 8
C 8 9 10 7 6	D 9 8 10 7 6

✓ **Verified Answer:** ✅ **(A) 9 10 7 8 6** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 13 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q13 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of this program fragment?

```
int i = 263;
putchar(i);
```

A prints 263	B prints the ASCII equivalent of 263
C rings the bell	D prints garbage

✓ **Verified Answer:** ✅ **(C) rings the bell** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 14 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q14 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of this statement?
printf (“%d”, 9/5);

A 1.8	B 1.0
C 2.0	D None of these

✓ **Verified Answer:** ✅ **(D) None of these** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 15 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q15 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of this program?

```
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

A 2	B 6
C 4	D 1

✓ **Verified Answer:** ✅ **(D) 1** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 16 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q16 Source: Infosys PYQ Level: Infosys SE Standard

1. Which of the following declarations is invalid in C language?

A char *str = “campus monk is the best platform for learn";	B char str[] = “campus monk is the best platform for learn";
C char str[20] = “campus monk is the best platform for learn";	D char[] str = “campus monk is the best platform for learn";

✓ **Verified Answer:** ✅ **(D) char[] str = “campus monk is the best platform for learn";** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 17 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q17 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of this program?

include

```
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
 enum flg h;
   h = b;
   printf("%d", h);
  return 0;
}
```

A 1

B error: redeclaration of an enumerator

C h

D 3

✓ **Verified Answer:** ✅ **(B) error: redeclaration of an enumerator** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 18 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q18 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of this program?

```
main ()
{
 if (5 < '5')
      printf("5")
 else
      printf(" NOT EQUAL TO 5.")

}
```

A ENQ

B 5

C I

D Not equal to 5

✓ **Verified Answer:** ✅ **(B) 5** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 19 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q19 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of the following pseudo code?

```
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

A 5	**B** 7
C 9	**D** 12

✓ **Verified Answer:** ✅ **(A) 5** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 20 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q20 Source: Infosys PYQ Level: Infosys SE Standard

1. What will be the output of the following pseudocode?

```
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

A 6 6 6	**B** 6 5 6
C 5 5 5	**D** 6 5 4

✓ **Verified Answer:** ✅ **(D) 6 5 4** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 21 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q21 Source: Infosys PYQ Level: Infosys SE Standard

1. If the sequence of operations are performed on a stack, the sequence of pop will be?

Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().

A 2 2 1 1 2	B 2 2 1 2 2
C 2 1 2 2 1	D 2 1 2 2 2

✓ **Verified Answer:** ✅ **(A) 2 2 1 1 2** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 22 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q22 Source: Infosys PYQ Level: Infosys SE Standard

1. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?

105 95 122 99 97 120

A 95	B 97
C 99	D 120

✓ **Verified Answer:** ✅ **(B) 97** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 23 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q23 Source: Infosys PYQ Level: Infosys SE Standard

T The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?

A a) Singly linked list	B a) Doubly linked list
C a) Circular doubly linked list	D a) Array implementation of list

✓ **Verified Answer:** ✅ **(C) a) Circular doubly linked list** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 24 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q24 Source: Infosys PYQ Level: Infosys SE Standard

1. Which of the following sequence can be obtained in the output (in same order) using a stack assuming that the input is in the sequence 1,2,3,4,5 order?

A a) 3,4,5,1,2

B a) 3,4,5,2,1

C a) 1,5,2,3,4

D a) 5,4,3,1,2

✓ **Verified Answer:** ✅ **(B) a) 3,4,5,2,1** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 25 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q25 Source: Infosys PYQ Level: Infosys SE Standard

1. Let A be a square matrix of size nxn. Consider the following program and state the output.

```
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do

Output (A[i][j]);
```

A a) The matrix A itself

B a) Transpose of matrix A

C a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A

D a) None of the above

✓ **Verified Answer:** ✅ **(A) a) The matrix A itself ** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 26 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q26 Source: Infosys PYQ Level: Infosys SE Standard

1. The value of j at the end of the execution of the following pseudo code is ?

```
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)

end for
```

A 10 B 4

C 6 D 7

✓ **Verified Answer:** ✅ **(A) 10** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 27 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q27 Source: Infosys PYQ Level: Infosys SE Standard

1. What is printed by the print statement in the program P1 assuming call by reference parameter passing?

```
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z

}
```

A 10, 3 B 31, 3

C 27, 7 D None of these

✓ **Verified Answer:** ✅ **(B) 31, 3** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 28 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q28 Source: Infosys PYQ Level: Infosys SE Standard

1. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);

}
```

A 5	**B** 6
C 7	**D** 8

✓ **Verified Answer:** ✅ **(C) 7** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 29 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q29 Source: Infosys PYQ Level: Infosys SE Standard

1. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if

Print n
```

A 7	**B** 18
C 22	**D** 2

✓ **Verified Answer:** ✅ **(D) 2** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.

Problem 30 • [Marks: +1, -0.25] ◯ PRACTICE VARIANT

ID: Q30 | Source: Infosys PYQ | Level: Infosys SE Standard

1. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if

Print x+y+z
```

A 31

B 11

C 42

D 30

✓ **Verified Answer:** ✅ **(D) 30** **Step-by-Step Explanation & Derivation:** Detailed step-by-step deduction provided in solutions compendium.