Infosys Full Length Mock Test- 5

🎯 Infosys Systems Engineer (SE) | 🗓️ 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

Total Questions: 60 | **Total Marks:** 76 | **Duration:** 7200000 Minutes

Section: Reasoning

Problem 1 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q1 | Source: Infosys PYQ | Level: Infosys SE Standard

A 3×3 figure series fills one extra cell each step (1 cell, 2 cells, 3 cells). How many filled cells are in step 6?

A 4	B 5
C 6	D 8

✓ **Verified Answer:** ✅ **(C) 6** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The count equals the step number. Step 6 has 6 filled cells.

Problem 2 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q2 | Source: Infosys PYQ | Level: Infosys SE Standard

In what ratio is profit shared by A and B?
S1: A invested ₹40,000 and B invested ₹60,000 for the same time. S2: The total profit is ₹20,000.

A S1 alone is sufficient, S2 is not	B S2 alone is sufficient, S1 is not
C Either alone	D Both needed

✓ **Verified Answer:** ✅ **(A) S1 alone is sufficient, S2 is not** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Same time, so the ratio is the capital ratio 2 : 3 from S1. The total amount in S2 is not required to find the ratio.

Problem 3 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q3 Source: Infosys PYQ Level: Infosys SE Standard

Statements: All kernels are programs. Some programs are drivers. No driver is a firmware blob. Conclusions: I. Some kernels are drivers. II. Some programs are not firmware blobs.

A Only I follows

B Only II follows

C Both follow

D Neither follows

✓ **Verified Answer:** ✅ **(B) Only II follows** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Kernels sit inside programs but need not meet drivers, so I does not follow. Some programs are drivers, and no driver is a firmware blob, so those programs are not firmware blobs. II follows.

Problem 4 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q4 Source: Infosys PYQ Level: Infosys SE Standard

Find the missing number.
8
4
2
27
9
3
64
16
?

A 4

B 6

C 8

D 2

✓ **Verified Answer:** ✅ **(A) 4** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Each row is a cube, a square, then the root: 2^3, 2^2, 2; 3^3, 3^2, 3; 4^3, 4^2, 4.

Problem 5 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q5 Source: Infosys PYQ Level: Infosys SE Standard

If A=1, B=2, ... and GAME is coded as 26, the same way TEAM is coded as

A 36

B 38

C 39

D 42

✓ **Verified Answer:** ✅ **(C) 39** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** GAME = 7+1+13+5 = 26. TEAM = 20+5+1+13 = 39.

Problem 6 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q6 Source: Infosys PYQ Level: Infosys SE Standard

Find the missing number.
2
7
14
3
8
24
4
9
?

A 32
B 34
C 36
D 40

Verified Answer: ✅ **(C) 36** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Third = first × second. 2×7=14, 3×8=24, 4×9=36.

Problem 7 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q7 Source: Infosys PYQ Level: Infosys SE Standard

Who is taller, X or Y? S1: X is taller than
Z. S2: Z is taller than Y.

A S1 alone
B S2 alone
C Either alone
D Both together are needed

Verified Answer: ✅ **(D) Both together are needed** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** S1 and S2 together give X > Z > Y, so X is taller. Neither statement alone compares X with Y.

Problem 8 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q8 Source: Infosys PYQ Level: Infosys SE Standard

Statements: Some queues are stacks. All
stacks are linear. No linear structure is a graph. Conclusions: I.
Some queues are linear. II. No stack is a graph.

A Only I
B Only II
C Both I and II
D Neither

Verified Answer: ✅ **(C) Both I and II** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Queues that are stacks are linear, so I follows. Every stack is linear and no linear structure is a graph, so no stack is a graph. Both follow.

Problem 9 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q9 Source: Infosys PYQ Level: Infosys SE Standard

If FILTER is coded as GJMUFS, how is BUFFER coded?

A CVGGFS	B ATGEDQ
C CVHGFS	D BWGGFS

✓ **Verified Answer:** ✅ **(A) CVGGFS** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Every letter moves one step forward. BUFFER → C V G G F S.

Problem 10 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q10 Source: Infosys PYQ Level: Infosys SE Standard

What is the average of x and y? S1: x + y = 40. S2: x − y = 8.

A S1 alone is sufficient, S2 is not	B S2 alone is sufficient, S1 is not
C Either alone is sufficient	D Both are needed

✓ **Verified Answer:** ✅ **(A) S1 alone is sufficient, S2 is not** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Average = (x+y)/2. S1 gives the sum, so the average is 20. S2 alone does not give the sum.

Problem 11 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q11 Source: Infosys PYQ Level: Infosys SE Standard

Statements: All sprints are iterations. All iterations are timeboxes. Some timeboxes are buffers. Conclusions: I. All sprints are timeboxes. II. Some buffers are sprints.

A Only I follows	B Only II follows
C Both follow	D Neither follows

✓ **Verified Answer:** ✅ **(A) Only I follows** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Sprints → iterations → timeboxes, so I follows. Buffers overlap timeboxes, not necessarily sprints. II does not follow.

Problem 12 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q12 Source: Infosys PYQ Level: Infosys SE Standard

If 2 * 3 = 10, 4 * 5 = 28 and 6 * 7 = 54,
then 8 * 9 = ?

A 80	B 84
C 88	D 90

✓ **Verified Answer:** ✅ **(C) 88** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** a * b maps to a×b + a + b? 6+3+1=10. Rule a×b + a − 2: 6+2=8 no. a×(b+2)−2: 2×5−0. 2×3+4=10, 4×5+8=28, 6×7+12=54, extras +4+8+12. Next +16: 8×9+16=88. Also a(b+1)+b−2. Use a×b + 2a: 6+4=10, 20+8=28, 42+12=54, 72+16=88. Yes 88.

Problem 13 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q13 Source: Infosys PYQ Level: Infosys SE Standard

Find the missing number.
3
5
16
4
7
25
5
9
?

A 34	B 36
C 40	D 45

✓ **Verified Answer:** ✅ **(B) 36** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Third = first² + second + 2. 9+5+2=16, 16+7+2=25, 25+9+2=36.

Problem 14 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q14 Source: Infosys PYQ Level: Infosys SE Standard

Statements: No cache is a disk. Some disks are tapes. All tapes are media. Conclusions: I. Some media are disks. II. Some caches are tapes.

A Only I follows	B Only II follows
C Both follow	D Neither follows

✓ **Verified Answer:** ✅ **(A) Only I follows** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Some disks are tapes and all tapes are media, so some media are disks. Caches are disjoint from disks and need not meet tapes. Only I.

Problem 15 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q15 Source: Infosys PYQ Level: Infosys SE Standard

Is integer n divisible by 6? S1: n is divisible by 2 and by 3. S2: n ends with the digit 4.

A S1 alone is sufficient, S2 is not	B S2 alone is sufficient, S1 is not
C Either alone	D Both needed

✓ **Verified Answer:** ✅ **(A) S1 alone is sufficient, S2 is not** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** A number divisible by 2 and 3 is divisible by 6. S1 is enough. Ending with 4 means even, but not necessarily a multiple of 3.

Problem 16 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q16 Source: Infosys PYQ Level: Infosys SE Standard

Two cards are drawn from 52 without replacement. Probability both are aces is

A 1/221	B 1/169
C 1/17	D 2/52

✓ **Verified Answer:** ✅ **(A) 1/221** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** C(4,2)/C(52,2) = 6/1326 = 1/221.

Problem 17 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q17 Source: Infosys PYQ Level: Infosys SE Standard

[P&C] The number of distinct arrangements of the letters in LEVEL is

A 30	B 60
C 120	D 24

✓ **Verified Answer:** ✅ **(A) 30** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** LEVEL has 5 letters, L twice and E twice. 5! / (2! × 2!) = 30.

Problem 18 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q18 Source: Infosys PYQ Level: Infosys SE Standard

A finishes in 20 days, B in 30 days. Working together they take

A 10 days	B 12 days
C 15 days	D 25 days

✓ **Verified Answer:** ✅ **(B) 12 days** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Combined rate = 1/20 + 1/30 = 1/12. Time = 12 days.

Problem 19 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q19 Source: Infosys PYQ Level: Infosys SE Standard

An item marked ₹2,500 is sold after 20% discount. If CP is ₹1,800, profit percent is

A 10%	B 11.11%
C 12%	D 20%

✓ **Verified Answer:** ✅ **(B) 11.11%** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** SP = 80% of 2500 = 2000. Profit = 200. % = 200/1800 × 100 = 11.11%.

Problem 20 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q20 Source: Infosys PYQ Level: Infosys SE Standard

A and B together take 8 days. A alone takes 12 days. B alone takes

A 18 days	B 20 days
C 24 days	D 30 days

✓ **Verified Answer:** ✅ **(C) 24 days** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** B = 1/8 − 1/12 = 1/24. B takes 24 days.

Problem 21 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q21 Source: Infosys PYQ Level: Infosys SE Standard

CP = ₹1,200 and profit = 15%. Selling price is

A ₹1,350	B ₹1,360
C ₹1,380	D ₹1,400

✓ **Verified Answer:** ✅ **(C) ₹1,380** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** SP = 115% of 1200 = ₹1,380.

Problem 22 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q22 Source: Infosys PYQ Level: Infosys SE Standard

A fair coin is tossed three times. Probability of exactly two heads is

A 1/8	B 3/8
C 1/2	D 3/4

✓ **Verified Answer:** ✅ **(B) 3/8** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** C(3,2)/8 = 3/8.

Problem 23 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q23 Source: Infosys PYQ Level: Infosys SE Standard

A bag has 3 white and 5 black balls. One ball is drawn. Probability it is black is

A 3/8	B 1/2
C 5/8	D 2/5

✓ **Verified Answer:** ✅ **(C) 5/8** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** 5 black out of 8 = 5/8.

Problem 24 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q24 Source: Infosys PYQ Level: Infosys SE Standard

How many ways can 5 distinct books be arranged on a shelf if two particular books must stay together?

A 48	B 60
C 120	D 240

✓ **Verified Answer:** ✅ **(A) 48** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Tie the two books as one bundle: 4 units can be arranged in 4! ways and the bundle in 2! ways. 24 × 2 = 48.

Problem 25 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q25 Source: Infosys PYQ Level: Infosys SE Standard

From 6 men and 4 women, a committee of 4 with exactly 2 women can be formed in how many ways?

A 60	B 90
C 120	D 180

✓ **Verified Answer:** ✅ **(B) 90** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** C(4,2) × C(6,2) = 6 × 15 = 90.

Problem 26 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q26 Source: Infosys PYQ Level: Infosys SE Standard

Arrange:
P: Two-minute demos expose that gap early. Q: Specs that never meet a user stay elegant and wrong. R: Put a real task in front of one stranger every Friday. S: Notes from that session beat another internal review.

A Q

B Q

C Q R S P

D P

✓ **Verified Answer:** ✅ **(C) Q R S P** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Q names the risk. R is the weekly test. S values the notes. P notes that short demos also expose the gap; the tightest story is Q R S P.

Problem 27 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q27 Source: Infosys PYQ Level: Infosys SE Standard

Choose
the correct sentence.

A Every

B Every one of the modules has a test.

C Every

D Every

✓ **Verified Answer:** ✅ **(B) Every one of the modules has a test.** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Every one is singular: has. Modules stays plural after of.

Problem 28 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q28 Source: Infosys PYQ Level: Infosys SE Standard

Choose
the correct sentence.

A Little of the traffic has cleared.

B Little

C Few

D Little

✓ **Verified Answer:** ✅ **(A) Little of the traffic has cleared.** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Traffic is uncountable; little + has.

Problem 29 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q29 Source: Infosys PYQ Level: Infosys SE Standard

Passage
A service-level objective is useful only when the team can see the error budget being spent. If latency is promised at 300 ms for 99% of calls, the remaining 1% is not a licence to ignore timeouts. Burn-rate alerts that fire after the month is already lost teach nobody. The better habit is a short window alert plus a long window alert, so a sharp incident and a slow leak are both visible. Documents that list SLOs without owners become wallpaper.
Burn-rate alerts that fire after the month is lost

A teach nobody
B are
C replace
D fix

✓ **Verified Answer:** ✅ **(A) teach nobody** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The third sentence.

Problem 30 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q30 Source: Infosys PYQ Level: Infosys SE Standard

Choose
the correct sentence.

A She
B She lay on the couch after the on-call.
C She
D She

✓ **Verified Answer:** ✅ **(B) She lay on the couch after the on-call.** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Past of intransitive lie (recline) is lay.

Problem 31 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q31 Source: Infosys PYQ Level: Infosys SE Standard

Arrange:
P: A runbook that names the first three commands beats a long essay. Q: Night pages fail when the only help is a slide deck. R: Keep the commands in the same repo as the service. S: Then the next intern can act without a meeting.

A Q
B P
C Q P R S
D Q

✓ **Verified Answer:** ✅ **(C) Q P R S** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Q is the failure. P is the better artefact. R says where it lives. S is the outcome. Q P R S.

Problem 32 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q32 Source: Infosys PYQ Level: Infosys SE Standard

Passage
A service-level objective is useful only when the team can see the error budget being spent. If latency is promised at 300 ms for 99% of calls, the remaining 1% is not a licence to ignore timeouts. Burn-rate alerts that fire after the month is already lost teach nobody. The better habit is a short window alert plus a long window alert, so a sharp incident and a slow leak are both visible. Documents that list SLOs without owners become wallpaper.
SLO documents without owners

A run
B cut
C replace alerts
D become wallpaper

✓ **Verified Answer:** ✅ **(D) become wallpaper** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Last sentence.

Problem 33 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q33 Source: Infosys PYQ Level: Infosys SE Standard

One-word:
Lasting only for a short time.

A Chronic
B Perennial
C Ephemeral
D Perpetual

✓ **Verified Answer:** ✅ **(C) Ephemeral** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Ephemeral means short-lived.

Problem 34 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q34 Source: Infosys PYQ Level: Infosys SE Standard

Arrange:
P: Cardinality explosions then make the bill jump overnight. Q:
High-cardinality labels on every request look harmless in staging.
R: Cap the label set and sample the rest. S: Staging traffic is
too tidy to show the cost.

A Q
B Q S P R
C P
D Q

✓ **Verified Answer:** ✅ **(B) Q S P R** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Q looks harmless. S explains why staging hides it. P is the production bill. R is the control. Q S P R.

Problem 35 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q35 Source: Infosys PYQ Level: Infosys SE Standard

Arrange:
P: Feature flags then let the fix ride with the next build. Q: Hotfix branches that live for weeks drift from main. R: A short-lived branch plus a flag is usually enough. S: Long-lived hotfix trains surprise the next release.

A Q S R P

B Q

C S

D Q

✓ **Verified Answer:** ✅ **(A) Q S R P** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Q is the problem. S is the cost. R is the small pattern. P is how flags help. Q S R P.

Problem 36 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q36 Source: Infosys PYQ Level: Infosys SE Standard

Passage
A service-level objective is useful only when the team can see the error budget being spent. If latency is promised at 300 ms for 99% of calls, the remaining 1% is not a licence to ignore timeouts. Burn-rate alerts that fire after the month is already lost teach nobody. The better habit is a short window alert plus a long window alert, so a sharp incident and a slow leak are both visible. Documents that list SLOs without owners become wallpaper.
Short-window plus long-window alerts help because

A they

B a sharp incident and a slow leak are both visible

C they

D they

✓ **Verified Answer:** ✅ **(B) a sharp incident and a slow leak are both visible** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The fourth sentence.

Problem 37 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q37 Source: Infosys PYQ Level: Infosys SE Standard

Passage
A service-level objective is useful only when the team can see the error budget being spent. If latency is promised at 300 ms for 99% of calls, the remaining 1% is not a licence to ignore timeouts. Burn-rate alerts that fire after the month is already lost teach nobody. The better habit is a short window alert plus a long window alert, so a sharp incident and a slow leak are both visible. Documents that list SLOs without owners become wallpaper.
The main idea of the passage is that

A a

B SLOs work only with visible budgets, dual-window alerts and owners

C monthly

D latency

✓ **Verified Answer:** ✅ **(B) SLOs work only with visible budgets, dual-window alerts and owners** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The passage ties SLOs to seeing the budget, using short and long alerts, and naming owners.

Problem 38 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q38 Source: Infosys PYQ Level: Infosys SE Standard

Fill:
The outage postmortem was _____ and named every missed alert.

A evasive

B candid

C obscure

D reluctant

✓ **Verified Answer:** ✅ **(B) candid** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Candid means frank and open.

Problem 39 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q39 Source: Infosys PYQ Level: Infosys SE Standard

Antonym
of “amplify”:

A Enlarge

B Boost

C Diminish

D Raise

✓ **Verified Answer:** ✅ **(C) Diminish** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Diminish is the opposite of amplify.

Problem 40 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q40 Source: Infosys PYQ Level: Infosys SE Standard

"Move
the needle" means

A Make a measurable difference	B Rotate
C Delete	D Pause

✓ **Verified Answer:** ✅ **(A) Make a measurable difference** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The idiom means to cause a noticeable change.

Problem 41 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q41 Source: Infosys PYQ Level: Infosys SE Standard

Choose
the correct sentence.

A No sooner had the job started than the queue grew.	B No
C No	D No

✓ **Verified Answer:** ✅ **(A) No sooner had the job started than the queue grew.** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** No sooner + inversion + than.

Problem 42 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q42 Source: Infosys PYQ Level: Infosys SE Standard

Choose
the correct sentence.

A The	B The
C The criteria are listed in the RFC.	D The

✓ **Verified Answer:** ✅ **(C) The criteria are listed in the RFC.** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Criteria is plural; the singular is criterion.

Problem 43 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q43 Source: Infosys PYQ Level: Infosys SE Standard

Synonym
of “succinct”:

A Wordy	B Brief
C Vague	D Loud

✓ **Verified Answer:** ✅ **(B) Brief** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Succinct means briefly and clearly expressed.

Problem 44 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q44 Source: Infosys PYQ Level: Infosys SE Standard

Passage
A service-level objective is useful only when the team can see the error budget being spent. If latency is promised at 300 ms for 99% of calls, the remaining 1% is not a licence to ignore timeouts. Burn-rate alerts that fire after the month is already lost teach nobody. The better habit is a short window alert plus a long window alert, so a sharp incident and a slow leak are both visible. Documents that list SLOs without owners become wallpaper.
The remaining 1% of calls

A may	B proves
C is not a licence to ignore timeouts	D should

✓ **Verified Answer:** ✅ **(C) is not a licence to ignore timeouts** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The second sentence says the 1% is not a licence to ignore timeouts.

Problem 45 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q45 Source: Infosys PYQ Level: Infosys SE Standard

Arrange:
P: Secrets in container images leak the moment the image is pulled. Q: Inject secrets at runtime from a manager, not from a Dockerfile. R: Image scans will not catch a token baked in last year. S: Rotate anything that has already shipped inside a layer.

A P R Q S	B P
C Q	D P

✓ **Verified Answer:** ✅ **(A) P R Q S** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** P is the leak path. R says scans miss old tokens. Q is the correct inject path. S is cleanup. P R Q S.

Problem 46 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q46 Source: Infosys PYQ Level: Infosys SE Standard

[Loops]
What is printed?
Integer
i, p
Set
p = 1
for
i = 1 to 4 do
p
= p * i
end
for
Print
p

A 10
B 16
C 24
D 120

✓ **Verified Answer:** ✅ **(C) 24** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** p multiplies 1×2×3×4 = 24.

Problem 47 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q47 Source: Infosys PYQ Level: Infosys SE Standard

[Data
Structures] Queue Q receives 5, then 15, then 25. One dequeue
runs. What is front(Q)?
Queue
Q
enqueue(Q,
5)
enqueue(Q,
15)
enqueue(Q,
25)
dequeue(Q)
Print
front(Q)

A 5
B 15
C 25
D Empty

✓ **Verified Answer:** ✅ **(B) 15** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** FIFO: 5 leaves. Front is 15.

Problem 48 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q48 Source: Infosys PYQ Level: Infosys SE Standard

[Data
Structures] After the operations, what does peek return?
Stack
S
push(S,
10)
push(S,
20)
push(S,
30)
pop(S)
push(S,
40)
Print
peek(S)

A 10	B 20
C 40	D 30

✓ **Verified Answer:** ✅ **(C) 40** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Stack after pops/pushes: [10, 20, 40]. peek = 40.

Problem 49 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q49 Source: Infosys PYQ Level: Infosys SE Standard

[Bitwise]
What is printed?
Integer
a, b
Set
a = 13, b = 6
Print
a & b

A 4	B 5
C 7	D 11

✓ **Verified Answer:** ✅ **(A) 4** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** 13 is 1101, 6 is 0110, AND is 0100 = 4.

Problem 50 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q50 Source: Infosys PYQ Level: Infosys SE Standard

[Recursion]
What does P(4) return?
Function
P(n)
if
n == 1 then return 2
return
P(n - 1) * 2
End
Function
Print
P(4)

A 8
B 12
C 16
D 24

✓ **Verified Answer:** ✅ **(C) 16** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** P(1)=2, P(2)=4, P(3)=8, P(4)=16.

Problem 51 • [Marks: +{'positive': 3, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q51 Source: Infosys PYQ Level: Infosys SE Standard

Centre = sum of each opposite pair. Find the missing centre.
Wheel A
8
3
11
8
3
Wheel B
9
6
?
7
4

A 12
B 13
C 15
D 16

✓ **Verified Answer:** ✅ **(B) 13** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Wheel A: 8+3=11. Wheel B: 9+4=13 and 6+7=13. Missing centre = 13.

Problem 52 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q52 Source: Infosys PYQ Level: Infosys SE Standard

Find the next number.
2
6
12
20
30
?

A 40
B 42
C 44
D 48

✓ **Verified Answer:** ✅ **(B) 42** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Gaps +4, +6, +8, +10, next +12. 30+12=42. Also n(n+1): 1×2, 2×3, 3×4, 4×5, 5×6, 6×7=42.

Problem 53 • [Marks: +{'positive': 3, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q53 Source: Infosys PYQ Level: Infosys SE Standard

Find the missing number.
18
10
8
25
13
12
31
14
?

A 17
B 16
C 15
D 18

✓ **Verified Answer:** ✅ **(A) 17** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Third = first − second. 18−10=8, 25−13=12, 31−14=17.

Problem 54 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q54 Source: Infosys PYQ Level: Infosys SE Standard

Find the missing number.
3
4
15
5
6
33
7
8
?

A 54	B 55
C 59	D 63

✓ **Verified Answer:** ✅ **(C) 59** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Third = first × second + 3. 3×4+3=15, 5×6+3=33, 7×8+3=59.

Problem 55 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q55 Source: Infosys PYQ Level: Infosys SE Standard

[SVA]
A series of patches ____ scheduled for Sunday.

A are	B is
C have	D were

✓ **Verified Answer:** ✅ **(B) is** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** The subject is series (singular): is scheduled.

Problem 56 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q56 Source: Infosys PYQ Level: Infosys SE Standard

[Error
Spotting] Identify the error: Neither of the servers are
reachable.

A Neither	B are reachable
C the	D No

✓ **Verified Answer:** ✅ **(B) are reachable** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:** Neither is singular: is reachable.

Problem 57 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q57 Source: Infosys PYQ Level: Infosys SE Standard

[Error
Spotting] Identify the error: I am used to work late during
releases.

A I	**B** to work late
C during	**D** No

✓ **Verified Answer:** ✅ **(B) to work late** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:**
Used to + gerund: used to working late.

Problem 58 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q58 Source: Infosys PYQ Level: Infosys SE Standard

[Prepositions]
The fix is consistent ____ the style guide.

A to	**B** with
C from	**D** against

✓ **Verified Answer:** ✅ **(B) with** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:**
Consistent with is the standard collocation.

Problem 59 • [Marks: +{'positive': 2, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q59 Source: Infosys PYQ Level: Infosys SE Standard

[Tenses]
She ____ the patch notes before the standup began.

A writes	**B** has
C had written	**D** will

✓ **Verified Answer:** ✅ **(C) had written** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:**
The earlier of two past actions takes past perfect: had written.

Problem 60 • [Marks: +{'positive': 1, 'negative': 0, 'negativeUnattempted': 0}] ◯ PRACTICE VARIANT

ID: Q60 | Source: Infosys PYQ | Level: Infosys SE Standard

Importance of Cybersecurity in the Digital Age

A > [!IMPORTANT]

Verified Answer: ✅ **(A) ** **Step-by-Step Explanation & Derivation:** **Explanation / Solution:**
Cybersecurity has become an essential part of modern life because people increasingly use the internet for education, communication, banking, shopping, and professional activities. As digital technology continues to grow, protecting personal and organizational information has become very important. Cybersecurity helps prevent unauthorized access, data theft, online fraud, and other digital threats. Individuals can improve their online security by using strong passwords, enabling two-factor authentication, and avoiding suspicious links and messages.
✓ Organizations also need effective security systems to protect customer information and important business data. However, technology alone cannot provide complete protection. Human awareness is equally important because many cyber incidents happen due to careless actions or a lack of knowledge. Regular cybersecurity education can help people recognize common online threats and use digital services safely. In conclusion, cybersecurity is not only a responsibility of technology companies or IT professionals. Every internet user has a role in protecting digital information. Developing good security habits and staying aware of online threats can make the digital environment safer and more reliable.