🏆 Infosys SE Elite Crack Vault — 01 Bitwise Operators XOR AND OR and Shift Operations Elite

🎯 Infosys Systems Engineer (SE) | 📊 42 Questions | 📅 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

Problem 01 • Bitwise Operators & Logic

🔥 MUST-SOLVE

ID: SEC03_EBOOK_Q001 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- a) 0 0
- b) 5 5
- c) 0 5
- d) Run time error

✓ **Verified Answer:** Option C

Problem 02 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q002 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main()
{
Point t1;
return 0;
}
```

- a) Constructor called
- b) Compile time error
- c) Run time error
- d) Blank line

✓ **Verified Answer:** Option B

Problem 03 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q003 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
 }
```

- a) 7 6 3
- b) 7 5 4
- c) 6 7 8
- d) 6 5 4

✓ **Verified Answer:** Option A

Problem 04 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q031 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a) 11
- b) 13
- c) 16
- d) 9

✓ **Verified Answer:** Option A

Problem 05 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q032 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

- a) 13
- b) 10
- c) 15
- d) 3

✓ **Verified Answer:** Option A

Problem 06 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q033 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code:
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

- a) 22
- b) 24
- c) 26
- d) 28

✓ **Verified Answer:** Option A

Problem 07 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q042 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
a=1 and b=4.
Integer fun (Integer a, Integer b)

a = (a^a) & (a+a)

b = (a^a) & (a+a)

return a + b
End function fun()
```

- a) 7
- b) 8
- c) 0
- d) -5

✓ **Verified Answer:** Option C

Problem 08 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q043 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c
Set a =4, b=5, c= 3
B = 3 + c
a = b & a
c = c + b
a = a + b
Print a + b + c
```

- a) 20
- b) 25
- c) 30
- d) 35

✓ **Verified Answer:** Option B

Problem 09 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q044 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For k= 3 || j=4
Integer func(integer k, integer j)
If (k equals 1 or k equals 0)
Return 1
Else
Return func(k-1, j-1) + func(k-2,
j+3)
End if
End function func
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** Option C

Problem 10 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q064 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

✓ **Verified Answer:** Option D

Problem 11 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q065 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
a=9, b=3, c=8
a=(5+7)+c
if((c^7) < (5+c))
a= 2+c
b=3+c
a=c+b
End if
Print a+b+c
```

- a. 30
- b. 31
- c. 32
- d. 33

✓ **Verified Answer:** Option B

Problem 12 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q066 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer p, q, r
Set p=7, q=3, r=4
if(q>r && (q^3)<3)
q= (5+1)+r
End if
Print p+q+r
```

- a. 11
- b. 14
- c. 19
- d. 22

✓ **Verified Answer:** Option B

Problem 13 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q067 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer a,b,c
Set a=6, b=4, c=7
if(c<b || (9+5)<b)
b= (a+4)+c
c=(c+c)+a
End if
Print a+b+c
```

- a. 15
- b. 16
- c. 17
- d. 18

✓ **Verified Answer:** Option C

Problem 14 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q069 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer p,q,r
Set p=9, q=6, r=8
For (each I from 3 to 6)
p= (p^r)+q
if((3+p+r)<(r-q))
p= 1+q
q= 2+q
End if
End for
Print p+q
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** Option Ans

Problem 15 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q080 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** Option A

Problem 16 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q081 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** Option D

Problem 17 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q084 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1 b=7 c=13
c=(b+1)^a
a=(5&2)&c
a=(b+7)+b
Print a+b+c
```

- a. 32
- b. 35
- c. 37
- d. 39

✓ **Verified Answer:** Option C

Problem 18 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q089 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** Option A

Problem 19 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q090 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** Option B

Problem 20 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q099 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the postfix of the given Infix
expression:
11+20/5*(20-15)^6^5
```

- a. 11 20 5/20 15-6^5^*+
- b. 11 21 5/20 15+6^5^*-
- c. 11 22 5/20 15-6^5^*-
- d. 20 11 5/20 15+5^6^*+

✓ **Verified Answer:** Option A

Problem 21 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q105 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if


Return 0
End function fun()
```

- a. 9
- b. 4
- c. 5
- d. 13

✓ **Verified Answer:** Option B

Problem 22 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q107 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer x,y,z
Set x=1, y=8, z=2
If(x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a. 11
- b. 13
- c. 16
- d. 9

✓ **Verified Answer:** Option A

Problem 23 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q115 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Seven elements
A,B,C,D,E,F and G are pushed
onto a stack in reverse order i.e.
starting from G. the stack is
popped five times and each
element inserted into a queue. Two
elements are deleted from queue &
pushed back onto stack. Now one
element is popped from stack.
Which is the last popped element?
```

- a. A
- b. B
- c. E
- d. D

✓ **Verified Answer:** Option B

Problem 24 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q124 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output.
Integer a, b, c, s
Set a=16, b=23, c=7
S = (a+b)&&(a-b) | | (a*c)
If(a not equals 0)
Print s+a-b*c
Else
Print s+s
End if
```

- a. -23
- b. 144
- c. -144
- d. 23

✓ **Verified Answer:** Option C

Problem 25 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q130 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main()
{
int x=2,y=0;
int Z=(y++)?y==1&&x :0;
printf("%d\n",z);
return 0;
}
```

- a. 0
- b. 1
- c. Garbage Value
- d. Error

✓ **Verified Answer:** Option A

Problem 26 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q137 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=12, b=39
printf(“%d”, a&b);
}
```

- a. 468
- b. 1
- c. 4
- d. Error

✓ **Verified Answer:** Option C

Problem 27 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q139 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=30, b=40, x;
x=(a≠10)&&(b=50);
printf(“x=%d\n”, x);
return 0;
}
```

- a. 1
- b. 0
- c. Depends on
- d. Garbage value

✓ **Verified Answer:** Option A

Problem 28 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q140 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<iostream>
using namespace std;
int main()
{
int k=12,n=30;
k=(k>5 && n =4 ? 100 : 200);
cout<<“k=“<<k;
}
```

- a. k=1
- b. k=0
- c. k=100
- d. error

✓ **Verified Answer:** Option D

Problem 29 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q142 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int x=91;
X >>= 2;
printf(“%d\n”,x);
}
```

- a. 182
- b. 91
- c. 22
- d. 45

✓ **Verified Answer:** Option C

Problem 30 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day04_Q01 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- 0 0
- 5 5
- 0 5
- a) Run time error

✓ **Verified Answer:** 0 5

Problem 31 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day04_Q02 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
class Point    {
Point()
{  cout<<"Constructor called";   }
};
int main(){
Point t1;
return 0;
}
```

- Constructor called
- Compile time error
- Run time error
- Blank line

✓ **Verified Answer:** Compile time error

Problem 32 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day04_Q03 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}
```

- 7 6 3
- 7 5 4
- 6 7 8
- 6 5 4

✓ **Verified Answer:** 7 6 3

Problem 33 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q01 Source: Day 06 - Pseudo Code_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (
```

- 71
- 56
- 47
- 54

✓ **Verified Answer:** 54

Problem 34 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q04 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q }
```

- 44
- 41
- 11
- 26

✓ **Verified Answer:** 26

Problem 35 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q05 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)
```

- 12
- 16
- 27
- 10

✓ **Verified Answer:** 16

Problem 36 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q06 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a,
```

- 10
- 12
- Error
- 11

✓ **Verified Answer:** 11

Problem 37 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q07 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c ) a = b
```

- 19
- 21
- 20
- 22

✓ **Verified Answer:** 20

Problem 38 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q08 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^
```

- 11
- 13
- 16
- 9

✓ **Verified Answer:** 11

Problem 39 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q10 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   void main () { int x = 91; x >>= 2; printf ("%d\n", x
```

- 182
- 91
- 22
- 82

✓ **Verified Answer:** 22

Problem 40 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day07_Q04 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? int f(int x, int *py, int **ppz) { int y, z; **ppz += 1; z
```

- 18
- 19
- 21
- 22

✓ **Verified Answer:** 19

Problem 41 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day07_Q05 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { int a = 12; void *ptr = (int *)&a;
```

- 12
- Compiler Error
- Run Time Error
- 0

✓ **Verified Answer:** Compiler Error

Problem 42 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day07_Q06 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2
```

- 2
- 11
- 3
- 0

✓ **Verified Answer:** 3