🏆 Infosys SE Elite Crack Vault — 10 Master Pseudocode Sectional Full Length Simulations Elite

🎯 Infosys Systems Engineer (SE) | 📊 46 Questions | 📅 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

Problem 01 • Bitwise Operators & Logic

🔥 MUST-SOLVE

ID: SEC03_MOCK_Day04_Q01 | Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- 0 0
- 5 5
- 0 5
- a) Run time error

✓ **Verified Answer:** 0 5

Problem 02 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q02 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
class Point    {
Point()
{  cout<<“Constructor called”;   }
};
int main(){
Point t1;
return 0;
}
```

- Constructor called
- Compile time error
- Run time error
- Blank line

✓ **Verified Answer:** Compile time error

Problem 03 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q03 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}
```

- 7 6 3
- 7 5 4
- 6 7 8
- 6 5 4

✓ **Verified Answer:** 7 6 3

Problem 04 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q04 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    Where are placed the list of processes that are prepared to be executed and waiting?
```

- Job queue
- Ready queue
- Execution queue
- Process queue

✓ **Verified Answer:** Ready queue

Problem 05 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q05 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    Who among the following can block the running process?
```

- Fork
- Read
- Down
- All of these

✓ **Verified Answer:** All of these

Problem 06 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q06 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    Which of the following does not interrupt the running process?
```

- Timer interrupt
- Device
- Power failure
- Scheduler process

✓ **Verified Answer:** Scheduler process

Problem 07 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q07 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    The \u0021 article referred to as a
```

- Unicode escape sequence
- Octal escape
- Hexadecimal
- Line feed

✓ **Verified Answer:** Unicode escape sequence

Problem 08 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q08 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    Which of the following is a valid declaration of a char?
```

- char ch = '\utea';
- char ca = 'tea';
- char cr = \u0223;
- char cc = '\itea';

✓ **Verified Answer:** char ch = '\utea';

Problem 09 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q09 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    Which of the following is a valid long literal?
```

- ABH8097
- L990023
- 904423
- 0xnf029L

✓ **Verified Answer:** 0xnf029L

Problem 10 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q10 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    What does the expression float a = 35 / 0 return?
```

- 0
- Not a Number
- Infinity
- Run time exception

✓ **Verified Answer:** Infinity

Problem 11 • OOP & Language Architecture

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q11 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.    Which option is false about the final keyword?
a)   A) A final method cannot be overridden in its subclasses.
b)   B) A final class cannot be extended.
c)   C) A final class cannot extend other classes.
d)   D) A final method can be inherited.
```

- A&B
- B&C
- C&D
- None of these

✓ **Verified Answer:** C&D

Problem 12 • Data Structures, Arrays & Pointers

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q12 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.    Construct post order Transversal for the constructed tree with the given In-Order and Preorder Tr
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- 9 10 7 8 6
- 9 7 6 10 8
- 8 9 10 7 6
- 9 8 10 7 6

✓ **Verified Answer:** 9 10 7 8 6

Problem 13 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q13 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program fragment?
int i = 263;
putchar(i);
```

- prints 263
- prints the ASCII equivalent of 263
- rings the bell
- prints garbage

✓ **Verified Answer:** rings the bell

Problem 14 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q14 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this statement?
printf (“%d”, 9/5);
```

- 1.8
- 1.0
- 2.0
- None of these

✓ **Verified Answer:** None of these

Problem 15 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q15 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

- 2
- 6
- 4
- 1

✓ **Verified Answer:** 1

Problem 16 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q16 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     Which of the following declarations is invalid in C language?
```

- char *str = “campus monk is the best platform for learn";
- char str[] = “campus monk is the best platform for learn";
- char str[20] = “campus monk is the best platform for learn";
- char[] str = “campus monk is the best platform for learn";

✓ **Verified Answer:** char[] str = “campus monk is the best platform for learn";

Problem 17 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_MOCK_Day04_Q17 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
#include
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
enum flg h;
h = b;
printf(“%d”, h);
return 0;
}
```

- 1
- error: redeclaration of an enumerator
- h
- 3

✓ **Verified Answer:** error: redeclaration of an enumerator

Problem 18 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q18 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
main ()
{
if (5 < '5')
printf("5")
else
printf(" NOT EQUAL TO 5.")
}
```

- ENQ
- 5
- I
- Not equal to 5

✓ **Verified Answer:** 5

Problem 19 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q19 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of the following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- 5
- 7
- 9
- 12

✓ **Verified Answer:** 5

Problem 20 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q20 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of the following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- 6 6 6
- 6 5 6
- 5 5 5
- 6 5 4

✓ **Verified Answer:** 6 5 4

Problem 21 • Data Structures, Arrays & Pointers

CORE SE

ID: SEC03_MOCK_Day04_Q21 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     If the sequence of operations are performed on a stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().
```

- 2 2 1 1 2
- 2 2 1 2 2
- 2 1 2 2 1
- 2 1 2 2 2

✓ **Verified Answer:** 2 2 1 1 2

Problem 22 • Technical Programming Concepts

CORE SE

ID: SEC03_MOCK_Day04_Q22 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     In an empty BST, insert the following elements in a similar sequence. Which element will be at l
105     95    122    99    97   120
```

- 95
- 97
- 99
- 120

✓ **Verified Answer:** 97

Problem 23 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q23 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
T The concatenation of two lists is to be performed in O(1) time. Which of the following implementatior
```

- a) Singly linked list
- a) Doubly linked list
- a) Circular doubly linked list
- a) Array implementation of list

✓ **Verified Answer:** a) Circular doubly linked list

Problem 24 • Data Structures, Arrays & Pointers

CORE SE

ID: SEC03_MOCK_Day04_Q24 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     Which of the following sequence can be obtained in the output (in same order) using a stack assu
```

- a) 3,4,5,1,2
- a) 3,4,5,2,1
- a) 1,5,2,3,4
- a) 5,4,3,1,2

✓ **Verified Answer:** a) 3,4,5,2,1

Problem 25 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q25 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     Let A be a square matrix of size nxn. Consider the following program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp - C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

- a) The matrix A itself
- a) Transpose of matrix A
- a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
- a) None of the above

✓ **Verified Answer:** a) The matrix A itself

Problem 26 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q26 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     The value of j at the end of the execution of the following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- 10
- 4
- 6
- 7

✓ **Verified Answer:** 10

Problem 27 • Technical Programming Concepts

CORE SE

ID: SEC03_MOCK_Day04_Q27 | Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
1.     What is printed by the print statement in the program P1 assuming call by reference parameter pa
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

- 10, 3
- 31, 3
- 27, 7
- None of these

✓ **Verified Answer:** 31, 3

Problem 28 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q28 | Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
1.     The value returned by the following function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- 5
- 6
- 7
- 8

✓ **Verified Answer:** 7

Problem 29 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q29 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     Find the output of the following pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- 7
- 18
- 22
- 2

✓ **Verified Answer:** 2

Problem 30 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q30 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     Find the output of the following pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- 31
- 11
- 42
- 30

✓ **Verified Answer:** 30

Problem 31 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q01 Source: Day 06 - Pseudo Code_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (
```

- 71
- 56
- 47
- 54

✓ **Verified Answer:** 54

Problem 32 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day06_Q02 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) Print "c
```

- 1 Times
- 2 Times
- 3 Times
- 4 Times

✓ **Verified Answer:** 2 Times

Problem 33 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day06_Q03 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   int main(void) { int a = 10, x; x = a-- + +445; print
```

- 19
- 435
- 455
- 23

✓ **Verified Answer:** 455

Problem 34 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q04 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q }
```

- 44
- 41
- 11
- 26

✓ **Verified Answer:** 26

Problem 35 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q05 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)
```

- 12
- 16
- 27
- 10

✓ **Verified Answer:** 16

Problem 36 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q06 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a,
```

- 10
- 12
- Error
- 11

✓ **Verified Answer:** 11

Problem 37 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q07 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c ) a = b
```

- 19
- 21
- 20
- 22

✓ **Verified Answer:** 20

Problem 38 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q08 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^
```

- 11
- 13
- 16
- 9

✓ **Verified Answer:** 11

Problem 39 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day06_Q09 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   void main() { int a = 10; if (a == 010) printf("BCA")
```

- BCA
- B.tech
- 10
- Error

✓ **Verified Answer:** B.tech

Problem 40 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q10 | Source: Day 06 - Pseudo Code_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   void main () { int x = 91; x >>= 2; printf ("%d\n", x
```

- 182
- 91
- 22
- 82

✓ **Verified Answer:** 22

Problem 41 • Data Structures, Arrays & Pointers

CORE SE

ID: SEC03_MOCK_Day07_Q01 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { int num = 987; int rem; while(num =
```

- 0
- 1
- 10
- 5

✓ **Verified Answer:** 1

Problem 42 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day07_Q02 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { float x = 0.0; long int y = 10; pri
```

- 3
- 1
- 5
- 2

✓ **Verified Answer:** 1

Problem 43 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day07_Q03 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Predict the output of the given pseudocode if the value of the number is 6: Read number k = 2 i = 2 whi
```

- 1440.0
- 1340.0
- 1700.0
- 1560.0

✓ **Verified Answer:** 1440.0

Problem 44 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day07_Q04 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? int f(int x, int *py, int **ppz) { int y, z; **ppz += 1; z
```

- 18
- 19
- 21
- 22

✓ **Verified Answer:** 19

Problem 45 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day07_Q05 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { int a = 12; void *ptr = (int *)&a;
```

- 12
- Compiler Error
- Run Time Error
- 0

✓ **Verified Answer:** Compiler Error

Problem 46 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day07_Q06 | Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json | Level: Infosys SE Standard

/ Code Snippet

```
Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2
```

- 2
- 11
- 3
- 0

✓ **Verified Answer:** 3