🏆 Infosys SE Elite Crack Vault — 02 Loop Execution Nested Loops and Boundary Conditions Elite

🎯 Infosys Systems Engineer (SE) | 📊 78 Questions | 📅 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

---

Problem 01 • Bitwise Operators & Logic

🔥 MUST-SOLVE

`ID: SEC03_EBOOK_Q003` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
 }
```

- a) 7 6 3
- b) 7 5 4
- c) 6 7 8
- d) 6 5 4

✓ **Verified Answer:** `Option A`

Problem 02 • Operating Systems & Systems Architecture

MUST-SOLVE

ID: SEC03_EBOOK_Q006 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following does not
interrupt the running process?
```

- a) Timer interrupt
- b) Device
- c) Power failure
- d) Scheduler process

✓ **Verified Answer:** `Option D`

Problem 03 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q010 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What does the expression float a =
35 / 0 return?
```

- a) 0
- b) Not a Number
- c) Infinity
- d) Run time exception

✓ **Verified Answer:** `Option C`

Problem 04 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q012 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Construct post order Transversal
for the constructed tree with the
given
In-Order
and
Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- a) 9 10 7 8 6
- b) 9 7 6 10 8
- c) 8 9 10 7 6
- d) 9 8 10 7 6

✓ **Verified Answer:** `Option A`

Problem 05 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q016 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following declarations
is invalid in C language?
```

- a) char *str = “campus monk is the
- b) char str[] = “campus monk is the
- c) char str[20] = “campus monk is the
- d) char[] str = “campus monk is the

✓ **Verified Answer:** `Option D`

Problem 06 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q018` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of this
program?
main ()
{
 if (5 < ’5’)
        printf(“5”)
 else
        printf(“ NOT EQUAL TO 5.”)
}
```

- a) ENQ
- b) 5
- c) I
- d) Not equal to 5

✓ **Verified Answer:** `Option B`

Problem 07 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q019` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of the
following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- a) 5
- b) 7
- c) 9
- d) 12

✓ **Verified Answer:** `Option A`

Problem 08 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q020 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- a) 6 6 6
- b) 6 5 6
- c) 5 5 5
- d) 6 5 4

✓ **Verified Answer:** `Option D`

Problem 09 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q021 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of operations are
performed on a stack, the sequence
of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Pop(),
Push(2), Pop().
```

- a) 2 2 1 1 2
- b) 2 2 1 2 2
- c) 2 1 2 2 1
- d) 2 1 2 2 2

✓ **Verified Answer:** `Option A`

Problem 10 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q023 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The concatenation of two lists is to
be performed in O(1) time. Which of
the following implementation of a
list should be used?
```

- a) Singly linked list
- b) Doubly linked list
- c) Circular doubly linked list
- d) Array implementation of list

✓ **Verified Answer:** `Option C`

Problem 11 • Operating Systems & Systems Architecture

MUST-SOLVE

ID: SEC03_EBOOK_Q025 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Let A be a square matrix of size
nxn.
Consider
the
following
program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

- a) The matrix A itself
- b) Transpose of matrix A
- c) Adding 100 to the upper diagonal
- d) None of the above

✓ **Verified Answer:** `Option A`

Problem 12 • Recursion & Function Call Stacks

MUST-SOLVE

`ID: SEC03_EBOOK_Q026` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** `Option A`

Problem 13 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

✓ **Verified Answer:** `Option C`

Problem 14 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q029` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a) 7
- b) 18
- c) 22
- d) 2

✓ **Verified Answer:** `Option D`

Problem 15 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q030` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- a) 31
- b) 11
- c) 42
- d) 30

✓ **Verified Answer:** `Option D`

Problem 16 • Bitwise Operators & Logic

MUST-SOLVE

`ID: SEC03_EBOOK_Q031` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a) 11
- b) 13
- c) 16
- d) 9

✓ **Verified Answer:** `Option A`

Problem 17 • Bitwise Operators & Logic

MUST-SOLVE

`ID: SEC03_EBOOK_Q032` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

- a) 13
- b) 10
- c) 15
- d) 3

✓ **Verified Answer:** `Option A`

Problem 18 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q033 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code:
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

- a) 22
- b) 24
- c) 26
- d) 28

✓ **Verified Answer:** `Option A`

Problem 19 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q037 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a, b, c
Set b = 10, a=1
If  (0)
a = a – 1
else
a = b + 1
b = a – 1
a = a – 1
end if
print a
```

- a) 3
- b) 5
- c) 10
- d) 11

✓ **Verified Answer:** `Option C`

Problem 20 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q038 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

- a) 7
- b) 4
- c) 6
- d) 8

✓ **Verified Answer:** `Option D`

Problem 21 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q039 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Consider a stack of integers. The
stack is allocated 7 memory cells:
STACK: 12, 34, 66, 79, _, _, _.
Now
consider
the
following
operations:
A. PUSH (STACK, 8)
B. PUSH (STAC, 54)
C. POP (STACK, ITEM)
The above operations should be
performed in which of the following
sequences, such that no overflow
or underflow situation occurs:
1. B-> A-> C
2. A-> B-> C
3. C-> B-> A
```

- a) Only 1
- b) Any of them
- c) Only 2
- d) Only 3

✓ **Verified Answer:** `Option B`

Problem 22 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q040 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
x=1 and y=4.
Integer fun (Integer x, Integer y)

If (y > x)


return 1+ fun (x, y-1)

End if

return x + 1
End function fun()
```

- a) 5
- b) -15
- c) 14
- d) 22

✓ **Verified Answer:** `Option A`

Problem 23 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q042 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
a=1 and b=4.
Integer fun (Integer a, Integer b)

a = (a^a) & (a+a)

b = (a^a) & (a+a)

return a + b
End function fun()
```

- a) 7
- b) 8
- c) 0
- d) -5

✓ **Verified Answer:** `Option C`

Problem 24 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q044 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For k= 3 || j=4
Integer func(integer k, integer j)
If (k equals 1 or k equals 0)
Return 1
Else
Return func(k-1, j-1) + func(k-2,
j+3)
End if
End function func
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option C`

Problem 25 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q045 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option A`

Problem 26 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q047 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For a B- tree of order 6, to be a
multi-way search tree, each non
root node has at least how many
Non empty Children?
```

- a) 3
- b) 4
- c) 5
- d) 6

✓ **Verified Answer:** `Option A`

Problem 27 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q049` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
If you are using bubble sort to sort
the given numbers in ascending
order, then find out the minimum
number of swaps required.
10, 7, 5, 8, 9
```

- a) 7
- b) 6
- c) 5
- d) 4

✓ **Verified Answer:** `Option B`

Problem 28 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q052` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
```

- a) 122
- b) 127
- c) 118
- d) 131

✓ **Verified Answer:** `Option A`

Problem 29 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q053 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 30 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q054 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
```

- a) -3 -1 -0 -2
- b) -1 -3 -4 -2
- c) -2 -4 -1 -0
- d) -1 -2 -3 -4

✓ **Verified Answer:** `Option D`

Problem 31 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q055 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
```

- a) 6453210
- b) 0123456
- c) 1265340
- d) 0612354

✓ **Verified Answer:** `Option B`

Problem 32 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q056 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 33 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q057 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
```

- a) 4 False
- b) 3 False
- c) 2 False
- d) 1 False

✓ **Verified Answer:** `Option D`

Problem 34 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q058 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
How many times will the loop
execute?
for val=0 to 3 do
val=2*val
val- -
end-for
```

- a) -1
- b) 1
- c) Infinite Loop
- d) Infinite

✓ **Verified Answer:** `Option C`

Problem 35 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q059 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option B`

Problem 36 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q060 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
```

- a) 0 1
- b) 1 2
- c) 2 3
- d) 3 4

✓ **Verified Answer:** `Option A`

Problem 37 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q061 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option C`

Problem 38 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q062 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 39 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q063 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
```

- a. 32
- b. 34
- c. 36
- d. 38

✓ **Verified Answer:** `Option A`

Problem 40 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q069 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer p,q,r
Set p=9, q=6, r=8
For (each I from 3 to 6)
p= (p^r)+q
if((3+p+r)<(r-q))
p= 1+q
q= 2+q
End if
End for
Print p+q
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** `Option Ans`

Problem 41 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q071 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For var 0 to 5 do
If var%2==0 and var/2==0 then do
Display var
End if
End for
```

- a. 0
- b. 1
- c. 2
- d. 3

✓ **Verified Answer:** `Option B`

Problem 42 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q072 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output when num
= 3 and values passed are 5,1,8
Set integer res=0
For c = 1 to num do
Input value
res+=value
- - res
End for
Display res
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** `Option C`

Problem 43 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q073 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set integer marks = 30
switch(marks)
Case 30: marks=25
Case 25: marks=20
Default: marks=50
Break
End switch
Display marks
```

- a. 10
- b. 30
- c. 50
- d. 70

✓ **Verified Answer:** `Option B`

Problem 44 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q074 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
public static void main(String[]
args) {
    double n= 10;
       System.out.println(n/0);
     }
}
```

- a. Error
- b. Infinity
- c. Exception
- d. Zero

✓ **Verified Answer:** `Option A`

Problem 45 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q080 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** `Option A`

Problem 46 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q081 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** `Option D`

Problem 47 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q082 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args) {

int i;

for(i=0,i++<=10;)

System.out.printIn(i);

  }
}
```

- a. 10
- b. 1 2 3 4 5 6 7 8 9 10 11
- c. Error
- d. 1 2 3 4 5 6 7 8 9 10

✓ **Verified Answer:** `Option B`

Problem 48 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q086 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

- a. 1 time
- b. 2 Time
- c. 3 Time
- d. 4 Time

✓ **Verified Answer:** `Option B`

Problem 49 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q087 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

- a. 62
- b. 65
- c. 75
- d. 75

✓ **Verified Answer:** `Option B`

Problem 50 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q088 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What would the following pseudo
code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if
```

- a. Find out the largest number
- b. Find out the smallest

✓ **Verified Answer:** `Option A`

Problem 51 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q089 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** `Option A`

Problem 52 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q090 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** `Option B`

Problem 53 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q091 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
```

- a. 5
- b. 7
- c. 9
- d. 11

✓ **Verified Answer:** `Option B`

Problem 54 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q092 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
```

- a. 0123456###
- b. 0123336###
- c. 0121216###
- d. 0000006###

✓ **Verified Answer:** `Option A`

Problem 55 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q095 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
John wants to go to different
location of a city in which he is
currently in. He has listed all of
them. However, he wants to visit
one location before visiting the
other. What application of graph he
uses to determine that location?
6

        /     \
1
5
   /               \
2                   4
```

- a. DFS
- b. BFS
- c. Djikstra's algorithm
- d. Topological sorting

✓ **Verified Answer:** `Option C`

Problem 56 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q097 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following data
structure is used to convert
expression from one form to
another?
```

- a. Graph
- b. Stack
- c. Linked list
- d. Queue

✓ **Verified Answer:** `Option B`

Problem 57 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q098 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
what is the output of the following
code?
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

- a. -1,1,2,3,4
- b. 1,2,3,4,4
- c. 0,1,2,3,4,5
- d. 1,1,2,2,0

✓ **Verified Answer:** `Option A`

Problem 58 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q106 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a. 7
- b. 8
- c. 22
- d. 12

✓ **Verified Answer:** `Option D`

Problem 59 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q108 Source: 1. Pseudo Codes Technical ebook.pdf Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet. int main()
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

- a. 24
- b. 25
- c. 100
- d. Depends on compiler

✓ **Verified Answer:** `Option C`

Problem 60 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q109 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find out how many times
will “hi” be printed.
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

- a. 1 time
- b. 2019 times
- c. 2021 times
- d. 2020 times

✓ **Verified Answer:** `Option D`

Problem 61 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q110 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
how many times will "abc"
be printed.
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)


continue;
else
break;
printf("abc\n");
}
}
```

- a. Infinite times
- b. 11 times
- c. 0 times
- d. 10 times

✓ **Verified Answer:** `Option C`

Problem 62 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q111 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
int i=0;
for (; i<=5; i++);
printf("%d", i);
return 0;
}
```

- a. 5
- b. 0 1 2 3 4 5
- c. 6
- d. 0 1 2 3 4

✓ **Verified Answer:** `Option C`

Problem 63 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q112 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ != 0)
printf("%d", ++i);
return 0;
}
```

- a. No output printed
- b. 012 3 65535
- c. 012 3.....32767 -32766 -
- d. Inifinite loop

✓ **Verified Answer:** `Option D`

Problem 64 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q116 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of
operations are performed on a
stack, the sequence of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Push(2),
Pop().
```

- a. 2 2 1 1 2
- b. 2 2 1 2 2
- c. 2 1 2 2 1
- d. 2 1 2 2 1

✓ **Verified Answer:** `Option B`

Problem 65 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q117 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Consider the following
operations performed on a stack of
size 5. Push(a), Pop(), Push(b),
Push(c), Pop(), Push(d), Pop(),
Pop(), Push(e) Which of the
following statements is correct?
```

- a. Underflow occurs
- b. Stack operations are performed
- c. Overflow occurs
- d. None

✓ **Verified Answer:** `Option B`

Problem 66 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q120 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
relation is correct for a binary
search tree?
```

- a. Parent node> Right node>
- b. Right node> Parent node>
- c. Right node> Left node>
- d. Parent node> Left

✓ **Verified Answer:** `Option B`

Problem 67 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q122 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
pseudo code. Integer a, b, c
Set a=5, b=3
For( each c from b to a)
If (a)
a=a-1 n
End if
If(b)
b =b-1
End if
End for
Print a+b
```

- a. 4
- b. 6
- c. 8
- d. 1

✓ **Verified Answer:** `Option A`

Problem 68 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q127 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer a, b, c, sum
Set sum= a+b+c
If((sum EQUALS 180)and (a NOT
EQUALS 0) and (b NOT EQUALS
0) and (c EQUALS 0))
Print “Success”
Else
Print “Fail”
End If
```

- a. Success
- b. Fail
- c. 0
- d. 1

✓ **Verified Answer:** `Option B`

Problem 69 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q128 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
Integer x, y, Z .
Set x=9, y=2, z=1
If (x+y>8)
If (7>x+z)
z=7
End if
If (9>x-z)
z=9
End if
y=y+z+1
End if


Print x+y+z
```

- a. 31
- b. 11
- c. 42
- d. 30

✓ **Verified Answer:** `Option D`

Problem 70 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q133 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main(void)
{
int i;
for(int j=0; j<1; j++)
{
if(i==0,1)
{
printf(“Be a programmer”);
}
else
{
printf(“Learning c”);
}
}
printf(“%d\n”, ++i);
return 0;
}
```

- a. Be a programmer1
- b. Be a programmer0
- c. Learning c1
- d. Learning c0

✓ **Verified Answer:** `Option A`

Problem 71 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q134 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following
cannot be checked in a switch
case statement?
```

- a. Char
- b. Float
- c. Int
- d. Enum

✓ **Verified Answer:** `Option B`

Problem 72 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q141 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int i;
for( i=1;i<5;i++)
{
if(i<=3)
continue;
printf (“Hi %d”, i);
}
}
```

- a. HiHiHi123
- b. Hi5
- c. Hi4
- d. Hi4Hi5

✓ **Verified Answer:** `Option C`

Problem 73 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q143 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=10;
if( a == 010)
printf (“BCA”);
else
printf (“Btech”);
}
```

- a. BCA
- b. Btech
- c. 10
- d. Error

✓ **Verified Answer:** `Option B`

Problem 74 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day04_Q03 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
{
int z = x & (x >> 1);
if (z)
printf("%d ", x);
}
}
```

- 7 6 3
- 7 5 4
- 6 7 8
- 6 5 4

✓ **Verified Answer:** `7 6 3`

Problem 75 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q06 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     Which of the following does not interrupt the running process?
```

- Timer interrupt
- Device
- Power failure
- Scheduler process

✓ **Verified Answer:** `Scheduler process`

Problem 76 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q10 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     What does the expression float a = 35 / 0 return?
```

- 0
- Not a Number
- Infinity
- Run time exception

✓ **Verified Answer:** `Infinity`

Problem 77 • Data Structures, Arrays & Pointers

CORE SE

ID: SEC03_MOCK_Day04_Q12 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.    Construct post order Transversal for the constructed tree with the given In-Order and Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- 9 10 7 8 6
- 9 7 6 10 8
- 8 9 10 7 6
- 9 8 10 7 6

✓ **Verified Answer:** `9 10 7 8 6`

Problem 78 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_MOCK_Day04_Q18 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
main ()
{
if (5 < ’5’)
printf(“5”)
else
printf(“ NOT EQUAL TO 5.”)
}
```

- ENQ
- 5
- I
- Not equal to 5

✓ **Verified Answer:** `5`