🏆 Infosys SE Elite Crack Vault — 03 Recursion Call Stack and Accumulator Tracing Elite

🎯 Infosys Systems Engineer (SE) | 📊 39 Questions | 📅 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

---

Problem 01 • Bitwise Operators & Logic

🔥 MUST-SOLVE

`ID: SEC03_EBOOK_Q001` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- a) 0 0
- b) 5 5
- c) 0 5
- d) Run time error

✓ **Verified Answer:** `Option C`

Problem 02 • Bitwise Operators & Logic

MUST-SOLVE

`ID: SEC03_EBOOK_Q002` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main()
{
Point t1;
return 0;
}
```

- a) Constructor called
- b) Compile time error
- c) Run time error
- d) Blank line

✓ **Verified Answer:** `Option B`

Problem 03 • Recursion & Function Call Stacks

MUST-SOLVE

`ID: SEC03_EBOOK_Q010` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What does the expression float a =
35 / 0 return?
```

- a) 0
- b) Not a Number
- c) Infinity
- d) Run time exception

✓ **Verified Answer:** `Option C`

Problem 04 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q015 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
int main() {
    int i = 5;
    printf(“%d”, i = ++i == 6);
return 0;
}
```

- a) 2
- b) 6
- c) 4
- d) 1

✓ **Verified Answer:** `Option D`

Problem 05 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q017 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf(“%d”, h);
   return 0;
}
```

- a) 1
- b) error: redeclaration of an
- c) h
- d) 3

✓ **Verified Answer:** `Option B`

Problem 06 • Recursion & Function Call Stacks

🔥 MUST-SOLVE

ID: SEC03_EBOOK_Q026 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** `Option A`

Problem 07 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q027 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What is printed by the print
statement in the program P1
assuming
call
by
reference
parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

- a) 10,3
- b) 31,3
- c) 27,7
- d) None of these

✓ **Verified Answer:** `Option B`

Problem 08 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

✓ **Verified Answer:** `Option C`

Problem 09 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q040 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
x=1 and y=4.
Integer fun (Integer x, Integer y)

If (y > x)


return 1+ fun (x, y-1)

End if

return x + 1
End function fun()
```

- a) 5
- b) -15
- c) 14
- d) 22

✓ **Verified Answer:** `Option A`

Problem 10 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q042 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
a=1 and b=4.
Integer fun (Integer a, Integer b)

a = (a^a) & (a+a)

b = (a^a) & (a+a)

return a + b
End function fun()
```

- a) 7
- b) 8
- c) 0
- d) -5

✓ **Verified Answer:** `Option C`

Problem 11 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q044 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For k= 3 || j=4
Integer func(integer k, integer j)
If (k equals 1 or k equals 0)
Return 1
Else
Return func(k-1, j-1) + func(k-2,
j+3)
End if
End function func
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option C`

Problem 12 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q046 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b=/= !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}
```

- a) 1,1
- b) 2,1
- c) 3,1
- d) 4,1

✓ **Verified Answer:** `Option D`

Problem 13 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q053 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 14 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q065 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
a=9, b=3, c=8
a=(5+7)+c
if((c^7) < (5+c))
a= 2+c
b=3+c
a=c+b
End if
Print a+b+c
```

- a. 30
- b. 31
- c. 32
- d. 33

✓ **Verified Answer:** `Option B`

Problem 15 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q068 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
Set a=5, b=7, c=9
if((a+b)<c)
a= a+c
b= (c+a)+c
c= (9+9)+a
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

✓ **Verified Answer:** `Option B`

Problem 16 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q105 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer fun(int a, int b)
If (a && b)
Return a + fun(a-1, b-1)
End if


Return 0
End function fun()
```

- a. 9
- b. 4
- c. 5
- d. 13

✓ **Verified Answer:** `Option B`

Problem 17 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q111 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
int i=0;
for (; i<=5; i++);
printf("%d", i);
return 0;
}
```

- a. 5
- b. 0 1 2 3 4 5
- c. 6
- d. 0 1 2 3 4

✓ **Verified Answer:** `Option C`

Problem 18 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q112 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include<stdio.h>
int main()
{
unsigned int i=65535;
while(i++ =/= 0)
printf("%d", ++i);
return 0;
}
```

- a. No output printed
- b. 012 3 65535
- c. 012 3.....32767 -32766 -
- d. Inifinite loop

✓ **Verified Answer:** `Option D`

Problem 19 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q113 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
int main()
{
int a=500,b=100, c;
if(!a⩾400)
b=300;
c=200;
printf("%d%d",b,c);
return 0;
}
```

- a. 300 200
- b. 100 200
- c. 100 Garbage value
- d. 300 Garbage value

✓ **Verified Answer:** `Option B`

Problem 20 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q125 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
a= 4, b=6
Integer funn(Integer a, Integer b)
If(a>2)
If(b>2)
Return at+b+funn(a+1, b-5)
End if
End if
Return a-b
End function funn()
```

- a. 14
- b. 10
- c. 2
- d. 5

✓ **Verified Answer:** `Option A`

Problem 21 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q129 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
int main()
{
int y = 128;
const int x=y;
y=120;
printf("%d\n", x);
return 0;
}
```

- a. 0
- b. 128
- c. Garbage Value
- d. Error

✓ **Verified Answer:** `Option B`

Problem 22 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q130 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main()
{
int x=2,y=0;
int Z=(y++)?y==1&&x :0;
printf(“%d\n”,z);
return 0;
}
```

- a. 0
- b. 1
- c. Garbage Value
- d. Error

✓ **Verified Answer:** `Option A`

Problem 23 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q131 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#includex<stdio.h>
int main()
{
Printf(“\\n”);
return 0;
}
```

- a. \n
- b. \n
- c. Error
- d. n

✓ **Verified Answer:** `Option B`

Problem 24 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q132 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the complete of the
following code where the output is
8,14.
#include<stdio.h>
int main()
{
int p=6, q=6;
intr=6*(____________);
printf (“%d%d”, p,r);
return 0;
}
```

- a. (p + q + p++)
- b. (p++ + q + p)
- c. (p++ +q + p++)
- d. none

✓ **Verified Answer:** `Option C`

Problem 25 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q133 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
#include<stdio.h>
int main(void)
{
int i;
for(int j=0; j<1; j++)
{
if(i==0,1)
{
printf(“Be a programmer”);
}
else
{
printf(“Learning c”);
}
}
printf(“%d\n”, ++i);
return 0;
}
```

- a. Be a programmer1
- b. Be a programmer0
- c. Learning c1
- d. Learning c0

✓ **Verified Answer:** `Option A`

Problem 26 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q135 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
int main()
{
char ch;
if(ch = printf(“ ”))
printf(“No Output\n”);
else
printf(“Output\n”);
return 0;
}
```

- a. No Output
- b. Output
- c. No Output Output
- d. Error

✓ **Verified Answer:** `Option B`

Problem 27 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q136 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
int main(void)
{
int a=10, x;
X= a-- + +445
printf (“%d”,x);
return 0;
}
```

- a. 19
- b. 20
- c. 22
- d. 23

✓ **Verified Answer:** `Option B`

Problem 28 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q138 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int x;
printf(“%d\n, 4%3);
printf(“%d\n, 4%-3);
printf(“%d\n, -4%3);
printf(“%d\n, -4%-3);
return 0;
}
```

- a. 1 1 -1 -1
- b. 1 -1 1 -1
- c. 1 -1 -1 1
- d. 1 -1 -1 -1

✓ **Verified Answer:** `Option A`

Problem 29 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q139 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the
following code.
#include<stdio.h>
void main()
{
int a=30, b=40, x;
x=(a≠10)&&(b=50);
printf(“x=%d\n”, x);
return 0;
}
```

- a. 1
- b. 0
- c. Depends on
- d. Garbage value

✓ **Verified Answer:** `Option A`

Problem 30 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day04_Q01 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json

Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- 0 0
- 5 5
- 0 5
- a) Run time error

✓ **Verified Answer:** `0 5`

Problem 31 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day04_Q02 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     #include
using namespace std;
class Point    {
Point()
{  cout<<“Constructor called”;   }
};
int main(){
Point t1;
return 0;
}
```

- Constructor called
- Compile time error
- Run time error
- Blank line

✓ **Verified Answer:** `Compile time error`

Problem 32 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q10 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     What does the expression float a = 35 / 0 return?
```

- 0
- Not a Number
- Infinity
- Run time exception

✓ **Verified Answer:** `Infinity`

Problem 33 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q15 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

- 2
- 6
- 4
- 1

✓ **Verified Answer:** `1`

Problem 34 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q17 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     What will be the output of this program?
#include
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
enum flg h;
h = b;
printf(“%d”, h);
return 0;
}
```

- 1
- error: redeclaration of an enumerator
- h
- 3

✓ **Verified Answer:** `error: redeclaration of an enumerator`

Problem 35 • Recursion & Function Call Stacks

CORE SE

`ID: SEC03_MOCK_Day04_Q26` `Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json`

`Level: Infosys SE Standard`

/ Code Snippet

```
1.     The value of j at the end of the execution of the following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- 10
- 4
- 6
- 7

✓ **Verified Answer:** `10`

Problem 36 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day04_Q28 Source: Day 04 - Technical MCQ - Pseudo Codes Based on PYQ With Video Sol_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
1.     The value returned by the following function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- 5
- 6
- 7
- 8

✓ **Verified Answer:** `7`

Problem 37 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day06_Q03 Source: Day 06 - Pseudo Code_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following code. #include   int main(void) { int a = 10, x; x = a-- + +445; print
```

- 19
- 435
- 455
- 23

✓ **Verified Answer:** `455`

Problem 38 • Bitwise Operators & Logic

CORE SE

ID: SEC03_MOCK_Day06_Q06 Source: Day 06 - Pseudo Code_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a,
```

- 10
- 12
- Error
- 11

✓ **Verified Answer:** `11`

Problem 39 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_MOCK_Day07_Q02 Source: Day 07 - Section III _ Pseudo Codes Based on PYQ_QUESTIONS.json Level: Infosys SE Standard

/ Code Snippet

```
What is the output of the following C code? #include   int main() { float x = 0.0; long int y = 10; pri
```

- 3
- 1
- 5
- 2

✓ **Verified Answer:** `1`