🏆 Infosys SE Elite Crack Vault — 05 OOP and Language Architecture Elite

🎯 Infosys Systems Engineer (SE) | 📊 51 Questions | 📅 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

---

Problem 01 • Bitwise Operators & Logic

🔥 MUST-SOLVE

`ID: SEC03_EBOOK_Q001` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<“ “;
Test t[5];
cout<< Test::getX();      }
```

- a) 0 0
- b) 5 5
- c) 0 5
- d) Run time error

✓ **Verified Answer:** `Option C`

Problem 02 • Bitwise Operators & Logic

MUST-SOLVE

`ID: SEC03_EBOOK_Q002` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main()
{
Point t1;
return 0;
}
```

- a) Constructor called
- b) Compile time error
- c) Run time error
- d) Blank line

✓ **Verified Answer:** `Option B`

Problem 03 • OOP & Language Architecture

MUST-SOLVE

`ID: SEC03_EBOOK_Q011` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Which option is false about the
final keyword?
```

- a) A final method cannot be
- b) A final class cannot be extended.
- c) A final class cannot extend other
- d) A final method can be

✓ **Verified Answer:** `Option C&D`

Problem 04 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q016 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following declarations
is invalid in C language?
```

- a) char *str = “campus monk is the
- b) char str[] = “campus monk is the
- c) char str[20] = “campus monk is the
- d) char[] str = “campus monk is the

✓ **Verified Answer:** `Option D`

Problem 05 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q018 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
main ()
{
 if (5 < ’5’)
        printf(“5”)
 else
        printf(“ NOT EQUAL TO 5.”)
}
```

- a) ENQ
- b) 5
- c) I
- d) Not equal to 5

✓ **Verified Answer:** `Option B`

Problem 06 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q019` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of the
following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- a) 5
- b) 7
- c) 9
- d) 12

✓ **Verified Answer:** `Option A`

Problem 07 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q020` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- a) 6 6 6
- b) 6 5 6
- c) 5 5 5
- d) 6 5 4

✓ **Verified Answer:** `Option D`

Problem 08 • Recursion & Function Call Stacks

MUST-SOLVE

`ID: SEC03_EBOOK_Q026` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** `Option A`

Problem 09 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

✓ **Verified Answer:** `Option C`

Problem 10 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q029` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a) 7
- b) 18
- c) 22
- d) 2

✓ **Verified Answer:** `Option D`

Problem 11 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q030 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- a) 31
- b) 11
- c) 42
- d) 30

✓ **Verified Answer:** `Option D`

Problem 12 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q037 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a, b, c
Set b = 10, a=1
If  (0)
a = a – 1
else
a = b + 1
b = a – 1
a = a – 1
end if
print a
```

- a) 3
- b) 5
- c) 10
- d) 11

✓ **Verified Answer:** `Option C`

Problem 13 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q038 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

- a) 7
- b) 4
- c) 6
- d) 8

✓ **Verified Answer:** `Option D`

Problem 14 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q045 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option A`

Problem 15 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q049 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
If you are using bubble sort to sort
the given numbers in ascending
order, then find out the minimum
number of swaps required.
10, 7, 5, 8, 9
```

- a) 7
- b) 6
- c) 5
- d) 4

✓ **Verified Answer:** `Option B`

Problem 16 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q052` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
```

- a) 122
- b) 127
- c) 118
- d) 131

✓ **Verified Answer:** `Option A`

Problem 17 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q054` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display – y
end-for
```

- a) -3 -1 -0 -2
- b) -1 -3 -4 -2
- c) -2 -4 -1 -0
- d) -1 -2 -3 -4

✓ **Verified Answer:** `Option D`

Problem 18 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q055 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
```

- a) 6453210
- b) 0123456
- c) 1265340
- d) 0612354

✓ **Verified Answer:** `Option B`

Problem 19 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q057 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
```

- a) 4 False
- b) 3 False
- c) 2 False
- d) 1 False

✓ **Verified Answer:** `Option D`

Problem 20 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q058 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
How many times will the loop
execute?
for val=0 to 3 do
val=2*val
val- -
end-for
```

- a) -1
- b) 1
- c) Infinite Loop
- d) Infinite

✓ **Verified Answer:** `Option C`

Problem 21 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q059 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option B`

Problem 22 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q060 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
```

- a) 0 1
- b) 1 2
- c) 2 3
- d) 3 4

✓ **Verified Answer:** `Option A`

Problem 23 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q061 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option C`

Problem 24 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q062 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end – for
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 25 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q063 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
```

- a. 32
- b. 34
- c. 36
- d. 38

✓ **Verified Answer:** `Option A`

Problem 26 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q071 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For var 0 to 5 do
If var%2==0 and var/2==0 then do
Display var
End if
End for
```

- a. 0
- b. 1
- c. 2
- d. 3

✓ **Verified Answer:** `Option B`

Problem 27 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q072 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output when num
= 3 and values passed are 5,1,8
Set integer res=0
For c = 1 to num do
Input value
res+=value
- - res
End for
Display res
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** `Option C`

Problem 28 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q073 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set integer marks = 30
switch(marks)
Case 30: marks=25
Case 25: marks=20
Default: marks=50
Break
End switch
Display marks
```

- a. 10
- b. 30
- c. 50
- d. 70

✓ **Verified Answer:** `Option B`

Problem 29 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q074 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
public static void main(String[]
args) {
    double n= 10;
       System.out.println(n/0);
     }
}
```

- a. Error
- b. Infinity
- c. Exception
- d. Zero

✓ **Verified Answer:** `Option A`

Problem 30 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q076 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
    Public static void main(string[]args) {

Int n= 257n;



System.out.printIn(b);
}
}
```

- a. 1
- b. -128
- c. -1
- d. 128

✓ **Verified Answer:** `Option A`

Problem 31 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q077 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{

Public static void
main(String[]args) {

Int n=10;


System.out.print(n);


If(n==10)


{


   N=20;


   System.out.printIn(n);

}
}
```

- a. 10 20 10
- b. 10 20 20
- c. 10 10 20
- d. Error

✓ **Verified Answer:** `Option B`

Problem 32 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q078 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{

Public static void main(string[]args)
{

Int maximum = 10

  System.out.printIn(‘’maximum’’);
      }
}
```

- a. 10
- b. Maximum
- c. Error
- d. Exception

✓ **Verified Answer:** `Option B`

Problem 33 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q079 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int I=1;

white(i==1)
System.out.printIn(“i”);
}
}
```

- a. Infinite times 1
- b. Infinite times i
- c. i
- d. 1

✓ **Verified Answer:** `Option B`

Problem 34 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q080 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** `Option A`

Problem 35 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q081 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** `Option D`

Problem 36 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q082 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args) {

int i;

for(i=0,i++<=10;)

System.out.printIn(i);

  }
}
```

- a. 10
- b. 1 2 3 4 5 6 7 8 9 10 11
- c. Error
- d. 1 2 3 4 5 6 7 8 9 10

✓ **Verified Answer:** `Option B`

Problem 37 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q086 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

- a. 1 time
- b. 2 Time
- c. 3 Time
- d. 4 Time

✓ **Verified Answer:** `Option B`

Problem 38 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q087 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

- a. 62
- b. 65
- c. 75
- d. 75

✓ **Verified Answer:** `Option B`

Problem 39 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q088 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What would the following pseudo
code do?
Int x,y,z
If(x>=y AND x>=z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z>=y AND z>=x)
Print z
End if
```

- a. Find out the largest number
- b. Find out the smallest

✓ **Verified Answer:** `Option A`

Problem 40 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q091 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
```

- a. 5
- b. 7
- c. 9
- d. 11

✓ **Verified Answer:** `Option B`

Problem 41 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q092 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
```

- a. 0123456###
- b. 0123336###
- c. 0121216###
- d. 0000006###

✓ **Verified Answer:** `Option A`

Problem 42 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q094 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the following
code.
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

- a. Nothing will be printed
- b. Symbol not found error
- c. Runtime error
- d. Compile time error

✓ **Verified Answer:** `Option A`

Problem 43 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q095 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
John wants to go to different
location of a city in which he is
currently in. He has listed all of
them. However, he wants to visit
one location before visiting the
other. What application of graph he
uses to determine that location?
6

        /     \
1
5
   /               \
2                   4
```

- a. DFS
- b. BFS
- c. Djikstra's algorithm
- d. Topological sorting

✓ **Verified Answer:** `Option C`

Problem 44 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q098 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
what is the output of the following
code?
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

- a. -1,1,2,3,4
- b. 1,2,3,4,4
- c. 0,1,2,3,4,5
- d. 1,1,2,2,0

✓ **Verified Answer:** `Option A`

Problem 45 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q103 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
following code.
public class Main
{
public static void main(String args[])
{
int x=1 2
/ ;
if(x==0.5)
System.out.print(x+1);
System.out.print(x*2);
}
}
```

- a. 1.5
- b. 1
- c. 0
- d. Error

✓ **Verified Answer:** `Option C`

Problem 46 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q104 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
#include <stdio.h>
void f()
{
static int i;
++I;
printf("%d", i);

int main()
{
f();
f();
 f();
}
```

- a. 1 1 1
- b. 0 0 0
- c. 3 2 1
- d. 1 2 3

✓ **Verified Answer:** `Option D`

Problem 47 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q106 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet.
Integer n
Set n = 11
Integer arr[4]={10,11,1,12}
Arr[1]= arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
If(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a. 7
- b. 8
- c. 22
- d. 12

✓ **Verified Answer:** `Option D`

Problem 48 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q108 Source: 1. Pseudo Codes Technical ebook.pdf Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the code
snippet. int main()
{
int m=100;
{
int m;
for (m=0;m<25;m++)
}
printf("%d",m);
}
```

- a. 24
- b. 25
- c. 100
- d. Depends on compiler

✓ **Verified Answer:** `Option C`

Problem 49 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q109 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find out how many times
will “hi” be printed.
main()
{
int I=0;
do
{
i++;
print(“hi\n”);
}
while(i<2020);
}
```

- a. 1 time
- b. 2019 times
- c. 2021 times
- d. 2020 times

✓ **Verified Answer:** `Option D`

Problem 50 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q110 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
how many times will "abc"
be printed.
main()
{
int x;
for(x=-1; x<=10; x++)
{
if(x<5)


continue;
else
break;
printf("abc\n");
}
}
```

- a. Infinite times
- b. 11 times
- c. 0 times
- d. 10 times

✓ **Verified Answer:** `Option C`

Problem 51 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q122 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the
pseudo code. Integer a, b, c
Set a=5, b=3
For( each c from b to a)
If (a)
a=a-1 n
End if
If(b)
b =b-1
End if
End for
Print a+b
```

- a. 4
- b. 6
- c. 8
- d. 1

✓ **Verified Answer:** `Option A`