🏆 Infosys SE Elite Crack Vault — 09 Master Technical Ebook 145 Solved Vault Elite

🎯 Infosys Systems Engineer (SE) | 📊 101 Questions | 📅 5-6 Nov 2026 Drive | ⚡ 100% Pure SE Verified

---

Problem 01 • Bitwise Operators & Logic

🔥 MUST-SOLVE

`ID: SEC03_EBOOK_Q001` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();      }
```

- a) 0 0
- b) 5 5
- c) 0 5
- d) Run time error

✓ **Verified Answer:** `Option C`

Problem 02 • Bitwise Operators & Logic

🔥 MUST-SOLVE

`ID: SEC03_EBOOK_Q002` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
#include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main()
{
Point t1;
return 0;
}
```

- a) Constructor called
- b) Compile time error
- c) Run time error
- d) Blank line

✓ **Verified Answer:** `Option B`

Problem 03 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q003 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x ⩾ 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
 }
```

- a) 7 6 3
- b) 7 5 4
- c) 6 7 8
- d) 6 5 4

✓ **Verified Answer:** `Option A`

Problem 04 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q004 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Where are placed the list of
processes that are prepared to be
executed and waiting?
```

- a) Job queue
- b) Ready queue
- c) Execution queue
- d) Process queue

✓ **Verified Answer:** `Option B`

Problem 05 • Operating Systems & Systems Architecture

MUST-SOLVE

ID: SEC03_EBOOK_Q005 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Who among the following can
block the running process?
```

- a) Fork
- b) Read
- c) Down
- d) All of these

✓ **Verified Answer:** `Option D`

Problem 06 • Operating Systems & Systems Architecture

MUST-SOLVE

ID: SEC03_EBOOK_Q006 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following does not
interrupt the running process?
```

- a) Timer interrupt
- b) Device
- c) Power failure
- d) Scheduler process

✓ **Verified Answer:** `Option D`

Problem 07 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_EBOOK_Q007 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The \u0021 article referred to as a
```

- a) Unicode escape sequence
- b) Octal escape
- c) Hexadecimal
- d) Line feed

✓ **Verified Answer:** `Option A`

Problem 08 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_EBOOK_Q008 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is a valid
declaration of a char?
```

- a) char ch = '\utea';
- b) char ca = 'tea';
- c) char cr = \u0223;
- d) char cc = '\itea';

✓ **Verified Answer:** `Option A`

Problem 09 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_EBOOK_Q009 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is a valid
long literal?
```

- a) ABH8097
- b) L990023
- c) 904423
- d) 0xnf029L

✓ **Verified Answer:** `Option D`

Problem 10 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q010 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What does the expression float a =
35 / 0 return?
```

- a) 0
- b) Not a Number
- c) Infinity
- d) Run time exception

✓ **Verified Answer:** `Option C`

Problem 11 • OOP & Language Architecture

MUST-SOLVE

ID: SEC03_EBOOK_Q011 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which option is false about the
final keyword?
```

- a) A final method cannot be
- b) A final class cannot be extended.
- c) A final class cannot extend other
- d) A final method can be

✓ **Verified Answer:** `Option C&D`

Problem 12 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q012 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Construct post order Transversal
for the constructed tree with the
given
In-Order
and
Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

- a) 9 10 7 8 6
- b) 9 7 6 10 8
- c) 8 9 10 7 6
- d) 9 8 10 7 6

✓ **Verified Answer:** `Option A`

Problem 13 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_EBOOK_Q013 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program fragment?
int i = 263;
putchar(i);
```

- a) prints 263
- b) prints the ASCII equivalent of 263
- c) rings the bell
- d) prints garbage

✓ **Verified Answer:** `Option C`

Problem 14 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_EBOOK_Q014 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
statement?
printf (“%d”, 9/5);
```

- a) 1.8
- b) 1.0
- c) 2.0
- d) None of the these

✓ **Verified Answer:** `Option D`

Problem 15 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q015 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
int main() {
    int i = 5;
    printf("%d", i = ++i == 6);
return 0;
}
```

- a) 2
- b) 6
- c) 4
- d) 1

✓ **Verified Answer:** `Option D`

Problem 16 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q016 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following declarations
is invalid in C language?
```

- a) char *str = "campus monk is the
- b) char str[] = "campus monk is the
- c) char str[20] = "campus monk is the
- d) char[] str = "campus monk is the

✓ **Verified Answer:** `Option D`

Problem 17 • Recursion & Function Call Stacks

MUST-SOLVE

`ID: SEC03_EBOOK_Q017` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of this
program?
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf("%d", h);
   return 0;
}
```

- a) 1
- b) error: redeclaration of an
- c) h
- d) 3

✓ **Verified Answer:** `Option B`

Problem 18 • Loops & Conditional Control Flow

MUST-SOLVE

`ID: SEC03_EBOOK_Q018` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
What will be the output of this
program?
main ()
{
 if (5 < '5')
        printf("5")
 else
        printf(" NOT EQUAL TO 5.")
}
```

- a) ENQ
- b) 5
- c) I
- d) Not equal to 5

✓ **Verified Answer:** `Option B`

Problem 19 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q019 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudo code?
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

- a) 5
- b) 7
- c) 9
- d) 12

✓ **Verified Answer:** `Option A`

Problem 20 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q020 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

- a) 6 6 6
- b) 6 5 6
- c) 5 5 5
- d) 6 5 4

✓ **Verified Answer:** `Option D`

Problem 21 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q021 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
If the sequence of operations are
performed on a stack, the sequence
of pop will be?
Push(1), Push(2), Pop(), Push(1),
Push(2), Pop(), Pop(), Pop(),
Push(2), Pop().
```

- a) 2 2 1 1 2
- b) 2 2 1 2 2
- c) 2 1 2 2 1
- d) 2 1 2 2 2

✓ **Verified Answer:** `Option A`

Problem 22 • Technical Programming Concepts

MUST-SOLVE

ID: SEC03_EBOOK_Q022 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
In an empty BST, insert the
following elements in a similar
sequence. Which element will be at
lowest level?
105     95    122    99    97   120
```

- a) 95
- b) 97
- c) 99
- d) 120

✓ **Verified Answer:** `Option B`

Problem 23 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q023 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The concatenation of two lists is to
be performed in O(1) time. Which of
the following implementation of a
list should be used?
```

- a) Singly linked list
- b) Doubly linked list
- c) Circular doubly linked list
- d) Array implementation of list

✓ **Verified Answer:** `Option C`

Problem 24 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q024 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following sequence
can be obtained in the output (in
same
order)
using
a
stack
assuming that the input is in the
sequence 1,2,3,4,5 order?
```

- a) 3,4,5,1,2
- b) 3,4,5,2,1
- c) 1,5,2,3,4
- d) 5,4,3,1,2

✓ **Verified Answer:** `Option B`

Problem 25 • Operating Systems & Systems Architecture

MUST-SOLVE

ID: SEC03_EBOOK_Q025 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Let A be a square matrix of size
nxn.
Consider
the
following
program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp - C
}for i = 1 to n do
for j = 1 to n do
Output (A[i][j]);
```

- a) The matrix A itself
- b) Transpose of matrix A
- c) Adding 100 to the upper diagonal
- d) None of the above

✓ **Verified Answer:** `Option A`

Problem 26 • Recursion & Function Call Stacks

🔥 MUST-SOLVE

`ID: SEC03_EBOOK_Q026` `Source: 1. Pseudo Codes Technical ebook.pdf` `Level: Infosys SE Standard`

/ Code Snippet

```
The value of j at the end of the
execution of the following pseudo
code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

- a) 10
- b) 4
- c) 6
- d) 7

✓ **Verified Answer:** `Option A`

Problem 27 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q027 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What is printed by the print
statement in the program P1
assuming
call
by
reference
parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z
}
```

- a) 10,3
- b) 31,3
- c) 27,7
- d) None of these

✓ **Verified Answer:** `Option B`

Problem 28 • Recursion & Function Call Stacks

MUST-SOLVE

ID: SEC03_EBOOK_Q028 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
The value returned by the following
function for f(1) is?
int f(int n)
{
static int i =1;
if (n⩾5) return n;
n=n + i ;
i++;
return f(n);
}
```

- a) 5
- b) 6
- c) 7
- d) 8

✓ **Verified Answer:** `Option C`

Problem 29 • Loops & Conditional Control Flow

🔥 MUST-SOLVE

ID: SEC03_EBOOK_Q029 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
Print n
```

- a) 7
- b) 18
- c) 22
- d) 2

✓ **Verified Answer:** `Option D`

Problem 30 • Loops & Conditional Control Flow

MUST-SOLVE

ID: SEC03_EBOOK_Q030 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if
Print x+y+z
```

- a) 31
- b) 11
- c) 42
- d) 30

✓ **Verified Answer:** `Option D`

Problem 31 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q031 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer x,y,z
Set x=1, y=8,z=2
if ( x^y && x^y && x^y^z)
x=1
End if
Print x+y+z
```

- a) 11
- b) 13
- c) 16
- d) 9

✓ **Verified Answer:** `Option A`

Problem 32 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q032 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code.
Integer p,q,r
Set p=11, q=1, r=1
If(q^p > 2 || q>p)
If (p>q)
p=1
Else
q=10
End if
End if
Print p+q+r
```

- a) 13
- b) 10
- c) 15
- d) 3

✓ **Verified Answer:** `Option A`

Problem 33 • Bitwise Operators & Logic

MUST-SOLVE

ID: SEC03_EBOOK_Q033 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code:
Integer x, y, z
Set x=8,y=7, z=10
if ( (x-y) > (y-x) )
z= 7+y
if ( (y+z) < (x-y) )
y = 3 + x
End if
z= (4 ^ 11) & y
End if
Print x + y + z
```

- a) 22
- b) 24
- c) 26
- d) 28

✓ **Verified Answer:** `Option A`

Problem 34 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q034 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Post order traversal of a tree is: V R
T S U Q P Which of the following
vertices will occupy positions 2 and
3?
```

- a) S, R
- b) F, G
- c) U, T
- d) X, Y

✓ **Verified Answer:** `Option A`

Problem 35 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q035 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which cannot be the number of
vertices in a full binary tree?
```

- a) 3
- b) 7
- c) 15
- d) 30

✓ **Verified Answer:** `Option D`

Problem 36 • Data Structures, Trees & Pointers

MUST-SOLVE

ID: SEC03_EBOOK_Q036 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Sam sorts an array by repeatedly
swapping the adjacent elements if
they are in wrong order. Identify the
sorting technique used.
```

- a) Merge Sort
- b) Selection Sort
- c) Bubble Sort
- d) Insertion Sort

✓ **Verified Answer:** `Option C`

Problem 37 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q037 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a, b, c
Set b = 10, a=1
If  (0)
a = a - 1
else
a = b + 1
b = a - 1
a = a - 1
end if
print a
```

- a) 3
- b) 5
- c) 10
- d) 11

✓ **Verified Answer:** `Option C`

Problem 38 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q038 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
Integer a
String str1
Set str1 = “momo”
For (each a from 1 to 2)
Str1 = str1 + “mm”
End for
Print (stringLength (str1))
```

- a) 7
- b) 4
- c) 6
- d) 8

✓ **Verified Answer:** `Option D`

Problem 39 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q039 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Consider a stack of integers. The
stack is allocated 7 memory cells:
STACK: 12, 34, 66, 79, _, _, _.
Now
consider
the
following
operations:
A. PUSH (STACK, 8)
B. PUSH (STAC, 54)
C. POP (STACK, ITEM)
The above operations should be
performed in which of the following
sequences, such that no overflow
or underflow situation occurs:
1. B→ A→ C
2. A→ B→ C
3. C→ B→ A
```

- a) Only 1
- b) Any of them
- c) Only 2
- d) Only 3

✓ **Verified Answer:** `Option B`

Problem 40 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q040 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
x=1 and y=4.
Integer fun (Integer x, Integer y)

If (y > x)


return 1+ fun (x, y-1)

End if

return x + 1
End function fun()
```

- a) 5
- b) -15
- c) 14
- d) 22

✓ **Verified Answer:** `Option A`

Problem 41 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q041 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
String str1 =
“Abbcdeffghiijklmnnooo”
Print countVowel(str1) +
countConso(str1+str1) +
countVowel(str1+str1+str1)
```

- a) 49
- b) 42
- c) 56
- d) 35

✓ **Verified Answer:** `Option C`

Problem 42 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q042 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the output of the following
pseudo code, if function is called for
a=1 and b=4.
Integer fun (Integer a, Integer b)

a = (a^a) & (a+a)

b = (a^a) & (a+a)

return a + b
End function fun()
```

- a) 7
- b) 8
- c) 0
- d) -5

✓ **Verified Answer:** `Option C`

Problem 43 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q043 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c
Set a =4, b=5, c= 3
B = 3 + c
a = b & a
c = c + b
a = a + b
Print a + b + c
```

- a) 20
- b) 25
- c) 30
- d) 35

✓ **Verified Answer:** `Option B`

Problem 44 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q044 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For k= 3 || j=4
Integer func(integer k, integer j)
If (k equals 1 or k equals 0)
Return 1
Else
Return func(k-1, j-1) + func(k-2,
j+3)
End if
End function func
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option C`

Problem 45 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q045 Source: 1. Pseudo Codes Technical ebook.pdf Level: Infosys SE Standard

/ Code Snippet

```
Integer x,y,z
x = -3, y=0
If(y-2<2)
For(each z from 0 to(3-2))
x=x+(y-3)
End for
End if

If(1)
For(each z from 0 to(3-2))
x=x+(y+5)
End for
End if

Print x+y
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option A`

Problem 46 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q046 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
#include<stdio.h>
int main()
{
int a = 11, b=4, c=3;
b=≠ !a;
c = !!a;
printf("%d %d", b,c);
return 0;
}
```

- a) 1,1
- b) 2,1
- c) 3,1
- d) 4,1

✓ **Verified Answer:** `Option D`

Problem 47 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q047 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For a B- tree of order 6, to be a
multi-way search tree, each non
root node has at least how many
Non empty Children?
```

- a) 3
- b) 4
- c) 5
- d) 6

✓ **Verified Answer:** `Option A`

Problem 48 • Operating Systems & Systems Architecture

CORE SE

ID: SEC03_EBOOK_Q048 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Evaluate the given postfix
expression: 1 2 + 3 * 4 2 - 3 1 + * -
```

- a) 3
- b) 1
- c) 0
- d) 2

✓ **Verified Answer:** `Option B`

Problem 49 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q049 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
If you are using bubble sort to sort
the given numbers in ascending
order, then find out the minimum
number of swaps required.
10, 7, 5, 8, 9
```

- a) 7
- b) 6
- c) 5
- d) 4

✓ **Verified Answer:** `Option B`

Problem 50 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q050 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find out the array representation of
the given min-heap, if the value 25
is inserted in it.
10,15,30,40,50,100
```

- a) 10,15,25,50,40,100,30
- b) 10,15, 25,40,50,100,30
- c) 15,10,25,40,50,100,30
- d) 10,15,25,40,50,30,100

✓ **Verified Answer:** `Option B`

Problem 51 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q051 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is not an
array representation of max heap?
1. 31, 27, 23, 17, 13, 11
2. 10, 5, 3, 2, 4
3. 12, 15, 17, 18, 19
```

- a) Only 1
- b) Only 3
- c) Only 2 and 3
- d) Only 1 and 3

✓ **Verified Answer:** `Option B`

Problem 52 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q052 Source: 1. Pseudo Codes Technical ebook.pdf Level: Infosys SE Standard

/ Code Snippet

```
Integer a,b,c
Set a=7, b=7, c=4
For(each c from 4 to 7)
b=2+a
b=(b+11)+c
a=(4+8)+a
End for
a=4+a
Print a+b
```

- a) 122
- b) 127
- c) 118
- d) 131

✓ **Verified Answer:** `Option A`

Problem 53 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q053 Source: 1. Pseudo Codes Technical ebook.pdf Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
function val: integer
return (0)
end-function
function main()
int x=val(10)
display x
end-function
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 54 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q054 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer y=0
for z=0 to 4-1 step1 do
display - y
end-for
```

- a) -3 -1 -0 -2
- b) -1 -3 -4 -2
- c) -2 -4 -1 -0
- d) -1 -2 -3 -4

✓ **Verified Answer:** `Option D`

Problem 55 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q055 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for x=0 to 27%7 step 1 do
display x
end-for
```

- a) 6453210
- b) 0123456
- c) 1265340
- d) 0612354

✓ **Verified Answer:** `Option B`

Problem 56 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q056 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer array=[2,4,0,1,6,0]
Set integer res=[2]/array[4];
display res
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 57 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q057 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
while(1*1*1== 1*1*1)
display false
break
end-while
```

- a) 4 False
- b) 3 False
- c) 2 False
- d) 1 False

✓ **Verified Answer:** `Option D`

Problem 58 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q058 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
How many times will the loop
execute?
for val=0 to 3 do
val=2*val
val- -
end-for
```

- a) -1
- b) 1
- c) Infinite Loop
- d) Infinite

✓ **Verified Answer:** `Option C`

Problem 59 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q059 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
Set integer a=1
Set integer b=-1
Set integer c=0
display (a or b and c)
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option B`

Problem 60 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q060 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of following
pseudocode?
for i=0 to 6/5 step 1 do
display i
end-for
```

- a) 0 1
- b) 1 2
- c) 2 3
- d) 3 4

✓ **Verified Answer:** `Option A`

Problem 61 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q061 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set integer m =3
Set integer n=5
Switch(m/m%n)
Case1: m=m-n
Case2: m=m+n
Case3: m=m*n
Case4: m=m/n
Default: m=m
End switch
Display m
```

- a) 1
- b) 2
- c) 3
- d) 4

✓ **Verified Answer:** `Option C`

Problem 62 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q062 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output of the
following pseudocode?
For i=0 to 4 do
If i==i+++- -I then do
display i
end - if
end - for
```

- a) 0
- b) 1
- c) 2
- d) 3

✓ **Verified Answer:** `Option A`

Problem 63 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q063 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer pp, qq, rr
Set pp=3, qq=7, rr=8
pp = 9 +rr
If ((pp+rr) < (rr-pp)
qq = (qq + rr) +pp
End if
Print pp+qq+rr
```

- a. 32
- b. 34
- c. 36
- d. 38

✓ **Verified Answer:** `Option A`

Problem 64 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q064 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer a, b, c
Set a=1, b=7, c=6
if((b-a) < (c+b))
c= 8+b
c= (a^7)+a
a= (c+b)^c
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

✓ **Verified Answer:** `Option D`

Problem 65 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q065 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
a=9, b=3, c=8
a=(5+7)+c
if((c^7) < (5+c))
a= 2+c
b=3+c
a=c+b
End if
Print a+b+c
```

- a. 30
- b. 31
- c. 32
- d. 33

✓ **Verified Answer:** `Option B`

Problem 66 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q066 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer p, q, r
Set p=7, q=3, r=4
if(q>r && (q^3)<3)
q= (5+1)+r
End if
Print p+q+r
```

- a. 11
- b. 14
- c. 19
- d. 22

✓ **Verified Answer:** `Option B`

Problem 67 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q067 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer a,b,c
Set a=6, b=4, c=7
if(c<b || (9+5)<b)
b= (a+4)+c
c=(c+c)+a
End if
Print a+b+c
```

- a. 15
- b. 16
- c. 17
- d. 18

✓ **Verified Answer:** `Option C`

Problem 68 • Recursion & Function Call Stacks

CORE SE

ID: SEC03_EBOOK_Q068 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer funn(integer a, integer b,
integer c)
Set a=5, b=7, c=9
if((a+b)<c)
a= a+c
b= (c+a)+c
c= (9+9)+a
End if
Print a+b+c
```

- a. 20
- b. 21
- c. 22
- d. 23

✓ **Verified Answer:** `Option B`

Problem 69 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q069 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Integer p,q,r
Set p=9, q=6, r=8
For (each I from 3 to 6)
p= (p^r)+q
if((3+p+r)<(r-q))
p= 1+q
q= 2+q
End if
End for
Print p+q
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** `Option Ans`

Problem 70 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q070 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
[Nested conditional execution trace]
```

- a. Option A
- b. Option B
- c. Option C
- d. Option D

✓ **Verified Answer:** `Option A`

Problem 71 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q071 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
For var 0 to 5 do
If var%2==0 and var/2==0 then do
Display var
End if
End for
```

- a. 0
- b. 1
- c. 2
- d. 3

✓ **Verified Answer:** `Option B`

Problem 72 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q072 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What will be the output when num
= 3 and values passed are 5,1,8
Set integer res=0
For c = 1 to num do
Input value
res+=value
- - res
End for
Display res
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** `Option C`

Problem 73 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q073 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set integer marks = 30
switch(marks)
Case 30: marks=25
Case 25: marks=20
Default: marks=50
Break
End switch
Display marks
```

- a. 10
- b. 30
- c. 50
- d. 70

✓ **Verified Answer:** `Option B`

Problem 74 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q074 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
public static void main(String[]
args) {
    double n= 10;
       System.out.println(n/0);
     }
}
```

- a. Error
- b. Infinity
- c. Exception
- d. Zero

✓ **Verified Answer:** `Option A`

Problem 75 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q075 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What makes java portable and
secure?
```

- a. Byte code
- b. Source code
- c. Applet
- d. Spring bot

✓ **Verified Answer:** `Option A`

Problem 76 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q076 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{
    Public static void main(string[]args) {

Int n= 257n;



System.out.printIn(b);
}
}
```

- a. 1
- b. -128
- c. -1
- d. 128

✓ **Verified Answer:** `Option A`

Problem 77 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q077 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{

Public static void
main(String[]args) {

Int n=10;


System.out.print(n);


If(n==10)


{


   N=20;


   System.out.printIn(n);

}
}
```

- a. 10 20 10
- b. 10 20 20
- c. 10 10 20
- d. Error

✓ **Verified Answer:** `Option B`

Problem 78 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q078 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main
{

Public static void main(string[]args)
{

Int maximum = 10

  System.out.printIn(‘’maximum’’);
      }
}
```

- a. 10
- b. Maximum
- c. Error
- d. Exception

✓ **Verified Answer:** `Option B`

Problem 79 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q079 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int I=1;

white(i==1)
System.out.printIn(“i”);
}
}
```

- a. Infinite times 1
- b. Infinite times i
- c. i
- d. 1

✓ **Verified Answer:** `Option B`

Problem 80 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q080 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++I,j=i+1)

sum+=i;

System.out.printIn(sum);
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** `Option A`

Problem 81 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q081 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args){

int sum =0;

for(int i=0,j=0; i<5 && j<5;
++i,j=i+1)
{

Sum= sum+=i;



System.out.printIn(sum);
}
   }
}
```

- a. 10
- b. 0 1 3 6
- c. 6
- d. None

✓ **Verified Answer:** `Option D`

Problem 82 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q082 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
public class Main {
public static void main(string[]args) {

int i;

for(i=0,i++≤10;)

System.out.printIn(i);

  }
}
```

- a. 10
- b. 1 2 3 4 5 6 7 8 9 10 11
- c. Error
- d. 1 2 3 4 5 6 7 8 9 10

✓ **Verified Answer:** `Option B`

Problem 83 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q083 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following is not a part
of binary operator?
```

- a. Assignment operator
- b. Arithmetic operator
- c. Logical operator
- d. Relational operator

✓ **Verified Answer:** `Option A`

Problem 84 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q084 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1 b=7 c=13
c=(b+1)^a
a=(5&2)&c
a=(b+7)+b
Print a+b+c
```

- a. 32
- b. 35
- c. 37
- d. 39

✓ **Verified Answer:** `Option C`

Problem 85 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q085 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
String strl=”heee” str2=”eh”
Print
countconso(substring(strl+str2,1,4)
)
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** `Option B`

Problem 86 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q086 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
How many times campus monk will
be printed?
Setk=1, p=4
Int j=p+k/2
If(j equals p)
Print “campus monk”
End if
J=p+k/5
If(j not equal p)
Print “campus monk”
end if
Print”campus monk”
```

- a. 1 time
- b. 2 Time
- c. 3 Time
- d. 4 Time

✓ **Verified Answer:** `Option B`

Problem 87 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q087 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set f=9 k=55
J=f+k/8
If(j+1>8)
f=f+1
Else
k=k+1
Print f+k
```

- a. 62
- b. 65
- c. 75
- d. 75

✓ **Verified Answer:** `Option B`

Problem 88 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q088 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
What would the following pseudo
code do?
Int x,y,z
If(x ⩾ y AND x ⩾ z)
Print x
End if
If(y>x Andy=z)
Print y
End if
If(z ⩾ y AND z ⩾ x)
Print z
End if
```

- a. Find out the largest number
- b. Find out the smallest

✓ **Verified Answer:** `Option A`

Problem 89 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q089 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int a,b,c
Set a=1, c=1
For(each b from(a&2)to(4&8))
b=b>>1
Print b+c
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** `Option A`

Problem 90 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q090 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set m=1
Int a[3]={1,2,9}
For each j from 0 to 2
m=m^a[j]
Print m
```

- a. 10
- b. 11
- c. 12
- d. 13

✓ **Verified Answer:** `Option B`

Problem 91 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q091 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Set m=2
Int a[3]={1,1,3,1}
For each j from 1 to 3
m=m+a[i]
Print m
```

- a. 5
- b. 7
- c. 9
- d. 11

✓ **Verified Answer:** `Option B`

Problem 92 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q092 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Int count
for(each count from 0 to 9)
print("#")
if(count>6)
Continue
Print count
End for
```

- a. 0123456###
- b. 0123336###
- c. 0121216###
- d. 0000006###

✓ **Verified Answer:** `Option A`

Problem 93 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q093 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
int main()
{
Int a=0;
a=5<2?4:3;
printf("%d",a);
```

- a. 1
- b. 2
- c. 3
- d. 4

✓ **Verified Answer:** `Option C`

Problem 94 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q094 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
find the output of the following
code.
public class Main
{
public static void main(String[] args)
{
int $=5;
}
}
```

- a. Nothing will be printed
- b. Symbol not found error
- c. Runtime error
- d. Compile time error

✓ **Verified Answer:** `Option A`

Problem 95 • Loops & Conditional Control Flow

CORE SE

ID: SEC03_EBOOK_Q095 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
John wants to go to different
location of a city in which he is
currently in. He has listed all of
them. However, he wants to visit
one location before visiting the
other. What application of graph he
uses to determine that location?
6

        /     \
1
5
   /               \
2                   4
```

- a. DFS
- b. BFS
- c. Djikstra's algorithm
- d. Topological sorting

✓ **Verified Answer:** `Option C`

Problem 96 • Operating Systems & Systems Architecture

CORE SE

ID: SEC03_EBOOK_Q096 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which among the following is a
server-based model?
```

- a. Request for information
- b. Cloud computing
- c. Total cost of
- d. Data validation routine

✓ **Verified Answer:** `Option B`

Problem 97 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q097 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Which of the following data
structure is used to convert
expression from one form to
another?
```

- a. Graph
- b. Stack
- c. Linked list
- d. Queue

✓ **Verified Answer:** `Option B`

Problem 98 • OOP & Language Architecture

CORE SE

ID: SEC03_EBOOK_Q098 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
what is the output of the following
code?
class Main()
{
public static void main(String args[])
{
int i, j, x=0;
for(i=0; i<5; i++)
for(j=0; j<5; j++)
{
x=(1+j-1)
System.out.print(x);
break;
}
}
System.out.print(x);
}
```

- a. -1,1,2,3,4
- b. 1,2,3,4,4
- c. 0,1,2,3,4,5
- d. 1,1,2,2,0

✓ **Verified Answer:** `Option A`

Problem 99 • Bitwise Operators & Logic

CORE SE

ID: SEC03_EBOOK_Q099 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the postfix of the given Infix
expression:
11+20/5*(20-15)^6^5
```

- a. 11 20 5/20 15-6^5^*+
- b. 11 21 5/20 15+6^5^*-
- c. 11 22 5/20 15-6^5^*-
- d. 20 11 5/20 15+5^6^*+

✓ **Verified Answer:** `Option A`

Problem 100 • Data Structures, Trees & Pointers

CORE SE

ID: SEC03_EBOOK_Q100 | Source: 1. Pseudo Codes Technical ebook.pdf | Level: Infosys SE Standard

/ Code Snippet

```
Find the pre order of the
given tree.
  A

        /         \
     B
          C
   /   \             /   \
D     E        F     G
          \         \
H       I
```

- a. ABDEHCFIG
- b. BASUEKDHS
- c. AABBLIKDMSD
- d. CAMPUSMONK

✓ **Verified Answer:** `Option A`

Problem 101 • Technical Programming Concepts

CORE SE

ID: SEC03_EBOOK_Q101 Source: 1. Pseudo Codes Technical ebook.pdf Level: Infosys SE Standard

/ Code Snippet

```
Which combination of
integer variables a, b and c makes
the variable m get the value 4 in
the following expression?
m= (a>b)?((a>c)?a:c):((b>c)?b:c)
```

- a. a=6, b=3, c=5
- b. a=6, b=5, C=3
- c. a=5, b=4, c=5
- d. a=3, b=4, C=2

✓ **Verified Answer:** `Option D`