INFOSYS SE PSEUDOCODE VAULT • COMPLETE PSEUDOCODE MASTER COMPENDIUM

All 5 Core Topics Combined • 100% Solved & Traced • Total Solved Questions: 238

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Operator Precedence

Q1. What will be the output of the following pseudocode?

```
Set Integer a = 18
Set Integer b = 5
Set Integer c = 2
display a - b * c + 6
```

(A) 10
(B) 14
(C) 16
(D) 19

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** Multiplication first: 18 – (5×2) + 6 = 14.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Arithmetic

Q2. What will be the output of the following pseudocode?

```
Set Integer x = 24
Set Integer y = 7
display (x / y) * y + (x % y)
```

(A) 21
(B) 24
(C) 25
(D) 28

Correct Answer: Option (B) : 24

■ **Step-by-Step Logic:** 24/7=3 and 24%7=3; 3×7+3 = 24.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Logical Operators

Q3. What will be the output of the following pseudocode?

```
Set Integer a = 12
Set Integer b = 7
Set Integer c = 5
display (a > b) and ((b - c) == 2)
```

(A) true
(B) false
(C) 2
(D) 12

Correct Answer: Option (A) : true

■ **Step-by-Step Logic:** 12>7 is true and 7–5=2 is true, so the result is true.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Logical Operators

Q4. What will be the output of the following pseudocode?

```
Set Integer x = 9
display (x % 2 == 0) or ((x > 5) and (x < 10))
```

(A) true
(B) false
(C) 9
(D) 0

Correct Answer: Option (A) : true

■ **Step-by-Step Logic:** First condition is false, but 9>5 and 9<10 are both true.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Bitwise XOR

Q5. What will be the output of the following pseudocode?

```
Set Integer a = 15
Set Integer b = 9
Set Integer c = 6
display (a ^ b) + c
```

(A) 8
(B) 10
(C) 12
(D) 14

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 15^9 = 6; 6+6 = 12.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Bitwise AND

Q6. What will be the output of the following pseudocode?

```
Set Integer a = 27
Set Integer b = 14
display (a & b) + (a % b)
```

(A) 19
(B) 21
(C) 23
(D) 25

Correct Answer: Option (C) : 23

■ **Step-by-Step Logic:** 27&14 = 10 and 27%14 = 13; total = 23.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Bitwise OR

Q7. What will be the output of the following pseudocode?

```
Set Integer a = 18
Set Integer b = 11
display (a | b) - (a & b)
```

(A) 21
(B) 23
(C) 25
(D) 27

Correct Answer: Option (C) : 25

■ **Step-by-Step Logic:** 18|11=27 and 18&11=2; 27–2=25.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: XOR + AND

Q8. What will be the output of the following pseudocode?

```
Set Integer a = 13
Set Integer b = 7
display (a ^ b) + (a & b)
```

(A) 13
(B) 15
(C) 17
(D) 19

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** 13^7=10 and 13&7=5; total = 15. Infosys Medium Pseudocode Practice • Page 33

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Pre/Post Increment

Q9. What will be the output of the following pseudocode?

```
Set Integer x = 4
Set Integer y = x++ + ++x
Set Integer z = y + x
display z
```

(A) 14
(B) 15
(C) 16
(D) 17

Correct Answer: Option (C) : 16

■ **Step-by-Step Logic:** x++ contributes 4 and makes x=5; ++x makes x=6 and contributes 6. y=10; z=10+6=16.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Post/Pre Decrement

Q10. What will be the output of the following pseudocode?

```
Set Integer x = 10
Set Integer y = --x
Set Integer z = y + x--
display z
```

(A) 16
(B) 17
(C) 18
(D) 19

Correct Answer: Option (C) : 18

■ **Step-by-Step Logic:** --x makes x=9, y=9; x-- contributes 9, then x becomes 8. z=18.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Relational Logic

Q11. What will be the output of the following pseudocode?

```
Set Integer p = 8
Set Integer q = 12
display (p + q > 20) and (q - p == 4)
```

(A) true
(B) false
(C) 4
(D) 20

Correct Answer: Option (B) : false

■ **Step-by-Step Logic:** p+q=20, so 20>20 is false. The second condition is true; false AND true = false.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Ternary Logic

Q12. What will be the output of the following pseudocode?

```
Set Integer a = 14
Set Integer b = 9
Set Integer m = (a % 2 == 0) ? a/2 : b*2
display m + b
```

(A) 14
(B) 16
(C) 18
(D) 21

Correct Answer: Option (B) : 16

■ **Step-by-Step Logic:** a is even, so m=7; 7+9=16.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Compound Assignment

Q13. What will be the output of the following pseudocode?

```
Set Integer x = 7
x = x * 3 - 4
x = x + (x % 5)
display x
```

(A) 18
(B) 19
(C) 20
(D) 21

Correct Answer: Option (B) : 19

■ **Step-by-Step Logic:** 7×3–4=17; 17%5=2; final x=19.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Operators

Q14. What will be the output of the following pseudocode?

```
Set Integer a = 20
Set Integer b = 6
display (a / b) + (a % b) * 2
```

(A) 5
(B) 7
(C) 9
(D) 11

Correct Answer: Option (B) : 7

■ **Step-by-Step Logic:** 20/6=3; 20%6=2; 3+2×2=7.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Left Shift

Q15. What will be the output of the following pseudocode?

```
Set Integer x = 11
Set Integer y = 2
display (x << y) - x
```

(A) 22
(B) 33
(C) 44
(D) 55

Correct Answer: Option (B) : 33

■ **Step-by-Step Logic:** 11<<2 = 44; 44–11=33.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Right Shift

Q16. What will be the output of the following pseudocode?

```
Set Integer x = 45
Set Integer y = 2
display (x >> y) + x % 4
```

(A) 10
(B) 11
(C) 12
(D) 13

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 45>>2 = 11; 45%4=1; total=12. Infosys Medium Pseudocode Practice • Page 34

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Left Shift in Expression

Q17. What will be the output of the following pseudocode?

```
Set Integer a = 6
Set Integer b = 3
display (a << b) / 4
```

(A) 8
(B) 10
(C) 12
(D) 16

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 6<<3=48; 48/4=12.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Right Shift in Expression

Q18. What will be the output of the following pseudocode?

```
Set Integer a = 50
display (a >> 1) - (a >> 3)
```

(A) 17
(B) 19
(C) 21
(D) 23

Correct Answer: Option (B) : 19

■ **Step-by-Step Logic:** 50>>1=25 and 50>>3=6; 25–6=19.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Shift + XOR

Q19. What will be the output of the following pseudocode?

```
Set Integer x = 9
display (x << 1) ^ x
```

(A) 19
(B) 23
(C) 27
(D) 31

Correct Answer: Option (C) : 27

■ **Step-by-Step Logic:** 9<<1=18; 18 XOR 9 = 27.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + AND

Q20. What will be the output of the following pseudocode?

```
Set Integer x = 29
display (x >> 2) & 7
```

(A) 5
(B) 6
(C) 7
(D) 8

Correct Answer: Option (C) : 7

■ **Step-by-Step Logic:** 29>>2=7; 7 AND 7 = 7.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Double Shift

Q21. What will be the output of the following pseudocode?

```
Set Integer x = 7
Set Integer y = (x << 2)
display y >> 1
```

(A) 7
(B) 12
(C) 14
(D) 28

Correct Answer: Option (C) : 14

■ **Step-by-Step Logic:** 7<<2=28; 28>>1=14.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift and Modulo

Q22. What will be the output of the following pseudocode?

```
Set Integer x = 37
display (x >> 1) % 6
```

(A) 0
(B) 1
(C) 2
(D) 3

Correct Answer: Option (A) : 0

■ **Step-by-Step Logic:** 37>>1=18; 18%6=0.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift Condition

Q23. What will be the output of the following pseudocode?

```
Set Integer x = 23
if ((x >> 2) >= 5)
display x - 3
else
display x + 3
end-if
```

(A) 20
(B) 23
(C) 26
(D) 28

Correct Answer: Option (A) : 20

■ **Step-by-Step Logic:** 23>>2=5, so the condition is true and 23–3=20.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + Arithmetic

Q24. What will be the output of the following pseudocode?

```
Set Integer a = 14
Set Integer b = 2
display (a << b) - (a >> b)
```

(A) 51
(B) 53
(C) 55
(D) 57

Correct Answer: Option (B) : 53

■ **Step-by-Step Logic:** 14<<2=56; 14>>2=3; 56–3=53. Infosys Medium Pseudocode Practice • Page 35

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift Chain

Q25. What will be the output of the following pseudocode?

```
Set Integer x = 3
x = x << 2
x = x >> 1
x = x << 1
display x
```

(A) 6
(B) 10
(C) 12
(D) 24

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 3→12→6→12.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + OR

Q26. What will be the output of the following pseudocode?

```
Set Integer x = 5
display (x << 2) | 3
```

(A) 19
(B) 20
(C) 23
(D) 24

Correct Answer: Option (C) : 23

■ **Step-by-Step Logic:** 5<<2=20; 20|3=23.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + XOR

Q27. What will be the output of the following pseudocode?

```
Set Integer x = 12
display (x >> 1) ^ 5
```

(A) 1
(B) 3
(C) 5
(D) 7

Correct Answer: Option (B) : 3

■ **Step-by-Step Logic:** 12>>1=6; 6 XOR 5 = 3.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Bit Test with Shift

Q28. What will be the output of the following pseudocode?

```
Set Integer x = 40
display (x >> 3) & 1
```

(A) 0
(B) 1
(C) 2
(D) 5

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** 40>>3=5; 5 AND 1 = 1.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shifted Difference

Q29. What will be the output of the following pseudocode?

```
Set Integer a = 31
display (a << 1) - (a >> 2)
```

(A) 54
(B) 55
(C) 56
(D) 57

Correct Answer: Option (B) : 55

■ **Step-by-Step Logic:** 31<<1=62; 31>>2=7; 62–7=55.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: For Loop with Condition

Q30. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 1 to 10 step 1 do
if (i % 3 != 0)
s = s + i
end-if
end-for
display s
```

(A) 30
(B) 37
(C) 42
(D) 45

Correct Answer: Option (B) : 37

■ **Step-by-Step Logic:** Total 1..10=55; multiples of 3 are 3+6+9=18; 55−18=37.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Nested Loop

Q31. What will be the output of the following pseudocode?

```
Set Integer c = 0
for i = 1 to 4 step 1 do
for j = 1 to 5 step 1 do
if (i + j == 6)
c = c + 1
end-if
end-for
end-for
display c
```

(A) 2
(B) 3
(C) 4
(D) 5

Correct Answer: Option (C) : 4

■ **Step-by-Step Logic:** Pairs are (1,5),(2,4),(3,3),(4,2): 4.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Nested Loop Sum

Q32. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 1 to 3 step 1 do
for j = 1 to i + 1 step 1 do
s = s + j
end-for
end-for
display s
```

(A) 17
(B) 18
(C) 19
(D) 20

Correct Answer: Option (C) : 19

■ **Step-by-Step Logic:** For i=1,2,3 the inner sums are 3,6,10; total=19. Infosys Medium Pseudocode Practice • Page 36

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: While Loop

Q33. What will be the output of the following pseudocode?

```
Set Integer x = 5
Set Integer s = 0
while (x <= 25)
s = s + x
x = x + 5
end-while
display s
```

(A) 50
(B) 60
(C) 75
(D) 80

Correct Answer: Option (C) : 75

■ **Step-by-Step Logic:** 5+10+15+20+25=75.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Break in Nested Loop

Q34. What will be the output of the following pseudocode?

```
Set Integer c = 0
for i = 1 to 4 step 1 do
for j = 1 to 4 step 1 do
if (j == 3)
break
end-if
c = c + 1
end-for
end-for
display c
```

(A) 4
(B) 6
(C) 8
(D) 12

Correct Answer: Option (C) : 8

■ **Step-by-Step Logic:** The inner loop adds 1 for j=1 and j=2, then breaks at j=3. 4×2=8.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Continue

Q35. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 1 to 8 step 1 do
if (i % 3 == 0)
continue
end-if
s = s + i
end-for
display s
```

(A) 24
(B) 27
(C) 30
(D) 33

Correct Answer: Option (B) : 27

■ **Step-by-Step Logic:** 1..8 sum=36; skip 3 and 6, so 36–9=27.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Reverse Loop

Q36. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 12 to 2 step -2 do
s = s + i / 2
end-for
display s
```

(A) 18
(B) 21
(C) 24
(D) 27

Correct Answer: Option (B) : 21

■ **Step-by-Step Logic:** Values of i/2: 6,5,4,3,2,1; sum=21.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop with Changing Step

Q37. What will be the output of the following pseudocode?

```
Set Integer i = 1
Set Integer s = 0
while (i < 20)
s = s + i
i = i * 2 + 1
end-while
display s
```

(A) 24
(B) 26
(C) 28
(D) 30

Correct Answer: Option (B) : 26

■ **Step-by-Step Logic:** i values are 1,3,7,15; sum=26.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Nested Loop Count

Q38. What will be the output of the following pseudocode?

```
Set Integer c = 0
for i = 1 to 5 step 1 do
for j = i to 5 step 1 do
c = c + 1
end-for
end-for
display c
```

(A) 10
(B) 12
(C) 15
(D) 20

Correct Answer: Option (C) : 15

■ **Step-by-Step Logic:** Counts are 5+4+3+2+1=15.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop with Modulo

Q39. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 2 to 14 step 2 do
if (i % 4 == 0)
s = s + i
end-if
end-for
display s
```

(A) 12
(B) 16
(C) 20
(D) 24

Correct Answer: Option (D) : 24

■ **Step-by-Step Logic:** Multiples of 4 are 4,8,12; sum=24.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Nested Conditional Loop

Q40. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 1 to 5 step 1 do
if (i % 2 == 1)
for j = 1 to i step 2 do
s = s + j
end-for
end-if
end-for
display s
```

(A) 12
(B) 14
(C) 16
(D) 18

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** For i=1,3,5 the inner sums are 1,4,9; total=14. Infosys Medium Pseudocode Practice • Page 37

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop State

Q41. What will be the output of the following pseudocode?

```
Set Integer x = 3
for i = 1 to 4 step 1 do
x = x + i
x = x - 1
end-for
display x
```

(A) 8
(B) 9
(C) 10
(D) 11

Correct Answer: Option (B) : 9

■ **Step-by-Step Logic:** Each iteration changes x by i–1. Total change=0+1+2+3=6; final x=9.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop Product

Q42. What will be the output of the following pseudocode?

```
Set Integer p = 1
for i = 2 to 8 step 2 do
p = p * (i / 2)
end-for
display p
```

(A) 12
(B) 24
(C) 36
(D) 48

Correct Answer: Option (B) : 24

■ **Step-by-Step Logic:** Factors are 1,2,3,4; product=24.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: While + Modulo

Q43. What will be the output of the following pseudocode?

```
Set Integer n = 29
Set Integer c = 0
while (n > 0)
if (n % 2 == 1)
c = c + 1
end-if
n = n / 2
end-while
display c
```

(A) 2
(B) 3
(C) 4
(D) 5

Correct Answer: Option (B) : 3

■ **Step-by-Step Logic:** Binary 29 is 11101, containing four 1s.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Nested Loop Arithmetic

Q44. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 1 to 3 step 1 do
for j = 1 to 3 step 1 do
s = s + i * j
end-for
end-for
display s
```

(A) 12
(B) 18
(C) 24
(D) 36

Correct Answer: Option (D) : 36

■ **Step-by-Step Logic:** The double sum factorizes: (1+2+3)×(1+2+3)=6×6=36.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Break with Sum

Q45. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 2 to 12 step 2 do
s = s + i
if (s > 15)
break
end-if
end-for
display s
```

(A) 12
(B) 18
(C) 20
(D) 24

Correct Answer: Option (B) : 18

■ **Step-by-Step Logic:** Running sums: 2,6,12,20; break after 20.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Continue with Product

Q46. What will be the output of the following pseudocode?

```
Set Integer p = 1
for i = 1 to 6 step 1 do
if (i % 2 == 0)
continue
end-if
p = p * i
end-for
display p
```

(A) 9
(B) 12
(C) 15
(D) 20

Correct Answer: Option (C) : 15

■ **Step-by-Step Logic:** Odd values 1,3,5 are multiplied: 1×3×5=15.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop with Shift

Q47. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 1 to 4 step 1 do
s = s + (i << 1)
end-for
display s
```

(A) 16
(B) 18
(C) 20
(D) 24

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** 2+4+6+8=20.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop with Right Shift

Q48. What will be the output of the following pseudocode?

```
Set Integer s = 0
for i = 8 to 32 step 8 do
s = s + (i >> 2)
end-for
display s
```

(A) 15
(B) 18
(C) 20
(D) 24

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** The shifted values are 2,4,6,8; sum=20. Infosys Medium Pseudocode Practice • Page 38

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Nested Loop with Break

Q49. What will be the output of the following pseudocode?

```
Set Integer c = 0
for i = 1 to 4 step 1 do
for j = 1 to 4 step 1 do
c = c + 1
if (c == 7)
break
end-if
end-for
end-for
display c
```

(A) 7
(B) 8
(C) 12
(D) 13

Correct Answer: Option (D) : 13

■ **Step-by-Step Logic:** The counter continues across outer iterations. It reaches 7, breaks the current inner loop, then continues; 4 more inner iterations occur, so final c=13.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Loop and Comparison

Q50. What will be the output of the following pseudocode?

```
Set Integer c = 0
for i = 1 to 9 step 1 do
if (i * i < 50)
c = c + 1
end-if
end-for
display c
```

(A) 6
(B) 7
(C) 8
(D) 9

Correct Answer: Option (B) : 7

■ **Step-by-Step Logic:** i=1..7 satisfy $i^2<50$; count=7.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Index Calculation

Q51. What will be the output of the following pseudocode?

```
Set Integer a = [4, 7, 2, 9, 5]
display a[a[2]] + a[1]
```

(A) 7
(B) 9
(C) 11
(D) 13

Correct Answer: Option (B) : 9

■ **Step-by-Step Logic:** a[2]=2, so a[a[2]]=a[2]=2; 2+7=9.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Transformation

Q52. What will be the output of the following pseudocode?

```
Set Integer a = [3, 5, 7, 9]
for i = 0 to 3 step 1 do
a[i] = a[i] + i
end-for
display a[3] - a[1]
```

(A) 3
(B) 4
(C) 5
(D) 6

Correct Answer: Option (D) : 6

■ **Step-by-Step Logic:** After updates, a=[3,6,9,12]; 12–6=6.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Maximum

Q53. What will be the output of the following pseudocode?

```
Set Integer a = [8, 3, 15, 6, 11]
Set Integer m = a[0]
for i = 1 to 4 step 1 do
if (a[i] > m)
m = a[i]
end-if
end-for
display m % 4
```

(A) 1
(B) 2
(C) 3
(D) 4

Correct Answer: Option (C) : 3

■ **Step-by-Step Logic:** Maximum is 15; 15%4=3.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Pair Sum

Q54. What will be the output of the following pseudocode?

```
Set Integer a = [2, 5, 8, 11]
Set Integer s = 0
for i = 0 to 2 step 1 do
s = s + a[i] + a[i+1]
end-for
display s
```

(A) 36
(B) 39
(C) 42
(D) 45

Correct Answer: Option (B) : 39

■ **Step-by-Step Logic:** Pairs: 7+13+19=39.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Conditional Update

Q55. What will be the output of the following pseudocode?

```
Set Integer a = [4, 7, 10, 13]
for i = 0 to 3 step 1 do
if (a[i] % 2 == 0)
a[i] = a[i] / 2
else
a[i] = a[i] + 1
end-if
end-for
display a[0] + a[1] + a[2] + a[3]
```

(A) 25
(B) 27
(C) 29
(D) 31

Correct Answer: Option (C) : 29

■ **Step-by-Step Logic:** Array becomes [2,8,5,14]; sum=29.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Reverse

Q56. What will be the output of the following pseudocode?

```
Set Integer a = [3, 6, 9, 12, 15]
display a[4] - a[0] + a[3] - a[1]
```

(A) 12
(B) 15
(C) 18
(D) 21

Correct Answer: Option (C) : 18

■ **Step-by-Step Logic:** 15–3+12–6=18. Infosys Medium Pseudocode Practice • Page 39

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Count

Q57. What will be the output of the following pseudocode?

```
Set Integer a = [5, 10, 15, 20, 25]
Set Integer c = 0
for i = 0 to 4 step 1 do
if (a[i] % 10 == 5)
c = c + 1
end-if
end-for
display c
```

(A) 2
(B) 3
(C) 4
(D) 5

Correct Answer: Option (B) : 3

■ **Step-by-Step Logic:** 5,15,25 satisfy the condition: 3.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Running Sum

Q58. What will be the output of the following pseudocode?

```
Set Integer a = [2, 4, 6, 8]
Set Integer s = a[0]
for i = 1 to 3 step 1 do
a[i] = a[i] + s
s = a[i]
end-for
display a[3]
```

(A) 16
(B) 20
(C) 24
(D) 30

Correct Answer: Option (B) : 20

■ **Step-by-Step Logic:** Running values become 2,6,12,20; a[3]=20.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Nested Index

Q59. What will be the output of the following pseudocode?

```
Set Integer a = [1, 3, 0, 2]
display a[a[3]] + a[a[1]]
```

(A) 1
(B) 2
(C) 3
(D) 4

Correct Answer: Option (B) : 2

■ **Step-by-Step Logic:** a[3]=2, so a[2]=0; a[1]=3, so a[3]=2; total=2.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Difference

Q60. What will be the output of the following pseudocode?

```
Set Integer a = [12, 5, 9, 4]
Set Integer m = a[0]
for i = 1 to 3 step 1 do
if (a[i] < m)
m = a[i]
end-if
end-for
display a[0] - m
```

(A) 6
(B) 7
(C) 8
(D) 9

Correct Answer: Option (C) : 8

■ **Step-by-Step Logic:** Minimum is 4; 12–4=8.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Shift

Q61. What will be the output of the following pseudocode?

```
Set Integer a = [3, 5, 7, 9]
display (a[3] >> 1) + (a[0] << 1)
```

(A) 8
(B) 10
(C) 12
(D) 14

Correct Answer: Option (B) : 10

■ **Step-by-Step Logic:** 9>>1=4; 3<<1=6; total=10.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array XOR

Q62. What will be the output of the following pseudocode?

```
Set Integer a = [6, 10, 12, 3]
display (a[0] ^ a[1]) + a[3]
```

(A) 13
(B) 15
(C) 17
(D) 19

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** 6^10=12; 12+3=15.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Pair Comparison

Q63. What will be the output of the following pseudocode?

```
Set Integer a = [4, 9, 6, 11]
Set Integer c = 0
for i = 0 to 2 step 1 do
if (a[i] < a[i+1])
c = c + 1
end-if
end-for
display c
```

(A) 1
(B) 2
(C) 3
(D) 4

Correct Answer: Option (B) : 2

■ **Step-by-Step Logic:** The true comparisons are 4<9 and 6<11, so count=2.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Sum with Step

Q64. What will be the output of the following pseudocode?

```
Set Integer a = [2, 4, 6, 8, 10, 12]
Set Integer s = 0
for i = 0 to 5 step 2 do
s = s + a[i]
end-for
display s
```

(A) 12
(B) 16
(C) 18
(D) 20

Correct Answer: Option (C) : 18

■ **Step-by-Step Logic:** Indices 0,2,4 give 2+6+10=18. Infosys Medium Pseudocode Practice • Page 40

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Array Rotation Logic

Q65. What will be the output of the following pseudocode?

```
Set Integer a = [10, 20, 30, 40]
Set Integer t = a[3]
for i = 3 to 1 step -1 do
a[i] = a[i-1]
end-for
a[0] = t
display a[1] + a[3]
```

(A) 30
(B) 40
(C) 50
(D) 60

Correct Answer: Option (B) : 40

■ **Step-by-Step Logic:** After right rotation: [40,10,20,30]; a[1]+a[3]=40.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Length

Q66. What will be the output of the following pseudocode?

```
Set String s = "PLACEMENT"
Set Integer n = stringLength(s)
display (n << 1) - 3
```

(A) 13
(B) 15
(C) 17
(D) 19

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** Length=9; 9<<1=18; 18–3=15.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Indexing

Q67. What will be the output of the following pseudocode?

```
Set String s = "INFOSYS"
display s[1] + s[5]
```

(A) NS
(B) NY
(C) FY
(D) SY

Correct Answer: Option (B) : NY

■ **Step-by-Step Logic:** s[1]=N and s[5]=Y, so the result is NY.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Condition

Q68. What will be the output of the following pseudocode?

```
Set String s = "COMPUTER"
if (stringLength(s) % 2 == 0)
display stringLength(s) / 2
else
display stringLength(s) + 2
end-if
```

(A) 4
(B) 5
(C) 6
(D) 10

Correct Answer: Option (A) : 4

■ **Step-by-Step Logic:** COMPUTER has 8 characters; 8/2=4.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String + Loop

Q69. What will be the output of the following pseudocode?

```
Set String s = "CODE"
Set Integer total = 0
for i = 0 to stringLength(s)-1 step 1 do
total = total + i
end-for
display total
```

(A) 4
(B) 5
(C) 6
(D) 7

Correct Answer: Option (C) : 6

■ **Step-by-Step Logic:** Indices 0+1+2+3=6.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Index + Shift

Q70. What will be the output of the following pseudocode?

```
Set String s = "TESTING"
Set Integer n = s[1] == 'E'
display stringLength(s) << n
```

(A) 7
(B) 14
(C) 21
(D) 28

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** The comparison is true, represented as 1; length 7<<1=14.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Length + Modulo

Q71. What will be the output of the following pseudocode?

```
Set String s = "ALGORITHM"
display stringLength(s) % 4
```

(A) 0
(B) 1
(C) 2
(D) 3

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** ALGORITHM has 9 characters; 9%4=1.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Reverse Access

Q72. What will be the output of the following pseudocode?

```
Set String s = "INFOSYS"
display s[stringLength(s)-1]
```

(A) I
(B) S
(C) Y
(D) Error

Correct Answer: Option (B) : S

■ **Step-by-Step Logic:** Last index is 6; s[6] = S. Infosys Medium Pseudocode Practice • Page 41

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Character Count

Q73. What will be the output of the following pseudocode?

```
Set String s = "PLACEMENT"
Set Integer c = 0
for i = 0 to stringLength(s)-1 step 1 do
if (s[i] == 'E')
c = c + 1
end-if
end-for
display c
```

(A) 1
(B) 2
(C) 3
(D) 4

Correct Answer: Option (B) : 2

■ **Step-by-Step Logic:** PLACEMENT contains E twice.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Length + Right Shift

Q74. What will be the output of the following pseudocode?

```
Set String s = "INTERVIEW"
display stringLength(s) >> 1
```

(A) 3
(B) 4
(C) 5
(D) 6

Correct Answer: Option (B) : 4

■ **Step-by-Step Logic:** INTERVIEW has 9 characters; 9>>1=4.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: String Conditional

Q75. What will be the output of the following pseudocode?

```
Set String s = "NQT2026"
if (stringLength(s) > 6)
display s[0]
else
display s[1]
end-if
```

(A) N
(B) Q
(C) T
(D) 2

Correct Answer: Option (A) : N

■ **Step-by-Step Logic:** Length is 7, so the first branch displays s[0]=N.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Arithmetic

Q76. What will be the output of the following pseudocode?

```
Integer calc(Integer a, Integer b)
a = a + b
b = a - b
return a * b
End function
display calc(7, 3)
```

(A) 60
(B) 70
(C) 80
(D) 90

Correct Answer: Option (B) : 70

■ **Step-by-Step Logic:** a becomes 10; b becomes 7; return 10×7=70.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with Loop

Q77. What will be the output of the following pseudocode?

```
Integer f(Integer n)
Set Integer s = 1
for i = 1 to n step 1 do
s = s + i
end-for
return s
End function
display f(6)
```

(A) 20
(B) 21
(C) 22
(D) 23

Correct Answer: Option (C) : 22

■ **Step-by-Step Logic:** 1+(1+2+3+4+5+6)=22.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with Shift

Q78. What will be the output of the following pseudocode?

```
Integer f(Integer n)
return (n << 2) + (n >> 1)
End function
display f(10)
```

(A) 40
(B) 45
(C) 50
(D) 55

Correct Answer: Option (B) : 45

■ **Step-by-Step Logic:** 10<<2=40; 10>>1=5; total=45.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with XOR

Q79. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
return (a ^ b) * 2
End function
display f(12, 5)
```

(A) 18
(B) 26
(C) 30
(D) 34

Correct Answer: Option (A) : 18

■ **Step-by-Step Logic:** 12 XOR 5 = 9; 9×2=18.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Condition

Q80. What will be the output of the following pseudocode?

```
Integer f(Integer n)
if (n % 4 == 0)
return n / 2
else
return n + 4
end-if
End function
display f(14)
```

(A) 9
(B) 14
(C) 18
(D) 28

Correct Answer: Option (C) : 18

■ **Step-by-Step Logic:** 14 is not divisible by 4, so 14+4=18. Infosys Medium Pseudocode Practice • Page 42

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Digit Logic

Q81. What will be the output of the following pseudocode?

```
Integer f(Integer n)
Set Integer s = 0
while (n > 0)
s = s + n % 10
n = n / 10
end-while
return s
End function
display f(386)
```

(A) 14
(B) 15
(C) 16
(D) 17

Correct Answer: Option (D) : 17

■ **Step-by-Step Logic:** 3+8+6=17.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Nested

Q82. What will be the output of the following pseudocode?

```
Integer g(Integer x)
return x * 2
End function
Integer f(Integer x)
return g(x) + g(x+1)
End function
display f(4)
```

(A) 16
(B) 18
(C) 20
(D) 22

Correct Answer: Option (B) : 18

■ **Step-by-Step Logic:** g(4)=8 and g(5)=10; total=18.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Modulo

Q83. What will be the output of the following pseudocode?

```
Integer f(Integer n)
return (n * n + 3) % 10
End function
display f(7)
```

(A) 2
(B) 5
(C) 8
(D) 9

Correct Answer: Option (A) : 2

■ **Step-by-Step Logic:** 49+3=52; 52%10=2.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Loop Product

Q84. What will be the output of the following pseudocode?

```
Integer f(Integer n)
Set Integer p = 1
for i = 1 to n step 1 do
if (i % 2 == 0)
p = p * i
end-if
end-for
return p
End function
display f(6)
```

(A) 24
(B) 36
(C) 48
(D) 60

Correct Answer: Option (C) : 48

■ **Step-by-Step Logic:** Multiply even values 2×4×6=48.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Boolean

Q85. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
if ((a & 1) == 1 and (b & 1) == 0)
return a + b
else
return a - b
end-if
End function
display f(9, 6)
```

(A) 3
(B) 9
(C) 15
(D) 54

Correct Answer: Option (C) : 15

■ **Step-by-Step Logic:** 9 is odd and 6 is even, so return 9+6=15.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Array Formula

Q86. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b, Integer c)
return (a + b) ^ c
End function
display f(5, 3, 6)
```

(A) 4
(B) 8
(C) 12
(D) 14

Correct Answer: Option (D) : 14

■ **Step-by-Step Logic:** 5+3=8; 8 XOR 6 = 14.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Recursive-style

Q87. What will be the output of the following pseudocode?

```
Integer f(Integer n)
if (n <= 1)
return 1
end-if
return n + f(n-2)
End function
display f(7)
```

(A) 10
(B) 12
(C) 16
(D) 18

Correct Answer: Option (C) : 16

■ **Step-by-Step Logic:** f(7)=7+5+3+1=16.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Shifted Return

Q88. What will be the output of the following pseudocode?

```
Integer f(Integer n)
Set Integer a = n << 1
Set Integer b = n >> 1
return a - b
End function
display f(13)
```

(A) 13
(B) 19
(C) 20
(D) 21

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** 13<<1=26; 13>>1=6; difference=20. Infosys Medium Pseudocode Practice • Page 43

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with Multiple Updates

Q89. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
a = a * 2
b = b + a
a = a - b
return a + b
End function
display f(4, 3)
```

(A) 7
(B) 8
(C) 9
(D) 10

Correct Answer: Option (B) : 8

■ **Step-by-Step Logic:** a=8; b=11; a=-3; return -3+11=8.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with Loop and Shift

Q90. What will be the output of the following pseudocode?

```
Integer f(Integer n)
Set Integer s = 0
for i = 1 to n step 1 do
s = s + (i << 1)
end-for
return s
End function
display f(5)
```

(A) 20
(B) 25
(C) 30
(D) 35

Correct Answer: Option (C) : 30

■ **Step-by-Step Logic:** 2×(1+2+3+4+5)=30.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Array + Function

Q91. What will be the output of the following pseudocode?

```
Integer f(Integer x)
return (x >> 1) + 3
End function
Set Integer a = [8, 12, 16]
display f(a[2])
```

(A) 9
(B) 10
(C) 11
(D) 12

Correct Answer: Option (C) : 11

■ **Step-by-Step Logic:** a[2]=16; 16>>1=8; 8+3=11.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Loop + XOR

Q92. What will be the output of the following pseudocode?

```
Set Integer x = 0
for i = 1 to 5 step 1 do
x = x ^ i
end-for
display x
```

(A) 0
(B) 1
(C) 2
(D) 3

Correct Answer: Option (A) : 0

■ **Step-by-Step Logic:** 0^1=1, ^2=3, ^3=0, ^4=4, ^5=1.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Loop + AND

Q93. What will be the output of the following pseudocode?

```
Set Integer x = 15
for i = 1 to 3 step 1 do
x = x & (14 - i)
end-for
display x
```

(A) 8
(B) 10
(C) 12
(D) 14

Correct Answer: Option (B) : 10

■ **Step-by-Step Logic:** x=15&13=13; 13&12=12; 12&11=8.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Condition + Shift

Q94. What will be the output of the following pseudocode?

```
Set Integer x = 19
if ((x & 1) == 1)
x = x << 1
x = x + 3
else
x = x >> 1
end-if
display x
```

(A) 19
(B) 38
(C) 41
(D) 44

Correct Answer: Option (C) : 41

■ **Step-by-Step Logic:** 19 is odd; 19<<1=38; +3=41.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Nested Loop + Modulo

Q95. What will be the output of the following pseudocode?

```
Set Integer c = 0
for i = 1 to 4 step 1 do
for j = 1 to 4 step 1 do
if ((i + j) % 3 == 0)
c = c + 1
end-if
end-for
end-for
display c
```

(A) 4
(B) 5
(C) 6
(D) 7

Correct Answer: Option (B) : 5

■ **Step-by-Step Logic:** Pairs with sum divisible by 3: 5 pairs. Correct answer B.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Array + Right Shift

Q96. What will be the output of the following pseudocode?

```
Set Integer a = [18, 25, 32, 41]
display (a[3] >> 2) + (a[0] % 5)
```

(A) 11
(B) 12
(C) 13
(D) 14

Correct Answer: Option (C) : 13

■ **Step-by-Step Logic:** 41>>2=10; 18%5=3; total=13. Infosys Medium Pseudocode Practice • Page 44

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Function + Logical

Q97. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
if (a > 10 and b < 10)
return (a << 1) + b
else
return a + (b << 1)
end-if
End function
display f(12, 7)
```

(A) 24
(B) 26
(C) 31
(D) 38

Correct Answer: Option (C) : 31

■ **Step-by-Step Logic:** 12>10 and 7<10, so (12<<1)+7 = 24+7=31.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Loop + Array Update

Q98. What will be the output of the following pseudocode?

```
Set Integer a = [1, 2, 3, 4, 5]
for i = 1 to 4 step 1 do
a[i] = a[i] + a[i-1]
end-for
display a[4]
```

(A) 10
(B) 12
(C) 15
(D) 16

Correct Answer: Option (C) : 15

■ **Step-by-Step Logic:** Running cumulative values become [1,3,6,10,15].

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Function + Modulo + Shift

Q99. What will be the output of the following pseudocode?

```
Integer f(Integer n)
return ((n % 5) << 2) + (n >> 3)
End function
display f(26)
```

(A) 5
(B) 7
(C) 9
(D) 11

Correct Answer: Option (B) : 7

■ **Step-by-Step Logic:** 26%5=1; 1<<2=4; 26>>3=3; total=7.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Nested Conditions

Q100. What will be the output of the following pseudocode?

```
Set Integer a = 9
Set Integer b = 6
Set Integer c = 3
if (a > b)
if ((a - b) == c)
display a + b + c
else
display a - b
end-if
else
display b + c
end-if
```

(A) 12
(B) 15
(C) 18
(D) 21

Correct Answer: Option (C) : 18

■ **Step-by-Step Logic:** 9>6 and 9–6=3, so the nested condition is true; 9+6+3=18.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q101. How many times does the loop body run, and

```
what is printed?
Integer
i, count
Set
i = 1, count = 0
while
i < 20 do
i
= i * 2
count
= count + 1
end
while
Print
count
```

(A) 3
(B) 4
(C) 5
(D) 6

Correct Answer: Option (C) : 5

■ **Step-by-Step Logic:** Trace i and count: start i=1. Pass 1: i=2, count=1. Pass 2: i=4, count=2. Pass 3: i=8, count=3. Pass 4: i=16, count=4. Pass 5: i=32, count=5. Now i=32 is not less than 20, so the loop stops. Printed value is 5.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q102. What will be the output of the following pseudocode?

```
What is the output of the following Pseudo
Code? Integer division is used.
Integer
a, b
Set
a = 17, b = 5
Print
(a / b) + (a % b)
```

(A) 3
(B) 4
(C) 5
(D) 7

Correct Answer: Option (C) : 5

■ **Step-by-Step Logic:** Integer division: 17 / 5 = 3. Remainder: 17 % 5 = 2. Printed value = 3 + 2 = 5.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q103. What will be the output of the following pseudocode?

```
What is the output of the following Pseudo
Code?
Integer
x, i
Set
x = 0
for
i = 1 to 6 do
if
i % 2 == 0 then
continue
end
if
x
= x + i
end
for
Print
x
```

(A) 9
(B) 12
(C) 16
(D) 21

Correct Answer: Option (A) : 9

■ **Step-by-Step Logic:** continue skips even values of i. The loop runs i = 1 to 6, so only the odd values 1, 3 and 5 are added. x = 1 + 3 + 5 = 9.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q104. What will be the output of the following pseudocode?

```
What value is printed by the following
Pseudo Code?
Function
Mystery(n)
if
n <= 1 then
return
1
end
if
return
n * Mystery(n - 1)
End
Function
Print
Mystery(5)
```

(A) 15
(B) 24
(C) 120
(D) 125

Correct Answer: Option (C) : 120

■ **Step-by-Step Logic:** Mystery(n) computes n!. Mystery(5) = 5 × 4 × 3 × 2 × 1 = 120.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q105. What will be the output of the following pseudocode?

```
What is printed after the following Pseudo
Code runs?
Integer
a, b
Set
a = 12, b = 8
a
= a + b
b
= a - b
a
= a - b
Print
a, b
```

(A) 12 8
(B) 8 12
(C) 20 8
(D) 20 12

Correct Answer: Option (B) : 8 12

■ **Step-by-Step Logic:** This swaps the two values without a third variable. a = 12+8 = 20, b = 20-8 = 12, a = 20-12 = 8. Output: 8 12.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q106. What will be the output of the following pseudocode?

```
What is printed by the following Pseudo
Code?
Integer
i, j, count
Set
count = 0
for
i = 1 to 4 do
for
j = 1 to i do
count
= count + 1
end
for
end
for
Print
count
```

(A) 4
(B) 8
(C) 10
(D) 16

Correct Answer: Option (C) : 10

■ **Step-by-Step Logic:** The inner loop runs i times for each i from 1 to 4. Total iterations = 1+2+3+4 = 10. So count prints 10.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q107. What will be the output of the following pseudocode?

```
What is the output of the following Pseudo
Code?
Integer
a, b
Set
a = 9, b = 5
Print
a ^ b
```

(A) 4
(B) 12
(C) 13
(D) 14

Correct Answer: Option (B) : 12

■ **Step-by-Step Logic:** 9 in binary is 1001 and 5 is 0101. XOR sets a bit where the bits differ: 1100, which is 12.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q108. What will be the output of the following pseudocode?

```
What value is printed by the following
Pseudo Code?
Function
F(n)
if
n == 0 then return 0
if
n == 1 then return 1
return
F(n - 1) + F(n - 2)
End
Function
Print
F(6)
```

(A) 5
(B) 8
(C) 13
(D) 21

Correct Answer: Option (B) : 8

■ **Step-by-Step Logic:** F is the Fibonacci sequence: F(0)=0, F(1)=1, F(2)=1, F(3)=2, F(4)=3, F(5)=5, F(6)=8. So the printed value is 8.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q109. What will be the output of the following pseudocode?

```
A queue follows FIFO. What is printed by the
following Pseudo Code?
Queue
Q
enqueue(Q,
2)
enqueue(Q,
4)
enqueue(Q,
6)
dequeue(Q)
enqueue(Q,
8)
Print
front(Q)
```

(A) 2
(B) 4
(C) 6
(D) 8

Correct Answer: Option (B) : 4

■ **Step-by-Step Logic:** After three enqueues the queue is [2, 4, 6] with 2 at the front. dequeue removes 2. enqueue 8 makes [4, 6, 8]. front returns 4.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q110. What will be the output of the following pseudocode?

```
A stack follows LIFO. What is printed by the
following Pseudo Code?
Stack
S
push(S,
5)
push(S,
8)
push(S,
3)
pop(S)
push(S,
7)
Print
peek(S)
```

(A) 3
(B) 5
(C) 7
(D) 8

Correct Answer: Option (C) : 7

■ **Step-by-Step Logic:** Stack after the three pushes: [5, 8, 3] with 3 on top. pop removes 3. push 7 makes the stack [5, 8, 7]. peek returns the top element, which is 7.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q111. What will be the output of the following pseudocode?

```
What is printed?
Integer
n, d
Set
n = 48, d = 0
while
n > 1 do
n
= n / 2
d
= d + 1
end
while
Print
d
```

(A) 3
(B) 4
(C) 5
(D) 6

Correct Answer: Option (C) : 5

■ **Step-by-Step Logic:** 48→24→12→6→3→1. That is five divisions. d = 5. (Integer division: 3/2=1.)

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q112. What will be the output of the following pseudocode?

```
What is printed?
Integer
A[5] = {2, 4, 6, 8, 10}
Integer
i, s
Set
s = 0
for
i = 0 to 4 do
if
A[i] % 4 == 0 then s = s + A[i]
end
for
Print
s
```

(A) 12
(B) 18
(C) 24
(D) 30

Correct Answer: Option (A) : 12

■ **Step-by-Step Logic:** Values divisible by 4 are 4 and 8. s = 4 + 8 = 12.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q113. What will be the output of the following pseudocode?

```
What is printed?
Integer
x
Set
x = 10
Print
x & 3
```

(A) 1
(B) 2
(C) 3
(D) 8

Correct Answer: Option (B) : 2

■ **Step-by-Step Logic:** 10 is 1010 and 3 is 0011. AND is 0010, which is 2.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q114. What will be the output of the following pseudocode?

```
What is printed?
Stack
S
push(S,
1)
push(S,
4)
push(S,
9)
pop(S)
pop(S)
Print
peek(S)
```

(A) 1
(B) 4
(C) 9
(D) Empty

Correct Answer: Option (A) : 1

■ **Step-by-Step Logic:** After three pushes the top is 9. Two pops remove 9 then 4. peek returns 1.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q115. What will be the output of the following pseudocode?

```
What does G(4) return?
Function
G(n)
if
n <= 1 then return 1
return
n * G(n - 1)
End
Function
Print
G(4)
```

(A) 10
(B) 16
(C) 24
(D) 64

Correct Answer: Option (C) : 24

■ **Step-by-Step Logic:** G is factorial. G(4)=4×3×2×1=24.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q116. What will be the output of the following pseudocode?

```
[Bitwise]
What is printed?
Integer
a
Set
a = 6
Print
a | 3
```

(A) 7
(B) 5
(C) 2
(D) 18

Correct Answer: Option (A) : 7

■ **Step-by-Step Logic:** 6 is 0110, 3 is 0011, OR is 0111 = 7.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q117. What will be the output of the following pseudocode?

```
[Queue]
What is printed?
Queue
Q
enqueue(Q,
11)
enqueue(Q,
22)
enqueue(Q,
33)
dequeue(Q)
dequeue(Q)
Print
front(Q)
```

(A) 11
(B) 22
(C) 33
(D) Empty

Correct Answer: Option (C) : 33

■ **Step-by-Step Logic:** Queue starts [11,22,33]. Two dequeues remove 11 then 22. Front is 33.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q118. What will be the output of the following pseudocode?

```
[Loops]
What is printed?
Integer
i, s
Set
s = 0
for
i = 1 to 10 do
if
i % 2 == 1 then s = s + i
end
for
Print
s
```

(A) 25
(B) 30
(C) 45
(D) 55

Correct Answer: Option (A) : 25

■ **Step-by-Step Logic:** The loop adds the odd values 1+3+5+7+9 = 25.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q119. What will be the output of the following pseudocode?

```
[Recursion]
What does S(5) return?
Function
S(n)
if
n == 0 then return 0
return
n + S(n - 1)
End
Function
Print
S(5)
```

(A) 10
(B) 15
(C) 16
(D) 25

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** S(n) is the sum 5+4+3+2+1+0 = 15.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q120. What will be the output of the following pseudocode?

```
[Arrays]
What is printed?
Integer
A[4] = {3, 5, 7, 9}
Integer
i, p
Set
p = 1
for
i = 0 to 3 do
p
= p * A[i]
end
for
Print
p
```

(A) 24
(B) 315
(C) 945
(D) 105

Correct Answer: Option (C) : 945

■ **Step-by-Step Logic:** Product 3×5×7×9 = 945.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q121. What will be the output of the following pseudocode?

```
[Loops]
What is printed?
Integer
i, p
Set
p = 1
for
i = 1 to 4 do
p
= p * i
end
for
Print
p
```

(A) 10
(B) 16
(C) 24
(D) 120

Correct Answer: Option (C) : 24

■ **Step-by-Step Logic:** p multiplies 1×2×3×4 = 24.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q122. What will be the output of the following pseudocode?

```
[Data
Structures] Queue Q receives 5, then 15, then 25. One
dequeue
runs. What is front(Q)?
Queue
Q
enqueue(Q,
5)
enqueue(Q,
15)
enqueue(Q,
25)
dequeue(Q)
Print
front(Q)
```

(A) 5
(B) 15
(C) 25
(D) Empty

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** FIFO: 5 leaves. Front is 15.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q123. What will be the output of the following pseudocode?

```
[Data
Structures] After the operations, what does peek return?
Stack
S
push(S,
10)
push(S,
20)
push(S,
30)
pop(S)
push(S,
40)
Print
peek(S)
```

(A) 10
(B) 20
(C) 40
(D) 30

Correct Answer: Option (C) : 40

■ **Step-by-Step Logic:** Stack after pops/pushes: [10, 20, 40]. peek = 40.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q124. What will be the output of the following pseudocode?

```
[Bitwise]
What is printed?
Integer
a, b
Set
a = 13, b = 6
Print
a & b
```

(A) 4
(B) 5
(C) 7
(D) 11

Correct Answer: Option (A) : 4

■ **Step-by-Step Logic:** 13 is 1101, 6 is 0110, AND is 0100 = 4.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q125. What will be the output of the following pseudocode?

```
[Recursion]
What does P(4) return?
Function
P(n)
if
n == 1 then return 2
return
P(n - 1) * 2
End
Function
Print
P(4)
```

(A) 8
(B) 12
(C) 16
(D) 24

Correct Answer: Option (C) : 16

■ **Step-by-Step Logic:** P(1)=2, P(2)=4, P(3)=8, P(4)=16.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q126. What will be the output of the following pseudocode?

```
What
does R(6) return?
Function
R(n)
if
n < 3 then return n
return
R(n - 1) + 2
End
Function
Print
R(6)
```

(A) 6
(B) 8
(C) 10
(D) 12

Correct Answer: Option (C) : 10

■ **Step-by-Step Logic:** R(2)=2. Each later call adds 2. R(6)=2 + 2×4 = 10.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q127. What will be the output of the following pseudocode?

```
What
is printed?
Stack
S
push(S,
3)
push(S,
6)
push(S,
9)
pop(S)
push(S,
12)
Print
peek(S)
```

(A) 3
(B) 6
(C) 12
(D) 9

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** After pop, 9 is gone. 12 is pushed. peek returns 12.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q128. What will be the output of the following pseudocode?

```
What
is printed?
Integer
i, c
Set
c = 0
for
i = 1 to 8 do
if
i % 2 == 0 then c = c + i
end
for
Print
c
```

(A) 16
(B) 18
(C) 20
(D) 36

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** Even values 2+4+6+8 = 20.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q129. What will be the output of the following pseudocode?

```
What
is printed?
Integer
x
Set
x = 11
Print
x | 4
```

(A) 15
(B) 7
(C) 8
(D) 44

Correct Answer: Option (A) : 15

■ **Step-by-Step Logic:** 11 is 1011, 4 is 0100, OR is 1111 = 15.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q130. What will be the output of the following pseudocode?

```
What
is printed?
Queue
Q
enqueue(Q,
7)
enqueue(Q,
14)
enqueue(Q,
21)
dequeue(Q)
enqueue(Q,
28)
Print
front(Q)
```

(A) 7
(B) 14
(C) 21
(D) 28

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** 7 is removed first. The new front is 14.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q131. What will be the output of the following pseudocode?

```
What
does U(4) return?
Function
U(n)
if
n == 0 then return 1
return
n + U(n - 1)
End
Function
Print
U(4)
```

(A) 8
(B) 9
(C) 11
(D) 24

Correct Answer: Option (C) : 11

■ **Step-by-Step Logic:** U(0)=1, then +1+2+3+4 = 11.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q132. What will be the output of the following pseudocode?

```
What
is printed?
Integer
z
Set
z = 14
Print
z & 7
```

(A) 6
(B) 7
(C) 8
(D) 21

Correct Answer: Option (A) : 6

■ **Step-by-Step Logic:** 14 is 1110, 7 is 0111, AND is 0110 = 6.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q133. What will be the output of the following pseudocode?

```
What
is printed?
Integer
i, n
Set
n = 0
for
i = 1 to 6 do
if
i % 3 == 0 then n = n + i
end
for
Print
n
```

(A) 6
(B) 9
(C) 12
(D) 21

Correct Answer: Option (B) : 9

■ **Step-by-Step Logic:** Multiples of 3 from 1 to 6 are 3 and 6. Sum = 9.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q134. What will be the output of the following pseudocode?

```
What
is printed?
Queue
Q
enqueue(Q,
4)
enqueue(Q,
8)
enqueue(Q,
12)
dequeue(Q)
Print
front(Q)
```

(A) 4
(B) 8
(C) 12
(D) Empty

Correct Answer: Option (B) : 8

■ **Step-by-Step Logic:** 4 leaves first. Front is 8.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q135. What will be the output of the following pseudocode?

```
What
is printed?
Stack
S
push(S,
2)
push(S,
5)
push(S,
8)
pop(S)
push(S,
11)
Print
peek(S)
```

(A) 2
(B) 5
(C) 11
(D) 8

Correct Answer: Option (C) : 11

■ **Step-by-Step Logic:** Pop removes 8. Push 11. peek returns 11.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q136. What will be the output of the following pseudocode?

```
What
is printed?
Stack
S
push(S,
6)
push(S,
9)
push(S,
15)
pop(S)
push(S,
21)
Print
peek(S)
```

(A) 6
(B) 9
(C) 21
(D) 15

Correct Answer: Option (C) : 21

■ **Step-by-Step Logic:** Pop removes 15. Push 21. peek returns 21.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q137. What will be the output of the following pseudocode?

```
What
is printed?
Integer
k
Set
k = 21
Print
k >> 2
```

(A) 5
(B) 6
(C) 10
(D) 84

Correct Answer: Option (A) : 5

■ **Step-by-Step Logic:** 21 is 10101. Right shift 2 gives 101 = 5.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q138. What will be the output of the following pseudocode?

```
What
is printed?
Integer
i, t
Set
t = 1
for
i = 1 to 5 do
t
= t * 2
end
for
Print
t
```

(A) 10
(B) 16
(C) 32
(D) 64

Correct Answer: Option (C) : 32

■ **Step-by-Step Logic:** Start 1, multiply by 2 five times: 32.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q139. What will be the output of the following pseudocode?

```
What
is printed?
Queue
Q
enqueue(Q,
3)
enqueue(Q,
9)
enqueue(Q,
15)
dequeue(Q)
Print
front(Q)
```

(A) 3
(B) 9
(C) 15
(D) Empty

Correct Answer: Option (B) : 9

■ **Step-by-Step Logic:** 3 leaves. Front is 9.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q140. What will be the output of the following pseudocode?

```
What
does W(5) return?
Function
W(n)
if
n <= 1 then return 2
return
W(n - 1) + 3
End
Function
Print
W(5)
```

(A) 11
(B) 14
(C) 15
(D) 17

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** W(1)=2. Add 3 four times: 2+12=14.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q141. What will be the output of the following pseudocode?

```
What will be the
output of the following pseudo code
Integer
i, j, k, d
Set
j = 6, i = 8, k = 2, d = 1
if
((j ^ i) mod k equals 0) then
d = d + 1
else
d = d - 1
end
if
Print
d
```

(A) 1
(B) 3
(C) 0
(D) 2

Correct Answer: Option (D) : 2

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 2.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q142. What will be the output of the following pseudocode?

```
1.     #include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<“ “;
Test t[5];

cout<< Test::getX();      }
```

(A) 0 0
(B) 5 5
(C) 0 5
(D) a) Run time error

Correct Answer: Option (C) : 0 5

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 0 5.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q143. What will be the output of the following pseudocode?

```
1.     #include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<“Constructor called”;   }
};
int main(){
Point t1;
return 0;
}
```

(A) Constructor called
(B) Compile time error
(C) Run time error
(D) Blank line

Correct Answer: Option (B) : Compile time error

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : Compile time error.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q144. What will be the output of the following pseudocode?

```
1.     #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }

 }
```

(A) 7 6 3
(B) 7 5 4
(C) 6 7 8
(D) 6 5 4

Correct Answer: Option (A) : 7 6 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 7 6 3.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q145. What will be the output of the following pseudocode?

```
1.     Where are placed the list of processes that are
prepared to be executed and waiting?
```

(A) Job queue
(B) Ready queue
(C) Execution queue
(D) Process queue

Correct Answer: Option (B) : Ready queue

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : Ready queue.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q146. What will be the output of the following pseudocode?

```
1.     Who among the following can block the running
process?
```

(A) Fork
(B) Read
(C) Down
(D) All of these

Correct Answer: Option (D) : All of these

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : All of these.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q147. What will be the output of the following pseudocode?

```
1.     Which of the following does not interrupt the
running process?
```

(A) Timer interrupt
(B) Device
(C) Power failure
(D) Scheduler process

Correct Answer: Option (D) : Scheduler process

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : Scheduler process.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q148. What will be the output of the following pseudocode?

```
1.     The \u0021 article referred to as a
```

(A) Unicode escape sequence
(B) Octal escape
(C) Hexadecimal
(D) Line feed

Correct Answer: Option (A) : Unicode escape sequence

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : Unicode escape sequence.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q149. What will be the output of the following pseudocode?

```
1.     Which of the following is a valid declaration of a
char?
```

(A) char ch = '\utea';
(B) char ca = 'tea';
(C) char cr = \u0223;
(D) char cc = '\itea';

Correct Answer: Option (A) : char ch = '\utea';

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : char ch = '\utea';.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q150. What will be the output of the following pseudocode?

```
1.    Which of the following is a valid long literal?
```

(A) ABH8097
(B) L990023
(C) 904423
(D) 0xnf029L

Correct Answer: Option (D) : 0xnf029L

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 0xnf029L.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q151. What will be the output of the following pseudocode?

```
1.    What does the expression float a = 35 / 0 return?
```

(A) 0
(B) Not a Number
(C) Infinity
(D) Run time exception

Correct Answer: Option (C) : Infinity

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : Infinity.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q152. What will be the output of the following pseudocode?

```
1.    Which option is false about the final keyword?
a)   A) A final method cannot be overridden in its
subclasses.
b)   B) A final class cannot be extended.
c)   C) A final class cannot extend other classes.
d)   D) A final method can be inherited.
```

(A) A&B
(B) B&C
(C) C&D
(D) None of these

Correct Answer: Option (C) : C&D

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : C&D.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q153. What will be the output of the following pseudocode?

```
1.    Construct post order Transversal for the
constructed tree with the given In-Order and Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

(A) 9 10 7 8 6
(B) 9 7 6 10 8
(C) 8 9 10 7 6
(D) 9 8 10 7 6

Correct Answer: Option (A) : 9 10 7 8 6

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 9 10 7 8 6.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q154. 1. What will be the output of this program fragment?

```
int i = 263;
      putchar(i);
```

(A) prints 263
(B) prints the ASCII equivalent of 263
(C) rings the bell
(D) prints garbage

Correct Answer: Option (C) : rings the bell

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : rings the bell.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q155. 1. What will be the output of this statement?

```
printf (“%d”, 9/5);
```

(A) 1.8
(B) 1.0
(C) 2.0
(D) None of these

Correct Answer: Option (D) : None of these

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : None of these.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q156. 1. What will be the output of this program?

```
#include<stdio.h>
      int main() {
      int i = 5;
      printf(“%d”, i = ++i == 6);
      return 0;
      }
```

(A) 2
(B) 6
(C) 4
(D) 1

Correct Answer: Option (D) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 1.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q157. What will be the output of the following pseudocode?

```
1.    Which of the following declarations is invalid in
C language?
```

(A) char
(B) char str[] = “campus monk is the best platform for learn";
(C) char str[20] = “campus monk is the best platform for learn";
(D) char[] str = “campus monk is the best platform for learn";

Correct Answer: Option (D) : char[] str = “campus monk is the best platform for learn";

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : char[] str = “campus monk is the best platform for learn";.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q158. 1. What will be the output of this program?

```
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf(“%d”, h);
   return 0;
}
```

(A) 1
(B) error: redeclaration of an enumerator
(C) h
(D) 3

Correct Answer: Option (B) : error: redeclaration of an enumerator

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : error: redeclaration of an enumerator.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q159. 1. What will be the output of this program?

```
main ()
{
 if (5 < '5')
        printf("5")
 else
        printf(" NOT EQUAL TO 5.")

}
```

(A) ENQ
(B) 5
(C) I
(D) Not equal to 5

Correct Answer: Option (B) : 5

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 5.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q160. 1. What will be the output of the following pseudo code?

```
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

(A) 5
(B) 7
(C) 9
(D) 12

Correct Answer: Option (A) : 5

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 5.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q161. 1. What will be the output of the following pseudocode?

```
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

(A) 6 6 6
(B) 6 5 6
(C) 5 5 5
(D) 6 5 4

Correct Answer: Option (D) : 6 5 4

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 6 5 4.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q162. What will be the output of the following pseudocode?

```
1.     If the sequence of operations are performed on a
stack, the sequence of pop will be?

Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(),
Pop(), Push(2), Pop().
```

(A) 2 2 1 1 2
(B) 2 2 1 2 2
(C) 2 1 2 2 1
(D) 2 1 2 2 2

Correct Answer: Option (A) : 2 2 1 1 2

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 2 2 1 1 2.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q163. What will be the output of the following pseudocode?

```
1.     In an empty BST, insert the following elements in
a similar sequence. Which element will be at lowest
level?

105     95    122    99    97    120
```

(A) 95
(B) 97
(C) 99
(D) 120

Correct Answer: Option (B) : 97

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 97.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q164. What will be the output of the following pseudocode?

```
T The concatenation of two lists is to be performed in
O(1) time. Which of the following implementation of a
list should be used?
```

(A) a) Singly linked list
(B) a) Doubly linked list
(C) a) Circular doubly linked list
(D) a) Array implementation of list

Correct Answer: Option (C) : a) Circular doubly linked list

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : a) Circular doubly linked list.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q165. What will be the output of the following pseudocode?

```
1.     Which of the following sequence can be obtained in
the output (in same order) using a stack assuming that
the input is in the sequence 1,2,3,4,5 order?
```

(A) a) 3,4,5,1,2
(B) a) 3,4,5,2,1
(C) a) 1,5,2,3,4
(D) a) 5,4,3,1,2

Correct Answer: Option (B) : a) 3,4,5,2,1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : a) 3,4,5,2,1.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q166. What will be the output of the following pseudocode?

```
1.     Let A be a square matrix of size nxn. Consider the
following program and state the output.
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do

Output (A[i][j]);
```

(A) a) The matrix A itself
(B) a) Transpose of matrix A
(C) a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
(D) a) None of the above

Correct Answer: Option (A) : a) The matrix A itself

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : a) The matrix A itself.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q167. What will be the output of the following pseudocode?

```
1.     The value of j at the end of the execution of the
following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)

end for
```

(A) 10
(B) 4
(C) 6
(D) 7

Correct Answer: Option (A) : 10

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 10.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q168. What will be the output of the following pseudocode?

```
1.     What is printed by the print statement in the
program P1 assuming call by reference parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z

}
```

(A) 10, 3
(B) 31, 3
(C) 27, 7
(D) None of these

Correct Answer: Option (B) : 31, 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 31, 3.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q169. What will be the output of the following pseudocode?

```
1.     The value returned by the following function for
f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);

}
```

(A) 5
(B) 6
(C) 7
(D) 8

Correct Answer: Option (C) : 7

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 7.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q170. What will be the output of the following pseudocode?

```
1.     Find the output of the following pseudo code.
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if

Print n
```

(A) 7
(B) 18
(C) 22
(D) 2

Correct Answer: Option (D) : 2

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 2.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q171. What will be the output of the following pseudocode?

```
1.     Find the output of the following pseudo code.
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if

Print x+y+z
```

(A) 31
(B) 11
(C) 42
(D) 30

Correct Answer: Option (D) : 30

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 30.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q172. What will be the output of the following pseudocode?

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c >
b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c <
a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a
Print a + b + c
```

(A) 71
(B) 56
(C) 47
(D) 54

Correct Answer: Option (D) : 54

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 54.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q173. How many times campus monk will be printed? Set k = 1, p = 4 Int j = p + k / 2 If (j equals p) Print "campus monk" End if j = p + k / 5 If (j not equal p) Print "campus monk" End if Print "campus monk"

(A) 1 Times
(B) 2 Times
(C) 3 Times
(D) 4 Times

Correct Answer: Option (B) : 2 Times

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 2 Times.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q174. What will be the output of the following pseudocode?

```
Find the output of the following code. #include <stdio.h> int main(void) { int a = 10, x; x = a-- + +445; printf ("%d", x); return 0; }
```

(A) 19
(B) 435
(C) 455
(D) 23

Correct Answer: Option (C) : 455

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 455.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q175. What will be the output of the following pseudocode?

```
Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q } Print p + q + r
```

(A) 44
(B) 41
(C) 11
(D) 26

Correct Answer: Option (D) : 26

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 26.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q176. What will be the output of the following pseudocode?

```
What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)) { p = 11 + q; } Print p + q + r;
```

(A) 12
(B) 16
(C) 27
(D) 10

Correct Answer: Option (B) : 16

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 16.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q177. What will be the output of the following pseudocode? Initial values: a = 4, b = 4, c = 7 Int fun(int a, int b, int c) { For (each c from 3 to 5) { a = (c + c) ^ b; If ((a + c) < (c + a)) { b = (a + 11) + c; } Else { c = b + b; a = 3 + b; continue; } } Return a + b; }

(A) 10
(B) 12
(C) Error
(D) 11

Correct Answer: Option (D) : 11

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 11.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q178. What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c) a = b + c Else c = (4 + 12) + a b = 11 + a End if Print (a + b + c)

(A) 19
(B) 21
(C) 20
(D) 22

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 20.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q179. What will be the output of the following pseudocode?

```
Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^ y ^ z) x = 1 End if Print x + y + z
```

(A) 11
(B) 13
(C) 16
(D) 9

Correct Answer: Option (A) : 11

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 11.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q180. What will be the output of the following pseudocode?

```
Find the output of the following code. #include <stdio.h> void main() { int a = 10; if (a == 010) printf("BCA"); else printf("B.Tech"); }
```

(A) BCA
(B) B.tech
(C) 10
(D) Error

Correct Answer: Option (B) : B.tech

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : B.tech.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q181. What will be the output of the following pseudocode?

```
Find the output of the following code. #include <stdio.h> void main () { int x = 91; x >>= 2; printf ("%d\n", x); }
```

(A) 182
(B) 91
(C) 22
(D) 82

Correct Answer: Option (C) : 22

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 22.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q182. What will be the output of the following pseudocode?

```
What is the output of the following C code? #include <stdio.h> int main() { int num = 987; int rem; while(num != 0) { rem = num % 4; num = num / 10; } printf("%d", rem); }
```

(A) 0
(B) 1
(C) 10
(D) 5

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q183. What will be the output of the following pseudocode?

```
What is the output of the following C code? #include <stdio.h> int main() { float x = 0.0; long int y = 10; printf("%d", sizeof(y) == sizeof(x + y)); return 0; }
```

(A) 3
(B) 1
(C) 5
(D) 2

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q184. What will be the output of the following pseudocode?

```
Predict the output of the given pseudocode if the value of the number is 6: Read number k = 2 i = 2 while i <= number: k = k * i i = i + 1 end while write k
```

(A) 1440.0
(B) 1340.0
(C) 1700.0
(D) 1560.0

Correct Answer: Option (A) : 1440.0

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 1440.0.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q185. What will be the output of the following pseudocode?

```
What is the output of the following C code? int f(int x, int *py, int **ppz) { int y, z; **ppz += 1; z = **ppz; *py += 2; y = *py; x += 3; return x + y + z; } void main() { int c, *b, **a; c = 4; b = &c; a = &b; printf("%d ", f(c, b, a)); return 0; }
```

(A) 18
(B) 19
(C) 21
(D) 22

Correct Answer: Option (B) : 19

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 19.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q186. What will be the output of the following pseudocode?

```
What is the output of the following C code? #include <stdio.h> int main() { int a = 12; void *ptr = (int *)&a; printf("%d", *ptr); getchar(); return 0; }
```

(A) 12
(B) Compiler Error
(C) Run Time Error
(D) 0

Correct Answer: Option (B) : Compiler Error

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : Compiler Error.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q187. What will be the output of the following pseudocode?

```
Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2) && y + (3 & 3) && z + (2 ^ 2)) x = x - 2 y = x Else x = z y = y ^ 2 End if Print x + y + z
```

(A) 2
(B) 11
(C) 3
(D) 0

Correct Answer: Option (C) : 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 3.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q188. What will be the output of the following pseudocode?

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x) return 0; }
```

(A) 0
(B) 1
(C) 5
(D) Compilation Error

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q189. What will be the output of the following pseudocode?

```
Q1.) Integer p, q, r Set p = 0, q = 2, r = 9 r = 7 + p q = q + r for (each r from 4 to 7) p = (p + p) & q if ((p + q) < (r - p) || 8 < p) p = (p + 2) + q Jump out of the loop End if End for Print p + q
```

(A) 5
(B) 9
(C) 19
(D) 20

Correct Answer: Option (B) : 9

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 9.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q190. What will be the output of the following pseudocode?

```
Q2.) #include<iostream> using namespace std; int main() { int a = 3, b = 2, c = 5; int result = (a++ << 2) + (--b << 1) - (c-- >> 1) + (a & b); cout << result; return 0; }
```

(A) 12
(B) 14
(C) 10
(D) 16

Correct Answer: Option (A) : 12

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 12.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q191. What will be the output of the following pseudocode?

```
Q3.) Integer value, n Set value = 1, n = 45 while (value less than equal to n) value = value << 1 end loop Print value
```

(A) 16
(B) 32
(C) 64
(D) 36

Correct Answer: Option (C) : 64

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 64.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q192. What will be the output of the following pseudocode?

```
Q4.) Predict the output of the following pseudocode.
Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2)
&& y + (3 & 3) && z + (2 ^ 2)) x = x -2 y = x Else x = z y
= y ^ 2 End if Print x + y + z
```

(A) 2
(B) 11
(C) 0
(D) 3

Correct Answer: Option (D) : 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 3.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q193. What will be the output of the following pseudocode?

```
Q5. What is the output int main() { int x = 10; int *y,
**z; y = &x; z = &y; **z=7; print(x,*y,**z) return 0; }
```

(A) 10 10 10
(B) 10 7 7
(C) 7 7 7
(D) 10 10 7

Correct Answer: Option (C) : 7 7 7

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 7 7 7.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q194. What will be the output of the following pseudocode?

```
Q6. What is the output for p=15 and q=4. Integer solve
(Integer p, Integer q) Integer value while(q) value = p
MOD q p = q q = value End while return p End function
solve()
```

(A) 3
(B) 1
(C) 2
(D) 0

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q195. What will be the output of the following pseudocode?

```
Q7.what is the output for number=4 int something(int
number) { if(number <= 0) return 1; else return number *
something(number-1); } something(4);
```

(A) 12
(B) 24
(C) 1
(D) 20

Correct Answer: Option (B) : 24

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 24.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q196. Q8. What will be the output of the following pseudocode? int a , b ,c Set a=0,b=1,c=2 If (b^c || a&b || a>>1) c=9 a =b+c else c =1 a=a+c End if Print a+b+c

(A) 20

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q197. What will be the output of the following pseudocode?

```
Q9. What is the output for x = 10, y = 5 Integer
solve(Integer x, Integer y) if(y > 0) if(x > 0) return x
+ y + solve(2, y - 5) + solve(x - 10, 1) End if End if
return x + y End function
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q198. What will be the output of the following pseudocode?

```
Q10. What is the output of following Integer value, n Set
value = 32, n = 1 while(value >= n) value = value >> 1
end loop Print value
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q199. What will be the output of the following pseudocode?

```
What is the output of following pseudo code: Fun() { Int
a=10 , b=20 , c=30; If(c>b>a) Print("True"); Else
Print("False"); return 0; }
```

(A) True
(B) False
(C) Error
(D) -1

Correct Answer: Option (B) : False

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : False.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q200. What will be the output of the following pseudocode?

```
What is the output of following code: Int main(){ Int
n=(1<<2+3<<4) Print(n); Return 0; }
```

(A) 112
(B) 512
(C) 52
(D) 0

Correct Answer: Option (B) : 512

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 512.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q201. What will be the output of the following pseudocode?

```
What is the output of following: Integer x, y Set x = 15,
y = 12 y = x – 1 do{ Print x x = y + (x – 2) } while(x <
40) end do while
```

(A) 14 26
(B) 15 27 39
(C) 27 39
(D) 15

Correct Answer: Option (B) : 15 27 39

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 15 27 39.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q202. What will be the output of the following pseudocode?

```
What is the output if fun(5) is called? Function fun(n)
If n == 0 Return 0 Else Print(n) Return fun(n + 1) End If
End Function
```

(A) 1 2 3 4 5
(B) 5 4 3 2 1
(C) Stack overflow
(D) -1

Correct Answer: Option (C) : Stack overflow

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : Stack overflow.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q203. What will be the output of the following pseudocode?

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x);
return 0; }
```

(A) 0
(B) 1
(C) 5
(D) Compilation Error

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q204. What will be the output of the following pseudocode?

```
1. Integer a = 5, b = 9 2. a = a ^ b 3. b = a ^ b 4. a = a
^ b 5. if (a == 9 && b == 5) 6. Print "Swapped" 7. else
8. Print "Not swapped"
```

(A) Line 2
(B) Line 3
(C) Line 4
(D) No error

Correct Answer: Option (D) : No error

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : No error.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q205. What will be the output of the following pseudocode?

```
int main() { int x = 9, y = 2, z = 6; int a = x & y | z;
printf("%d", a); return 0; }
```

(A) Error
(B) 2
(C) 3
(D) 6

Correct Answer: Option (D) : 6

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 6.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q206. What will be the output of the following pseudocode?

```
Integer p, q, r Set p = 4, q = 2, r = 5 p = (q + p) + p
if ((q + p) < (r - q) && 3 > p) then p = (q + r) + p if
(((p + r) + (r + q)) <= (p + r + q)) then r = q + p else
r = (p + r) + p end if p = (9 & 6) + q else q = r & r if
((q - 5) < (5 - q)) then r = (6 + 6) & q q = (q + 7) + r
end if p = (1 ^ 11) + q end if Print p + q + r
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q207. What will be the output of the following pseudocode?

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c >
b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c <
a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a
Print a + b + c
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q208. What will be the output of the following pseudocode?

```
Integer a, b, c Set a = 1, b = 6, c = 7 b = (a & b) + b
for (each c from 3 to 5) { b = (a + a) ^ a b = (12 + 5) +
a } a = (a ^ 9) + a Print a + b
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 1]

Topic: Infosys SE College Mock Test

Q209. What will be the output of the following pseudocode?

```
What is printed?
int f(int n) {
        if (n <= 1) return n;
        return f(n-1) + 2 * f(n-2);
}
print(f(6))
```

(A) 15
(B) 21
(C) 27
(D) 31

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 1]

Topic: Infosys SE College Mock Test

Q210. What will be the output of the following pseudocode?

```
What is printed?
x = 45; count = 0;
while (x != 0) {
        x = x & (x - 1);
        count++;
}
print(count ^ (45 >> 2))
```

(A) 4
(B) 11
(C) 15
(D) 7

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 1]

Topic: Infosys SE College Mock Test

Q211. What will be the output of the following pseudocode?

```
What is printed?
s = 0
for i = 1 to 5
        for j = i to 5
                if ((i + j) % 3 == 0) continue
                if (j == 5) break
                s = s + i * j
        end for
end for
print(s)
```

(A) 38
(B) 42
(C) 46
(D) 50

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 1]

Topic: Infosys SE College Mock Test

Q212. What will be the output of the following pseudocode?

```
A stack is used (operands are evaluated left to right).
What is printed?
push(3); push(5); push(7);
x = pop();
push(x * 2);
push(pop() + pop());
print(pop() - pop())
```

(A) 14
(B) 16
(C) 19
(D) 22

Correct Answer: Option (A) : 14

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 14.

[College ITM Mock Paper 1]

Topic: Infosys SE College Mock Test

Q213. What will be the output of the following pseudocode?

```
What is the final content of arr? (indexing starts at 0;
updates are in place)
arr = [4, 1, 3, 2]
for i = 0 to 3
        arr[i] = arr[i] + arr[arr[i] % 4]
end for
```

(A) [8, 2, 5, 7]
(B) [8, 2, 5, 6]
(C) [8, 5, 5, 7]
(D) [5, 2, 5, 7]

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 2]

Topic: Infosys SE College Mock Test

Q214. What will be the output of the following pseudocode?

```
What is printed?
int f(int n) {
        if (n == 0) return 1;
        if (n == 1) return 2;
        return f(n-1) + f(n-2) * 2;
}
print(f(5))
```

(A) 26
(B) 30
(C) 32
(D) 34

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 2]

Topic: Infosys SE College Mock Test

Q215. What will be the output of the following pseudocode?

```
What is printed? (x and y are unsigned integers)
x = 58; y = 0;
while (x > 0) {
        y = (y << 1) | (x & 1);
        x = x >> 1;
}
print(y)
```

(A) 23
(B) 29
(C) 37
(D) 41

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 2]

Topic: Infosys SE College Mock Test

Q216. What will be the output of the following pseudocode?

```
What is printed?
s = 0
for i = 1 to 4
        for j = 1 to 4
                if (i == j) continue
                if (i + j > 6) break
                s = s + (i * j)
        end for
end for
print(s)
```

(A) 40
(B) 44
(C) 46
(D) 48

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 2]

Topic: Infosys SE College Mock Test

Q217. What will be the output of the following pseudocode?

```
A queue is used (FIFO). What is printed?
enqueue(2); enqueue(4); enqueue(6);
a = dequeue();
enqueue(a + 10);
b = dequeue();
c = dequeue();
print(b + c)
```

(A) 10
(B) 16
(C) 18
(D) 22

Correct Answer: Option (A) : 10

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 10.

[College ITM Mock Paper 2]

Topic: Infosys SE College Mock Test

Q218. What will be the output of the following pseudocode?

```
What is the final content of arr? (0-indexed; each
statement uses the array's state at that point)
arr = [1, 2, 3, 4, 5]
temp = arr[0]
arr[0] = arr[4]
arr[4] = arr[2]
arr[2] = arr[1]
arr[1] = temp
```

(A) [5, 1, 2, 4, 3]
(B) [5, 1, 3, 4, 2]
(C) [5, 2, 1, 4, 3]
(D) [5, 1, 2, 4, 2]

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 3]

Topic: Infosys SE College Mock Test

Q219. What will be the output of the following pseudocode?

```
What is printed?
```

(A) 40
(B) 46
(C) 52
(D) 44

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 3]

Topic: Infosys SE College Mock Test

Q220. What will be the output of the following pseudocode?

```
What is printed?
```

(A) 37
(B) 41
(C) 45
(D) 39

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 3]

Topic: Infosys SE College Mock Test

Q221. What will be the output of the following pseudocode?

```
What is printed?
```

(A) 130
(B) 124
(C) 136
(D) 118

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 3]

Topic: Infosys SE College Mock Test

Q222. What will be the output of the following pseudocode?

```
A stack is used (LIFO). What is printed?
```

(A) 39
(B) 33
(C) 42
(D) 30

Correct Answer: Option (A) : 39

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 39.

[College ITM Mock Paper 3]

Topic: Infosys SE College Mock Test

Q223. What will be the output of the following pseudocode?

```
What is the final content of arr? (0-indexed; each
statement uses the array's state at that point)
```

(A) [60, 40, 30, 20, 50, 10]
(B) [60, 20, 30, 40, 50, 10]
(C) [10, 40, 30, 20, 50, 60]
(D) [60, 40, 50, 20, 30, 10]

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 4]

Topic: Infosys SE College Mock Test

Q224. What will be the output of the following pseudocode?

```
What is printed? (% is the modulo operator)
int gcd(int a, int b) {
        if (b == 0) return a;
        return gcd(b, a % b);
}
print(gcd(252, 105))
```

(A) 21
(B) 42
(C) 7
(D) 14

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 4]

Topic: Infosys SE College Mock Test

Q225. What will be the output of the following pseudocode?

```
What is printed? (^=XOR, |=OR, &=AND, >>=right shift)
a = 13; b = 25;
c = (a ^ b) & (a | b);
d = c >> 2;
print(c + d)
```

(A) 25
(B) 29
(C) 20
(D) 33

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 4]

Topic: Infosys SE College Mock Test

Q226. How many swaps are performed in total?

```
arr = [5, 2, 8, 1, 9, 3]
swaps = 0
for i = 0 to 4
        for j = 0 to 4 - i
                if (arr[j] > arr[j+1])
                        temp = arr[j]
                        arr[j] = arr[j+1]
                        arr[j+1] = temp
                        swaps = swaps + 1
                end if
        end for
end for
print(swaps)
```

(A) 7
(B) 8
(C) 6
(D) 9

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 4]

Topic: Infosys SE College Mock Test

Q227. What will be the output of the following pseudocode?

```
This algorithm reverses the first k elements of a queue
using a stack. What is printed?
queue = [1, 2, 3, 4, 5]
stack = []
k = 3
for i = 1 to k
        push(stack, dequeue(queue))
end for
while (stack is not empty)
        enqueue(queue, pop(stack))
end while
for i = 1 to (5 - k)
        enqueue(queue, dequeue(queue))
end for
print(queue)
```

(A) [3, 2, 1, 4, 5]
(B) [1, 2, 3, 4, 5]
(C) [5, 4, 3, 2, 1]
(D) [3, 2, 1, 5, 4]

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 4]

Topic: Infosys SE College Mock Test

Q228. What will be the output of the following pseudocode?

```
This algorithm moves all non-zero elements to the front,
preserving order, and fills the rest with zeroes.
What is the final arr?
arr = [3, 0, 4, 0, 5, 0, 2]
pos = 0
for i = 0 to 6
        if (arr[i] != 0)
                arr[pos] = arr[i]
                pos = pos + 1
        end if
end for
while (pos <= 6)
        arr[pos] = 0
        pos = pos + 1
end while
print(arr)
```

(A) [3, 4, 5, 2, 0, 0, 0]
(B) [3, 0, 4, 0, 5, 0, 2]
(C) [3, 4, 5, 2, 0, 0, 2]
(D) [0, 0, 0, 3, 4, 5, 2]

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 5]

Topic: Infosys SE College Mock Test

Q229. What will be the output of the following pseudocode?

```
What is printed? (This computes the number of grid paths
from one corner to another, moving only
right or down.)
int f(int n, int m) {
        if (n == 0 || m == 0) return 1;
        return f(n-1, m) + f(n, m-1);
}
print(f(3, 2))
```

(A) 10
(B) 8
(C) 12
(D) 9

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 5]

Topic: Infosys SE College Mock Test

Q230. What will be the output of the following pseudocode?

```
What is printed? (>>=right shift, <<=left shift, &=AND,
^=XOR)
x = 0;
for i = 0 to 7
        if (((45 >> i) & 1) == 1)
                x = x + (1 << (7 - i))
        end if
end for
y = x ^ 45
print(y)
```

(A) 153
(B) 180
(C) 135
(D) 171

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 5]

Topic: Infosys SE College Mock Test

Q231. This is a binary search for target = 50 in a sorted array. How many comparisons are made before

```
the loop ends (the target is not present)?
arr = [2, 5, 8, 12, 16, 23, 38, 45, 56, 72, 91]
low = 0; high = 10; target = 50; comparisons = 0
while (low <= high)
        mid = (low + high) / 2
        comparisons = comparisons + 1
        if (arr[mid] == target)
                break
        else if (arr[mid] < target)
                low = mid + 1
        else
                high = mid - 1
        end if
end while
print(comparisons)
```

(A) 4
(B) 3
(C) 5
(D) 6

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 5]

Topic: Infosys SE College Mock Test

Q232. What will be the output of the following pseudocode?

```
This stack trace evaluates a postfix-style expression.
What is printed?
push(6); push(2); push(3);
c = pop(); b = pop(); push(b + c);
d = pop(); e = pop(); push(e - d);
push(3); push(8); push(2);
f = pop(); g = pop(); push(g / f);
h = pop(); i = pop(); push(i + h);
j = pop(); k = pop(); push(k * j);
print(pop())
```

(A) 7
(B) 10
(C) 14
(D) 4

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 5]

Topic: Infosys SE College Mock Test

Q233. What will be the output of the following pseudocode?

```
This is Kadane's algorithm for maximum subarray sum. What
is printed?
arr = [-2, 3, -1, 5, -3, 4, -2, 6]
maxSoFar = arr[0]; maxEndingHere = arr[0]
for i = 1 to 7
        maxEndingHere = max(maxEndingHere + arr[i],
arr[i])
        maxSoFar = max(maxSoFar, maxEndingHere)
end for
print(maxSoFar)
```

(A) 12
(B) 10
(C) 9
(D) 15

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 6]

Topic: Infosys SE College Mock Test

Q234. What will be the output of the following pseudocode?

```
What is printed? (/ is integer division, % is modulo)
int f(int n) {
        if (n <= 1) return n;
        if (n % 2 == 0) return f(n / 2);
        return f(n - 1) + f(n + 1);
}
print(f(11))
```

(A) 5
(B) 4
(C) 6
(D) 3

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 6]

Topic: Infosys SE College Mock Test

Q235. What will be the output of the following pseudocode?

```
What is printed? (^=XOR, >>=right shift, &=AND)
n = 13
g = n ^ (n >> 1)
print(g + (g & 5))
```

(A) 12
(B) 11
(C) 16
(D) 14

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 6]

Topic: Infosys SE College Mock Test

Q236. What will be the output of the following pseudocode?

```
What is printed?
s = 0
for i = 1 to 5
        for j = 1 to 5
                if ((i + j) % 4 == 0) continue
                if (j > i + 1) break
                s = s + i * j
        end for
end for
print(s)
```

(A) 142
(B) 138
(C) 146
(D) 150

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 6]

Topic: Infosys SE College Mock Test

Q237. The following sorts a stack using a temporary stack (the top of a stack is its last element). How many

```
times is an element moved from tmp back to st?
st = [3, 1, 4, 2]; tmp = []; moves = 0
while (st is not empty)
        t = pop(st)
        while (tmp is not empty and top(tmp) > t)
                push(st, pop(tmp))
                moves = moves + 1
        end while
        push(tmp, t)
end while
print(moves)
```

(A) 3
(B) 2
(C) 4
(D) 5

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 6]

Topic: Infosys SE College Mock Test

Q238. What will be the output of the following pseudocode?

```
What is printed? (dynamic programming for the minimum
number of coins; INF is a very large number)
coins = [1, 3, 4]
dp[0] = 0; dp[1..6] = INF
for i = 1 to 6
        for each c in coins
                if (i >= c)
                        dp[i] = min(dp[i], dp[i - c] + 1)
                end if
        end for
end for
print(dp[6])
```

(A) 2
(B) 3
(C) 4
(D) 6

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.