INFOSYS SE PSEUDOCODE VAULT • BITWISE OPERATORS & LOGIC

XOR, AND, OR, Bit Shifts, Precedence, Compound Expressions • Total Solved Questions: 93

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Operator Precedence

Q1. What will be the output of the following pseudocode?

```
Set Integer a = 18
Set Integer b = 5
Set Integer c = 2
display a - b * c + 6
```

(A) 10
(B) 14
(C) 16
(D) 19

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** Multiplication first: 18 – (5×2) + 6 = 14.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Arithmetic

Q2. What will be the output of the following pseudocode?

```
Set Integer x = 24
Set Integer y = 7
display (x / y) * y + (x % y)
```

(A) 21
(B) 24
(C) 25
(D) 28

Correct Answer: Option (B) : 24

■ **Step-by-Step Logic:** 24/7=3 and 24%7=3; 3×7+3 = 24.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Logical Operators

Q3. What will be the output of the following pseudocode?

```
Set Integer a = 12
Set Integer b = 7
Set Integer c = 5
display (a > b) and ((b - c) == 2)
```

(A) true
(B) false
(C) 2
(D) 12

Correct Answer: Option (A) : true

■ **Step-by-Step Logic:** 12>7 is true and 7–5=2 is true, so the result is true.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Logical Operators

Q4. What will be the output of the following pseudocode?

```
Set Integer x = 9
display (x % 2 == 0) or ((x > 5) and (x < 10))
```

(A) true
(B) false
(C) 9
(D) 0

Correct Answer: Option (A) : true

■ **Step-by-Step Logic:** First condition is false, but 9>5 and 9<10 are both true.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Bitwise XOR

Q5. What will be the output of the following pseudocode?

```
Set Integer a = 15
Set Integer b = 9
Set Integer c = 6
display (a ^ b) + c
```

(A) 8
(B) 10
(C) 12
(D) 14

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 15^9 = 6; 6+6 = 12.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Bitwise AND

Q6. What will be the output of the following pseudocode?

```
Set Integer a = 27
Set Integer b = 14
display (a & b) + (a % b)
```

(A) 19
(B) 21
(C) 23
(D) 25

Correct Answer: Option (C) : 23

■ **Step-by-Step Logic:** 27&14 = 10 and 27%14 = 13; total = 23.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Bitwise OR

Q7. What will be the output of the following pseudocode?

```
Set Integer a = 18
Set Integer b = 11
display (a | b) - (a & b)
```

(A) 21
(B) 23
(C) 25
(D) 27

Correct Answer: Option (C) : 25

■ **Step-by-Step Logic:** 18|11=27 and 18&11=2; 27–2=25.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: XOR + AND

Q8. What will be the output of the following pseudocode?

```
Set Integer a = 13
Set Integer b = 7
display (a ^ b) + (a & b)
```

(A) 13
(B) 15
(C) 17
(D) 19

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** 13^7=10 and 13&7=5; total = 15. Infosys Medium Pseudocode Practice • Page 33

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Pre/Post Increment

Q9. What will be the output of the following pseudocode?

```
Set Integer x = 4
Set Integer y = x++ + ++x
Set Integer z = y + x
display z
```

(A) 14
(B) 15
(C) 16
(D) 17

Correct Answer: Option (C) : 16

■ **Step-by-Step Logic:** x++ contributes 4 and makes x=5; ++x makes x=6 and contributes 6. y=10; z=10+6=16.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Post/Pre Decrement

Q10. What will be the output of the following pseudocode?

```
Set Integer x = 10
Set Integer y = --x
Set Integer z = y + x--
display z
```

(A) 16
(B) 17
(C) 18
(D) 19

Correct Answer: Option (C) : 18

■ **Step-by-Step Logic:** --x makes x=9, y=9; x-- contributes 9, then x becomes 8. z=18.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Relational Logic

Q11. What will be the output of the following pseudocode?

```
Set Integer p = 8
Set Integer q = 12
display (p + q > 20) and (q - p == 4)
```

(A) true
(B) false
(C) 4
(D) 20

Correct Answer: Option (B) : false

■ **Step-by-Step Logic:** p+q=20, so 20>20 is false. The second condition is true; false AND true = false.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Ternary Logic

Q12. What will be the output of the following pseudocode?

```
Set Integer a = 14
Set Integer b = 9
Set Integer m = (a % 2 == 0) ? a/2 : b*2
display m + b
```

(A) 14
(B) 16
(C) 18
(D) 21

Correct Answer: Option (B) : 16

■ **Step-by-Step Logic:** a is even, so m=7; 7+9=16.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Compound Assignment

Q13. What will be the output of the following pseudocode?

```
Set Integer x = 7
x = x * 3 - 4
x = x + (x % 5)
display x
```

(A) 18
(B) 19
(C) 20
(D) 21

Correct Answer: Option (B) : 19

■ **Step-by-Step Logic:** 7×3–4=17; 17%5=2; final x=19.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Operators

Q14. What will be the output of the following pseudocode?

```
Set Integer a = 20
Set Integer b = 6
display (a / b) + (a % b) * 2
```

(A) 5
(B) 7
(C) 9
(D) 11

Correct Answer: Option (B) : 7

■ **Step-by-Step Logic:** 20/6=3; 20%6=2; 3+2×2=7.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Left Shift

Q15. What will be the output of the following pseudocode?

```
Set Integer x = 11
Set Integer y = 2
display (x << y) - x
```

(A) 22
(B) 33
(C) 44
(D) 55

Correct Answer: Option (B) : 33

■ **Step-by-Step Logic:** 11<<2 = 44; 44–11=33.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Right Shift

Q16. What will be the output of the following pseudocode?

```
Set Integer x = 45
Set Integer y = 2
display (x >> y) + x % 4
```

(A) 10
(B) 11
(C) 12
(D) 13

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 45>>2 = 11; 45%4=1; total=12. Infosys Medium Pseudocode Practice • Page 34

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Left Shift in Expression

Q17. What will be the output of the following pseudocode?

```
Set Integer a = 6
Set Integer b = 3
display (a << b) / 4
```

(A) 8
(B) 10
(C) 12
(D) 16

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** 6<<3=48; 48/4=12.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Right Shift in Expression

Q18. What will be the output of the following pseudocode?

```
Set Integer a = 50
display (a >> 1) - (a >> 3)
```

(A) 17
(B) 19
(C) 21
(D) 23

Correct Answer: Option (B) : 19

■ **Step-by-Step Logic:** 50>>1=25 and 50>>3=6; 25–6=19.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Shift + XOR

Q19. What will be the output of the following pseudocode?

```
Set Integer x = 9
display (x << 1) ^ x
```

(A) 19
(B) 23
(C) 27
(D) 31

Correct Answer: Option (C) : 27

■ **Step-by-Step Logic:** 9<<1=18; 18 XOR 9 = 27.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + AND

Q20. What will be the output of the following pseudocode?

```
Set Integer x = 29
display (x >> 2) & 7
```

(A) 5
(B) 6
(C) 7
(D) 8

Correct Answer: Option (C) : 7
■ **Step-by-Step Logic:** 29>>2=7; 7 AND 7 = 7.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Double Shift

Q21. What will be the output of the following pseudocode?

```
Set Integer x = 7
Set Integer y = (x << 2)
display y >> 1
```

(A) 7
(B) 12
(C) 14
(D) 28

Correct Answer: Option (C) : 14
■ **Step-by-Step Logic:** 7<<2=28; 28>>1=14.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift and Modulo

Q22. What will be the output of the following pseudocode?

```
Set Integer x = 37
display (x >> 1) % 6
```

(A) 0
(B) 1
(C) 2
(D) 3

Correct Answer: Option (A) : 0
■ **Step-by-Step Logic:** 37>>1=18; 18%6=0.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift Condition

Q23. What will be the output of the following pseudocode?

```
Set Integer x = 23
if ((x >> 2) >= 5)
display x - 3
else
display x + 3
end-if
```

(A) 20
(B) 23
(C) 26
(D) 28

Correct Answer: Option (A) : 20
■ **Step-by-Step Logic:** 23>>2=5, so the condition is true and 23–3=20.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + Arithmetic

Q24. What will be the output of the following pseudocode?

```
Set Integer a = 14
Set Integer b = 2
display (a << b) - (a >> b)
```

(A) 51
(B) 53
(C) 55
(D) 57

Correct Answer: Option (B) : 53
■ **Step-by-Step Logic:** 14<<2=56; 14>>2=3; 56–3=53. Infosys Medium Pseudocode Practice • Page 35

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift Chain

Q25. What will be the output of the following pseudocode?

```
Set Integer x = 3
x = x << 2
x = x >> 1
x = x << 1
display x
```

(A) 6
(B) 10
(C) 12
(D) 24

Correct Answer: Option (C) : 12
■ **Step-by-Step Logic:** 3→12→6→12.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + OR

Q26. What will be the output of the following pseudocode?

```
Set Integer x = 5
display (x << 2) | 3
```

(A) 19
(B) 20
(C) 23
(D) 24

Correct Answer: Option (C) : 23
■ **Step-by-Step Logic:** 5<<2=20; 20|3=23.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shift + XOR

Q27. What will be the output of the following pseudocode?

```
Set Integer x = 12
display (x >> 1) ^ 5
```

(A) 1
(B) 3
(C) 5
(D) 7

Correct Answer: Option (B) : 3
■ **Step-by-Step Logic:** 12>>1=6; 6 XOR 5 = 3.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Bit Test with Shift

Q28. What will be the output of the following pseudocode?

```
Set Integer x = 40
display (x >> 3) & 1
```

(A) 0
(B) 1
(C) 2
(D) 5

Correct Answer: Option (B) : 1
■ **Step-by-Step Logic:** 40>>3=5; 5 AND 1 = 1.

[OnlineStudy4U 100 Medium-Level MCQs]
Topic: Shifted Difference

Q29. What will be the output of the following pseudocode?

```
Set Integer a = 31
display (a << 1) - (a >> 2)
```

(A) 54
(B) 55
(C) 56
(D) 57

Correct Answer: Option (B) : 55
■ **Step-by-Step Logic:** 31<<1=62; 31>>2=7; 62–7=55.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Arithmetic

Q30. What will be the output of the following pseudocode?

```
Integer calc(Integer a, Integer b)
a = a + b
b = a - b
return a * b
End function
display calc(7, 3)
```

(A) 60
(B) 70
(C) 80
(D) 90

Correct Answer: Option (B) : 70

■ **Step-by-Step Logic:** a becomes 10; b becomes 7; return 10×7=70.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with Shift

Q31. What will be the output of the following pseudocode?

```
Integer f(Integer n)
return (n << 2) + (n >> 1)
End function
display f(10)
```

(A) 40
(B) 45
(C) 50
(D) 55

Correct Answer: Option (B) : 45

■ **Step-by-Step Logic:** 10<<2=40; 10>>1=5; total=45.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with XOR

Q32. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
return (a ^ b) * 2
End function
display f(12, 5)
```

(A) 18
(B) 26
(C) 30
(D) 34

Correct Answer: Option (A) : 18

■ **Step-by-Step Logic:** 12 XOR 5 = 9; 9×2=18.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Modulo

Q33. What will be the output of the following pseudocode?

```
Integer f(Integer n)
return (n * n + 3) % 10
End function
display f(7)
```

(A) 2
(B) 5
(C) 8
(D) 9

Correct Answer: Option (A) : 2

■ **Step-by-Step Logic:** 49+3=52; 52%10=2.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Boolean

Q34. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
if ((a & 1) == 1 and (b & 1) == 0)
return a + b
else
return a - b
end-if
End function
display f(9, 6)
```

(A) 3
(B) 9
(C) 15
(D) 54

Correct Answer: Option (C) : 15

■ **Step-by-Step Logic:** 9 is odd and 6 is even, so return 9+6=15.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function Shifted Return

Q35. What will be the output of the following pseudocode?

```
Integer f(Integer n)
Set Integer a = n << 1
Set Integer b = n >> 1
return a - b
End function
display f(13)
```

(A) 13
(B) 19
(C) 20
(D) 21

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** 13<<1=26; 13>>1=6; difference=20. Infosys Medium Pseudocode Practice • Page 43

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Function with Multiple Updates

Q36. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
a = a * 2
b = b + a
a = a - b
return a + b
End function
display f(4, 3)
```

(A) 7
(B) 8
(C) 9
(D) 10

Correct Answer: Option (B) : 8

■ **Step-by-Step Logic:** a=8; b=11; a=-3; return -3+11=8.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Condition + Shift

Q37. What will be the output of the following pseudocode?

```
Set Integer x = 19
if ((x & 1) == 1)
x = x << 1
x = x + 3
else
x = x >> 1
end-if
display x
```

(A) 19
(B) 38
(C) 41
(D) 44

Correct Answer: Option (C) : 41

■ **Step-by-Step Logic:** 19 is odd; 19<<1=38; +3=41.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Function + Logical

Q38. What will be the output of the following pseudocode?

```
Integer f(Integer a, Integer b)
if (a > 10 and b < 10)
return (a << 1) + b
else
return a + (b << 1)
end-if
End function
display f(12, 7)
```

(A) 24
(B) 26
(C) 31
(D) 38

Correct Answer: Option (C) : 31

■ **Step-by-Step Logic:** 12>10 and 7<10, so (12<<1)+7 = 24+7=31.

[OnlineStudy4U 100 Medium-Level MCQs]

Topic: Mixed Function + Modulo + Shift

Q39. What will be the output of the following pseudocode?

```
Integer f(Integer n)
return ((n % 5) << 2) + (n >> 3)
End function
display f(26)
```

(A) 5
(B) 7
(C) 9
(D) 11

Correct Answer: Option (B) : 7

■ **Step-by-Step Logic:** 26%5=1; 1<<2=4; 26>>3=3; total=7.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q40. What will be the output of the following pseudocode?

```
What is the output of the following Pseudo
Code? Integer division is used.
Integer
a, b
Set
a = 17, b = 5
Print
(a / b) + (a % b)
```

(A) 3
(B) 4
(C) 5
(D) 7

Correct Answer: Option (C) : 5

■ **Step-by-Step Logic:** Integer division: 17 / 5 = 3. Remainder: 17 % 5 = 2. Printed value = 3 + 2 = 5.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q41. What will be the output of the following pseudocode?

```
What is printed after the following Pseudo
Code runs?
Integer
a, b
Set
a = 12, b = 8
a
= a + b
b
= a - b
a
= a - b
Print
a, b
```

(A) 12 8
(B) 8 12
(C) 20 8
(D) 20 12

Correct Answer: Option (B) : 8 12

■ **Step-by-Step Logic:** This swaps the two values without a third variable. a = 12+8 = 20, b = 20-8 = 12, a = 20-12 = 8. Output: 8 12.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q42. What will be the output of the following pseudocode?

```
What is the output of the following Pseudo
Code?
Integer
a, b
Set
a = 9, b = 5
Print
a ^ b
```

(A) 4
(B) 12
(C) 13
(D) 14

Correct Answer: Option (B) : 12

■ **Step-by-Step Logic:** 9 in binary is 1001 and 5 is 0101. XOR sets a bit where the bits differ: 1100, which is 12.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q43. What will be the output of the following pseudocode?

```
What is printed?
Integer
x
Set
x = 10
Print
x & 3
```

(A) 1
(B) 2
(C) 3
(D) 8

Correct Answer: Option (B) : 2

■ **Step-by-Step Logic:** 10 is 1010 and 3 is 0011. AND is 0010, which is 2.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q44. What will be the output of the following pseudocode?

```
What is printed?
Stack
S
push(S,
1)
push(S,
4)
push(S,
9)
pop(S)
pop(S)
Print
peek(S)
```

(A) 1
(B) 4
(C) 9
(D) Empty

Correct Answer: Option (A) : 1

■ **Step-by-Step Logic:** After three pushes the top is 9. Two pops remove 9 then 4. peek returns 1.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q45. What will be the output of the following pseudocode?

```
[Bitwise]
What is printed?
Integer
a
Set
a = 6
Print
a | 3
```

(A) 7
(B) 5
(C) 2
(D) 18

Correct Answer: Option (A) : 7

■ **Step-by-Step Logic:** 6 is 0110, 3 is 0011, OR is 0111 = 7.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q46. What will be the output of the following pseudocode?

```
[Queue]
What is printed?
Queue
Q
enqueue(Q,
11)
enqueue(Q,
22)
enqueue(Q,
33)
dequeue(Q)
dequeue(Q)
Print
front(Q)
```

(A) 11
(B) 22
(C) 33
(D) Empty

Correct Answer: Option (C) : 33

■ **Step-by-Step Logic:** Queue starts [11,22,33]. Two dequeues remove 11 then 22. Front is 33.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q47. What will be the output of the following pseudocode?

```
[Data
Structures] Queue Q receives 5, then 15, then 25. One
dequeue
runs. What is front(Q)?
Queue
Q
enqueue(Q,
5)
enqueue(Q,
15)
enqueue(Q,
25)
dequeue(Q)
Print
front(Q)
```

(A) 5
(B) 15
(C) 25
(D) Empty

Correct Answer: Option (B) : 15

■ **Step-by-Step Logic:** FIFO: 5 leaves. Front is 15.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q48. What will be the output of the following pseudocode?

```
[Data
Structures] After the operations, what does peek return?
Stack
S
push(S,
10)
push(S,
20)
push(S,
30)
pop(S)
push(S,
40)
Print
peek(S)
```

(A) 10
(B) 20
(C) 40
(D) 30

Correct Answer: Option (C) : 40

■ **Step-by-Step Logic:** Stack after pops/pushes: [10, 20, 40]. peek = 40.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q49. What will be the output of the following pseudocode?

```
[Bitwise]
What is printed?
Integer
a, b
Set
a = 13, b = 6
Print
a & b
```

(A) 4
(B) 5
(C) 7
(D) 11

Correct Answer: Option (A) : 4

■ **Step-by-Step Logic:** 13 is 1101, 6 is 0110, AND is 0100 = 4.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q50. What will be the output of the following pseudocode?

```
What
is printed?
Stack
S
push(S,
3)
push(S,
6)
push(S,
9)
pop(S)
push(S,
12)
Print
peek(S)
```

(A) 3
(B) 6
(C) 12
(D) 9

Correct Answer: Option (C) : 12

■ **Step-by-Step Logic:** After pop, 9 is gone. 12 is pushed. peek returns 12.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q51. What will be the output of the following pseudocode?

```
What
is printed?
Integer
x
Set
x = 11
Print
x | 4
```

(A) 15
(B) 7
(C) 8
(D) 44

Correct Answer: Option (A) : 15

■ **Step-by-Step Logic:** 11 is 1011, 4 is 0100, OR is 1111 = 15.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q52. What will be the output of the following pseudocode?

```
What
is printed?
Queue
Q
enqueue(Q,
7)
enqueue(Q,
14)
enqueue(Q,
21)
dequeue(Q)
enqueue(Q,
28)
Print
front(Q)
```

(A) 7
(B) 14
(C) 21
(D) 28

Correct Answer: Option (B) : 14

■ **Step-by-Step Logic:** 7 is removed first. The new front is 14.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q53. What will be the output of the following pseudocode?

```
What
is printed?
Integer
z
Set
z = 14
Print
z & 7
```

(A) 6
(B) 7
(C) 8
(D) 21

Correct Answer: Option (A) : 6

■ **Step-by-Step Logic:** 14 is 1110, 7 is 0111, AND is 0110 = 6.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q54. What will be the output of the following pseudocode?

```
What
is printed?
Queue
Q
enqueue(Q,
4)
enqueue(Q,
8)
enqueue(Q,
12)
dequeue(Q)
Print
front(Q)
```

(A) 4
(B) 8
(C) 12
(D) Empty

Correct Answer: Option (B) : 8

■ **Step-by-Step Logic:** 4 leaves first. Front is 8.

[OnlineStudy4U Master E-Book 4]

Topic: *Pseudocode Execution Tracing*

Q55. What will be the output of the following pseudocode?

```
What
is printed?
Stack
S
push(S,
2)
push(S,
5)
push(S,
8)
pop(S)
push(S,
11)
Print
peek(S)
```

(A) 2
(B) 5
(C) 11
(D) 8

Correct Answer: Option (C) : 11

■ **Step-by-Step Logic:** Pop removes 8. Push 11. peek returns 11.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q56. What will be the output of the following pseudocode?

```
What
is printed?
Stack
S
push(S,
6)
push(S,
9)
push(S,
15)
pop(S)
push(S,
21)
Print
peek(S)
```

(A) 6
(B) 9
(C) 21
(D) 15

Correct Answer: Option (C) : 21

■ **Step-by-Step Logic:** Pop removes 15. Push 21. peek returns 21.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q57. What will be the output of the following pseudocode?

```
What
is printed?
Integer
k
Set
k = 21
Print
k >> 2
```

(A) 5
(B) 6
(C) 10
(D) 84

Correct Answer: Option (A) : 5

■ **Step-by-Step Logic:** 21 is 10101. Right shift 2 gives 101 = 5.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q58. What will be the output of the following pseudocode?

```
What
is printed?
Queue
Q
enqueue(Q,
3)
enqueue(Q,
9)
enqueue(Q,
15)
dequeue(Q)
Print
front(Q)
```

(A) 3
(B) 9
(C) 15
(D) Empty

Correct Answer: Option (B) : 9

■ **Step-by-Step Logic:** 3 leaves. Front is 9.

[OnlineStudy4U Master E-Book 4]

Topic: Pseudocode Execution Tracing

Q59. What will be the output of the following pseudocode?

```
What will be the
output of the following pseudo code
Integer
i, j, k, d
Set
j = 6, i = 8, k = 2, d = 1
if
((j ^ i) mod k equals 0) then
d = d + 1
else
d = d - 1
end
if
Print
d
```

(A) 1
(B) 3
(C) 0
(D) 2

Correct Answer: Option (D) : 2

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 2.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q60. What will be the output of the following pseudocode?

```
1.     Where are placed the list of processes that are
prepared to be executed and waiting?
```

(A) Job queue
(B) Ready queue
(C) Execution queue
(D) Process queue

Correct Answer: Option (B) : Ready queue

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : Ready queue.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q61. What will be the output of the following pseudocode?

```
1.     Who among the following can block the running
process?
```

(A) Fork
(B) Read
(C) Down
(D) All of these

Correct Answer: Option (D) : All of these

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : All of these.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q62. What will be the output of the following pseudocode?

```
1.     Which of the following does not interrupt the
running process?
```

(A) Timer interrupt
(B) Device
(C) Power failure
(D) Scheduler process

Correct Answer: Option (D) : Scheduler process

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : Scheduler process.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q63. What will be the output of the following pseudocode?

```
1.    The \u0021 article referred to as a
```

(A) Unicode escape sequence
(B) Octal escape
(C) Hexadecimal
(D) Line feed

Correct Answer: Option (A) : Unicode escape sequence

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : Unicode escape sequence.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q64. What will be the output of the following pseudocode?

```
1.    Which of the following is a valid long literal?
```

(A) ABH8097
(B) L990023
(C) 904423
(D) 0xnf029L

Correct Answer: Option (D) : 0xnf029L

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 0xnf029L.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q65. What will be the output of the following pseudocode?

```
1.    What does the expression float a = 35 / 0 return?
```

(A) 0
(B) Not a Number
(C) Infinity
(D) Run time exception

Correct Answer: Option (C) : Infinity

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : Infinity.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q66. What will be the output of the following pseudocode?

```
1.    Which option is false about the final keyword?
a)    A) A final method cannot be overridden in its
subclasses.
b)    B) A final class cannot be extended.
c)    C) A final class cannot extend other classes.
d)    D) A final method can be inherited.
```

(A) A&B
(B) B&C
(C) C&D
(D) None of these

Correct Answer: Option (C) : C&D

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : C&D.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q67. What will be the output of the following pseudocode?

```
1.    Construct post order Transversal for the
constructed tree with the given In-Order and Preorder
Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8
```

(A) 9 10 7 8 6
(B) 9 7 6 10 8
(C) 8 9 10 7 6
(D) 9 8 10 7 6

Correct Answer: Option (A) : 9 10 7 8 6

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 9 10 7 8 6.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q68. What will be the output of the following pseudocode?

```
1.    Which of the following declarations is invalid in
C language?
```

(A) char
(B) char str[] = “campus monk is the best platform for learn";
(C) char str[20] = “campus monk is the best platform for learn";
(D) char[] str = “campus monk is the best platform for learn";

Correct Answer: Option (D) : char[] str = “campus monk is the best platform for learn";

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : char[] str = “campus monk is the best platform for learn";.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q69. What will be the output of the following pseudocode?

```
1.    In an empty BST, insert the following elements in
a similar sequence. Which element will be at lowest
level?

105    95    122    99    97    120
```

(A) 95
(B) 97
(C) 99
(D) 120

Correct Answer: Option (B) : 97

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 97.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q70. What will be the output of the following pseudocode?

```
1.    Which of the following sequence can be obtained in
the output (in same order) using a stack assuming that
the input is in the sequence 1,2,3,4,5 order?
```

(A) a) 3,4,5,1,2
(B) a) 3,4,5,2,1
(C) a) 1,5,2,3,4
(D) a) 5,4,3,1,2

Correct Answer: Option (B) : a) 3,4,5,2,1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : a) 3,4,5,2,1.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q71. What will be the output of the following pseudocode?

```
1.    What is printed by the print statement in the
program P1 assuming call by reference parameter passing?
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
Y= Y+4
Z= X+Y+Z

}
```

(A) 10, 3
(B) 31, 3
(C) 27, 7
(D) None of these

Correct Answer: Option (B) : 31, 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 31, 3.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q72. What will be the output of the following pseudocode?

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c
```

(A) 71
(B) 56
(C) 47
(D) 54

Correct Answer: Option (D) : 54

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 54.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q73. What will be the output of the following pseudocode?

```
Int p, q, r Set p = 6, q = 4, r = 7 p = (r + 5) + p If ((q & r & p) < (p & 6)) { r = 3 ^ r q = q & q } Print p + q + r
```

(A) 44
(B) 41
(C) 11
(D) 26

Correct Answer: Option (D) : 26

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 26.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q74. What will be the output of the following pseudocode?

```
What is the output of this code? Int p, q, r; Set p = 0, q = 7, r = 9; If ((q + p) < (p + q) && (p < r)) { p = 11 + q; } Print p + q + r;
```

(A) 12
(B) 16
(C) 27
(D) 10

Correct Answer: Option (B) : 16

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 16.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q75. What will be the output of this pseudocode? a = 7, b = 2, c = 8 If ((b ^ a) < a && (2 ^ 7) < c) a = b + c Else c = (4 + 12) + a b = 11 + a End if Print (a + b + c)

(A) 19
(B) 21
(C) 20
(D) 22

Correct Answer: Option (C) : 20

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 20.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q76. What will be the output of the following pseudocode?

```
Find the output of the code snippet. Integer x, y, z Set x = 1, y = 8, z = 2 If (x ^ y && x ^ y && x ^ y ^ z) x = 1 End if Print x + y + z
```

(A) 11
(B) 13
(C) 16
(D) 9

Correct Answer: Option (A) : 11

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 11.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q77. What will be the output of the following pseudocode?

```
Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2) && y + (3 & 3) && z + (2 ^ 2)) x = x - 2 y = x Else x = z y = y ^ 2 End if Print x + y + z
```

(A) 2
(B) 11
(C) 3
(D) 0

Correct Answer: Option (C) : 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 3.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q78. What will be the output of the following pseudocode?

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x) return 0; }
```

(A) 0
(B) 1
(C) 5
(D) Compilation Error

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q79. What will be the output of the following pseudocode?

```
Q4.) Predict the output of the following pseudocode. Integer x, y, z Set x = -2, y = 3, z = 1 if (x + (2 & 2) && y + (3 & 3) && z + (2 ^ 2)) x = x -2 y = x Else x = z y = y ^ 2 End if Print x + y + z
```

(A) 2
(B) 11
(C) 0
(D) 3

Correct Answer: Option (D) : 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 3.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q80. What will be the output of the following pseudocode?

```
Q5. What is the output int main() { int x = 10; int *y, **z; y = &x; z = &y; **z=7; print(x,*y,**z) return 0; }
```

(A) 10 10 10
(B) 10 7 7
(C) 7 7 7
(D) 10 10 7

Correct Answer: Option (C) : 7 7 7

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 7 7 7.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q81. Q8. What will be the output of the following pseudocode? int a , b ,c Set a=0,b=1,c=2 If (b^c || a&b || a>>1) c=9 a =b+c else c =1 a=a+c End if Print a+b+c

(A) 20

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 09 Mock Test]
Topic: Campus Monk Mock Pseudocode

Q82. What will be the output of the following pseudocode?

```
What is the output of following code: Int main(){ Int n=(1<<2+3<<4) Print(n); Return 0; }
```

(A) 112
(B) 512
(C) 52
(D) 0

Correct Answer: Option (B) : 512

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 512.

[Campus Monk Day 09 Mock Test]
Topic: Campus Monk Mock Pseudocode

Q83. What will be the output of the following pseudocode?

```
int main() { int x, y = 5, z = 5; x = y == z; Print(x); return 0; }
```

(A) 0
(B) 1
(C) 5
(D) Compilation Error

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 09 Mock Test]
Topic: Campus Monk Mock Pseudocode

Q84. What will be the output of the following pseudocode?

```
Integer p, q, r Set p = 4, q = 2, r = 5 p = (q + p) + p if ((q + p) < (r - q) && 3 > p) then p = (q + r) + p if (((p + r) + (r + q)) <= (p + r + q)) then r = q + p else r = (p + r) + p end if p = (9 & 6) + q else q = r & r if ((q - 5) < (5 - q)) then r = (6 + 6) & q q = (q + 7) + r end if p = (1 ^ 11) + q end if Print p + q + r
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 09 Mock Test]
Topic: Campus Monk Mock Pseudocode

Q85. What will be the output of the following pseudocode?

```
Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[Campus Monk Day 09 Mock Test]
Topic: Campus Monk Mock Pseudocode

Q86. What will be the output of the following pseudocode?

```
Integer a, b, c Set a = 1, b = 6, c = 7 b = (a & b) + b for (each c from 3 to 5) { b = (a + a) ^ a b = (12 + 5) + a } a = (a ^ 9) + a Print a + b
```

(A) undefined

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 1]
Topic: Infosys SE College Mock Test

Q87. What will be the output of the following pseudocode?

```
A stack is used (operands are evaluated left to right).
What is printed?
push(3); push(5); push(7);
x = pop();
push(x * 2);
push(pop() + pop());
print(pop() - pop())
```

(A) 14
(B) 16
(C) 19
(D) 22

Correct Answer: Option (A) : 14

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 14.

[College ITM Mock Paper 3]
Topic: Infosys SE College Mock Test

Q88. What will be the output of the following pseudocode?

```
What is printed?
```

(A) 40
(B) 46
(C) 52
(D) 44

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 3]
Topic: Infosys SE College Mock Test

Q89. What will be the output of the following pseudocode?

```
What is printed?
```

(A) 37
(B) 41
(C) 45
(D) 39

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 3]
Topic: Infosys SE College Mock Test

Q90. What will be the output of the following pseudocode?

```
What is printed?
```

(A) 130
(B) 124
(C) 136
(D) 118

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 4]
Topic: Infosys SE College Mock Test

Q91. What will be the output of the following pseudocode?

```
What is printed? (^=XOR, |=OR, &=AND, >>=right shift)
a = 13; b = 25;
c = (a ^ b) & (a | b);
d = c >> 2;
print(c + d)
```

(A) 25
(B) 29
(C) 20
(D) 33

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 5]

Topic: *Infosys SE College Mock Test*

Q92. What will be the output of the following pseudocode?

```
This stack trace evaluates a postfix-style expression.
What is printed?
push(6); push(2); push(3);
c = pop(); b = pop(); push(b + c);
d = pop(); e = pop(); push(e - d);
push(3); push(8); push(2);
f = pop(); g = pop(); push(g / f);
h = pop(); i = pop(); push(i + h);
j = pop(); k = pop(); push(k * j);
print(pop())
```

(A) 7
(B) 10
(C) 14
(D) 4

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.

[College ITM Mock Paper 6]

Topic: *Infosys SE College Mock Test*

Q93. What will be the output of the following pseudocode?

```
What is printed? (^=XOR, >>=right shift, &=AND)
n = 13
g = n ^ (n >> 1)
print(g + (g & 5))
```

(A) 12
(B) 11
(C) 16
(D) 14

Correct Answer: See Logic

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches See Logic.