INFOSYS SE PSEUDOCODE VAULT • ALGORITHMIC COMPLEXITY & THEORY

Time Complexity, OOP Pseudocode, Scoping, Static Variables • Total Solved Questions: 18

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q1. What will be the output of the following pseudocode?

```
1.     #include<iostream>
using namespace std;
class Test  {
static  int x;
public:
Test()   {    x++;    }
static int getX()  {   return x;    }   };
int Test::x=0;
int main()   {
cout<< Test::getX()<<" ";
Test t[5];

cout<< Test::getX();      }
```

(A) 0 0
(B) 5 5
(C) 0 5
(D) a) Run time error

Correct Answer: Option (C) : 0 5

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 0 5.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q2. What will be the output of the following pseudocode?

```
1.     #include<iostream>
using namespace std;
class Point    {
Point()
 {  cout<<"Constructor called";   }
};
int main(){
Point t1;
return 0;
}
```

(A) Constructor called
(B) Compile time error
(C) Run time error
(D) Blank line

Correct Answer: Option (B) : Compile time error

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : Compile time error.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q3. What will be the output of the following pseudocode?

```
1.     #include<stdio.h>
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }

 }
```

(A) 7 6 3
(B) 7 5 4
(C) 6 7 8
(D) 6 5 4

Correct Answer: Option (A) : 7 6 3

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 7 6 3.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q4. 1. What will be the output of this statement?

```
printf ("%d", 9/5);
```

(A) 1.8
(B) 1.0
(C) 2.0
(D) None of these

Correct Answer: Option (D) : None of these

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : None of these.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q5. 1. What will be the output of this program?

```
#include<stdio.h>
      int main() {
      int i = 5;
      printf("%d", i = ++i == 6);
      return 0;
      }
```

(A) 2
(B) 6
(C) 4
(D) 1

Correct Answer: Option (D) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 1.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q6. 1. What will be the output of this program?

```
#include<stdio.h>
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf("%d", h);
   return 0;
}
```

(A) 1
(B) error: redeclaration of an enumerator
(C) h
(D) 3

Correct Answer: Option (B) : error: redeclaration of an enumerator

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : error: redeclaration of an enumerator.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q7. 1. What will be the output of this program?

```
main ()
{
 if (5 < '5')
        printf("5")
 else
        printf(" NOT EQUAL TO 5.")

}
```

(A) ENQ
(B) 5
(C) I
(D) Not equal to 5

Correct Answer: Option (B) : 5

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 5.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q8. What will be the output of the following pseudocode?

```
1.     The value of j at the end of the execution of the
following pseudo code is ?
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)

end for
```

(A) 10
(B) 4
(C) 6
(D) 7

Correct Answer: Option (A) : 10

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 10.

[Campus Monk Day 04 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q9. What will be the output of the following pseudocode?

```
1.     The value returned by the following function for
f(1) is?
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);

}
```

(A) 5
(B) 6
(C) 7
(D) 8

Correct Answer: Option (C) : 7

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 7.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q10. What will be the output of the following pseudocode?

```
Find the output of the following code. #include <stdio.h>
int main(void) { int a = 10, x; x = a-- + +445; printf
("%d", x); return 0; }
```

(A) 19
(B) 435
(C) 455
(D) 23

Correct Answer: Option (C) : 455

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 455.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q11. What will be the output of the following pseudocode?

```
Find the output of the following code. #include <stdio.h>
void main() { int a = 10; if (a == 010) printf("BCA");
else printf("B.Tech"); }
```

(A) BCA
(B) B.tech
(C) 10
(D) Error

Correct Answer: Option (B) : B.tech

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : B.tech.

[Campus Monk Day 06 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q12. What will be the output of the following pseudocode?

```
Find the output of the following code. #include <stdio.h>
void main () { int x = 91; x >>= 2; printf ("%d\n", x); }
```

(A) 182
(B) 91
(C) 22
(D) 82

Correct Answer: Option (C) : 22

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (C) : 22.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q13. What will be the output of the following pseudocode?

```
What is the output of the following C code? #include
<stdio.h> int main() { int num = 987; int rem; while(num
!= 0) { rem = num % 4; num = num / 10; } printf("%d",
rem); }
```

(A) 0
(B) 1
(C) 10
(D) 5

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q14. What will be the output of the following pseudocode?

```
What is the output of the following C code? #include
<stdio.h> int main() { float x = 0.0; long int y = 10;
printf("%d", sizeof(y) == sizeof(x + y)); return 0; }
```

(A) 3
(B) 1
(C) 5
(D) 2

Correct Answer: Option (B) : 1

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 1.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q15. What will be the output of the following pseudocode?

```
What is the output of the following C code? int f(int x,
int *py, int **ppz) { int y, z; **ppz += 1; z = **ppz;
*py += 2; y = *py; x += 3; return x + y + z; } void
main() { int c, *b, **a; c = 4; b = &c; a = &b;
printf("%d ", f(c, b, a)); return 0; }
```

(A) 18
(B) 19
(C) 21
(D) 22

Correct Answer: Option (B) : 19

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : 19.

[Campus Monk Day 07 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q16. What will be the output of the following pseudocode?

```
What is the output of the following C code? #include
<stdio.h> int main() { int a = 12; void *ptr = (int *)&a;
printf("%d", *ptr); getchar(); return 0; }
```

(A) 12
(B) Compiler Error
(C) Run Time Error
(D) 0

Correct Answer: Option (B) : Compiler Error

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (B) : Compiler Error.

[Campus Monk Day 08 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q17. What will be the output of the following pseudocode?

```
Q2.) #include<iostream> using namespace std; int main() {
int a = 3, b = 2, c = 5; int result = (a++ << 2) + (--b
<< 1) - (c-- >> 1) + (a & b); cout << result; return 0; }
```

(A) 12
(B) 14
(C) 10
(D) 16

Correct Answer: Option (A) : 12

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (A) : 12.

[Campus Monk Day 09 Mock Test]

Topic: Campus Monk Mock Pseudocode

Q18. What will be the output of the following pseudocode?

```
int main() { int x = 9, y = 2, z = 6; int a = x & y | z;
printf("%d", a); return 0; }
```

(A) Error
(B) 2
(C) 3
(D) 6

Correct Answer: Option (D) : 6

■ **Step-by-Step Logic:** Evaluating the pseudocode step-by-step confirms the evaluated result matches Option (D) : 6.