INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

Technical MCQ - Pseudo Codes Based on PYQ With Video Sol

Section: 09_Mock_Test_Series | Drive Date: 5th & 6th November 2026 | Status: 100% Solved & Verified

Technical MCQ - Pseudo Codes Based on PYQ With Video Sol

Total Questions: 30 | **Total Marks:** 30 | **Duration:** 30 Minutes

Section: Technical

Question 1 [Marks: +1, -0.25]

```
1.    #include
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];
cout<< Test::getX();     }
```

Options:

- **(A)** 0 0
- **(B)** 5 5
- **(C)** 0 5
- **(D)** a) Run time error

Question 2 [Marks: +1, -0.25]

```
1.    #include
using namespace std;
class Point   {
Point()
{ cout<<"Constructor called";  }
```

```
};
int main(){
Point t1;
return 0;
}
```

Options:

- **(A)** Constructor called
- **(B)** Compile time error
- **(C)** Run time error
- **(D)** Blank line

Question 3 [Marks: +1, -0.25]

1.
```
#include
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }
}
```

Options:

- **(A)** 7 6 3
- **(B)** 7 5 4
- **(C)** 6 7 8
- **(D)** 6 5 4

Question 4 [Marks: +1, -0.25]

1. Where are placed the list of processes that are prepared to be executed and waiting?

Options:

- **(A)** Job queue
- **(B)** Ready queue
- **(C)** Execution queue
- **(D)** Process queue

Question 5 [Marks: +1, -0.25]

1. Who among the following can block the running process?

Options:

- **(A)** Fork
- **(B)** Read
- **(C)** Down
- **(D)** All of these

Question 6 [Marks: +1, -0.25]

1. Which of the following does not interrupt the running process?

Options:

- **(A)** Timer interrupt
- **(B)** Device
- **(C)** Power failure
- **(D)** Scheduler process

Question 7 [Marks: +1, -0.25]

1. The \u0021 article referred to as a

Options:

- **(A)** Unicode escape sequence
- **(B)** Octal escape
- **(C)** Hexadecimal
- **(D)** Line feed

Question 8 [Marks: +1, -0.25]

1. Which of the following is a valid declaration of a char?

Options:

- **(A)** char ch = '\utea';
- **(B)** char ca = 'tea';
- **(C)** char cr = \u0223;
- **(D)** char cc = '\itea';

Question 9 [Marks: +1, -0.25]

1. Which of the following is a valid long literal?

Options:

- **(A)** ABH8097
- **(B)** L990023
- **(C)** 904423
- **(D)** 0xnf029L

Question 10 [Marks: +1, -0.25]

1. What does the expression float a = 35 / 0 return?

Options:

- **(A)** 0
- **(B)** Not a Number
- **(C)** Infinity
- **(D)** Run time exception

Question 11 [Marks: +1, -0.25]

1. Which option is false about the final keyword?
   a) A) A final method cannot be overridden in its subclasses.
   b) B) A final class cannot be extended.
   c) C) A final class cannot extend other classes.
   d) D) A final method can be inherited.

Options:

- **(A)** A&B
- **(B)** B&C
- **(C)** C&D
- **(D)** None of these

Question 12 [Marks: +1, -0.25]

1. Construct post order Transversal for the constructed tree with the given In-Order and Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8

Options:

- **(A)** 9 10 7 8 6
- **(B)** 9 7 6 10 8
- **(C)** 8 9 10 7 6
- **(D)** 9 8 10 7 6

Question 13 [Marks: +1, -0.25]

1. What will be the output of this program fragment?

```
int i = 263;
putchar(i);
```

Options:

- **(A)** prints 263
- **(B)** prints the ASCII equivalent of 263
- **(C)** rings the bell
- **(D)** prints garbage

Question 14 [Marks: +1, -0.25]

1. What will be the output of this statement?

printf (“%d”, 9/5);

Options:

- **(A)** 1.8
- **(B)** 1.0
- **(C)** 2.0
- **(D)** None of these

Question 15 [Marks: +1, -0.25]

1. What will be the output of this program?

```
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

Options:

- **(A)** 2
- **(B)** 6
- **(C)** 4
- **(D)** 1

Question 16 [Marks: +1, -0.25]

1. Which of the following declarations is invalid in C language?

Options:

- **(A)** char *str = “campus monk is the best platform for learn";

- **(B)** char str[] = “campus monk is the best platform for learn";
- **(C)** char str[20] = “campus monk is the best platform for learn";
- **(D)** char[] str = “campus monk is the best platform for learn";

Question 17 [Marks: +1, -0.25]

1. What will be the output of this program?

```
include
```

```
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf(“%d”, h);
   return 0;
}
```

Options:

- **(A)** 1
- **(B)** error: redeclaration of an enumerator
- **(C)** h
- **(D)** 3

Question 18 [Marks: +1, -0.25]

1. What will be the output of this program?

```
main ()
{
 if (5 < ’5’)
        printf(“5”)
 else
        printf(“ NOT EQUAL TO 5.”)
}
```

Options:

- **(A)** ENQ
- **(B)** 5
- **(C)** I
- **(D)** Not equal to 5

Question 19 [Marks: +1, -0.25]

1. What will be the output of the following pseudo code?

Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n

Options:

- **(A)** 5
- **(B)** 7
- **(C)** 9
- **(D)** 12

Question 20 [Marks: +1, -0.25]

1. What will be the output of the following pseudocode?

Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while

Options:

- **(A)** 6 6 6
- **(B)** 6 5 6
- **(C)** 5 5 5
- **(D)** 6 5 4

Question 21 [Marks: +1, -0.25]

1. If the sequence of operations are performed on a stack, the sequence of pop will be?

Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().

Options:

- **(A)** 2 2 1 1 2
- **(B)** 2 2 1 2 2
- **(C)** 2 1 2 2 1

- **(D)** 2 1 2 2 2

Question 22 [Marks: +1, -0.25]

1. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?

105 95 122 99 97 120

Options:

- **(A)** 95
- **(B)** 97
- **(C)** 99
- **(D)** 120

Question 23 [Marks: +1, -0.25]

T The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?

Options:

- **(A)** a) Singly linked list
- **(B)** a) Doubly linked list
- **(C)** a) Circular doubly linked list
- **(D)** a) Array implementation of list

Question 24 [Marks: +1, -0.25]

1. Which of the following sequence can be obtained in the output (in same order) using a stack assuming that the input is in the sequence 1,2,3,4,5 order?

Options:

- **(A)** a) 3,4,5,1,2
- **(B)** a) 3,4,5,2,1
- **(C)** a) 1,5,2,3,4
- **(D)** a) 5,4,3,1,2

Question 25 [Marks: +1, -0.25]

1. Let A be a square matrix of size nxn. Consider the following program and state the output.

```
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
```

A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do

Output (A[i][j]);

Options:

- **(A)** a) The matrix A itself
- **(B)** a) Transpose of matrix A
- **(C)** a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
- **(D)** a) None of the above

Question 26 [Marks: +1, -0.25]

1. The value of j at the end of the execution of the following pseudo code is ?

```
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)

end for
```

Options:

- **(A)** 10
- **(B)** 4
- **(C)** 6
- **(D)** 7

Question 27 [Marks: +1, -0.25]

1. What is printed by the print statement in the program P1 assuming call by reference parameter passing?

```
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
{
```

```
Y= Y+4
Z= X+Y+Z
}
```

Options:

- **(A)** 10, 3
- **(B)** 31, 3
- **(C)** 27, 7
- **(D)** None of these

Question 28 [Marks: +1, -0.25]

1. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);
}
```

Options:

- **(A)** 5
- **(B)** 6
- **(C)** 7
- **(D)** 8

Question 29 [Marks: +1, -0.25]

1. Find the output of the following pseudo code.

```
Integer n
Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if
```

Print n

Options:

- **(A)** 7
- **(B)** 18
- **(C)** 22
- **(D)** 2

Question 30 [Marks: +1, -0.25]

1. Find the output of the following pseudo code.

```
Integer x,y,z
Set x=9, y=2, z=1
if ( x+y > 8)
if ( 7> x+z)
z=7
End if
If ( 9> x-z)
z=9
End if
y=y+z+1
End if

Print x+y+z
```

Options:

- **(A)** 31
- **(B)** 11
- **(C)** 42
- **(D)** 30
