INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

Technical MCQ - Pseudo Codes Based on PYQ With Video Sol — Solutions & Explanations

Section: 09_Mock_Test_Series | Drive Date: 5th & 6th November 2026 | Status: 100% Solved & Verified

Technical MCQ - Pseudo Codes Based on PYQ With Video Sol — Solutions & Explanations

Total Questions: 30 | **Total Marks:** 30

Section: Technical

Question 1

```
1.    #include
using namespace std;
class Test  {
static  int x;
public:
Test()  {   x++;   }
static int getX()  {   return x;   }  };
int Test::x=0;
int main()  {
cout<< Test::getX()<<" ";
Test t[5];

cout<< Test::getX();     }
```

Options:

- (A) 0 0
- (B) 5 5
- ✅ **(C) 0 5** *(Correct Answer)*
- (D) a) Run time error

Correct Answer: (C)

> 💡 **Explanation:**
> Answer: C

Question 2

```
1.  #include
using namespace std;
class Point  {
Point()
 {  cout<<“Constructor called”;  }
};
int main(){
Point t1;
return 0;
}
```

Options:

- (A) Constructor called
- ✅ **(B) Compile time error** *(Correct Answer)*
- (C) Run time error
- (D) Blank line

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 3

```
1.  #include
using namespace std;
int main()
{
for (int x = 10; x >= 0; x--)
 {
 int z = x & (x >> 1);
 if (z)
 printf("%d ", x);
 }

}
```

Options:

- ✅ **(A) 7 6 3** *(Correct Answer)*
- (B) 7 5 4
- (C) 6 7 8
- (D) 6 5 4

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 4

1. Where are placed the list of processes that are prepared to be executed and waiting?

Options:

- (A) Job queue
- ✅ **(B) Ready queue** *(Correct Answer)*
- (C) Execution queue
- (D) Process queue

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 5

1. Who among the following can block the running process?

Options:

- (A) Fork
- (B) Read
- (C) Down
- ✅ **(D) All of these** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 6

1. Which of the following does not interrupt the running process?

Options:

- (A) Timer interrupt
- (B) Device
- (C) Power failure
- ✅ **(D) Scheduler process** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 7

1. The \u0021 article referred to as a

Options:

- ✅ **(A) Unicode escape sequence** *(Correct Answer)*
- (B) Octal escape
- (C) Hexadecimal
- (D) Line feed

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 8

1. Which of the following is a valid declaration of a char?

Options:

- ✅ **(A) char ch = '\utea';** *(Correct Answer)*
- (B) char ca = 'tea';
- (C) char cr = \u0223;
- (D) char cc = '\itea';

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 9

1. Which of the following is a valid long literal?

Options:

- (A) ABH8097
- (B) L990023
- (C) 904423

- ✅ **(D) 0xnf029L** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 10

1. What does the expression float a = 35 / 0 return?

Options:

- (A) 0
- (B) Not a Number
- ✅ **(C) Infinity** *(Correct Answer)*
- (D) Run time exception

Correct Answer: (C)

> 💡 **Explanation:**
> Answer: C

Question 11

1. Which option is false about the final keyword?
   a) A) A final method cannot be overridden in its subclasses.
   b) B) A final class cannot be extended.
   c) C) A final class cannot extend other classes.
   d) D) A final method can be inherited.

Options:

- (A) A&B
- (B) B&C
- ✅ **(C) C&D** *(Correct Answer)*
- (D) None of these

Correct Answer: (C)

> 💡 **Explanation:**
> Answer: C

Question 12

1. Construct post order Transversal for the constructed tree with the given In-Order and Preorder Traversals:
In-Order: 9 7 10 6 8
Pre-Order: 6 7 9 10 8

Options:

- ✅ **(A) 9 10 7 8 6** *(Correct Answer)*
- (B) 9 7 6 10 8
- (C) 8 9 10 7 6
- (D) 9 8 10 7 6

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 13

1. What will be the output of this program fragment?
   int i = 263;
   putchar(i);

Options:

- (A) prints 263
- (B) prints the ASCII equivalent of 263
- ✅ **(C) rings the bell** *(Correct Answer)*
- (D) prints garbage

Correct Answer: (C)

> 💡 **Explanation:**
> Answer: C

Question 14

1. What will be the output of this statement?
printf (“%d”, 9/5);

Options:

- (A) 1.8
- (B) 1.0
- (C) 2.0
- ✅ **(D) None of these** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 15

1. What will be the output of this program?

```
#include
int main() {
int i = 5;
printf(“%d”, i = ++i == 6);
return 0;
}
```

Options:

- (A) 2
- (B) 6
- (C) 4
- ✅ **(D) 1** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 16

1. Which of the following declarations is invalid in C language?

Options:

- (A) char *str = “campus monk is the best platform for learn";
- (B) char str[] = “campus monk is the best platform for learn";
- (C) char str[20] = “campus monk is the best platform for learn";
- ✅ **(D) char[] str = “campus monk is the best platform for learn";** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 17

1. What will be the output of this program?

```
include
enum flg{a, b, c};
enum glf{c, e, f};
main()
{
  enum flg h;
    h = b;
    printf("%d", h);
   return 0;
}
```

Options:

- (A) 1
- ✅ **(B) error: redeclaration of an enumerator** *(Correct Answer)*
- (C) h
- (D) 3

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 18

1. What will be the output of this program?

```
main ()
{
 if (5 < '5')
       printf("5")
 else
       printf(" NOT EQUAL TO 5.")
}
```

Options:

- (A) ENQ
- ✅ **(B) 5** *(Correct Answer)*
- (C) I
- (D) Not equal to 5

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 19

1. What will be the output of the following pseudo code?

```
Input m = 9,n = 6,
m= m + 1;
n= n - 1;
m= m + n;
if(m>n)
print m
else
print n
```

Options:

- ✅ **(A) 5** *(Correct Answer)*
- (B) 7
- (C) 9
- (D) 12

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 20

1. What will be the output of the following pseudocode?

```
Integer i
Set i = 3
do
print i + 3
i = i - 1
while(i not equals 0)
end while
```

Options:

- (A) 6 6 6
- (B) 6 5 6
- (C) 5 5 5
- ✅ **(D) 6 5 4** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 21

1. If the sequence of operations are performed on a stack, the sequence of pop will be?

Push(1), Push(2), Pop(), Push(1), Push(2), Pop(), Pop(), Pop(), Push(2), Pop().

Options:

- ✅ **(A) 2 2 1 1 2** *(Correct Answer)*
- (B) 2 2 1 2 2
- (C) 2 1 2 2 1
- (D) 2 1 2 2 2

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 22

1. In an empty BST, insert the following elements in a similar sequence. Which element will be at lowest level?

105 95 122 99 97 120

Options:

- (A) 95
- ✅ **(B) 97** *(Correct Answer)*
- (C) 99
- (D) 120

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 23

T The concatenation of two lists is to be performed in O(1) time. Which of the following implementation of a list should be used?

Options:

- (A) a) Singly linked list
- (B) a) Doubly linked list
- ✅ **(C) a) Circular doubly linked list** *(Correct Answer)*
- (D) a) Array implementation of list

Correct Answer: (C)

> 💡 **Explanation:**
> Answer: C

Question 24

1. Which of the following sequence can be obtained in the output (in same order) using a stack assuming that the input is in the sequence 1,2,3,4,5 order?

Options:

- (A) a) 3,4,5,1,2
- ✅ **(B) a) 3,4,5,2,1** *(Correct Answer)*
- (C) a) 1,5,2,3,4
- (D) a) 5,4,3,1,2

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 25

1. Let A be a square matrix of size nxn. Consider the following program and state the output.

```
C=100
for i= 1 to n do
for j = 1 to n do
{
Temp = A[i][j] + C
A[i][j] = A [j][i]
A[j][i]= Temp – C
}for i = 1 to n do
for j = 1 to n do

Output (A[i][j]);
```

Options:

- ✅ **(A) a) The matrix A itself ** *(Correct Answer)*
- (B) a) Transpose of matrix A

- (C) a) Adding 100 to the upper diagonal elements and subtracting 100 from diagonal elements of A
- (D) a) None of the above

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 26

1. The value of j at the end of the execution of the following pseudo code is ?

```
Integer incr(Integer i)
Static Integer count = 0
count = count +i
return count
Main()
Integer i,j
for(start i from 0 to 4)
j= incr(i)
end for
```

Options:

- ✅ **(A) 10** *(Correct Answer)*
- (B) 4
- (C) 6
- (D) 7

Correct Answer: (A)

> 💡 **Explanation:**
> Answer: A

Question 27

1. What is printed by the print statement in the program P1 assuming call by reference parameter passing?

```
program P1()
{
X = 10
Y = 3
Func1(Y,X,X)
Print X
Print Y
}
Func1(X,Y,Z)
```

{
Y= Y+4
Z= X+Y+Z

}

Options:

- (A) 10, 3
- ✅ **(B) 31, 3** *(Correct Answer)*
- (C) 27, 7
- (D) None of these

Correct Answer: (B)

> 💡 **Explanation:**
> Answer: B

Question 28

1. The value returned by the following function for f(1) is?

```
int f(int n)
{
static int i =1;
if (n>=5) return n;
n=n + i ;
i++;
return f(n);

}
```

Options:

- (A) 5
- (B) 6
- ✅ **(C) 7** *(Correct Answer)*
- (D) 8

Correct Answer: (C)

> 💡 **Explanation:**
> Answer: C

Question 29

1. Find the output of the following pseudo code.

```
Integer n
```

Set n = 11
Integer arr[4] = { 10, 11, 1, 2 }
arr[1]=arr[1]-arr[3]
arr[2]=arr[2]+arr[2]
arr[3]=1+arr[3]
n=arr[3]
if(n>arr[2])
n=n-1
Else
n=n-1
End if

Print n

Options:

- (A) 7
- (B) 18
- (C) 22
- ✅ **(D) 2** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D

Question 30

1. Find the output of the following pseudo code.

Integer x,y,z
Set x=9, y=2, z=1
if (x+y > 8)
if (7> x+z)
z=7
End if
If (9> x-z)
z=9
End if
y=y+z+1
End if

Print x+y+z

Options:

- (A) 31
- (B) 11
- (C) 42

- ✅ **(D) 30** *(Correct Answer)*

Correct Answer: (D)

> 💡 **Explanation:**
> Answer: D
