INFOSYS SE ASSESSMENT 2026 • OFFICIAL PREPARATION VAULT

Technical MCQ - Pseudo Codes Based on PYQ 02

Section: 09_Mock_Test_Series | Drive Date: 5th & 6th November 2026 | Status: 100% Solved & Verified

Technical MCQ - Pseudo Codes Based on PYQ 02

Total Questions: 10 | **Total Marks:** 13 | **Duration:** 10 Minutes

Section: Technical Pseudo Codes -01

Question 1 [Marks: +1, -0]

What is the output of following pseudo code: Fun() { Int a=10 , b=20 , c=30; If(c>b>a) Print("True"); Else Print("False"); return 0; }

Options:

- **(A)** True
- **(B)** False
- **(C)** Error
- **(D)** -1

Question 2 [Marks: +1, -0]

What is the output of following code: Int main(){ Int n=(1<<2+3<<4) Print(n); Return 0; }

Options:

- **(A)** 112
- **(B)** 512
- **(C)** 52
- **(D)** 0

Question 3 [Marks: +1, -0]

What is the output of following: Integer x, y Set x = 15, y = 12 y = x – 1 do{ Print x x = y + (x – 2) } while(x < 40) end do while

Options:

- **(A)** 14 26
- **(B)** 15 27 39
- **(C)** 27 39

- **(D)** 15

Question 4 [Marks: +1, -0]

What is the output if fun(5) is called? Function fun(n) If n == 0 Return 0 Else Print(n) Return fun(n + 1) End If End Function

Options:

- **(A)** 1 2 3 4 5
- **(B)** 5 4 3 2 1
- **(C)** Stack overflow
- **(D)** -1

Question 5 [Marks: +1, -0]

int main() { int x, y = 5, z = 5; x = y == z; Print(x); return 0; }

Options:

- **(A)** 0
- **(B)** 1
- **(C)** 5
- **(D)** Compilation Error

Question 6 [Marks: +1, -0]

1. Integer a = 5, b = 9 2. a = a ^ b 3. b = a ^ b 4. a = a ^ b 5. if (a == 9 && b == 5) 6. Print "Swapped" 7. else 8. Print "Not swapped"

Options:

- **(A)** Line 2
- **(B)** Line 3
- **(C)** Line 4
- **(D)** No error

Question 7 [Marks: +1, -0]

int main() { int x = 9, y = 2, z = 6; int a = x & y | z; printf("%d", a); return 0; }

Options:

- **(A)** Error
- **(B)** 2
- **(C)** 3
- **(D)** 6

Question 8 [Marks: +2, -0]

Integer p, q, r Set p = 4, q = 2, r = 5 p = (q + p) + p if ((q + p) < (r - q) && 3 > p) then p = (q + r) + p if (((p + r) + (r + q)) <= (p + r + q)) then r = q + p else r = (p + r) + p end if p = (9 & 6) + q else q = r & r if ((q - 5) < (5 - q)) then r = (6 + 6) & q q = (q + 7) + r end if p = (1 ^ 11) + q end if Print p + q + r

Options:

- **(A)** undefined

Question 9 [Marks: +2, -0]

Integer a, b, c Set a = 2, b = 4, c = 7 b = 7 + a if (c > b) b = b + b end if b = 6 + a if ((a + b) < (b - a) || c < a) b = (c + 4) + c else a = c + b end if c = (c + 9) ^ a Print a + b + c

Options:

- **(A)** undefined

Question 10 [Marks: +2, -0]

Integer a, b, c Set a = 1, b = 6, c = 7 b = (a & b) + b for (each c from 3 to 5) { b = (a + a) ^ a b = (12 + 5) + a } a = (a ^ 9) + a Print a + b

Options:

- **(A)** undefined
