EDITGUARD

A Learned Knowledge Editing and Verification Platform for AI Customer-Support Assistants

Final measured project report

Controlled demonstration dataset | 15 October 2026

SERAC-inspired | Frozen base | Trained scope and answer models

Evidence boundaries

Automated label audit; no independent human review. Agent-authored challenges. Pending prose and abstentions remain uncredited. Source retrieval does not certify generated text.

The original oracle diagnostic includes CUDA execution failures. Its separately declared recovery is an operational supplement; current recovery status is disclosed in the results section.

Active protocol: editguard-final-39d010f6d32b8b7b
Matched questions: 816 | Oracle records: 384

1. Problem and contribution

Product limits and policies change while deployed customer-support models remain static. EditGuard addresses short factual questions about a fictional product catalogue. An administrator publishes an approved correction; subsequent questions can use it without retraining for that individual edit. The registered topic is Knowledge Editing.

The delivered platform combines two actually trained auxiliary models, approved versioned memory, a frozen handbook assistant, transactional conflict and rollback controls, five matched comparisons, a leakage-controlled benchmark and a locally deployable application. Generated answers remain fallible. No arbitrary-language accuracy guarantee or production-company claim is made.

The frozen evaluation contains 816 matched questions and 384 separate oracle-generation records. On the 720 controlled scope questions, request-bound QA credits the learned editor on 613/720 and updated RAG on 649/720. These are supported short-question forms; unfamiliar challenge wording has a separate result.

The learned editor receives complete-assertion credit on 207/816 (25.4%). The original oracle diagnostic was interrupted by a CUDA runtime fault: its 45/384 (11.7%) includes 319 execution errors and cannot be read as a complete generator-quality measurement. A separately named operational supplement, when available, preserves the original record. Complete-assertion and request-bound results are separate evidence.

2. Related work and architectural adaptations

SERAC wraps a fixed base model with edit memory, a scope classifier and a counterfactual generator. Its auxiliary components are trained separately; deployment stores new descriptors and routes relevant requests to conditional generation. Mitchell et al. compare embedding and cross-attention scope architectures and evaluate edit success and preservation. We use these ideas, rather than claim a faithful reproduction of their experiments or algorithm.

Our adaptations are structured product/plan/version/date descriptors, mandatory administrator approval, SQLite transactions, explicit overlapping-conflict resolution, retrieval before pair scoring, calibrated abstention and deterministic compatibility gates. The frozen base retrieves the initial fictional handbook; it does not rely on pretrained knowledge of imaginary products.

The selected DistilBERT classifier uses the versioned entity_neutral_v1 input transform. Only selectors literally referenced by a correction are canonicalized; incompatible selectors and properties remain. Approval, dates, original names and provenance remain in authoritative metadata. This engineered normalization is disclosed separately from learned entity reasoning.

The selected FLAN-T5-small answer model conditions on the question, applicable correction, date and necessary unchanged support context. It produces the original short answer text. A deterministic structured response is a distinct mode and never earns evidence of trained generation. Unknown scope, uncertainty and unresolved conflicts request clarification.

Primary reference: Mitchell et al., Memory-Based Model Editing at Scale, ICML 2022.

3. Dataset, review and split controls

The controlled handbook has 80 fictional entity families, 1,280 initial facts and 480 edit scenarios. Families were assigned before paraphrases and counterfactual values. The modest training pilot uses

four training and two validation families: 240/120 scope pairs and 96/48 answer examples. Training did not use the entire generated catalogue.

Scope data contains applicable pairs, ordinary negatives, different properties on the same product, the same property on another product, similar names, wrong tiers and incompatible versions. Pilot-v3 balances existing negative question forms without changing facts, labels or family assignments. Targets and example labels received a separately typed automated audit; human review is not claimed.

The final packet preserves all 720 scope, 288 answer and 96 challenge rows. Its 1,104 labels passed independent deterministic consistency checks against structured truth. Every source question, fact, label, split and lineage remains unchanged; current input formatting and explicit oracle metadata are derived separately. Original draft flags are retained and the separate machine registry authorizes only final evaluation.

The twelve final families are disjoint from selected training and development entities and edit lineages. Entity normalization creates nine identical same-label scope pairs shared with training, zero shared with validation and no contradictory pairs. The other 711 scope rows are reported separately. Shared controlled templates still limit linguistic generalization.

The 96 unfamiliar-wording/unseen-value challenges were agent-authored drafts, independently machine-audited. They are not manually authored or human-reviewed questions. The user explicitly authorized this automated final audit. Machine consistency checks do not establish external validity or broad natural-language truth.

4. Training and finite model selection

Training used one fixed seed and compact backbones after measured four-update CUDA profiles. The selected scope run stopped at 360 updates; the selected answer run stopped at 240. Both were executed by the user. Data, reviews, pretrained revisions, configurations, selected tensors, optimizer/scheduler/sampler/RNG state and exact training source are recorded. The completed exports passed 986 artifact/checkpoint audit checks.

On the common 120-pair development population, raw scope accuracy rose from 98/120 to 119/120. Validation selected temperature 1.0, threshold 0.97 and uncertainty margin 0.025: 48 correct edit applications, zero of 72 false applications and one clarification. This selection-data result is not an independent final-test estimate.

The answer revision gives equal 8x weight to the opening token of both Yes and No comparison targets. Remaining valid tokens have weight one and padding zero. Its weighted selection loss of 0.16824 cannot be compared with the earlier uniform loss. On a common unweighted objective, validation token NLL worsened from 0.04441 to 0.06173.

Generated development negative comparisons improved from 0/12 to 5/12 correct; seven still failed. Oracle complete-answer credit improved from 31/48 to 34/48 with identical revised scope routing. A reviewed complete storage wording alias increased scoring coverage equally for every configuration; original scores are preserved. No threshold, model or scorer was tuned against final outputs.

Recorded training-loop times were 112.55 seconds for scope and 264.54 for answer; complete command startup/export wall times are unavailable. CUDA reserved peaks were 1.410 and 1.656 GiB. Measurements are from an RTX 4050 laptop with 6 GiB VRAM and 23.71 GiB host RAM. Short profiling estimates and actual loop measurements are distinguished.

5. Frozen fair comparison and scoring

All five configurations answer the same 816 questions: 720 scope questions and 96 challenges. Unchanged base is a diagnostic reference; updated RAG materializes approved corrections, prompt-only receives eligible descriptors, similarity editing uses validation-selected embedding routing, and learned editing uses the trained scope classifier. Both editors use the same trained answer model.

Every updated baseline has the same approved memory and supporting facts. Questions are evaluated in separate mutually exclusive correction scenarios, each with one focal edit and at most eight foreign-product distractors. This is not a dense same-product multi-edit stress test. Deterministic generation uses the same 48-token answer budget and compatible context settings.

Oracle generation uses 288 answer examples plus 96 challenges, separately from the matched end-to-end population. It supplies the applicable correction but not the target answer. Retrieval, raw classifier pairs, actual guarded routes and oracle generation remain separate measurements so failures can be attributed.

Primary scoring checks complete endorsed subject, relation, product/plan/version, value, unit and requested polarity. A target mention, example, rejected possibility or correct database response is insufficient. Unsupported prose stays pending and uncredited; all abstentions/errors remain in fixed-denominator accuracy. Zero complete-assertion credit for a short baseline fragment does not prove that fragment factually wrong.

The frozen secondary rule accepts whole quantities or Yes/No for twelve explicit controlled question forms, after independently checking the requested scope and predicate against truth. It never overrides a primary incorrect verdict. Bare responses do not prove a complete scoped assertion. Unsupported challenge wording remains pending. No LLM judge substitutes for ground truth.

The full-assertion metric favors outputs that restate a scoped fact, a format the trained generator saw in its targets. Baseline fragments can correctly answer a question while receiving no complete-assertion credit. Therefore primary credit differences do not establish superiority in factual QA; use the separately locked request-bound comparison on its supported cohort and disclose unsupported challenge cases.

Paired uncertainty uses 2,000 entity-family bootstrap resamples, seed 42 and 95% intervals. Twelve clusters and one training seed limit precision; these intervals describe family sampling in this controlled benchmark, not uncertainty over retraining or deployed customers.

6. Measured results and their limits

On the fair controlled request-bound metric, the learned editor credits 613/720 (85.14%), updated RAG 649/720 (90.14%), similarity editing 632/720, prompt correction 533/720 and the frozen base 500/720. Updated RAG is the strongest of these configurations. The learned editor does not beat it overall.

The learned editor credits 72/72 direct corrections, 39/72 held-out paraphrases and 97/144 comparisons on the request-bound metric. Thirty-three paraphrases remain pending; 47 comparison answers are wrong. Out-of-scope factual credit is 405/432, with 23 clarifications and four wrong base answers. Retention on the distinct baseline-correct subset is 405/428. Preserving an incorrect initial answer is not factual correctness.

The 96 challenge questions remain a separate population. The learned editor has zero complete-assertion credits, 48 clarifications and 48 pending outputs. The secondary grammar cannot score these unfamiliar forms, so no secondary semantic correctness claim follows. Similarity editing

has 40/96 complete-assertion credits. This challenge exposes limited linguistic generalization.

Actual false correction application is 0/432 (0.0%), including metadata eligibility guards. Raw classifier statistics do not measure guarded routing or answer generation.

Serial CLI latency covers retrieval, routing and generation. It excludes loading, scoring, journal writes, HTTP and the API's extra before-answer generation; fixed ordering and shared caches can bias comparisons.

The existing secondary verdicts were aggregated with the same frozen 2,000-resample paired family bootstrap: learned minus updated RAG is -5.00 percentage points, 95% interval [-6.67, -3.06]. Every one of the 720 standard questions remains included. This is a descriptive aggregation of locked verdicts, with no rescoring, inference or test-guided selection.

The separately declared runtime recovery selected only the 319 original CUDA error statuses, permitted at most one new generation per selected ID and checked reconstructed input bytes. The 65 original successful outputs were preserved. Combined oracle complete-assertion credit is 247/384 (64.3%), with 0 execution errors and 90 pending outputs. This supplement replaces no original results, changes no model/configuration/scorer and has mixed-session timings; it measures operational recovery, not a model improvement.

On the separate 288 standard oracle questions, request-bound QA credits 208/288, with 47 incorrect and 33 pending. The original failed-preload session remains visible with unavailable fingerprints; the healthy resumed generation session has the expected base fingerprint before and after inference. That proves the healthy session's measured state, not the lost earlier GPU state.

Post-load CUDA snapshots report 933.1 MiB allocated and 1,002 MiB reserved. A full original-inference peak is unavailable; the fresh closure session loaded models without generating answers.


A separate isolated local HTTP workload measured 30 warm learned-mode requests: p50 230.4 ms and p95 372.0 ms, 0 execution errors. Three warmups are excluded, and the first request with lazy checkpoint loading took 68.78 seconds. Client timing includes transport, decoding and the API's before-answer generation. These repeated demonstration questions measure latency and availability, not held-out accuracy or concurrent load capacity. The workload includes a known wrong Yes comparison, so 30 answered requests do not mean 30 correct answers.

Configuration	Primary credit	Request QA	Pending	Coverage
Frozen base	0/816 (0.0%)	500/816	816	816/816 (100.0%)
Updated RAG	0/816 (0.0%)	649/816	816	816/816 (100.0%)
Prompt correction	0/816 (0.0%)	533/816	815	816/816 (100.0%)
Similarity editor	246/816 (30.1%)	632/816	522	816/816 (100.0%)
Learned editor	207/816 (25.4%)	613/816	491	745/816 (91.3%)

Primary requires a complete scoped assertion. Request QA is a separate frozen controlled-form metric. Pending counts refer to primary scoring; zero primary credit does not mean zero factual correctness.

EditGuard · answer quality with every outcome retained

Frozen final comparison · identical approved edits · deterministic 48-token generation · all five configurations




Pending complete assertions can be factually meaningful fragments; zero strict credit does not establish zero factual correctness.
The request QA diagnostic checks a bounded requested value/predicate separately; it does not prove a complete scoped fact.
Automated label audit; agent-authored challenge drafts. Abstracted overlap: 9 scope rows; 9 input pairs shared with training. Raw families remain separate.

final answer quality. Measured frozen-test data; see raw JSON/CSV for denominators and policy details.

EditGuard · calibration and descriptive coverage

Frozen validation-selected threshold 0.97, ambiguity margin 0.025; no threshold or model is selected from this plot




Reliability concerns independent question–focal-edit probabilities, before compatibility gates and retrieval selection.
Coverage curve ranks fixed 0.97 classifier decisions by distance from that threshold; tied confidences enter together.
The marked point uses the pre-existing ±0.025 uncertainty rule; this curve does not prescribe a new operating policy.

final calibration coverage. Measured frozen-test data; see raw JSON/CSV for denominators and policy details.

EditGuard · generalization and locality cohorts

Every cell shows credited answers / the complete cohort; comparison and out-of-scope questions stay explicit




Primary and request QA use different endorsement requirements; neither drops abstentions or pending outputs.
Challenge records preserve original unfamiliar agent-authored wording; they have no independent human authorship/review.
Abstracted overlap: 9 scope rows; 9 input pairs shared with training. Raw families remain separate.

final cohort accuracy. Measured frozen-test data; see raw JSON/CSV for denominators and policy details.

EditGuard · measured request latency

Serial CLI measurements · all requests including first use · model construction recorded separately

A. Actual latency distributions



B. Full-population p50 and p95

Configuration	Samples	p50 ms	p95 ms
Frozen base	816/816	167.4	289.5
Updated RAG	816/816	151.1	279.2
Prompt correction	816/816	154.6	286.7
Similarity editor	816/816	279.4	866.0
Learned editor	816/816	231.9	896.5


Recorded model construction per session: 101.97s, 37.12s, 33.84s, 27.07s

Request timing includes retrieval, routing and generation; it excludes model loading, scoring, observation writes and HTTP/browser overhead.
Fixed configuration order and shared caches can affect comparisons. Missing timing samples make full-population percentiles unavailable.
No extrapolated training duration or unmeasured service latency is shown.

final latency. Measured frozen-test data; see raw JSON/CSV for denominators and policy details.

EditGuard · retrieval, pair classification and actual routing

These stages measure separate events; metadata compatibility and approved-memory checks also affect runtime routing




Raw pair classification includes incompatible hard negatives. Runtime precision/recall use selected edit IDs, not prose influence.
Retrieval recall uses raw pre-gate candidates; it is not eligible-candidate recall. False applications concern explicit editors only.
All measurements shown concern the scope cohort. Abstracted overlap: 9 scope rows; 9 input pairs shared with training. Raw families remain separate.

final retrieval and routing. Measured frozen-test data; see raw JSON/CSV for denominators and policy details.

EditGuard · paired uncertainty and observed failure categories

Primary complete-assertion differences; predeclared paired family bootstrap, seed 42 and 2,000 resamples



Intervals resample complete entity families; a small family count limits precision and controlled wording limits external validity.
Failure categories summarize observable routing/scoring events; they do not infer correctness for pending semantic outputs.
Oracle answer accuracy is reported separately in the machine-readable metrics; deterministic answers receive no learned-generation credit.

final uncertainty failures. Measured frozen-test data; see raw JSON/CSV for denominators and policy details.

7. Reliability, engineering and deployment

The authoritative key is entity, relation, plan, version and a half-open effective interval. Corrections require a source, matching original value and administrator approval. Same-scope contradictory intervals do not use latest-write-wins. Explicit supersession links an approved predecessor; withdrawal restores applicable ancestors, and descendants must be withdrawn first. Mutations and revision increments are transactional; revision keys invalidate caches.

The isolated actual learned workflow passed 31 governance/integration assertions across 33 API requests. These checks validate authority, conflict blocking, historical boundaries and rollback, not representative model accuracy. Development demonstrations still include wrong negative polarity, unsupported paraphrase prose and an unaffected price question that clarifies.

Regression/CI covers the app, scoring, data review, checkpoint recovery, source/model bindings and container persistence. The structured Docker deployment and optional locally configured neural application are documented separately. The minimal stack is Python, FastAPI/Pydantic, SQLite and build-free HTML/CSS/JavaScript, with PyTorch/Transformers and Matplotlib for ML experiments.

The final runner uses an OS-released exclusive session lock, atomic per-observation journal and exact-bound recovery. Completed configurations cannot be silently rerun. A dependency-inventory startup rejection occurred before loading models or predictions; its source and log are archived. The amended protocol preserves byte-identical question/truth files and fixes only the guard mismatch.

Windows access-denied collisions interrupted two mutable progress writes; the lock owner and underlying cause are unknown. A declared finite retry wrapper changes only those writes. A later CUDA unknown error occurred after all 4,080 matched predictions had completed: 319 of the separate 384 oracle attempts were execution errors. All original errors remain uncredited in the original denominator.

The failed GPU instance's final parameter fingerprint was unavailable. Fresh-process closure confirmed unchanged serialized sources and model files and the expected loaded base fingerprint, with zero new predictions. It cannot reconstruct the lost GPU memory state. This distinction limits the original run's end-state integrity measurement and is disclosed rather than inferred away.

8. Panel demonstration and reproducibility

Demonstrate the initial handbook answer, a sourced administrator correction, direct and paraphrased questions, neighboring property/tier/version questions, explicit ambiguity or conflict, then withdrawal and restored history. Show the answer-kind badge and supporting fact alongside generated text. Include a documented model failure rather than implying every generated response is verified.

The repository supplies immutable data bundles, review registries, pinned run cards, training/evaluation scripts, recorded model metadata, local saved model exports, scientific figure sources, regression tests, CI, API documentation and deployment instructions. Large checkpoint binaries remain local artifacts rather than Git source. Offline result reaggregation and fresh training reproduction are distinct from rerunning the locked final test.

A defensible resume claim describes the SERAC-inspired editor, two trained auxiliary models, transactional correction memory and rollback, and evaluation across five matched configurations on a controlled held-out benchmark. Numerical claims must identify the metric, denominator and dataset. This release does not establish unrestricted dialogue, multi-hop reasoning, large edit memories or guaranteed arbitrary-language accuracy.

Evidence and version record

Answer: google/flan-t5-small | revision 0fc9ddf78a1e988dac52e2dac162b0ede4fd74ab | selected artifact artifacts/answer/pilot-v2-polarity1

Scope: distilbert/distilbert-base-uncased | revision 12040accade4e8a0f71eabdb258fecc2e7e948be | selected artifact artifacts/scope/pilot-v3-neutral2

reports/final/evaluation/manifest.json
SHA-256: 22fb7652e9cd878e 79434cd572480b2e 69f2fcad9e2a3dea ba12b1fa071c3f23

reports/final/evaluation/metrics.json
SHA-256: 8f5ce9c0ce619274 50cd82b0c6662a76 3286da061e61fdd4 027e71bc033fec3e

reports/final/evaluation/short_qa_metrics.json
SHA-256: 5b0db725fecf1cd6 98c45c976e926b8b 7617d26a1bbe3d5a 07844bfbe1b105e1

reports/final/protocol-v2.json
SHA-256: 8a938b33055220fd b24fa86ed056405f 186dc9b6c4b72fe1 36c76ff0dc3d86ab

reports/final/test_lock-v2.json
SHA-256: 9900b81a2b9aa41b 0dd40e19d3cfb04e 9ab000ae90507ff3 a406453f1af85e99

reports/final/figures-v2/manifest.json
SHA-256: f37e22c35cf10dff 0a64057927980aa1 00fd954d3a926461 301f8e4e2d77ebb0

reports/targeted-training-audit.json
SHA-256: 9c286b67e1415ac2 fc02f9564e5454bc 3ff5174b998c864e 320b788f39303e20

reports/final/runtime-failure-disclosure.json
SHA-256: 5c67d8483d8d634f ef745d1ec2396773 a2f361eeac83e984 62cce493f5b7e67a

reports/final/secondary-paired-uncertainty.json
SHA-256: 46cdf88058c10a71 c652bf1cac1732f4 cb2e92961f190d7c 85f6bb4a8c729caa

reports/final/neural-http.json
SHA-256: dade7dcdccef1842 5b100ca741cbb259 0c510b1c96591b25 4c4286245232d8b9

artifacts/answer/pilot-v2-polarity1/manifest.json
SHA-256: 8e435ac9bcd5486b b967c7ca09c38bf1 786b810c97a7c95a 365c6250ceeb0a72

artifacts/scope/pilot-v3-neutral2/manifest.json
SHA-256: c85e77193ff3cf51 37baf0a569d14258 5cfac3a1734393fa df49ce95f9b88459

configs/inference-final.json
SHA-256: c86a11c2ef63f34b 3b80976f0334b58e 04b55b7088c0b013 a3d0f5a3969e9134

editguard/api.py
SHA-256: b2609d51741d5424 a59e94cfb176b99a 074620f4ea67b940 106c31c024f53962

scripts/benchmark_neural_http.py
SHA-256: 1b4fda9518125fee 6b220cde8dbc4a2a 79ed9a1804c5aa5d 432aef6292ca2504

reports/final/oracle-runtime-recovery/combined_oracle_predictions.jsonl
SHA-256: 0d9550dd68a3e037 45d7c2842c3ec742 26b344710c004ed7 24a03c8ff5573eb9

reports/final/oracle-runtime-recovery/metrics.json
SHA-256: 0835ee2cbb46562e 9d5fa1268323ab71 c868f1197bc3b7fa 6af654a653f0edd7

reports/final/oracle-runtime-recovery/recovery_predictions.jsonl
SHA-256: cf1facb73adb662b 696411a23054157c 78cd4031c1c6975d fee2ba1fb98274a0

reports/final/oracle-runtime-recovery/short_qa_metrics.json
SHA-256: f4c8d12849df66ce dad55b38347a19cd 08fde4ccb6e9fc31 491158201d953bbc

reports/final/oracle-runtime-recovery/manifest.json
SHA-256: 0e9dfec877c2af7e 4f708d24de459d2c f07bfc64feca5600 c2614e8021a2d5a5