

1. Failed access -- reproduction attempt

```
$ docker build -t netlab .  
bash: docker: command not found  
$ docker run -d -p 8080:8080 --name app netlab  
bash: docker: command not found  
$ docker ps  
bash: docker: command not found  
$ curl -i localhost:8080/health  
curl: (7) Failed to connect to localhost port 8080: Connection refused
```

Docker is not installed in this execution environment, so a container-level curl failure could not be captured.

2. Port inspection -- environment limitation

```
$ docker port app
bash: docker: command not found
$ docker logs app
bash: docker: command not found
$ command -v docker || true

$ sed -n '1,16p' Dockerfile
EXPOSE 8080
CMD ["node", "server.js"]
```

The required Docker PORTS/log inspection is blocked by the missing Docker CLI; the application configuration

3. The mismatch -- pre-fix source inspection

```
$ git show HEAD^:server.js | sed -n '1,12p'
const express = require('express');
const app = express();

const PORT = 8080;
const HOST = '127.0.0.1';

app.get('/health', (req, res) => {
  res.status(200).json({ status: 'ok' });
});
```

The original process bound to 127.0.0.1, which only accepts loopback connections inside the container rather

4. The fix -- bind every container interface

```
$ git diff HEAD^ HEAD -- server.js
-const HOST = '127.0.0.1';
+// A container port must listen on all container interfaces so Docker can
+// forward traffic from the published host port to this process.
+const HOST = '0.0.0.0';

$ docker run -d -p 8080:8080 --name app netlab
# Run this command after rebuilding in a Docker-enabled environment.
```

The server now binds to 0.0.0.0:8080, matching the Dockerfile's exposed port and the README's 8080:8080 pub

5. Reachable -- post-fix health check

```
$ node server.js
Server running on http://0.0.0.0:8080
$ curl -i --max-time 5 localhost:8080/health
HTTP/1.1 200 OK
X-Powered-By: Express
Content-Type: application/json; charset=utf-8
Content-Length: 15

{"status":"ok"}
```

A real local process check after the binding fix returns HTTP 200 and the expected JSON body; Docker publis