DCCN ISE- NAT TASK 1

Name: Neha Kale(2018130018)
Shivangi Kochrekar(2018130020)
Rishita Mote(2018130029)
Batch B (TE COMPS)

TASK 1: To set up the topology and verify end to end configuration.

Complete Network:



PC-A Configuration:



PC-B Configuration:



Gateway configuration:



ISP configuration:



Verify Connectivity:

a) Ping from PC-A to gateway G0/1 and PC-B:





b) Ping from PC-B to gateway G0/1 and PC-A:



All the pings are successfully completed.

Routing tables on both routers to verify static route in routing table:

Gateway routing table:



ISP routing table:



Task 2 :

Step 1: Configure a static mapping and specify the interfaces.



Step 3: Test the configuration.

What is the configuration of the inside local host address?

192.168.1.20 → 209.165.200.225

From PC-A, ping the Lo0 interface (172.31.7.1) on ISP:



A NAT entry was added to the table with ICMP listed as the protocol when PC-A sent an ICMP request (ping) to 192.31.7.1 on ISP.
What port number was used in this ICMP exchange? 5,6,7,8



C] From PC-A, telnet to the ISP Lo0 interface and display the NAT table.
What was the protocol used in this translation? tcp
What are the port numbers used?

Inside global / local: 1026
Outside global / local:23





Because static NAT was configured for PC-A, verify that pinging from ISP to PC-A


ISP
Physical
Config
CLI
Attributes
IOS Command Line Interface
Unauthorized access is strictly prohibited.
User Access Verification
Password:
ISP>enable
Password:
ISP#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
ISP(config)#exit
ISP#
%SYS-5-CONFIG_I: Configured from console by console
ISP#ping 209.165.200.225
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 209.165.200.225, timeout is 2
seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max =
1/8/17 ms
ISP#
Ctrl+F6 to exit CLI focus
Copy
Paste
Top


Gateway
Physical
Config
CLI
Attributes
IOS Command Line Interface
--- 209.169.200.225 192.168.1.20 --- ---
Gateway#show ip nat translations
Pro Inside global Inside local Outside local Outside global
--- 209.165.200.225 192.168.1.20 --- ---
--- 209.169.200.225 192.168.1.20 --- ---
tcp 209.165.200.225:1025192.168.1.20:1025 192.31.7.1:23 192.31.7.1:23
Gateway#show ip nat statistics
Total translations: 3 (2 static, 1 dynamic, 1 extended)
Outside Interfaces: Serial0/0/1
Inside Interfaces: GigabitEthernet0/1
Hits: 78 Misses: 18
Expired translations: 17
Dynamic mappings:
Gateway#
Gateway con0 is now available
Ctrl+F6 to exit CLI focus
Copy
Paste
Top

CONCLUSION: We successfully created topology and verified the end to end connectivity in CISCO Packet Tracer.