
C++ Programming

Trainer : Akshita Chanchlani

Email: akshita.chanchlani@sunbeaminfo.com



Types of Member Functions within class

- Constructor : object initialization
- Destructor : used to release the resources
- Mutators/setter : modify state of object
- inspector/getter : do not change the state of the object
- facilitator



Constructor

- It is a member function of a class which is used to initialize object.
- Constructor has same name as that of class and don't have any return type.
- Constructor get automatically called when object is created i.e. memory is allocated to object.
- If we don't write any constructor, compiler provides a default constructor.
- Due to following reasons, constructor is considered as special function of the class:
 1. Its name is same as class name.
 2. It doesn't have any return type.
 3. It is designed to call implicitly.
 4. In the life time of the object , it gets called only once per object and according to order of its declaration.
- We can not call constructor on object, pointer or reference explicitly. It is designed to call implicitly.
- We can not declare constructor static, constant, volatile or virtual. We can declare constructor only inline.
- Constructor overloading means inside a class more than one constructor is defined.
- We can have constructors with
 - No argument : initialize data member to default values
 - One or more arguments : initialize data member to values passed to it
 - Argument of type of object : initialize object by using the values of the data members of the passed object. It



Types of Constructor

- Parameterless constructor
 - also called zero argument constructor or user defined default constructor
 - If we create object without passing argument then parameterless constructor gets called
 - Constructor do not take any parameter
- Parameterized constructor
 - If constructor take parameter then it is called parameterized constructor
 - If we create object, by passing argument then parameterized constructor gets called
- Default constructor
 - If we do not define constructor inside class then compiler generates default constructor for the class.
 - Compiler generated default constructor is parameterless.



Constructor's member initializer list

- If we want to initialize data members according to users requirement then we should use constructor body.

```
class Test
{
private:
    int num1;
    int num2;
    int num3;

public:
    Test( void )
    {
        this->num1 = 10;
        this->num2 = 20;
        this->num3 = num2;
    }
};
```

- If we want to initialize data member according to order of data member declaration then we can use constructors member initializer list.

```
class Test
{
private:
    int num1;
    int num2;
    int num3;

public:
    Test( void ) : num1( 10 ), num2( 20 ), num3( num2 )
    { }

};
```

Except array we can initialize any member inside constructors member initializer list.



Destructor

- It is a member function of a class which is used to release the resources.
- It is considered as special function of the class
 - Its name is same as class name and always preceds with tild operator(~)
 - It doesnt have return type or doesn't take parameter.
 - It is designed to call implicitly.
- Destructor calling sequence is exactly opposite of constructor calling sequence.
- Destructor is designed to call implicitly.
- If we do not define destructor inside class then compiler generates default destructor for the class.
- Default destructor do not de allocate resources allocated by the programmer. If we want to de allocate it then we should define destructor inside class.



Thank You

