

# Spring JDBC — Complete Updated Note (Connection Pool, How It Knows DB, Differences From JDBC)

This note gives a **complete, deep explanation** of Spring JDBC including:

- How Spring JDBC gets a **database connection**
  - How Spring JDBC uses **connection pooling**
  - How Spring knows **which database** to connect to
  - Difference between **JDBC vs Spring JDBC**
  - Working of **JdbcTemplate** internally
  - How SQL exceptions are handled
  - Full example with PostgreSQL (Neon DB)
- 

## 1. What Is Spring JDBC?

Spring JDBC is a module in Spring Framework which makes database access easier by using **JdbcTemplate**.

Traditional JDBC is verbose and requires you to manually:

- Open connection
- Create statements
- Execute queries
- Close ResultSet
- Close Connection
- Handle exceptions

Spring JDBC removes **all boilerplate** using a template pattern.

---

## 2. How Does Spring JDBC Know Which Database to Connect To?

Spring JDBC does **NOT** connect to the database directly. It uses a **DataSource**.

 **DataSource contains the necessary configuration:**

- URL
- Username
- Password
- Driver class

In Spring Boot:

```
spring.datasource.url=jdbc:postgresql://yourhost/db
spring.datasource.username=youruser
spring.datasource.password=yourpass
spring.datasource.driver-class-name=org.postgresql.Driver
```

Spring Boot automatically creates:

- DataSource object
- JdbcTemplate bean

So JdbcTemplate does NOT know the database — the DataSource provides the connection.

---

## 3. How Does Spring JDBC Get Connection Pool?

Spring Boot automatically configures **HikariCP** as the default **connection pool**.

### What is HikariCP?

A very fast, lightweight connection pool library used in Spring.

### Why Connection Pool Is Needed?

Opening a new database connection is slow. Connection pool keeps a set of open connections and reuses them.

### How Spring Gets Connection Pool?

Spring Boot automatically checks the classpath:

- If HikariCP is present → use it
- If not → tries Tomcat pool
- If not → uses simple driver-based DataSource

When PostgreSQL and Spring Boot dependencies are added, Boot auto-configures:

```
HikariDataSource → manages the pool
JdbcTemplate → uses this pool to get connections
```

You don't write any pooling code.

### Where does pool size come from?

Default:

```
maximumPoolSize = 10
```

You can override:

```
spring.datasource.hikari.maximum-pool-size=20  
spring.datasource.hikari.minimum-idle=5  
spring.datasource.hikari.idle-timeout=60000
```

## 4. How JdbcTemplate Works Internally

When you run:

```
jdbcTemplate.query("SELECT * FROM student", rowMapper);
```







JdbcTemplate internally: **1** Gets a connection from **HikariCP pool** (not DriverManager) **2** Creates PreparedStatement **3** Executes SQL **4** Iterates ResultSet **5** Calls RowMapper for each row **6** Closes ResultSet **7** Closes Statement **8** Returns connection to pool (NOT closing it fully) **9** Returns List of objects

You call **one line**, Spring does everything else.

## 5. JDBC vs Spring JDBC — Key Difference

Feature	JDBC	Spring JDBC
Connection	Manual	Automatic via DataSource + Pool
Queries	Manual PreparedStatement	JdbcTemplate
Closing resources	Manual	Auto-handled
Exception type	<code>SQLException</code>	Runtime translated exceptions
Repeated code	High	Almost none
Performance	Slower (no pooling)	Faster (HikariCP)
Error handling	Verbose	Simple
Recommended?	<b>✗</b> No	<b>✓</b> Yes

## 6. Why Spring JDBC Is Better Than Normal JDBC?

-  No try-catch-finally
  -  No manual connection closing
  -  No manual ResultSet handling
  -  Automatic exception translation
  -  Automatic connection pooling
  -  Clean API with JdbcTemplate
- 

## 7. RowMapper (Mapping SQL → Java)

Used to convert each database row into a Java object.

```
public class StudentRowMapper implements RowMapper<Student> {  
    public Student mapRow(ResultSet rs, int rowNum) throws SQLException {  
        return new Student(  
            rs.getInt("id"),  
            rs.getString("name"),  
            rs.getInt("age")  
        );  
    }  
}
```

Or lambda:

```
jdbcTemplate.query(sql, (rs, rowNum) ->  
    new Student(rs.getInt(1), rs.getString(2), rs.getInt(3))  
);
```

---

## 8. CRUD Operations in Spring JDBC

### ➤ Insert

```
jdbcTemplate.update(  
    "INSERT INTO student(name, age) VALUES (?, ?)",
```

```
        "Aman", 23
    );
```

### ➤ Fetch All

```
List<Student> list = jdbcTemplate.query(
    "SELECT * FROM student",
    new StudentRowMapper()
);
```

### ➤ Fetch One

```
Student s = jdbcTemplate.queryForObject(
    "SELECT * FROM student WHERE id = ?",
    new StudentRowMapper(), id
);
```

### ➤ Update

```
jdbcTemplate.update("UPDATE student SET age=? WHERE id=?", 25, 1);
```

### ➤ Delete

```
jdbcTemplate.update("DELETE FROM student WHERE id=?", id);
```

---

## 9. How Spring Boot Auto-Creates JdbcTemplate

Spring Boot auto-creates a bean:

```
@Bean
public JdbcTemplate jdbcTemplate(DataSource dataSource) {
    return new JdbcTemplate(dataSource);
}
```

Thus JdbcTemplate uses **the same pooled DataSource**.

---



## 10. Full Example — Spring JDBC with PostgreSQL (Neon DB)

### 1. Add PostgreSQL dependency

```
<dependency>
  <groupId>org.postgresql</groupId>
  <artifactId>postgresql</artifactId>
  <version>42.7.1</version>
</dependency>
```

### 2. application.properties

```
spring.datasource.url=jdbc:postgresql://<neon-host>/<database>?
sslmode=require
spring.datasource.username=<user>
spring.datasource.password=<password>
spring.datasource.driver-class-name=org.postgresql.Driver
```

### 3. Model

```
public class Student {
    private int id;
    private String name;
    private int age;

    // constructor + getter/setter
}
```

### 4. Repository

```
@Repository
public class StudentRepository {

    @Autowired
    private JdbcTemplate jdbcTemplate;

    public int add(Student s) {
        return jdbcTemplate.update(
            "INSERT INTO student(name, age) VALUES (?, ?)",
            s.getName(), s.getAge()
        );
    }
}
```

```

public List<Student> findAll() {
    return jdbcTemplate.query(
        "SELECT * FROM student",
        (rs, rowNum) -> new Student(
            rs.getInt("id"),
            rs.getString("name"),
            rs.getInt("age")
        )
    );
}
}

```

## 5. Controller

```

@RestController
@RequestMapping("/student")
public class StudentController {

    @Autowired
    StudentRepository repo;

    @PostMapping("/add")
    public String add(@RequestBody Student s) {
        repo.add(s);
        return "Student added";
    }

    @GetMapping("/all")
    public List<Student> all() {
        return repo.findAll();
    }
}

```

## Final Summary




Spring JDBC = JDBC with:

- Automatic connection pooling (HikariCP)
- Automatic DataSource
- Automatic resource closing
- Exception translation
- Highly optimized performance
- Cleaner readable code

Spring knows which database to use because **you configure DataSource**.  
JdbcTemplate gets connections from **HikariCP pool**, not DriverManager.

This makes Spring JDBC fast, safe, and production-ready.

---

If you need, I can also add:  NamedParameterJdbcTemplate section  Transactions in Spring JDBC  PDF export

Great question — many beginners think **RowMapper runs recursively**, but the truth is:

## RowMapper is NOT recursive

It **never calls itself**.

Spring JDBC calls it **once per row** in the ResultSet.

Let me explain clearly.

---

## 1. How RowMapper Actually Works (Simple Explanation)

Spring JDBC uses **JdbcTemplate** which internally does something like:

```
while(resultSet.next()) {  
    call rowMapper.mapRow(resultSet, rowNumber)  
}
```

So the flow is:

```
Row 1 → mapRow() called once  
Row 2 → mapRow() called once  
Row 3 → mapRow() called once  
...
```

There is **no recursive call**, only a simple loop.

---

## 2. Why it feels like recursion?

Because if there are 10 rows, `mapRow()` is executed 10 times.

Beginners think:

```
mapRow() runs inside itself → recursion ❌
```



But actually:

JdbcTemplate loops → calls mapRow() repeatedly → iteration ✓

### 3. Example to Understand Clearly

**Your RowMapper:**

```
public class StudentRowMapper implements RowMapper<Student> {  
    @Override  
    public Student mapRow(ResultSet rs, int rowNum) throws SQLException {  
        Student s = new Student();  
        s.setId(rs.getInt("id"));  
        s.setName(rs.getString("name"));  
        s.setAge(rs.getInt("age"));  
        return s;  
    }  
}
```

**JdbcTemplate does:**

```
ResultSet rs = statement.executeQuery();  
  
List<Student> list = new ArrayList<>();  
int rowNum = 0;  
  
while(rs.next()) {  
    Student s = rowMapper.mapRow(rs, rowNum);  
    list.add(s);  
    rowNum++;  
}
```

- ✓ Loop
- ✓ Not recursion
- ✓ RowMapper is called ONCE PER ROW

### 4. What exactly calls mapRow() repeatedly?

The `JdbcTemplate.query()` method:

```
public <T> List<T> query(String sql, RowMapper<T> rowMapper) {
    return resultSetExtractor.extractData(resultSet)
}
```

Internally:

```
while(rs.next()) {
    list.add(rowMapper.mapRow(rs, rowNumber++));
}
```

Spring handles the looping.

Your RowMapper only handles **mapping a single row**.

## 5. Why RowMapper is designed this way?






Because it separates responsibilities:

ComponentResponsibility	
<b>JdbcTemplate</b>	Fetch rows, loop over ResultSet
<b>RowMapper</b>	Convert <b>one</b> row → Java object

This is clean, reusable, testable.

## 6. Summary

**RowMapper:**

-  Does NOT use recursion
-  Is NOT called by itself
-  Is called by JdbcTemplate
-  Executes once per row
-  Converts SQL row → Java object

If you want, I can create a visual diagram like:

```
ResultSet:
Row 1 → mapRow()
Row 2 → mapRow()
Row 3 → mapRow()
...
```