

Default Access in Subclasses - Complete Notes



Key Question: Can subclasses access default members and methods?

Answer: YES, but ONLY if the subclass is in the SAME PACKAGE as the superclass.





















Understanding Default Access

Default access (no access modifier keyword) provides **package-level visibility**, not inheritance-based visibility.

Rule:

- Same Package: Default members are inherited and accessible in subclasses 
- Different Package: Default members are NOT accessible in subclasses 

Access Modifier Inheritance Table

Access Modifier	Same Class	Same Package	Subclass (Same Package)	Subclass (Different Package)	Different Package
private					
default					
protected					
public					

Example 1: Same Package (Default members ARE accessible)

Parent Class:

```
java
```

// File: mypackage/Vehicle.java

```
package mypackage;

public class Vehicle {
    public String brand;      // public - accessible everywhere
    protected int maxSpeed;   // protected - accessible in subclasses
    String fuelType;          // default - accessible in same package
    private String engineNumber; // private - not accessible in subclasses

    public void start() {
        System.out.println("Vehicle starting");
    }

    protected void accelerate() {
        System.out.println("Vehicle accelerating");
    }

    void refuel() {           // default method
        System.out.println("Vehicle refueling with " + fuelType);
    }

    private void performMaintenance() {
        System.out.println("Performing maintenance");
    }
}
```

Subclass in Same Package:

java

// File: mypackage/Car.java

package mypackage; // SAME PACKAGE

public class Car extends Vehicle {
 private int doors;

public Car(String brand, int maxSpeed, String fuelType, int doors) {
 this.brand = brand; // ✓ public - accessible
 this.maxSpeed = maxSpeed; // ✓ protected - accessible in subclass
 this.fuelType = fuelType; // ✓ default - accessible (same package)
 this.doors = doors;
 // this.engineNumber = "123"; // ✗ private - not accessible
 }

public void carActions() {
 start(); // ✓ public method - accessible
 accelerate(); // ✓ protected method - accessible
 refuel(); // ✓ default method - accessible (same package)
 // performMaintenance(); // ✗ private method - not accessible

 System.out.println("Car has " + doors + " doors");
 System.out.println("Fuel type: " + fuelType); // ✓ Can access default variable
 }

// Can override default method since we're in same package

@Override

void refuel() {
 System.out.println("Car refueling with " + fuelType + " at gas station");
}

// New method specific to Car

void openTrunk() {
 System.out.println("Car trunk opened");
}
}

Example 2: Different Package (Default members are NOT accessible)

Subclass in Different Package:

java

// File: anotherpackage/Motorcycle.java

package anotherpackage; // DIFFERENT PACKAGE

import mypackage.Vehicle;

public class Motorcycle extends Vehicle {
 private boolean hasSidecar;

public Motorcycle(String brand, int maxSpeed, boolean hasSidecar) {
 this.brand = brand; // ✓ public - accessible
 this.maxSpeed = maxSpeed; // ✓ protected - accessible in subclass
 // this.fuelType = "Petrol"; // ✗ default - not accessible (different package)
 this.hasSidecar = hasSidecar;
 }

public void motorcycleActions() {
 start(); // ✓ public method - accessible
 accelerate(); // ✓ protected method - accessible
 // refuel(); // ✗ default method - not accessible (different package)

 System.out.println("Motorcycle has sidecar: " + hasSidecar);
 // System.out.println("Fuel: " + fuelType); // ✗ Cannot access default variable
 }

// This creates a NEW method, NOT an override of parent's default method

void refuel() {
 System.out.println("Motorcycle refueling");
 // This doesn't override parent's refuel() because parent's refuel() is not visible
 }

void wheelie() {
 System.out.println("Motorcycle doing a wheelie!");
 }
}

Complete Working Example

java

```
// File: com/example/shapes/Shape.java
```

```
package com.example.shapes;
```

```
public class Shape {  
    public String color;      // public access  
    protected double area;   // protected access  
    String name;             // default access  
    private int id;          // private access  
  
    public Shape(String color, String name) {  
        this.color = color;  
        this.name = name;  
        this.id = generateId();  
    }  
  
    public void display() {  
        System.out.println("Shape: " + name + ", Color: " + color);  
    }  
  
    protected void calculateArea() {  
        System.out.println("Calculating area for " + name);  
    }  
  
    void showDetails() {      // default method  
        System.out.println("Name: " + name + ", Area: " + area + ", ID: " + id);  
    }  
  
    private int generateId() {  
        return (int)(Math.random() * 1000);  
    }  
  
    private void logInfo() {  
        System.out.println("Logging info for shape " + id);  
    }  
}
```

```
// File: com/example/shapes/Circle.java (SAME PACKAGE)
```

```
package com.example.shapes;    // Same package
```

```
public class Circle extends Shape {  
    private double radius;  
  
    public Circle(String color, double radius) {  
        super(color, "Circle"); // Call parent constructor  
        this.radius = radius;  
        this.area = Math.PI * radius * radius; // ✅ Can access protected variable
```

```

// Can access default variable from same package
System.out.println("Creating " + name + " with radius " + radius); // ✓
}

@Override
protected void calculateArea() {
    this.area = Math.PI * radius * radius;
    System.out.println("Circle area calculated: " + area);
}

// Can override default method since we're in same package
@Override
void showDetails() {
    System.out.println("Circle - Name: " + name + ", Radius: " + radius + ", Area: " + area);
}

public void circleSpecificMethod() {
    display();           // ✓ public method
    calculateArea();      // ✓ protected method
    showDetails();        // ✓ default method (same package)
    // logInfo();         // ✗ private method - not accessible
}
}

// File: com/example/geometry/Rectangle.java (DIFFERENT PACKAGE)
package com.example.geometry; // Different package
import com.example.shapes.Shape;

public class Rectangle extends Shape {
    private double length;
    private double width;

    public Rectangle(String color, double length, double width) {
        super(color, "Rectangle");
        this.length = length;
        this.width = width;
        this.area = length * width; // ✓ Can access protected variable

        // Cannot access default variable from different package
        // System.out.println("Creating " + name); // ✗ Compilation error
    }

    @Override
    protected void calculateArea() {
        this.area = length * width;
        System.out.println("Rectangle area calculated: " + area);
    }
}

```

```

}

// This creates a NEW method, not an override
void showDetails() {
    System.out.println("Rectangle - Length: " + length + ", Width: " + width + ", Area: " + area);
    // Cannot access 'name' variable here as it's default access from different package
}

public void rectangleActions() {
    display();           // ✅ public method
    calculateArea();     // ✅ protected method
    // showDetails();    // This calls the NEW showDetails() method defined in this class
    // Parent's showDetails() is not accessible from different package
}
}

```

Testing the Examples:

```

java

// File: TestDefaultAccess.java
package com.example.shapes; // Same package as Shape

public class TestDefaultAccess {
    public static void main(String[] args) {
        System.out.println("=== CIRCLE (SAME PACKAGE) ===");
        Circle circle = new Circle("Red", 5.0);
        circle.circleSpecificMethod();
        circle.showDetails(); // Calls overridden method

        System.out.println("\n=== RECTANGLE (DIFFERENT PACKAGE) ===");
        com.example.geometry.Rectangle rectangle =
            new com.example.geometry.Rectangle("Blue", 4.0, 6.0);
        rectangle.rectangleActions();
        rectangle.showDetails(); // Calls Rectangle's own method, not parent's
    }
}

```

Key Points to Remember:

✅ What Subclasses CAN Access:

1. Same Package:

- Public members
- Protected members

- **Default members** ✓
- **Can override default methods** ✓

2. Different Package:

- **Public members**
- **Protected members**
- **Cannot access default members** ✗

✗ What Subclasses CANNOT Access:

- **Private members** (regardless of package)
- **Default members** from different packages

Important Rules:

1. **Package Boundaries Matter:** Default access is about packages, not inheritance
2. **Method Overriding:** Can only override default methods if in same package
3. **Variable Access:** Default variables only accessible from same package subclasses
4. **Constructor Access:** Default constructors follow same rules
5. **Different Package = New Method:** Defining a method with same name in different package subclass creates NEW method, not override

Common Mistakes:

1. **Assuming inheritance overrides package rules** - It doesn't for default access
2. **Forgetting package declarations** - Always check package statements
3. **Thinking default = protected** - They are different!
4. **Confusing method override with new method** - Same name in different package = new method

Best Practices:

1. **Use protected instead of default** if you want subclass access across packages
2. **Keep related classes in same package** if they need default access
3. **Be explicit with access modifiers** - don't rely on default
4. **Document package-private members** clearly
5. **Consider package organization** when designing inheritance hierarchies

Summary:

Default access in subclasses depends entirely on package location:

- **Same package subclass:** ✓ Full access to default members

- **Different package subclass:** ✗ No access to default members

This is a crucial concept that combines inheritance with Java's package-based access control system