

Mini Replit Clone — Docker + Nix + FastAPI (Python Version)

Goal

Build a Replit-style system using:

- FastAPI (control API)
 - Docker (isolation)
 - Nix (reproducible Python environment)
 - Dynamic dependency installation via JSON request
 - Each project runs inside its own container
-



High-Level Architecture

User → FastAPI Control Server → Workspace Folder → Docker Container → Nix → pip install main.py



Folder Structure

mini-replit-python/ | | | api/ | | | main.py | | | docker/ | | | Dockerfile | |
flake.nix | | | workspaces/

1 Nix Environment (Python Runtime)

File: docker/flake.nix

```
{
  description = "Python Dev Environment";

  inputs = {
    nixpkgs.url = "github:NixOS/nixpkgs/nixos-23.11";
  };

  outputs = { self, nixpkgs }:
    let
      system = "x86_64-linux";
    in
      pkgs = import nixpkgs { inherit system; };
}
```

```

in
{
  devShells.${system}.default = pkgs.mkShell {
    buildInputs = [
      pkgs.python311
      pkgs.python311Packages.pip
    ];
  };
};
}

```

This guarantees:

- Python 3.11
- pip
- Reproducible runtime

2 Dockerfile

File: docker/Dockerfile

```

FROM nixos/nix

WORKDIR /workspace

RUN mkdir -p /etc/nix &&
    echo "experimental-features = nix-command flakes" >> /etc/nix/nix.conf

COPY flake.nix /workspace/

RUN nix develop --command true

EXPOSE 8000

CMD ["nix", "develop"]

```

Build image:

```
docker build -t mini-replit-python ./docker
```

3 FastAPI Control Server

File: api/main.py

```

import os
import uuid
import json
import subprocess
from pathlib import Path
from fastapi import FastAPI, HTTPException
from pydantic import BaseModel

app = FastAPI()

WORKSPACE_DIR = Path(__file__).resolve().parent.parent / "workspaces"
WORKSPACE_DIR.mkdir(exist_ok=True)

# Request model
class ProjectCreateRequest(BaseModel):
    dependencies: dict = {}

# CREATE PROJECT
@app.post("/create")
def create_project(request: ProjectCreateRequest):
    project_id = str(uuid.uuid4())
    project_path = WORKSPACE_DIR / project_id
    project_path.mkdir(parents=True, exist_ok=True)

    # Create requirements.txt
    requirements = "\n".join([
        f"{pkg}=={version.strip('^')}" if isinstance(version, str) else pkg
        for pkg, version in request.dependencies.items()
    ])

    (project_path / "requirements.txt").write_text(requirements)

    # Create starter FastAPI app
    main_file = f"""
from fastapi import FastAPI

app = FastAPI()

@app.get("/")
def root():
    return {{ "message": "Project {project_id} running" }}

"""

    (project_path / "main.py").write_text(main_file)

    return {"project_id": project_id}

# RUN PROJECT

```

```

@app.post("/run/{project_id}")
def run_project(project_id: str):
    project_path = WORKSPACE_DIR / project_id

    if not project_path.exists():
        raise HTTPException(status_code=404, detail="Project not found")

    container_name = f"repl-{project_id}"

    command = f"""
docker run -d
  --name {container_name}
  -v {project_path}:/workspace
  -p 0:8000
  --memory=256m
  --cpus=0.5
  --pids-limit=100
  mini-replit-python
  nix develop --command sh -c "if [ ! -d venv ]; then python -m venv venv
&& . venv/bin/activate && pip install -r requirements.txt; fi && . venv/bin/
activate && uvicorn main:app --host 0.0.0.0 --port 8000"
    """

    result = subprocess.run(command, shell=True, capture_output=True,
text=True)

    if result.returncode != 0:
        raise HTTPException(status_code=500, detail=result.stderr)

    return {"message": "Project running", "container": container_name}

```

Example Request

POST /create

```

{
  "dependencies": {
    "fastapi": "0.110.0",
    "uvicorn": "0.27.0"
  }
}

```

What Happens Internally

- 1 . User sends dependencies
 - 2 . System generates requirements.txt
 - 3 . User clicks /run
 - 4 . Docker container starts
 - 5 . Workspace mounted
 - 6 . Nix loads Python 3 . 1 1
 - 7 . If venv missing → create virtualenv
 - 8 . pip install dependencies
 - 9 . uvicorn runs FastAPI app
-



Security Controls

Docker limits:

- 2 5 6 MB RAM
- 0 . 5 CPU
- 1 0 0 process limit

Prevents abuse and fork bombs



Production Improvements

- Replace subprocess with docker SDK for Python
 - Add container stop endpoint
 - Add log streaming
 - Add port detection
 - Add authentication
 - Use Docker named volumes instead of host paths
 - Use Kubernetes for scaling
-



Final Result

You now have a fully dynamic mini Replit system in Python:

- User sends dependencies
- requirements.txt generated
- Docker + Nix provides runtime
- Virtualenv created inside container
- pip installs packages
- FastAPI app runs in isolated sandbox

This mirrors real cloud IDE architecture in a simplified educational form.