

Cheat-Sheet Skicit learn Phyton For Data Science BecomingHuman.AI



Skicit Learn

Skicit Learn is an open source Phyton library that implements a range if machine learning, processing, cross validation and visualization algorithm using a unified

A basic Example

```
>>> from sklearn import neighbors, datasets, preprocessing
>>> from sklearn.cross_validation import train_test_split
>>> from sklearn.metrics import accuracy_score
>>> iris = datasets.load_iris() >>> X, y = iris.data[:, :2], iris.target
>>> Xtrain, X test, y_train, y test = train_test_split (X, y, random stat33)
>>> scaler = preprocessing.StandardScaler().fit(X_train)
>>> X test = scaler.transform(X test)
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
>>> knn.fit(X_train, y_train)
>>> y_pred = knn.predict(X_test)
>>> accuracy_score(y_test, y_pred)
```

Prediction

Supervised Estimators

```
>>> y_pred = svc.predict(random.random((2,5)))
>>> y_pred = lr.predict(X_test)
>>> y_pred = knn.predict_proba(X_test)
```

Predict Labels
Predict Labels
Estimate probability of a label

Unsupervised Estimators

```
>>> y_pred = k_means.predict(X_test)
```

Predict labels in clustering algo

Loading the Data

Your data beeds to be nmueric and stored as NumPy arrays or SciPy sparse matric. other types that they are convertible to numeric arrays, such as Pandas Dataframe, are also acceptable

```
>>> import numpy as np >> X = np.random.random((10,5))
>>> y = np.array(['PH','IM','F','F','M','F','NI','tvl','F','F','F'])
>>> X[X < 0.7] = 0
```

Preprocessing The Data

Standardization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(X_train)
>>> standardized_X = scaler.transform(X_train)
>>> standardized_X_test = scaler.transform(X_test)
```

Normalization

```
>>> from sklearn.preprocessing import Normalizer
>>> scaler = Normalizer().fit(X_train)
>>> normalized_X = scaler.transform(X_train)
>>> normalized_X_test = scaler.transform(X_test)
```

Binarization

```
>>> from sklearn.preprocessing import Binarizer
>>> binarizer = Binarizer(threshold=0.0).fit(X)
>>> binary_X = binarizer.transform(X)
```

Encoding Categorical Features

```
>>> from sklearn.preprocessing import Imputer
>>> imp = Imputer(missing_values=0, strategy='mean', axis=0)
>>> imp.fit_transform(X_train)
```

Imputing Missing Values

```
>>> from sklearn.preprocessing import Imputer
>>> imp = Imputer(missing_values=0, strategy='mean', axis=0)
>>> imp.fit_transform(X_train)
```

Generating Polynomial Features

```
>>> from sklearn.preprocessing import PolynomialFeatures
>>> poly = PolynomialFeatures(5)
>>> poly.fit_transform(X)
```

Evaluate Your Model's Performance

Classification Metrics

Accuracy Score

```
>>> knn.score(X_test, y_test)
>>> from sklearn.metrics import accuracy_score
>>> accuracy_score(y_test, y_pred)
```

Estimator score method
Metric scoring functions

Classification Report

```
>>> from sklearn.metrics import classification_report
>>> print(classification_report(y_test, y_pred))
```

Precision, recall, f1-score
and support

Confusion Matrix

```
>>> from sklearn.metrics import confusion_matrix
>>> print(confusion_matrix(y_test, y_pred))
```

Regression Metrics

Mean Absolute Error

```
>>> from sklearn.metrics import mean_absolute_error
>>> y_true = [3, -0.5, 2]
>>> mean_absolute_error(y_true, y_pred)
```

Mean Squared Error

```
>>> from sklearn.metrics import mean_squared_error
>>> mean_squared_error(y_test, y_pred)
```

R² Score

```
>>> from sklearn.metrics import r2_score
>>> r2_score(y_true, y_pred)
```

Clustering Metrics

Adjusted Rand Index

```
>>> from sklearn.metrics import adjusted_rand_score
>>> adjusted_rand_score(y_true, y_pred)
```

Homogeneity

```
>>> from sklearn.metrics import homogeneity_score
>>> homogeneity_score(y_true, y_pred)
```

V-measure

```
>>> from sklearn.metrics import v_measure_score
>>> metrics.v_measure_score(y_true, y_pred)
```

Cross-Validation

```
>>> from sklearn.cross_validation import cross_val_score
>>> print(cross_val_score(knn, X_train, y_train, cv=4))
>>> print(cross_val_score(lr, X, y, cv=2))
```

Model Fitting

Supervised learning

```
>>> lr.fit(X, y)
>>> knn.fit(X_train, y_train)
>>> svc.fit(X_train, y_train)
```

Fit the model to the data

Unsupervised Learning

```
>>> k_means.fit(X_train)
>>> pca_model = pca.fit_transform(X_train)
```

Fit the model to the data
Fit to data, then transform it

Create Your Model

Supervised Learning Estimators

Linear Regression

```
>>> from sklearn.linear_model import LinearRegression
>>> lr = LinearRegression(normalize=True)
```

Support Vector Machines (SVM)

```
>>> from sklearn.svm import SVC
>>> svc = SVC(kernel='linear')
```

Naive Bayes

```
>>> from sklearn.naive_bayes import GaussianNB
>>> gnb = GaussianNB()
```

KNN

```
>>> from sklearn import neighbors
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
```

Unsupervised Learning Estimators

Principal Component Analysis (PCA)

```
>>> from sklearn.decomposition import PCA
>>> pca = PCA(n_components=0.95)
```

K Means

```
>>> from sklearn.cluster import KMeans
>>> k_means = KMeans(n_clusters=3, random_state=0)
```

Training And Test Data

```
>> from sklearn.cross_validation import train_test_split
>> X_train, X_test, y_train, y_test = train_test_split(X,
                                                         y,
                                                         random state=0)
```

Tune Your Model

Grid Search

```
>>> from sklearn.grid_search import GridSearchCV
>>> params = [{"n_neighbors": np.arange(1,3),
              "metric": ["euclidean","cityblock"]}
>>> grid = GridSearchCV(estimator=knn,
                       param_grid=params)
>>> grid.fit(X_train, y_train)
>>> print(grid.best_score_)
>>> print(grid.best_estimator_.n_neighbors)
```

Randomized Parameter Optimization

```
>>> from sklearn.grid_search import RandomizedSearchCV
>>> params = [{"n_neighbors": range(1,5),
              "weights": ["uniform","distance"]}
>>> rsearch = RandomizedSearchCV(estimator=knn,
                                param_distributions=params,
                                cv=4,
                                n_iter=8,
                                random_state=5)
>>> rsearch.fit(X_train, y_train)
>>> print(rsearch.best_score_)
```



Skicit-learn Algorithm

BecomingHuman.AI

