Namma Space — Round 1 technical abstract

Shivasheesh Verma, Class 11, Gulmohar High School
Sarvagya Kaushik, Class 11, Gulmohar High School
Vidhi Arora, Class 11, Springdale Senior School
shivasheeshverma@icloud.com · 1 November 2026

The viewer stays online. It does not run on the team's computer, so it stays open when that computer is asleep. Open https://namma-space-viewer.vercel.app/

The viewer is https://namma-space-viewer.vercel.app/ The demonstration video is a file. It plays on its own.

1. What was built

The deliverable is a free-roaming web viewer of one classroom. The picture is a Gaussian splat: the iPhone photos were trained into 888,760 coloured points, and that is the picture the link above serves, so the walls, desks, and boards keep the real photograph. The file is about 220 MB, so the first load takes a few minutes. Walking does not use those points as colliders. A measured floor plan, taken from the same capture's LiDAR, stops the visitor at the walls and at one closed door. A plan in the corner of the screen shows the room, the furniture, that door, a 2 m scale bar, and where the visitor is standing. Furniture is drawn on the plan but does not stop the walk. The room outline is 8.95 m by 7.43 m. Wall face to wall face is 8.92 m by 7.41 m.

2. Dataset

The room is the MuSHRoom classroom long capture: an iPhone 12 Pro Max, November 2023, released CC BY 4.0. It has 797 posed colour frames and a matching depth image for each frame. Colour used for training is 738 by 994. Depth is the phone LiDAR. The capture is a public indoor room, used because a same-day phone test on this desk contained one frame only, which cannot train a room. The photographs and the depth remain the dataset authors' work.

3. Standard operating procedure

The capture procedure this pipeline expects, and the one a later home scan should follow:

- Record on the 1× camera of a LiDAR iPhone, in Record3D (EXR + JPG) or an equivalent package that stores a photo, a depth image, a confidence map, and a pose for every frame.
- Hold the phone portrait, about chest height, tilted slightly down so each frame sees floor and wall. Do not roll it to landscape. A sideways hold turns the floor into a wall and the plan follows.
- Walk a slow loop of the room, then across the middle, then through the doorway without stopping the recording. Pause at corners. Keep neighbouring views overlapping. LiDAR reaches about 5 m, so walk up to each wall.
- Keep people out of the shot. Lock the exposure so a door jamb is sharp when you pause. A gimbal is useful only if it steadies that walk. A spin from one spot is not a scan.
- One continuous take keeps one coordinate frame. If tracking drops, start again with the same doorway in both recordings.
- Before leaving, check that depth, pose, and colour exist for the start, the middle, and the end, and that the doorway is seen from both sides.

4. Pipeline

- Import. Each frame becomes a colour image, a depth image, lens numbers, and a camera-to-world pose. The eight ways of attaching the picture to the pose are scored. A winner is kept only when it is clearly better, or when a later geometry check finds a floor, a room 2–4 m tall, and the cameras inside it.
- Up. The floor is levelled from the camera motion and the depth, then snapped to a vertical axis. The viewer draws the plan looking down on that frame with x to the right and +z at the top, which the page labels north up.
- Train. The 550 sharpest frames are kept and frames with people are removed. The 24 whose frame number is a multiple of 20 are held out. The other 526 train, and their LiDAR depth seeds the points at a 4 cm voxel. Colour is

trained for 30,000 steps. Depth is a light constraint, weight 0.05, so the scale stays in metres. The config is pipeline/mushroom_classroom_1m.json.

- Walls. A separate measured layout, from the same depth, supplies the floor polygon, the wall segments, and the closed door. Furniture in the photograph is not a collider.
- Viewer. The splat is drawn with Spark 2.3.1 and Three.js 0.180.0. WASD moves a body of radius 0.18 m. The eye is 1.60 m above the measured floor. A move that would enter a wall or the closed door is refused. The walk starts at the back of the room, in the aisle between the two desk rows.

5. Check

24 views held out of training, protocol raw pose, no test-time alignment: mean PSNR 22.9 dB, mean SSIM 0.739, depth mean absolute error 7.0 cm against the LiDAR (median 2.7 cm). The trained model held 999,454 Gaussians. The export kept 888,760 of them and dropped 110,694. That export is the picture on the viewer link. The spawn point sits inside the floor polygon and 0.64 m from the nearest wall.

6. What this is not

An iPad Pro house scan (ARKitScenes 45663064, 256×192, held sideways) was started on the measured-wall pipeline and then stopped. Its camera roll was not confident, the plan came out turned 90 degrees, and the colour stream is too small to match this classroom. That run is not part of the submission. A one-frame LiDAR photo taken on 1 November 2026 confirmed that the phone can save depth, confidence, and a pose. It is not a room.

7. How to view and how to rebuild

Open https://namma-space-viewer.vercel.app/ The page stays up when the team's computer is asleep. The picture there is the full 888,760-point file, about 220 MB, so the first load takes a few minutes. The demonstration video, Demonstration.mp4, is 3 minutes 59 seconds. It covers the scope, the capture, and a walk, and it plays from the file. RECONSTRUCT.md gives the train command. test/sample holds eight frames in the same JSON shape as the full capture. GitHub cannot store the 220 MB picture in the repository history. The code repository is https://github.com/Shivasheesh-verma/namma-space-round1.