

## Database & Deployment Details

### ER Diagram

```
erDiagram
    ASSESSMENTS {
        UUID id PK
        DATETIME created_at
        TEXT attack_type
        TEXT status
        UUID original_pdf_id FK
        UUID answers_pdf_id FK
        UUID attacked_pdf_id FK
        UUID report_pdf_id FK
    }
    STORED_FILES {
        UUID id PK
        TEXT path
        TEXT mime_type
        DATETIME uploaded_at
    }
    QUESTIONS {
        INTEGER id PK
        UUID assessment_id FK
        INTEGER q_number
        TEXT stem_text
        JSONB options_json
        TEXT gold_answer
        TEXT gold_reason
        TEXT attacked_stem
    }
    LLM_RESPONSES {
        INTEGER id PK
        INTEGER question_id FK
        TEXT model_name
        TEXT llm_answer
        TEXT llm_reason
        JSONB raw_json
        DATETIME created_at
    }

    ASSESSMENTS ||--o{ QUESTIONS : has
    ASSESSMENTS }o--|| STORED_FILES : original_pdf_id
    ASSESSMENTS }o--|| STORED_FILES : answers_pdf_id
    ASSESSMENTS }o--|| STORED_FILES : attacked_pdf_id
    ASSESSMENTS }o--|| STORED_FILES : report_pdf_id
```

```
QUESTIONS ||--o{ LLM_RESPONSES : has
```

---

## Database Initialization & Migration

- Initialize the database:

```
cd backend
flask db upgrade
```

- Create a new migration after changing models:

```
flask db migrate -m "Describe your change"
flask db upgrade
```

- Configuration:

- The database URI is set via the DATABASE\_URL environment variable (see .env).
  - Default: postgresql+psycopg://localhost/ftai
- 

## Accessing the Database

- Directly via psql:

```
psql <your-db-url>
```

- With a GUI:

- Use DBeaver, TablePlus, or pgAdmin with the same DATABASE\_URL.

- With SQLAlchemy in a script:

```
from app import db, create_app
app = create_app()
with app.app_context():
    # Now you can use db.session, db.engine, etc.
```

---

## Using the DB from Docker

- Run Postgres in Docker:

```
docker run --name fairtestai-db -e POSTGRES_PASSWORD=yourpassword -e POSTGRES_DB=ftai -
```

- Set your DATABASE\_URL in .env or environment:

```
DATABASE_URL=postgresql+psycopg://postgres:yourpassword@localhost:5432/ftai
```

- Run migrations:

```
cd backend
flask db upgrade
```

- Now your Flask app can connect to the Dockerized DB.

---

## How the DB is Used in the App

- **On Upload:**
  - Uploaded PDFs are saved as `StoredFile` entries.
  - An `Assessment` is created, linking to the uploaded files.
  - Questions are parsed and stored as `Question` entries.
- **On Processing:**
  - Attacked and report PDFs are generated and saved as new `StoredFile` entries.
  - The `Assessment` is updated to link to these new files.
  - LLM responses (if any) are stored as `LLMResponse` entries.

---

## Summary Table

| Task               | Command/Action   |
|--------------------|--|
| Initialize DB      | <code>flask db upgrade</code>  |
| Create migration   | <code>flask db migrate -m "desc"</code>                                |
| Apply migration    | <code>flask db upgrade</code>  |
| Access DB (psql)   | <code>psql &lt;db-url&gt;</code>                                       |
| Access DB (GUI)    | Use DBeaver/TablePlus/pgAdmin with <code>DATABASE_URL</code>           |
| Use DB from Docker | Run Postgres container, set <code>DATABASE_URL</code> , run migrations |
| Use DB in script   | Use <code>create_app()</code> and <code>app.app_context()</code>       |

---

## Example Docker Compose (Optional)

```
version: '3.8'
services:
  db:
    image: postgres:15
    environment:
      POSTGRES_PASSWORD: yourpassword
      POSTGRES_DB: ftai
    ports:
      - "5432:5432"
```

```
    volumes:
      - db_data:/var/lib/postgresql/data
  backend:
    build: ./backend
    environment:
      DATABASE_URL: postgresql+psycopg://postgres:yourpassword@db:5432/ftai
      OPENAI_API_KEY: your-openai-key
    depends_on:
      - db
    ports:
      - "5000:5000"
  volumes:
    db_data:
```