

CSC110 Lecture 24: Analyzing Built-In Data Type Operations

David Liu, Department of Computer Science

Navigation tip for web slides: press ? to see keyboard navigation controls.

Announcements and Today's Plan

Announcements

- Assignment 4 has been posted
 - Check out the [A4 FAQ \(+ corrections\)](#)
 - Important [simplifying precondition](#) for Part 4b,
`find_collision_len_times_sum`
 - [Additional TA office hours](#)
 - Review [advice on academic integrity](#)

Story so far

Up to this point, we've focused on running-time analysis where the complexity has been mainly due to **loops**.

The individual expressions/statements have been constant time (other than comprehensions):

- Arithmetic and comparison operations on numbers (+, <)
- Assignment statements (all data types)
- Calling `print` on numbers; calling `len` on collections
- Returning from a function

Today, we'll study the running time of individual operations on **collection data types** (`list/set/dict`) and **data classes**.

Today you'll learn to...

1. State the running times of **operations on built-in collection data types and data classes**.
2. Explain these running times for `list` operations based on how Python implements lists.
3. Analyze the running time of functions that use these operations.
4. Analyze the running time of functions that have multiple arguments (of different sizes).

Running time of list operations

Suppose we want to add an element to a list:

Add to the back:


```
>>> lst = [0] * 10000000  
>>> list.append(lst, 1234)
```

Add to the front:


```
>>> lst = [0] * 10000000  
>>> list.insert(lst, 0, 1234)
```






List length vs. time taken

```
list.append(lst, 1234)
```




```
list.insert(lst, 0, 1234)
```





| Address | Memory | |
|---------|-------------|----------------|
| ⋮ | <div></div> | |
| 400 | 601 | (list index 0) |
| 401 | 512 | |
| 402 | 699 | |
| 403 | 650 | |
| 404 | | |
| ⋮ | <div></div> | |
| 512 | 7 | |
| ⋮ | <div></div> | |
| 601 | 8 | |
| ⋮ | <div></div> | |
| 650 | -3 | |
| ⋮ | <div></div> | |
| 699 | 100 | |
| ⋮ | <div></div> | |

How the Python interpreter stores lists

Each Python list has references to its elements stored in a **contiguous block of memory**.

(contiguous = consecutive memory locations with no gaps)

This is called an **array-based list implementation**.

Benefits: constant-time indexing!

To lookup the value of `lst[i]`:

1. Get the starting address of the list.
 - E.g., 400
2. Add `i` to the starting address. That block contains the reference to `lst[i]`.
 - E.g., `lst[3]` is at address $400 + 3 = 403$.

List indexing (`lst[i]`) is $\Theta(1)$, **independent** of the size of the list or the index `i`.

| Address | Memory | |
|---------|--------|----------------|
| : | | |
| 400 | 601 | (list index 0) |
| 401 | 512 | |
| 402 | 699 | |
| 403 | 650 | |
| 404 | | |
| : | | |
| 512 | 7 | |
| : | | |
| 601 | 8 | |
| : | | |
| 650 | -3 | |
| : | | |
| 699 | 100 | |
| : | | |

Costs: insertion/deletion can be slow

All modifications to the list must preserve the **contiguity** of the list elements in memory.

When an element is inserted into a list, all elements after it must be shifted over to make room.

When an element is deleted from a list, all elements after it must be shifted back to fill in the gap.

| Address | Memory | |
|---------|--------|----------------|
| ⋮ | ⋮ | |
| 400 | 601 | (list index 0) |
| 401 | 512 | |
| 402 | 699 | |
| 403 | 650 | |
| 404 | | |
| ⋮ | ⋮ | |
| 512 | 7 | |
| ⋮ | ⋮ | |
| 601 | 8 | |
| ⋮ | ⋮ | |
| 650 | -3 | |
| ⋮ | ⋮ | |
| 699 | 100 | |
| ⋮ | ⋮ | |
| 742 | 27 | |
| ⋮ | ⋮ | |

For a list of length n , insertion/deletion at index i takes $\Theta(n - i)$ time.

- When $i = n - 1$ (**end** of the list), running time is $\Theta(1)$.
 - `list.append(lst, item)`
 - `list.pop(lst)`
- When $i = 0$, (**front** of list), running time is $\Theta(n)$.
 - `list.insert(lst, 0, item)`
 - `list.pop(lst, 0)`

Summary

| Operation | Running time |
|--|-----------------|
| List indexing (<code>lst[i]</code>) | $\Theta(1)$ |
| List index assignment (<code>lst[i] = ...</code>) | $\Theta(1)$ |
| List insertion at index i (<code>list.insert(lst, i, ...)</code>) | $\Theta(n - i)$ |
| List deletion at index i (<code>list.pop(lst, i)</code>) | $\Theta(n - i)$ |
| List insertion at end (<code>list.append(lst, ...)</code>) | $\Theta(1)$ |
| List deletion at end (<code>list.pop(lst)</code>) | $\Theta(1)$ |

Exercise 1: Running time of list operations

Analysing running time for
functions with multiple
parameters

```
def my_extend(lst1: list, lst2: list) -> None:
    """Add each element in lst2 to the end of lst1."""
    for item in lst2:
        list.append(lst1, item)
```

Analysis.

Let n_1 be the length of `lst1` and n_2 be the length of `lst2`.

The loop iterates n_2 times, and each time takes constant time (1 step).

The total running time is $n_2 \cdot 1 = n_2$ steps, which is $\Theta(n_2)$.

```
def my_concat(lst1: list, lst2: list) -> list:
    new_list = []

    for item in lst1:                # Loop 1
        list.append(new_list, item)
    for item in lst2:                # Loop 2
        list.append(new_list, item)

    return new_list
```

Analysis. Let n_1 be the length of `lst1` and n_2 be the length of `lst2`.

- The initial assignment statement takes 1 step.
- Loop 1 takes n_1 steps (n_1 iterations, 1 step per iteration)
- Loop 2 takes n_2 steps (n_2 iterations, 1 step per iteration)
- The return statement takes constant time.

The total running time is $1 + n_1 + n_2 + 1 = n_1 + n_2 + 2$, which is $\Theta(n_1 + n_2)$.

Exercise 2: Running-time analysis with multiple parameters

Sets, dictionaries, and data
classes

Sets

Set operations:

- `x in my_set`
- `set.add`
- `set.remove`

Each of these operations take $\Theta(1)$ —constant time!

Sets are implemented in Python using [hash tables](#), which are based on arrays.

Dictionaries

Dictionary operations:

- key search (`k in my_dict`)
- key lookup/assignment (`my_dict[k], my_dict[k] = ...`)

Also $\Theta(1)$, very similar implementation to sets!

Data classes

Data class operations:

- attribute lookup (`david.age`)
- attribute assignment (`david.age = ...`)

Also $\Theta(1)$, very similar implementation to dictionaries (and sets)!

Exercise 3: Sets, dictionaries, and data classes (if time)

Some built-in aggregation
functions

Most aggregation functions take $\Theta(n)$ time (where n is the size of the collection).

sum, max, min

`len` is special: it takes $\Theta(1)$ time—independent of the size of the collection!

Behind the scenes: a “hidden” size attribute stored by the Python interpreter for every collection object.

`any/all` are special, because they're implemented with an **early return**.

- `any` can stop as soon as it encounters a `True`
- `all` can stop as soon as it encounters a `False`

To be continued next class...

Summary

Today you learned to...

1. State the running times of **operations on built-in collection data types and data classes**.
2. Explain these running times for `list` operations based on how Python implements lists.
3. Analyze the running time of functions that use these operations.
4. Analyze the running time of functions that have multiple arguments (of different sizes).

Homework

- Readings:
 - Review: 9.5, 9.6
 - From today: 9.7
 - For tomorrow: 9.8
- Work on Assignment 4!

**LOOP BODY'S
RUNTIME IS
ALWAYS THE
SAME**



**LOOP BODY'S
RUNTIME
DEPENDS ON
THE ITERATION**

