Performance and Functional Testing

Treavue — Personalized Travel Itinerary Planner

Project documentation prepared for portfolio and repository use

Test objectives

Confirm that core user workflows are responsive, API behavior is predictable, trip data round-trips correctly, and frontend changes do not break the production build.

Test cases

ID	Test	Expected result
T01	**Backend health endpoint**	**Returns healthy response**
T02	**Generate itinerary with valid inputs**	**Returns structured itinerary**
T03	**Create and fetch trip**	**Same trip ID and payload are returned**
T04	**Update trip title/data**	**Updated data persists**
T05	**Delete trip**	**Record is removed; missing record is handled**
T06	**Supabase unavailable**	**Controlled error and local fallback**
T07	**Frontend typecheck/build**	**Completes without errors**
T08	**Owner isolation**	**Must deny cross-user access after auth/ownership is implemented**

Performance approach

Measure API latency with repeated requests and representative payloads; record median and high-percentile timings. Avoid claiming numerical performance results unless a run produced them.

Current evidence

Project development notes reported passing backend tests, frontend typecheck, production build, and a temporary Supabase CRUD round-trip. Re-run these checks against the exact version being submitted.

Limitations

This document does not assert a formal load test or production benchmark. Authentication/owner-isolation must be separately tested before release.