Project Executable Files and Run Guide

Treavue — Personalized Travel Itinerary Planner

Project documentation prepared for portfolio and repository use

Prerequisites

Node.js and pnpm for frontend; the project's configured Python environment and backend dependencies; access to the configured Supabase project for cloud persistence.

Backend — PowerShell

- Set-Location 'C:\Users\Sanjay Kumar\Downloads\Treavue-Travel-Planner\Treavue-Travel-Planner\backend'
- & 'C:\Users\Sanjay Kumar\.conda\envs\treavue\python.exe' -m uvicorn app.main:app --reload --host 127.0.0.1 --port 8001

Frontend — second PowerShell terminal

- Set-Location 'C:\Users\Sanjay Kumar\Downloads\Treavue-Travel-Planner\Treavue-Travel-Planner'
- $env:PORT='5173'
- $env:BASE_PATH='/'
- pnpm.cmd --dir artifacts\treavue run dev

Local URLs

- Frontend: http://localhost:5173
- FastAPI docs: http://127.0.0.1:8001/docs

Configuration

Use blank variable names in .env.example as a guide. Configure actual backend values locally, never paste secrets into documentation, GitHub, screenshots, or VITE_* variables.

Before public deployment

Complete authentication, verified access-token checks, per-user trip ownership, RLS, and cross-user denial tests.