

Experiment – 15

Aim –Observer design pattern (Behavioral pattern)

Concept - Observer design pattern is useful when you are interested in the state of an object and want to get notified whenever there is any change.

RestaurantOrder.java

```
import java.util.ArrayList;
import java.util.List;

public class RestaurantOrder {

    private List<Observer> observers = new ArrayList<Observer>();
    private int order;

    public int getOrder() {
        return order;
    }

    public void setOrder(int order) {
        this.order = order;
        notifyAllObservers();
    }

    public void attach(Observer observer) {
        observers.add(observer);
    }

    public void notifyAllObservers() {
        for (Observer observer : observers) {
            observer.update();
        }
    }
}
```

Observer.java

```
public abstract class Observer {
    protected RestaurantOrder restaurantOrder;
    public abstract void update();
}
```

OrderConfirmed.java

```
public class OrderConfirmed extends Observer{
    public OrderConfirmed(RestaurantOrder restaurantOrder) {
        this.restaurantOrder = restaurantOrder;
        this.restaurantOrder.attach(this);
    }
}
```

```
@Override
public void update() {
    System.out.println("Order confirm");
}
}
```

OrderDelivered.java

```
public class OrderDelivered extends Observer{
    public OrderDelivered(RestaurantOrder restaurantOrder) {
        this.restaurantOrder = restaurantOrder;
        this.restaurantOrder.attach(this);
    }

    @Override
    public void update() {
        System.out.println("Order deliver");
    }
}
```

OrderCancelled.java

```
public class OrderCancelled extends Observer{
    public OrderCancelled(RestaurantOrder restaurantOrder) {
        this.restaurantOrder = restaurantOrder;
        this.restaurantOrder.attach(this);
    }

    @Override
    public void update() {
        System.out.println("Order Cancel");
    }
}
```

Client.java

```
public class Client {
    public static void main(String[] args) {
        RestaurantOrder restaurantOrder = new RestaurantOrder();

        new OrderConfirmed(restaurantOrder);
        new OrderDelivered(restaurantOrder);
        new OrderCancelled(restaurantOrder);

        restaurantOrder.setOrder(1);
    }
}
```

OUTPUT :

```
"C:\Program Files\Java\jdk-17.0.2\bin\java.exe" "-javaagent:C:\Program Files\JetBrains\IntelliJ ID  
Order confirm  
Order deliver  
Order Cancel  
  
Process finished with exit code 0
```