Started on	Monday, 28 September 2026, 4:02 PM
State	Finished
Completed on	Monday, 28 September 2026, 4:48 PM
Time taken	45 mins 41 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1

Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>
int majorityElement(int* nu
    int candidate = nums[0]
    int count = 1;

    for (int i = 1; i < nun
        if (count == 0) {
            candidate = nun
            count = 1;
        } else if (nums[i]
            count++;
        } else {
            count--;
        }
    }

    return candidate;
}
int main() {
    int n;
    if (scanf("%d", &n) !=
        return 0;
    }
    int *nums = (int*)mallo
    if (nums == NULL) {
        return 1;
    }
    for (int i = 0; i < n;
        scanf("%d", &nums[i
    }
    int result = majorityEl
    printf("%d\n", result);
    free(nums);
    return 0;
}
```