Started on	Sunday, 11 October 2026, 11:40 AM
State	Finished
Completed on	Sunday, 11 October 2026, 11:59 AM
Time taken	19 mins 3 secs

Question 1 | Complete Marked out of 1.00

Default EOL character of text file in python is ,

- a. \n
- b. ,
- c. \t
- d. space

Question 2 | Complete Marked out of 1.00

The readlines() method returns _____

- a. a list of integers
- b. str
- c. a list of single characters
- d. a list of lines

Question 3 | Complete Marked out of 1.00

Which method is used to read a specific number of characters from a file?

- a. readline()
- b. readlines()
- c. readchar()
- d. read(size)

Question 4 | Complete Marked out of 1.00

Which function is used to open a file in Python?

- a. open()
- b. open_file()

c. file()
d. openfile()

Question 5 | Complete Marked out of 1.00

How do you check if a file is closed in Python?

- a. file.closed
- b. file.isclosed()
- c. file.is_closed()
- d. file.closed()

Question 6 | Complete Marked out of 1.00

What does the flush() method do in file handling?

- a. Deletes the file content
- b. Moves the file cursor to the beginning
- c. Closes the file
- d. Flushes the internal buffer to the file

Question 7 | Complete Marked out of 1.00

To open a file a.txt for reading, we use _____

- a. infile = open(file, “a.txt”, “r”)
- b. infile = open(“a.txt”, “r”)
- c. infile = open(file = “a.txt”, “r”)
- d. infile = open(file = “a.txt”, “r”)

Question 8 | Complete Marked out of 1.00

f.seek(5,1) means

- a. move the file pointer five characters ahead from the current position
- b. moves the file pointer to the end of a file
- c. move the file pointer to beginning of the file
- d. move the file pointer five characters behind from the current position

Question 9 | Complete Marked out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

- a. world
- b. An error is raised
- c. Hello
- d. Hello, world!

Question 10 | Complete Marked out of 1.00

What does the seek() method do in file handling?

- a. Reads the file line by line
- b. Deletes the file
- c. Writes data to the file
- d. Moves the file cursor to the specified position

Question 11 | Complete Marked out of 1.00

How can you read a file line by line efficiently in Python?

- a. Using the readlines() method
- b. Using a for loop
- c. Using the read() method
- d. Using the readline() method

Question 12 | Complete Marked out of 1.00

Which of the following modes opens a file for both reading and writing?

- a. a
- b. r+
- c. r
- d. w

Question 13 | Complete Marked out of 1.00

What does the buffering parameter in the open() function control?

a. The encoding of the file
b. The file's read/write position
c. The access mode of the file
d. The buffer size for the file operations

Question 14 | Complete Marked out of 1.00

What is the difference between r+ and w+ modes in file handling?

a. r+ is for read and write, w+ is for append only
b. r+ is for read and append, w+ is for read and write
c. r+ is for binary read and write, w+ is for text read and write
d. r+ is for read and write without truncating, w+ is for read and write with truncating

Question 15 | Complete Marked out of 1.00

Which of the following methods is used to read a single line from a file?

a. readlines()
b. readline(size)
c. readline()
d. read()