

225. Implement Stack using Queues

Easy Topics Companies

Implement a last-in-first-out (LIFO) stack using only two queues. The implemented stack should support all the functions of a normal stack (push, top, pop, and empty).

Implement the MyStack class:

- void push(int x) Pushes element x to the top of the stack.
- int pop() Removes the element on the top of the stack and returns it.
- int top() Returns the element on the top of the stack.
- boolean empty() Returns true if the stack is empty, false otherwise.

Notes:

- You must use **only** standard operations of a queue, which means that only push to back, peek/pop from front, size and is empty operations are valid.
- Depending on your language, the queue may not be supported natively. You may simulate a queue using a list or deque (double-ended queue) as long as you use only a queue's standard operations.

Example 1:

Input

Code

C Auto

```
1 typedef struct {
2     int* q1;
3     int* q2;
4     int f1, f2, r1, r2;
5 } MyStack;
6
7
8 MyStack* myStackCreate() {
9     MyStack* st = (MyStack*)malloc(sizeof(MyStack));
10    st->q1 = (int*)calloc(10, sizeof(int));
11    st->q2 = (int*)calloc(10, sizeof(int));
12    st->f1 = -1;
13    st->f2 = -1;
14    st->r1 = -1;
15    st->r2 = -1;
16    return st;
17 }
18
19 void myStackPush(MyStack* obj, int x) {
20     if (obj->f1 == -1 && obj->r1 == -1) {
21         obj->f1 = 0;
22         obj->r1 = 0;
23     }
24     else {
25         obj->r1++;
26     }
27     printf("%d\n", x);
28     obj->q1[obj->r1] = x;
29 }
```

Saved to local



shivsundarsah

Access all features with our Premium subscription!



My Lists



Notebook



Submissions



Progress



Points



Session

Try New Features

Orders

My Playgrounds

Revert to old version

Appearance

Sign Out

</> Code

C v Auto

```
31 int myStackPop(MyStack* obj) {
32     if (obj->f1 == -1) {
33         return -1;
34     }
35     int k1 = obj->f1;
36     int l1 = obj->r1;
37     int k2 = obj->f2;
38     int l2 = obj->r2;
39     int ch;
40     while (k1 < l1) {
41         if (k2 == -1) {
42             k2 = 0;
43             l2 = 0;
44         } else {
45             l2++;
46         }
47
48         obj->q2[l2] = obj->q1[k1];
49         k1++;
50     }
51     ch = obj->q1[k1];
52     k1--;
53     l1--;
54     int* temp = obj->q1;
55     obj->q1 = obj->q2;
56     obj->q2 = temp;
57
58     obj->f1 = k2;
59     obj->f2 = k1;
60
61     obj->r1 = l2;
62     obj->r2 = l1;
63     if(obj->r1 < obj->f1){
64         obj->r1 = -1;
```

Saved to local

/> Code

Auto

```
88     obj->q2[12] = obj->q1[k1];
89     k1++;
90 }
91
92 int* temp = obj->q1;
93 obj->q1 = obj->q2;
94 obj->q2 = temp;
95
96 return ch;
97 }
98
99
100 bool myStackEmpty(MyStack* obj) {
101     return (obj->f1 == -1);
102 }
103
104 void myStackFree(MyStack* obj) {
105     free(obj->q1);
106     free(obj->q2);
107     free(obj);
108 }
109 /**
110  * Your MyStack struct will be instantiated and called as such:
111  * MyStack* obj = myStackCreate();
112  * myStackPush(obj, x);
113
114  * int param_2 = myStackPop(obj);
115
116  * int param_3 = myStackTop(obj);
117
118  * bool param_4 = myStackEmpty(obj);
119
120  * myStackFree(obj);
121  */
```

Saved to local

Accepted Runtime: 3 ms

• Case 1

Input

```
["MyStack","push","push","top","pop","empty"]
```

```
[[],[1],[2],[],[],[ ]]
```

Stdout

```
1
```


```
2
```

Output

```
[null,null,null,2,2,false]
```

Expected

```
[null,null,null,2,2,false]
```

 [Contribute a testcase](#)