

Machine Problem 4: Kernel-Level Thread Scheduling

Introduction

In this machine problem you will add **scheduling of multiple kernel-level threads** to your code base. The emphasis is on **scheduling**. The test code for this MP (file `kernel1.C`) illustrates that a scheduler is not necessary for multiple threads to happily execute in a system. For example, the following code displays two routines (each executed by a different thread) that explicitly hand the control back and forth, and so achieve a simple form of multithreading:

```
void fun1() {
    console_puts("FUN 1 INVOKED BY THREAD 1\n");
    for(;;) {
        < do something ... >
        thread_dispatch_to(thread2);
    }
}
void fun2() {
    console_puts("FUN 2 INVOKED BY THREAD 2\n");
    for(;;) {
        < do something ... >
        thread_dispatch_to(thread1);
    }
}
```

In this piece of code the CPU is passed back and forth between Thread 1 and Thread 2. And this works fine, until we want to add a third thread. Do we really want to modify the code of `fun2()` to dispatch Thread 3 on the CPU? And does the programmer of Thread 3 really want to know that the CPU needs to be dispatched back to Thread 1? What if she does not want to release the CPU at all? So, we cannot rely on the threads to play nice, and we need a third party that allocates the CPU on behalf of the running threads: We need a **scheduler**. The interface of the scheduler is defined in file `Scheduler.H`. It exports the following functionality:

```
class Scheduler {
public:
    Scheduler();
    /* Setup the scheduler. This sets up the ready queue, for example.
       If the scheduler implements some sort of round-robin scheme, then the
       end_of_quantum handler is installed here as well. */
    virtual void yield();
    /* Called by the currently running thread in order to give up the CPU.
       The scheduler selects the next thread from the ready queue to load onto
       the CPU, and calls the dispatcher function defined in 'threads.h' to
       do the context switch. */
    virtual void resume(Thread * _thread);
    /* Add the given thread to the ready queue of the scheduler. This is called
       for threads that were waiting for an event to happen, or that have
       to give up the CPU in response to a preemption. */
    virtual void add(Thread * _thread);
    /* Make the given thread runnable by the scheduler. This function is typically
       called after a thread has been created. Depending on the
       implementation, this may not entail more than simply adding the
       thread to the ready queue (see scheduler_resume). */
    virtual void terminate(Thread * _thread);
```

```

/* Remove the given thread from the scheduler in preparation for destruction
   of the thread. */
};

```

You are to implement a simple First-In-First-Out (FIFO) scheduler. This is very easy to achieve: The scheduler maintains a so-called **ready queue**, which is a list of threads (or, better, their thread control blocks) that are waiting to get to the CPU. One thread is running on the CPU, typically. Whenever a running thread calls `yield()`, the scheduler finds the next thread to run at the head of the ready queue, and calls the dispatcher to invoke a context switch. Whenever the system decides that a thread, say Thread `t1`, should become ready to execute on the CPU again it calls `resume(t1)`, which adds `t1` to the end of the ready queue. Other threads may be waiting for events to happen, such as for a page fault or some other I/O operation to complete. We call these threads **blocked**. We don't worry about blocked threads for now, as all the threads are either busy executing or waiting on the ready queue. Later, when threads access devices, we will have to deal with blocked threads as well.

Implementation of the Scheduler

You realize the scheduler by implementing the exported functions (declared in file `Scheduler.H`) inside a file called `Scheduler.C`. Implement primarily the constructor and the functions `yield()`, `add()`, and `resume()`. When you are read to handle terminating thread functions, you should may have to implement the function `terminate()` as well.

Depending on how you want to implement the ready queue, you may have to modify the thread control block in `thread.H`.

Testing your Scheduler

The file `kernel.C` is set up to make testing of your scheduler easy. The file creates four threads, each of which is assigned a different function – called `fun1` for Thread 1 to `fun4` for Threads 4 – which call a function `pass_on_CPU()` to explicitly dispatch the next thread on the CPU in the way described above. A macro `_USES_SCHEDULER_` defines how control is passed among threads in file `kernel.C`. For details, look at the source code in `kernel.C`.

Threads with Terminating Thread Functions

Currently, there is no support in the low-level thread management for threads with thread functions that return. For example, all the thread functions in `kernel.C` contain infinite loops. The system at this point does not know what to do when the thread function returns. You are to study the thread management code and propose and implement a solution that allows a thread to cleanly terminate when its thread function returns. You need to worry about releasing the CPU, releasing memory, giving control to the next thread, etc. Test your solution by making the thread functions in `kernel.C` return. You can easily do this by modifying the `for` loops to have an upper bound. For example, modify the lines `for(int j = 0;; j++)` to read `for (int j = 0; j < 10; j++)` or similar. A macro `_TERMINATING_FUNCTIONS_` defines whether the thread functions for the first two threads terminate after 10 iterations or not. For details, look at the source code in `kernel.C`.

Opportunities for Bonus Points

If you want to extend your work beyond the bare minimum, here are a few options.

OPTION 1: Correct handling of interrupts. (This option carries 15 bonus points.) You will notice that interrupts are disabled after we start the first thread. One symptom is that the periodic clock update message is missing. This is caused by the way we create threads: We set up the context so that the Interrupt Enable Flag (IF) in the EFLAGS status register is zero, which disables interrupts once the created thread returns from the fake "exception" when it starts. This is ok, because we may not want to deal with interrupts when we are just starting up our thread. But at some point we need to re-enable interrupts. And turn them off again when we need to ensure mutual exclusion. It is up to you to modify the code in the scheduler and the thread management to ensure correct enabling/disabling of interrupts. **The functions to do that are provided in `machine.h`.**

OPTION 2: Round-Robin Scheduling: (This option carries 15 bonus points.¹) Once we have interrupts set up correctly, we can expand our simple FIFO scheduler into a basic round-robin scheduler. For this, **we want to generate an interrupt at a periodic interval (say 50 msec).** This can be done by either modifying or replacing the interrupt handler for the simple timer. The new interrupt handler triggers preemption of the currently running thread. During the preemption the currently running thread puts itself on the ready queue and then gives up the CPU.

If you think this is just a `resume()` followed by a `yield()`, think again. The situation is a bit more complicated than that. For example, the current thread is giving up the CPU **inside an interrupt handler, and the new thread may or may not be returning from a preemption, and therefore may or may not be returning from an interrupt handler.** In both cases we need to let the interrupt controller (PIC) know that the interrupt has been handled. In addition, we need to stop the original thread from informing the PIC when it returns from the interrupt possibly much later. It is very likely that you will need to modify the **low-level exception and interrupt handling code** to get this to work right.

A Note about the new Main File

The main file for this MP is somewhat similar in nature to the earlier MPs. We have removed page tables and paging, and we have added code to initialize threading, for scheduling, and for creating a small number of threads.

The Assignment

1. Implement the routines defined in file `Scheduler.H` (and described above) to initialize the scheduler, to add new threads, and to perform the scheduling operations.
2. You may need to modify file `Scheduler.H`. If so, document how and why.
3. Modify file `kernel.C` to replace explicit dispatching with calls to the scheduler. This can be done by uncommenting a definition of a macro that enables scheduling. **Details about how to do this are given in file `kernel.C`.**
4. Add support for threads with terminating thread functions. This may require modifications to file `thread.C`. If so, document how and why. Test your solution by uncommenting the definition of the appropriate macro in file `kernel.C`.
5. If you decide to pursue one or more of the options, proceed as follows.

¹Attack this problem only after you have convinced yourself that you are managing interrupts correctly. Otherwise you will waste a lot of time with this!

Option 1 Fix the interrupt management so that interrupts remain enabled outside of critical sections.

Option 2 Modify the scheduler to implement round-robin with a 50 msec time quantum. (Note: Since the preemption interrupt arrives periodically, this is not a very good round-robin scheduler. Whenever a thread gives up the CPU voluntarily, the next thread is short-changed.)

You should have access to a set of source files, BOCHS environment files, and a makefile that should make your implementation easier. In particular, the `kernel.C` file will contain documentation that describes where to add code and how to proceed about testing the code as you progress through the machine problem.

What to Hand In

You are to hand in the following items on CSNET:

- A ZIP file containing the following files:
 1. A design document (in PDF format) that describes your design and the implementation of the FIFO scheduler, and any of the selected options. **Clearly identify in your design document and in your submitted code what options you have selected, if any.**
 2. Two files, called `Scheduler.H` and `Scheduler.C`, which contain the definition and implementation of the functions to initialize the FIFO scheduler and to execute the scheduler operations.
 3. Thread termination may require modifications to other files (such as `thread.C`). If so, document what you have changed and why.
 4. Submit any other modified file, and clearly identify and comment the portions of code that you have modified.
- Grading of these MPs is a very tedious chore. These handin instructions are meant to mitigate the difficulty of grading, and to ensure that the grader does not overlook any of your efforts.
- **Failure to follow the handing instructions will result in lost points.**