

SQL

SQL is a standard language for accessing and manipulating databases.

Database link :

https://www.w3schools.com/sql/trysql.asp?filename=trysql_select_all

- SQL is a standard language for storing, manipulating and retrieving data in databases.
- how to use SQL in: MySQL, SQL Server, MS Access, Oracle, Sybase, Informix, Postgres, and other database systems.

What is SQL?

- SQL stands for Structured Query Language
- SQL lets you access and manipulate databases
- SQL became a standard of the American National Standards Institute (ANSI) in 1986, and of the International Organization for Standardization (ISO) in 1987

What Can SQL do?

- SQL can execute queries against a database
- SQL can retrieve data from a database
- SQL can insert records in a database
- SQL can update records in a database
- SQL can delete records from a database
- SQL can create new databases
- SQL can create new tables in a database
- SQL can create stored procedures in a database
- SQL can create views in a database
- SQL can set permissions on tables, procedures, and views

Using SQL in Your Web Site

- To build a web site that shows data from a database, you will need:
- An RDBMS database program (i.e. MS Access, SQL Server, MySQL)
- To use a server-side scripting language, like PHP or ASP
- To use SQL to get the data you want
- To use HTML / CSS to style the page

RDBMS

- RDBMS stands for Relational Database Management System.
- RDBMS is the basis for SQL, and for all modern database systems such as MS SQL Server, IBM DB2, Oracle, MySQL, and Microsoft Access.
- The data in RDBMS is stored in database objects called tables. A table is a collection of related data entries and it consists of columns and rows.

Example

- From - https://www.w3schools.com/sql/trysql.asp?filename=trysql_select_all
- Write SQL command - **SELECT * FROM Customers;**

What's in the table?

- Every table is broken up into smaller entities called fields. The fields in the Customers table consist of CustomerID, CustomerName, ContactName, Address, City, PostalCode and Country. A field is a column in a table that is designed to maintain specific information about every record in the table.
- A record, also called a row, is each individual entry that exists in a table. For example, there are 91 records in the above Customers table. A record is a horizontal entity in a table.
- A column is a vertical entity in a table that contains all information associated with a specific field in a table.

SQL Syntax : Database Tables

- A database most often contains one or more tables. Each table is identified by a name (e.g. "Customers" or "Orders"). Tables contain records (rows) with data.
- In this tutorial we will use the well-known Northwind sample database (included in MS Access and MS SQL Server).

Below is a selection from the "Customers" table:

CustomerID	CustomerName	ContactName	Address	City	PostalCode	Country
1	Alfreds Futterkiste	Maria Anders	Obere Str. 57	Berlin	12209	Germany
2	Ana Trujillo Emparedados y helados	Ana Trujillo	Avda. de la Constitución 2222	México D.F.	05021	Mexico
3	Antonio Moreno Taquería	Antonio Moreno	Mataderos 2312	México D.F.	05023	Mexico
4	Around the Horn	Thomas Hardy	120 Hanover Sq.	London	WA1 1DP	UK
5	Berglunds snabbköp	Christina Berglund	Berguvsvägen 8	Luleå	S-958 22	Sweden



The table above contains five records (one for each customer) and seven columns (CustomerID, CustomerName, ContactName, Address, City, PostalCode, and Country).

SQL Statements

- Most of the actions you need to perform on a database are done with SQL statements.
- The following SQL statement selects all the records in the "Customers" table:

```
SELECT * FROM Customers;
```

- SQL keywords are NOT case sensitive: select is the same as SELECT

Semicolon after SQL Statements?

- Some database systems require a semicolon at the end of each SQL statement.
- Semicolon is the standard way to separate each SQL statement in database systems that allow more than one SQL statement to be executed in the same call to the server.
- Usually we will use semicolon at the end of each SQL statement.

Some of The Most Important SQL Commands

- **SELECT** - extracts data from a database
- **UPDATE** - updates data in a database
- **DELETE** - deletes data from a database
- **INSERT INTO** - inserts new data into a database
- **CREATE DATABASE** - creates a new database
- **ALTER DATABASE** - modifies a database
- **CREATE TABLE** - creates a new table
- **ALTER TABLE** - modifies a table
- **DROP TABLE** - deletes a table
- **CREATE INDEX** - creates an index (search key)
- **DROP INDEX** - deletes an index

The SQL SELECT Statement

- The SELECT statement is used to select data from a database.
- The data returned is stored in a result table, called the result-set.

SELECT Syntax

```
SELECT column1, column2, ...  
FROM table_name;
```

- Here, column1, column2, ... are the field names of the table you want to select data from. If you want to select all the fields available in the table, use the following syntax:

SELECT * FROM *table_name*;

SELECT Column Example

- The following SQL statement selects the "CustomerName" and "City" columns from the "Customers" table:

SELECT CustomerName, City FROM Customers;

Result:

Number of Records: 91

CustomerName	City
Alfreds Futterkiste	Frankfurt
Ana Trujillo Emparedados y helados	México D.F.
Antonio Moreno Taquería	México D.F.
Around the Horn	London
Berglunds snabbköp	Luleå
Blauer See Delikatessen	Mannheim
Blondel père et fils	Strasbourg
Bólido Comidas preparadas	Madrid
Bon app'	Marseille

The SQL SELECT DISTINCT Statement

- The SELECT DISTINCT statement is used to return only distinct (different) values.
- Inside a table, a column often contains many duplicate values; and sometimes you only want to list the different (distinct) values.
- The SELECT DISTINCT statement is used to return only distinct (different) values.

SELECT DISTINCT Syntax

```
SELECT DISTINCT column1, column2, ...  
FROM table_name;
```


- Example : `SELECT Country FROM Customers;`
- `SELECT DISTINCT Country FROM Customers;`
- What's the difference?
- The following SQL statement lists the number of different (distinct) customer countries:
- `SELECT COUNT(DISTINCT Country) FROM Customers;`

The SQL WHERE Clause

- The WHERE clause is used to filter records.
- The WHERE clause is used to extract only those records that fulfill a specified condition.
- WHERE Syntax

```
SELECT column1, column2, ...  
FROM table_name  
WHERE condition;
```

- Example: The following SQL statement selects all the customers from the country "Mexico", in the "Customers" table:

```
SELECT * FROM Customers  
WHERE Country='Mexico';
```

Text Fields vs. Numeric Fields

- SQL requires single quotes around text values (most database systems will also allow double quotes).
- However, numeric fields should not be enclosed in quotes:

```
SELECT * FROM Customers  
WHERE CustomerID=1;
```

Operators in The WHERE Clause

The following operators can be used in the WHERE clause:

Operator	Description
=	Equal
<>	Not equal. Note: In some versions of SQL this operator may be written as !=
>	Greater than
<	Less than
>=	Greater than or equal
<=	Less than or equal
BETWEEN	Between an inclusive range
LIKE	Search for a pattern
IN	To specify multiple possible values for a column

The SQL AND, OR and NOT Operators

- The WHERE clause can be combined with AND, OR, and NOT operators.
- The AND and OR operators are used to filter records based on more than one condition:
- The AND operator displays a record if all the conditions separated by AND is TRUE.
- The OR operator displays a record if any of the conditions separated by OR is TRUE.
- The NOT operator displays a record if the condition(s) is NOT TRUE.

AND Syntax

```
SELECT column1, column2, ...  
FROM table_name  
WHERE condition1 AND condition2 AND condition3 ...;
```

OR Syntax

```
SELECT column1, column2, ...  
FROM table_name  
WHERE condition1 OR condition2 OR condition3 ...;
```

NOT Syntax

```
SELECT column1, column2, ...  
FROM table_name  
WHERE NOT condition;
```

AND example:

```
SELECT * FROM Customers  
WHERE City='Berlin' AND City='München';
```

OR example:

```
SELECT * FROM Customers  
WHERE City='Berlin' OR City='München';
```

NOT example:

```
SELECT * FROM Customers  
WHERE NOT Country='Germany';
```


Combining AND, OR and NOT

- You can also combine the AND, OR and NOT operators.
- The following SQL statement selects all fields from "Customers" where country is "Germany" AND city must be "Berlin" OR "München" (use parenthesis to form complex expressions):

```
SELECT * FROM Customers  
WHERE Country='Germany' AND (City='Berlin' OR City='München');
```

The following SQL statement selects all fields from "Customers" where country is NOT "Germany" and NOT "USA":

Example

```
SELECT * FROM Customers  
WHERE NOT Country='Germany' AND NOT Country='USA';
```

The SQL ORDER BY Keyword

- The ORDER BY keyword is used to sort the result-set in ascending or descending order.
- The ORDER BY keyword sorts the records in ascending order by default. To sort the records in descending order, use the DESC keyword.

ORDER BY Syntax

```
SELECT column1, column2, ...  
FROM table_name  
ORDER BY column1, column2, ... ASC|DESC;
```

ORDER BY Example

The following SQL statement selects all customers from the "Customers" table, sorted by the "Country" column:

Example

```
SELECT * FROM Customers  
ORDER BY Country;
```

ORDER BY DESC Example

The following SQL statement selects all customers from the "Customers" table, sorted DESCENDING by the "Country" column:

Example

```
SELECT * FROM Customers  
ORDER BY Country DESC;
```

ORDER BY Several Columns Example

The following SQL statement selects all customers from the "Customers" table, sorted by the "Country" and the "CustomerName" column:

Example

```
SELECT * FROM Customers  
ORDER BY Country, CustomerName;
```

The SQL INSERT INTO Statement

- The INSERT INTO statement is used to insert new records in a table.

INSERT INTO Syntax

It is possible to write the INSERT INTO statement in two ways.

The first way specifies both the column names and the values to be inserted:

```
INSERT INTO table_name (column1, column2, column3, ...)  
VALUES (value1, value2, value3, ...);
```

If you are adding values for all the columns of the table, you do not need to specify the column names in the SQL query. However, make sure the order of the values is in the same order as the columns in the table. The INSERT INTO syntax would be as follows:

```
INSERT INTO table_name  
VALUES (value1, value2, value3, ...);
```

INSERT INTO Example

The following SQL statement inserts a new record in the "Customers" table:

Example

```
INSERT INTO Customers (CustomerName, ContactName, Address, City, PostalCode,  
Country)  
VALUES ('Cardinal', 'Tom B. Erichsen', 'Skagen 21', 'Stavanger', '4006', 'Norway');
```


Insert Data Only in Specified Columns

Insert Data Only in Specified Columns

It is also possible to only insert data in specific columns.

The following SQL statement will insert a new record, but only insert data in the "CustomerName", "City", and "Country" columns (CustomerID will be updated automatically):

Example

```
INSERT INTO Customers (CustomerName, City, Country)
VALUES ('Cardinal', 'Stavanger', 'Norway');
```

What is a NULL Value?

- A field with a NULL value is a field with no value.
- If a field in a table is optional, it is possible to insert a new record or update a record without adding a value to this field. Then, the field will be saved with a NULL value.
- **Note:** A NULL value is different from a zero value or a field that contains spaces. A field with a NULL value is one that has been left blank during record creation!

How to Test for NULL Values?

- It is not possible to test for NULL values with comparison operators, such as =, <, or <>.
- We will have to use the IS NULL and IS NOT NULL operators instead

IS NULL Syntax

```
SELECT column_names  
FROM table_name  
WHERE column_name IS NULL;
```

IS NOT NULL Syntax

```
SELECT column_names  
FROM table_name  
WHERE column_name IS NOT NULL;
```

The IS NULL Operator

The IS NULL operator is used to test for empty values (NULL values).

The following SQL lists all customers with a NULL value in the "Address" field:

Example

```
SELECT CustomerName, ContactName, Address  
FROM Customers  
WHERE Address IS NULL;
```

Tip: Always use IS NULL to look for NULL values.

The IS NOT NULL Operator

The IS NOT NULL operator is used to test for non-empty values (NOT NULL values).

The following SQL lists all customers with a value in the "Address" field:

Example

```
SELECT CustomerName, ContactName, Address  
FROM Customers  
WHERE Address IS NOT NULL;
```

The SQL UPDATE Statement

The UPDATE statement is used to modify the existing records in a table.

UPDATE Syntax

```
UPDATE table_name  
SET column1 = value1, column2 = value2, ...  
WHERE condition;
```

Note: Be careful when updating records in a table! Notice the WHERE clause in the UPDATE statement. The WHERE clause specifies which record(s) that should be updated. If you omit the WHERE clause, all records in the table will be updated!

UPDATE Table

The following SQL statement updates the first customer (CustomerID = 1) with a new contact person *and* a new city.

Example

```
UPDATE Customers  
SET ContactName = 'Alfred Schmidt', City= 'Frankfurt'  
WHERE CustomerID = 1;
```

UPDATE Multiple Records

It is the WHERE clause that determines how many records that will be updated.

The following SQL statement will update the contactname to "Juan" for all records where country is "Mexico":

Example

```
UPDATE Customers  
SET ContactName='Juan'  
WHERE Country='Mexico';
```

Be careful when updating records. If you omit the WHERE clause, ALL records will be updated!

The SQL DELETE Statement

The DELETE statement is used to delete existing records in a table.

DELETE Syntax

```
DELETE FROM table_name  
WHERE condition;
```

Note: Be careful when deleting records in a table! Notice the WHERE clause in the DELETE statement. The WHERE clause specifies which record(s) should be deleted. If you omit the WHERE clause, all records in the table will be deleted!

SQL DELETE Example

The following SQL statement deletes the customer "Alfreds Futterkiste" from the "Customers" table:

Example

```
DELETE FROM Customers  
WHERE CustomerName='Alfreds Futterkiste';
```

Delete All Records

It is possible to delete all rows in a table without deleting the table. This means that the table structure, attributes, and indexes will be intact:

```
DELETE FROM table_name;
```

The following SQL statement deletes all rows in the "Customers" table, without deleting the table:

Example

```
DELETE FROM Customers;
```