


The Invisible **Internet Project**

The Invisible Internet is a privacy by design, people-powered network. It is a truly free and anonymizing Internet alternative.

Get Started

What you can do on the Invisible Internet





And More >

Download

authType == BlindData.AU if (clientKeys == null || clien throw new IllegalArgumentEx Create

authLen = 1;

if (authType == BlindData.AUTH_NONE

} else if (authType == BlindData.AU

Network

Admin and

Translators and

Donate


New User

12P Software

Privacy by Design: Foundational Privacy Network Design and Architecture

This is a blurb about how you can get an introduction to I2P and how it works.

Another blurb about things you can do on I2P like email and torrent.



Get Involved Here are a few ways to support the I2P Network

Contribute to the network by become a


reseed operator and help the I2P project grow.

languages.

Help translate the documentation into other

development.

Take a moment to **donate** to support further



12P Developers Documentation for people that want to make their

people that want to make their own

own applications or work on the software router Application Developers - Documentation for

applications read the documentation. Software Router - blurb for technical/network developers who are more advanced. They

may want to **Developer Resources**. Roadmap follow ups

// layer 2 (inner) encryption I2PAppContext ctx = I2PAppContext.getGlobalContext(); byte[] salt = new byte[SALT_LEN];

Network and SR

Devs

ctx.random().nextBytes(salt); HKDF hkdf = new HKDF(ctx); byte[] key = new byte[32]; // use first 12 bytes only byte[] iv = new byte[32]; int authLen;

12P Network Documentation for people that want to

make their own applications or work on the software router Researchers

Transport Layer

Router Message Protocol

Network Database

End to End Encryption

Tunnels

and Network Protocol Stack and Transport // layer 2 (inner) encryption

Researchers

ctx.random().nextBytes(salt); HKDF hkdf = new HKDF(ctx); byte[] key = new byte[32]; // use first 12 bytes only byte[] iv = new byte[32]; int authLen;

I2PAppContext ctx = I2PAppContext.getGlobalContext();

byte[] salt = new byte[SALT_LEN];

Every Tuesday LS2 Meeting


Calendar

First Tuesdays I2P Dev Meeting Every Tuesday Usability &

Design Meeting

See the Calendar of Events

SEPTEMBER





Blog




Download I2P

1.5.0 Release August 23, 2021 See Previous Release Notes EXAMPLE SESSION DIALOGUE -- simple telnet 127.0.0.1 A = Application

Latest Release

C = BOB's Command response.





Contact Us

prev

Support Technology API Docs

Getting Started

next

Contribute Donate Partners

Get Involved

Twitter Gitlab Reddit Mastodon

Follow Us



© 2021 The Invisible Internet Project

Content available under a Creative Commons license.



Data Policy

Impressum


Legal



The Invisible Internet Project


The Invisible Internet is a privacy by design, people-powered network. It is a truly free and anonymizing Internet alternative.

Get Started




What you can do on the Invisible Internet





Torrent



Create


12P Software

Your connection to the I2P Network

Learn about the **Invisible Internet**

Join a global, distributed private network. Learn about how the I2P network works.

Get started with I2P



Get Involved Want to support the I2P network? Here are a few


ways that you can get involved

Become a reseed operator. Help translate the software and

documentation into other languages.

I2P is free and community supported.

Please donate to support its future.



Create your own I2P applications or contribute to ongoing I2P core development

12P Developers

Documentation for **Application Developers**

Getting Started Documentation for I2P **Router Development**

Development Roadmap

byte[] salt = new byte[SALT_LEN]; ctx.random().nextBytes(salt); HKDF hkdf = new HKDF(ctx); byte[] key = new byte[32]; // use first 12 bytes only byte[] iv = new byte[32]; int authLen;

I2PAppContext ctx = I2PAppContext.getGlobalContext();

// layer 2 (inner) encryption

I2P's privacy protecting protocols and network infrastructure

12P Network


Find out more about the network

architecture and design. See the index of


Technical Information. Resources for Academic Researchers include Support, Metrics and

Documentation.

Events








EXAMPLE SESSION DIALOGUE -- simple telnet 127.0.0.1

Download I2P



I2P

Support Technology API Docs


Getting Started

Contribute Donate Partners

Get Involved

Twitter Gitlab Reddit Mastodon

Follow Us



Donate



© 2021 The Invisible Internet Project

Content available under a Creative Commons license.

Legal

Impressum




The Invisible Internet Project

The Invisible Internet is a privacy by design, people-powered network. It is a truly free and anonymizing Internet alternative.


Get Started

What you can do on the Invisible Internet





Torrent



Create


12P Software

Your connection to the I2P Network

Learn about the **Invisible Internet**

Join a global, distributed private network. Learn about how the I2P network works.

Get started with I2P



Get Involved Want to support the I2P network? Here are a few

ways that you can get involved


Help translate the software and

Become a reseed operator.

documentation into other languages.

I2P is free and community supported.

Please **donate** to support its future.



Create your own I2P applications or contribute to ongoing I2P core development

12P Developers

Documentation for **Application Developers**

Getting Started Documentation for I2P **Router Development**

Development Roadmap

byte[] salt = new byte[SALT_LEN]; ctx.random().nextBytes(salt); HKDF hkdf = new HKDF(ctx); byte[] key = new byte[32]; // use first 12 bytes only byte[] iv = new byte[32]; int authLen; _authType = authType; // debug if (authType == BlindData.AUTH_NONE) { authLen = 1;} else if (authType == BlindData.AUTH_DH || authType == BlindData.AUTH_PSK) { if (clientKeys == null || clientKeys.isEmpty()) throw new IllegalArgumentException("No client keys provided");

I2PAppContext ctx = I2PAppContext.getGlobalContext();

// layer 2 (inner) encryption

I2P's privacy protecting protocols and network infrastructure

12P Network


Find out more about the network

architecture and design. See the index of


Technical Information. Resources for **Academic Researchers** include Support, Metrics and

Documentation.

Events








EXAMPLE SESSION DIALOGUE -- simple telnet 127.0.0.1

Download I2P



I2P

Support Technology API Docs


Contribute Donate Partners

Data Policy

Get Involved

Twitter Gitlab Reddit Mastodon

Follow Us



Donate




© 2021 The Invisible Internet Project

Content available under a Creative Commons license.

Getting Started


Legal


Impressum






Calendar of Events







Contact Us

© 2021 The Invisible Internet Project

I2P

About

Forums

Blog

Getting Started

Support

API

Docs

Technology

Get Involved

Contribute

Donate

Partners

Follow Us

Twitter

Gitlab

Reddit

Mastodon



Donate

Your support helps

fund creators and

contributors!



Content available under a Creative Commons license.

Data Policy

Legal


Impressum

© 2021 The Invisible Internet Project

Content available under a Creative Commons license.

I2P

Get Involved



Getting Started

Follow Us

Legal

Impressum

