



## AHT150 ASPHALT HOSE 150 PSI

A Strong Yet Flexible Hose, Specially Designed As Tank Truck Or Tank Wagon Hose For Loading And Unloading Hot Asphalt.

- Temperature Range** : -15°C (-5°F) to +185°C (+365°F)
- Tube** : Black, Smooth, Polyacrylic Compound
- Reinforcement** : Plies Of Steel Wire Cord Plus Helix Wire
- Cover** : Black, Smooth (Wrapped Finish) Special Synthetic Rubber, Compounded For An Excellent Resistance To Weather, Ozone, Abrasion, Tar And Oil
- Coils** : Size 3/4" to 5" Supply In 61mt (200ft) Continuous Length
- Branding** : White Transfer Tape With Negative Text  
'SUNFLEX AHT 150 ASPHALT HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
AHT150-0150	38.0	1-1/2	56	2-13/64	10	150	30	450	228	1.87	1.26
AHT150-0200	50.8	2	71	2-51/64	10	150	30	450	305	2.85	1.92
AHT150-0250	63.5	2-1/2	81	3-3/16	10	150	30	450	381	3.19	2.14
AHT150-0300	76.2	3	94	3-45/64	10	150	30	450	457	4.20	2.82
AHT150-0350	90.0	3-1/2	112	4-13/32	10	150	30	450	540	5.12	3.44
AHT150-0400	101.6	4	126	4-31/32	10	150	30	450	610	6.30	4.23
AHT150-0500	127.0	5	155	6-7/64	10	150	30	450	762	8.33	5.60
AHT150-0600	152.4	6	184	7-1/4	10	150	30	450	914	10.45	7.02