


Week 12: Assignment / Explore File System Organization

CS5600 Spring, April 2025

Shorena K. Anzhilov

Question 1 : MSDOS-like file system

```
(root)
├── home
│   └── file1    (blocks 3 → 5)
├── var
│   ├── file2    (block 10)
│   └── tmp      (empty)
├── usr
│   └── pjd
│       └── file3 (block 8)
```



Question 2:

Block 3

- **File:** `file1`
- **Reasoning:** `file1` starts at block 3 and has a total length of 2000 bytes.
- **FAT Info:** Block 3 points to block 5, so this is the first chunk of the file.
- **Bytes in this block:** `0 - 1023`

Block 5

- **File:** `file1`
- **Reasoning:** This is the second block of `file1`, following block 3.
- **FAT Info:** Block 5 is marked as EOF.
- **Remaining file size:** `2000 - 1024 = 976 bytes`
- **Bytes in this block:** `1024 - 1999`

Block 8

- **File:** `file3`
- **Reasoning:** Directory entry for `file3` in block 9 shows that it starts at block 8 with a total length of 800 bytes.
- **FAT Info:** Block 8 is EOF.
- **Bytes in this block:** `0 - 799`

Block 10

- **File:** `file2`
- **Reasoning:** From directory entry in block 4. File starts at block 10 and is 1000 bytes long.
- **FAT Info:** Block 10 is EOF.
- **Bytes in this block:** `0 - 999`

Block 12

- **File:** *none (orphaned or unused block)*
- **Reasoning:** No directory entry points to block 12. It contains the string "`fff.`", but there is no metadata associating it with any file.
- **Bytes in this block:** *Not applicable*

Assumptions:

- ☐ Each block holds exactly **1024 bytes** of data.
- ☐ File byte ranges are calculated based on the total file size shown in the directory entries.
- ☐ Block numbers and FAT info were used to follow file continuation.
- ☐ Block 12 is not linked to any directory entry, so it's considered **unused or orphaned**.