

Real Time System Department  
Fog Computing of Self Balancing Robot

By

(Shoriya Chauhan)

Under the supervision of  
MSc. Alexandre Venito  
Prof. Gerhard Fohler

---

(8th May 2020)

# 1 Motivation

Improvement for the next generation industry is the key idea to implement this project. The traditional robots have dedicated controller and resources to meet the real time constraints. The main idea here is to be able to do complex functionality on fog node meeting the real time constraints, which can not be done via dedicated controller and resources. Fog computing may provide local data processing along with real time communication mechanism.

# 2 Project Flow

Here we are implementing a self balancing robot running on esp32 and the main PID control loop to be implemented on the fog node while meeting the requirement of the robot to be balanced.

Flow of the project:

- To understand the communication protocol of the lego sensors
- Implement communication of lego sensors with Arduino
- Integrate the sensors together to build self balancing bot
- Change from Arduino to esp32 for the wireless communication
- Structure the robot
- Get exact value of the PID
- Shift the PID function on fog node.

# 3 Literature Survey

Consider broomstick on the index finger, when trying to balance it we will have to move the finger in direction of the falling broomstick. Similarly the robot would fall either forward or backward which can be controlled by moving the robot either backward or forward. To make a balancing robot we need to control the center of gravity of the robot just at the pivot point.

## 3.1 Requirement for balancing the robot

- Direction the robot is falling
- Robot tilts

These information can be deduced from the accelerometer and gyroscope in a complementary filter.

Sense tilt and drive wheels to make robot erect




Figure 1: Tilt Angle and Balance

## 4 Hardware required

- Lego Motors
- Lego Gyroscopic Sensor (replaced it with MPU6050)
- MPU6050
- Ultrasonic Sensor
- Arduino Mega 2560
- L298N H bridge
- ESP32

Table 1: Sensors		
Sensors	Output	Unit
Rotary Encoder	Angle	deg
Ultrasonic Sensor	Distance	cm
Gyro Sensor	Angular Velocity	deg/sec

### 4.1 Lego Motors

Lego smart motor has built in encoders that can be used to make the robot move around in a very precise manner. It has a resolution of 360 counts per revolution which means it counts 360 when the robot completes one wheel rotation.



Figure 2: LEGO MOTOR

**What are encoders used for?** Encoders convert mechanical motion into electronic signal. By reading the encoder signals, the Arduino can figure out in which direction is the wheel turning and how many degrees.

## 4.2 Gyroscopic Sensor

Gyro offset and Gyro drift have major impact on balancing the robot. Gyro offset is the output when the gyro sensor does not rotate. In our case the gyro offset is 17. Gyro drift is time variation of gyro offset.

## 4.3 MPU 6050

The MPU 6050 is a 6 DOF (degrees of freedom) or a six-axis IMU sensor, which means that it gives six values as output: three values from the accelerometer and three from the gyroscope. The MPU 6050 is a sensor based on MEMS (micro electro mechanical systems) technology.




Figure 3: MPU6050

#### 4.4 Ultrasonic Sensor

Ultrasonic sensor here is used to avoid obstacle. The robot would rotate itself when it senses an obstacle within 20 cm. It is done by rotating one wheel faster than the other.



Figure 4: Ultrasonic Sensor

#### 4.5 L298N

The L298 is an integrated monolithic circuit in a 15-lead Multiwatt and PowerSO20 packages. It is a high voltage, high current dual full bridge driver designed to accept standard TTL logic levels and drive inductive loads such as relays, solenoids, DC and stepping motors.




Figure 5: L298N H-Bridge

## 5 Control System

To keep the robot balanced, the motors must counteract the robot falling. This action requires feedback and correcting elements. The feedback element is the MPU6050 gyroscope + accelerometer, which gives both acceleration and rotation in all three axes. The Arduino uses this to know the current orientation of the robot. The correcting element is the motor and wheel combination.

### 5.1 Angle Measurement using MPU6050

Gyroscopic sensor was replaced by MPU 6050 as it has both gyro meter and the accelero-meter therefore, it is easily to calculated the angle of inclination accurately using the complimentary filter.

The accelerometer can measure the force of the gravity, and with that information we can obtain the angle of the robot, the problem of the accelerometer is that it can also measure the rest of the forces the vehicle is someted, so it has lot of error and noise. The gyroscope measure the angular velocity, so if we integrate this measure we can obtain the angle the robot is moved, the problem of this measure is that is not perfect and the integration has a deviation, that means that in short time the measure is so good, but for long time terms the angle will deviate much form the real angle.

Those problems can be resolved be the combination of both sensors, that's called sensor fusion, and there are a lot of methods to combine it.

### 5.2 Complimentary Filter

Complimentary filter used to enhance the quality of accelerometer and gyroscope to give a define angle of inclination.

$$\text{currentAngle} = \underbrace{\alpha \cdot (\text{previousAngle} + \text{gyroAngle})}_{\text{HPF}} + \underbrace{(1-\alpha) \cdot (\text{accAngle})}_{\text{LPF}}$$

Figure 6: Complimentary Filter

The measurement from accelerometer gets affected by sudden horizontal movements and the measurement from gyroscope gradually drifts away from actual value. In other words, the accelerometer reading gets affected by short duration signals and the gyroscope reading by long duration signals. These readings are, in a way, complementary to each other. Combine them both using a Complimentary Filter and we get a stable, accurate measurement of the angle. The complementary filter is essentially a high pass filter acting on the gyroscope and a low pass filter acting on the accelerometer to filter out the drift and noise from the measurement.

$$\text{currentAngle} = 0.9934 * (\text{previousAngle} + \text{gyroAngle}) + 0.0066 * (\text{accAngle})$$

0.9934 and 0.0066 are filter coefficients for a filter time constant of 0.75s. The low pass filter allows any signal longer than this duration to pass through it and the high pass filter allows any signal shorter than this duration to pass through. The response of the filter can be tweaked by picking the correct time constant. Lowering the time constant will allow more horizontal acceleration to pass through.

### 5.3 PID Controller

PID stands for Proportional, Integral and Derivative. In this algorithm, the error signal received is the input. And the following equation is applied onto the error signal




Figure 7: PID Controller

The proportional term (gain) makes a change to the output that is proportional to the current error value. Larger values typically mean faster response since the larger the error, the larger the Proportional term correction signal. However, an excessively large proportional gain will lead to instability and oscillation. The Integral term is proportional to the amount of time the error is present. The integral term accelerates the movement of the process towards the set value and eliminates any residual steady-state error that occurs with a proportional only controller. The contribution from the integral term is dependent both on the magnitude of the error and on the duration of the error. With the derivative term, the controller output is proportional to the rate of change of the measurement or error. The derivative term slows the rate of change of the controller output, most notably near the controller set value. It therefore reduces the magnitude of the overshoot produced by the integral component and improves stability. Larger  $K_d$  values decrease overshoot, but slows down transient response and may lead to instability from signal noise amplification from differentiation of the error.

### TUNING a PID controller

Tuning: A good Control System will have low rise time, settling time, peak overshoot and steady state error. Therefore, the  $K_p$ ,  $K_d$ ,  $K_i$  need to be finely tuned to adjust the contribution of the above factors in order to acquire a good Control System.

- Set  $K_p=K_i=K_d= 0$ .
- Adjust  $K_p$  until the system remains in balance, but rapidly oscillates around equilibrium.
- Adjust  $K_d$  until the system reaches steady state. • If there is a steady state error, tune  $K_i$ . However, be warned that if the system is not actually reaching equilibrium, the integral term can dominate the controller and otherwise have negative effects on your controller.

## 6 Integrating ESP32

ESP32 is highly integrated solution for IoT Applications with bluetooth, WiFi. Esp32 uses I2C communication to communicate with mpu6050.

Pin Connections for self balancing robot

- MPU connection:  
SDA 21 – Pin3  
SCL 22 – Pin4
- Motor Connection




Figure 8: Motor Connector

VCC – Battery 9V  
GND – GND Battery



5V – 5V ESP32

ENA – 12

ENB – 14

IN1 – 26

IN2 – 27

IN3 – 18

IN4 – 19

OUT1 – Motor Connector AN IN

OUT2 – Motor Connector GND

OUT3 – Motor Connector AN IN

OUT4 – Motor Connector GND

## 7 Structure Modelling

The struture is so built that it tries to divides it weight equally and the center of mass is maintained. The base layer hols the L298N motor control and the esp32 and the top is where the mpu6050 is standing verticially. And integrating two batteries one for esp32 and other for L298N motor controller.




Figure 9: Structure

The struture is able to balance it self with the defined values of PID when the PId is implemented on the controller.

## 8 Fog Node

Here we using Python socket as our server node (fog node) to implement PID module. The esp32 functions to supply the current angle and the server replies back with the change in motor to be stable. With fog computing technology, all the processing happens on devices physically closer to where the data is collected, instead of sending data to the cloud.

### 8.1 Exeution time

The first the foremost step was to find the maximum delay that the robot can withstand to still be balanced. This is done by using the `millis()` or `micros()` function in Arduino to find the approximate execution time of the program in loop. We find that it takes around 1ms for the code to run and the robot to still be balanced. To this we added a delay funtion to find the minimum number of gyroscope value required in a time frame for it to be balanced. A delay of 20ms was fair enough for the bot to still be balanced with Kp value to be 280.

---

```
void loop() {  
    startTime =millis();  
    //Code for Angle Calculations  
    //Code for PID Funtion  
    delay(20);  
    Serial.println(millis()-startTime);  
}
```

---

And after shifting the PID code to the python server the total execution time on ESP32 was re-calculated. It takes around 2050 ms to get the motor speed and the turning direction.



Figure 10: Loop Execution

We have to reduce the the communication time from the esp32 to the fog node and back. Here we introduce OPC-UA (Open Platform Communication United Architecture) which is a data exchange standard for next generation industrial communication

## 9 Open Platform Communication Unified Architecture- OPC-UA

OPC-UA is a mechanism for transferring information between server and client which is secure, open and reliable. Here, we will implement the OPC-UA fog server for calculating the PID function and the esp32 will act like an OPC-UA client.

### 9.1 What is OPC-UA?

OPC is the interoperability standard for the secure and reliable exchange of data in the industrial automation space and in other industries. It is platform independent and ensures the seamless flow of information among devices from multiple vendors. The OPC Foundation is responsible for the development and maintenance of this standard.

Functionality of OPC-UA:

- Discovery: find the availability of OPC Servers on local PCs and/or networks
- Address space: all data is represented hierarchically (e.g. files and folders) allowing for simple and complex structures to be discovered and utilized by OPC Clients
- On-demand: read and write data/information based on access-permissions
- Subscriptions: monitor data/information and report-by-exception when values change based on a client's criteria
- Events: notify important information based on client's criteria
- Methods: clients can execute programs, etc. based on methods defined on the server

### 9.2 Information Modelling and Access

The OPC UA information modeling framework turns data into information. With complete object-oriented capabilities, even the most complex multi-level structures can be modeled and extended.

This framework is THE fundamental element of OPC Unified Architecture. It defines the rules and base building blocks necessary to expose an information model with OPC UA. While OPC UA already defines several core models that can be applied in many industries, other organizations build their models upon them, exposing their more specific information with OPC UA.

OPC UA also defines the necessary access mechanisms to information models.

Look-up mechanism (browsing) to locate instances and their semantic Read and write operations for current data and historical data Method execution Notification for data and events For Client-Server communication the full range of information model access is available via services and in doing so follows the design paradigm of service-oriented architecture (SOA), with which a service provider receives requests, processes them and sends the results back with the response.

Publish-Subscribe (PubSub), provides an alternative mechanism for data and event notification. While in Client-Server communication each notification is for a single client with guaranteed delivery, PubSub has been optimized for many-to-many configurations.

With PubSub, OPC UA applications do not directly exchange requests and responses. Instead, Publishers send messages to a Message Oriented Middleware, without knowledge of what, if any, Subscribers there may be. Similarly, Subscribers express interest in specific types of data, and process messages that contain this data, without a need to know where it originated from.

### **9.3 Software Required**

- Eclipse with PyDev installed
- OPC-UA installed on machine

### **9.4 Client-Server communication**

OPC UA with client / server communication is widespread in automation. In this proven "one-to-one" communication mechanism, each OPC UA client receives access to the data of the OPC UA server via point-to-point communication: The OPC UA client sends a request to the OPC UA Server and receives an answer from it. This form of communication enables reliable, secure and encrypted data exchange with reduced bandwidth and without data loss, even if the environment and network quality are not optimal and have interference. The client / server communication is always based on TCP / IP.

#### **9.4.1 Steps involved in configuration of OPC UA Client Server Communication**

- Server Initial Configuration
- Local Discovery Server LDS - Registration
- Client Configuration
- Local Discovery Server LDS - Discovery
- Connection configuration

Example Server code:

---

```

from opcua import Server
import time

server = Server()
url = "ipurl:portno"
server.set_endpoint(url)

name="OPCUA_SIMULATION_SERVER" //Address space defination
addspace=server.register_namespace(name)

node = server.get_objects_node() //Get the root node from the
address space

Param= node.add_objects(addspace, "Parameters")//need to define a
node where we need to store the parameter

angle = Param.add_variable(addspace, "angle",0)

//make the variable writable
angle.set_writable()

server.start()
print("Server started")

while True:
    angle=50;

    angle.set_value(angle)
    time.sleep(2)

```

---

UI Client application UAEXPERT 1.4.4 can be used to connect to the server for analyzing data but if some calculation have to be made to the dataset the client program has to be written.

The application can be used to get the node ids of the data variables.

Example Client code:

---

```

from opcua import Client
import time

url = "ipurl:portno"

client = Client(url)
client.connect()
print("Client connected")

while True:
    angle = client.get_node(nodeid,numericvalue)

```

---

```
Total = angle.get_value()
print(Total)

time.sleep(2)
```

---

## 9.5 Publish-Subscribe (PubSub) communication

With OPC UA with a PubSub model - PubSub stands for publish / subscribe - a "one-to-many" or "many-to-one" communication mechanism is used: a publisher makes data available from any number Subscribers in the network can be received. In combination with Time-Sensitive Networking (TSN), OPC UA PubSub enables real-time communication at the control level and meets the requirements of time-critical applications. OPC UA PubSub also supports peer to peer communications between multiple controllers, as well as, between controllers and human machine interfaces (HMI). It also guarantees real-time communications and asynchronous workflows between OPC UA servers and the cloud. In terms of security, PubSub specifications integrate SHA-256 algorithms to guarantee privacy and security when data is exchanged locally or through the cloud.

Lastly, OPC UA PubSub accommodates time-sensitive networking (TSN) technologies to drive time-critical applications in industries. According to EXOR International, the integration of OPC UA PubSub while accommodating TSN, speed up cycle times which occurred under two milliseconds and jitter of 100 nanoseconds. This ensures equipment can handle time-critical applications without encountering bottlenecks.

### 9.5.1 Steps involved in configuration of OPC UA PubSub Communication

- Subscriber Initial Configuration
- Subscriber registration to topic on broker(middleware)
- Publisher Initial Configuration
- Publisher registration to topic on broker
- Connection configuration
- PubSub communicate via broker

## 9.6 Good Reasons for OPC UA

### 9.6.1 Features

- Manufacturer-independent and platform-neutral
- Integrated security concept (encryption, signing and authentication)

- Consistent and scalable
- Information model and semantic services
- Unrestricted parallel operation with PROFINET
- Real-time capability of OPC UA PubSub in combination with Time-Sensitive Networking (TSN)

#### **9.6.2 Use**

- Standardized interface and wide availability
- Secure communication without additional hardware directly in the protocol
- Simple and clear interpretation of the data
- Simple networking on an Ethernet basis, use of the existing Industrial Ethernet infrastructure
- Internationally standardized interfaces for easy machine integration (companion specifications)
- High performance through fast communication
- When using TSN hardware and OPC UA PubSub, OPC UA data can be transmitted deterministically regardless of the load in the network

## 10 Problems faced

Problem : Lego Ultrasonic sensor does use simple I2C communication

Solution : Used Separate library for re-start frame I2C communication with arduino

Problem : Either the MPU6050 worked or the Motor- Due to separate ground

Solution : It is necessary when there are groups of circuit need to interface with each other and ground is the reference.

Problem : Shifting code from arduino to ESP32

Solution : ESP32 is not compatible with the libraries for MPU6050 and I2C used in arduino. Hence the code had to be modified for specific integration of gyroscope and accelerometer.

Problem : Getting exact value of the  $K_p$ ,  $K_i$  and  $K_d$  Solution : Have to change the Target angle as well as the  $K_p$   $K_i$   $K_d$  value on trial and error to get the exact value for the balance



## References

- [1] <https://www.instructables.com/id/Arduino-Self-Balancing-Robot-1/self-Balancing-Robot>
- [2] <https://www.instructables.com/id/Self-Balancing-Robot-1/>
- [3] <https://osoyoo.com/2018/08/08/self-balancing-robot-pid-control/>
- [4] <https://www.cs.cmu.edu/> 16311
- [5] <https://howtomechatronics.com/tutorials/arduino/arduino-dc-motor-control-tutorial-1298n-pwm-h-bridge/>
- [6] <http://opcfoundation.github.io/UA-LDS/>
- [7] <https://opcfoundation.org/about/what-is-opc/>
- [8] <https://new.siemens.com/global/de/produkte/automatisierung/industrielle-kommunikation/opc-ua.html>
- [9] <https://www.youtube.com/watch?v=NLNhHoo6X94>  
<https://www.youtube.com/watch?v=1NlbUAlOdcA>  
<https://www.youtube.com/watch?v=12dnhcEmrU0>
- [10] <https://www.exorint.com/en/blog/the-introduction-of-opc-ua-pubsub-publish-subscribe-and-its-importance-to-manufacturers>