

SHOTLIN

DIGITAL PRODUCT STUDIO



LNDRY Phase 1 MVP - Laundry Service API Contract and Endpoint Catalogue

Service booking, vendor operations, rider handovers, admin operations and platform services

Document code	LNDRY-API-001
Prepared for	LNDRY Phase 1 MVP
Baseline date	18 June 2026
Source baseline	Approved 34-page workflow and Bakaloo repositories

CONFIDENTIAL - IMPLEMENTATION ANNEXURE

This document is a target implementation contract. It does not state that every listed endpoint already exists in the Bakaloo codebase.

Document purpose

This document is the target REST and real-time API contract for implementing the LNDRY Phase 1 laundry-service marketplace on the reusable Bakaloo technical foundation. It is intended for backend, Flutter, dashboard, QA and project-management use. Endpoint names may be refined during implementation, but the capability, access control and business outcome must remain equivalent.

Important implementation status

The Bakaloo backend already contains reusable authentication, orders, payments, addresses, delivery, reviews, notifications, shops, staff, finance, reporting, uploads and operational infrastructure. The LNDRY-specific endpoints below are the agreed target surface; some are adaptations of existing endpoints and others are new.

Service-domain declaration

LNDRY is exclusively a laundry-service booking and fulfilment platform. Garment types such as shirts, trousers, sarees, blankets and shoes are customer-owned articles submitted to a vendor for cleaning or care. They are used only to calculate the service charge by piece, pair or kilogram. The MVP workflow is service selection, garment declaration, pickup scheduling, payment, collection, laundry processing and return delivery.

Service-domain vocabulary

Term	Meaning in LNDRY
Laundry service	A vendor-offered operation such as Wash & Fold, Wash & Iron, Dry Cleaning, Ironing or Shoe Care.
Garment type	A customer-owned article or service-measurement category, such as Shirt, Saree, Blanket, Shoes or Regular Clothes by kilogram.
Service rate	The vendor charge for processing a garment type, expressed per piece, per pair or per kilogram.
Service quotation	A server-calculated estimated service charge based on selected service, garment quantities or estimated weight.
Laundry service order	A booked service job covering pickup, vendor processing and return delivery of the customer's garments.
Pickup and delivery	Collection and return handover of the customer's own garments.

1. API-wide conventions

Convention	Required rule
Base URL	/api/v1 for application APIs; /api/webhook for verified third-party callbacks.
Authentication	Bearer JWT access token plus rotating refresh token. Dashboard uses HttpOnly secure cookies or equivalent secure token storage.
Role scopes	CUSTOMER, VENDOR_APPLICANT, VENDOR_OWNER, VENDOR_STAFF, RIDER, ADMIN, FINANCE_ADMIN, SUPER_ADMIN.
Identifiers	UUIDs for users, vendors, services, orders, assignments, payments and documents.
Date/time	ISO 8601 UTC in API. UI renders India Standard Time unless platform configuration changes.
Money	Integer paise in API and database. Never use floating-point currency calculations.
Pagination	page, limit, total, total_pages. Default 20; hard maximum 100 unless export endpoint.
Idempotency	Required on payment, order acceptance, refunds and critical state-changing retries.
Errors	Stable code, message, field_errors, request_id and safe metadata. No stack traces in production.
Audit	All vendor approval, price adjustment, assignment, OTP verification, admin override, refund and 2FA actions are auditable.
Caching	Public categories may be cached. Authenticated, order, capacity and payment responses use no-store.
Versioning	Breaking changes require /api/v2 or compatible deprecation period.

2. Standard response and error envelope

```

Success
{
  "success": true,
  "data": { ... },
  "meta": { "request_id": "...", "page": 1, "total": 42 }
}

```

```

Error
{

```

```

"success": false,
"error": {
  "code": "SLOT_FULL",
  "message": "The selected pickup slot is no longer available.",
  "field_errors": {},
  "request_id": "..."
}
}

```

3. Order state and transition rules

PAYMENT_PENDING -> WAITING_VENDOR_CONFIRMATION -> VENDOR_ACCEPTED -> PICKUP_ASSIGNED -> GOING_FOR_PICKUP -> PICKUP_OTP_VERIFIED -> PICKED_UP -> RECEIVED_AT_VENDOR -> PROCESSING -> PACKED -> DELIVERY_ASSIGNED -> OUT_FOR_DELIVERY -> DELIVERY_OTP_VERIFIED -> DELIVERED

- Vendor processing detail may be RECEIVED, WASHING, DRYING, IRONING and PACKED; the customer sees grouped statuses such as At Partner and Processing.
- Alternative terminal states include PAYMENT_FAILED, VENDOR_REJECTED, AUTO_REJECTED, CUSTOMER_CANCELLED, ADMIN_CANCELLED and REFUNDED.
- No client application may directly write an arbitrary status string. The backend validates every transition and actor permission.

4. Complete endpoint catalogue

A. Platform, session and authentication APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/	Public	Monitoring	Root service status.	Returns service, timestamp, uptime and health URL.
GET	/health	Public	Monitoring	Liveness probe for process health.	Returns OK and uptime.
GET	/health/ready	Public/internal	Deployment	Checks PostgreSQL and Redis readiness.	Returns dependency states; 503 if unavailable.
POST	/api/v1/auth/send-otp	Public	Customer/Vendor/Rider login	Sends mobile login OTP with role intent.	Input: phone, account_type. Output: challenge_id, expires_in.
POST	/api/v1/auth/verify-otp	Public	Customer/Vendor/Rider login	Verifies login OTP and issues JWT/refresh token.	Input: phone, challenge_id, otp, device. Output: user, roles, tokens.
POST	/api/v1/auth/refresh-token	Refresh token	All apps	Rotates access token.	Input: refresh_token/device_id. Output: new access token.
POST	/api/v1/auth/logout	Authenticated	All apps	Revokes current refresh token and device session.	Input: device_id or refresh token. Output: success.
GET	/api/v1/auth/session	Authenticated	All apps	Restores app session and resolved role.	Returns profile summary, permissions and onboarding state.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/auth/my-roles	Authenticated	Vendor/Rider app	Lists available roles for a phone linked to multiple roles.	Returns CUSTOMER, VENDOR_OWNER, VENDOR_STAFF or RIDER assignments.
POST	/api/v1/auth/select-role	Authenticated	Vendor/Rider app	Issues role-scoped token after user chooses workspace.	Input: role, vendor_id. Output: scoped JWT.
POST	/api/v1/devices	Authenticated	All apps	Registers FCM device token.	Input: device_id, platform, fcm_token, app_version.
DELETE	/api/v1/devices/:deviceid	Authenticated	All apps	Removes stale notification device token.	Output: removed=true.

B. Customer profile and address APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/customer/me	Customer	Profile screen	Loads customer profile.	Returns name, phone, email, photo and account status.
PATCH	/api/v1/customer/me	Customer	Edit profile	Updates permitted customer details.	Input: name, email, photo_url.
DELETE	/api/v1/customer/account	Customer + re-auth	Account settings	Requests account deletion/anonymisation.	Input: reason, confirmation OTP if configured.
GET	/api/v1/addresses	Customer	Address selector	Lists saved addresses.	Returns address text, label, lat/Ing, default flag and instructions.
POST	/api/v1/addresses	Customer	Add address	Creates exact pickup/delivery address.	Input: house, road, landmark, city, postal_code, lat, Ing, label, instructions.
GET	/api/v1/addresses/:id	Customer	Address details	Loads one saved address.	Returns full address and coordinates.
PUT	/api/v1/addresses/:id	Customer	Edit address	Updates address fields and exact pin.	Input: editable address fields.
DELETE	/api/v1/addresses/:id	Customer	Address settings	Soft-deletes a saved address.	Output: success.
PUT	/api/v1/addresses/:id/default	Customer	Address selector	Marks one address as default.	Output: selected default address.
POST	/api/v1/addresses/validate-location	Customer	Address confirmation	Checks whether any approved vendor serves the coordinate.	Input: lat, Ing. Output: serviceable, eligible_vendor_count.
GET	/api/v1/maps/place-autocomplete	Authenticated	Address search	Server proxy for Google Places predictions.	Input: query, session_token, location bias. Output: place predictions.
GET	/api/v1/maps/place-details/:placeid	Authenticated	Exact pin screen	Resolves selected place to address	Returns formatted address, lat, Ing,

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
				and coordinates.	postal code.

C. Customer discovery, search and vendor comparison APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/laundry/categories	Public/Customer	Home and category screen	Lists active laundry categories.	Supports locale, image, display order and availability.
GET	/api/v1/laundry/categories/:id	Public/Customer	Category details	Loads category metadata and garment-type filters.	Returns category and supported common garment types.
GET	/api/v1/discovery/home	Customer	Home screen	Returns address-aware home content in one response.	Categories, nearby vendors, active order and previous orders.
GET	/api/v1/discovery/vendors	Customer	Vendor results	Returns eligible vendors for location/category/slot.	Query: lat,lng,category_id,date,slot,sort,price, garment_type_id, page.
GET	/api/v1/discovery/vendors/:vendorId	Customer	Vendor profile	Loads public vendor profile.	Returns rating, distance, hours, services, policies and images.
GET	/api/v1/discovery/vendors/:vendorId/services	Customer	Vendor service list	Lists published services and starting prices.	Query: category_id, garment_type_id.
GET	/api/v1/discovery/services/:serviceId	Customer	Service detail	Loads inclusions, exclusions, garment-rate lines and completion time.	Returns garment rates, rate units, min/max and slot summary.
GET	/api/v1/search	Customer	Global search	Searches service, category, garment type and vendor name.	Query: q, lat,lng. Returns grouped results.
GET	/api/v1/search/suggestions	Customer	Search suggestions	Returns fast autocomplete suggestions.	Query: q. Output: typed suggestions.
GET	/api/v1/discovery/filters	Customer	Filter sheet	Returns supported sorts and garment-type filters for current result.	Returns nearest, price, rating, value, available-now.
POST	/api/v1/discovery/value-score	Internal/Customer	Value-for-money sort	Calculates stable ranking using price, rating, distance and completion rate.	Input: result context. Output: ranked vendor IDs and score explanation.

D. Customer service quotation, pickup-slot reservation and payment APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
POST	/api/v1/quotes	Customer	Garment selection	Creates a server-side price quotation.	Input: vendor_id, service_id, garment_lines with quantity or

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
					estimated_weight_kg. Output: quote_id, estimate, expiry.
PATCH	/api/v1/quotes/:quoteId	Customer	Garment selection	Updates quotation after quantity or weight changes.	Returns recalculated estimate.
GET	/api/v1/vendors/:vendorId/pickup-slots	Customer	Pickup slot screen	Returns only slots with remaining capacity.	Query: date, service_id, quote_id.
POST	/api/v1/slot-holds	Customer	Booking confirmation	Temporarily holds selected slot to prevent oversell.	Input: vendor_id, date, slot_id, quote_id. Output: hold_id, expires_at.
DELETE	/api/v1/slot-holds/:holdId	Customer	Booking cancellation	Releases temporary slot hold.	Output: released=true.
POST	/api/v1/orders/prepare	Customer	Booking review	Validates quote, address, slot and vendor eligibility before payment.	Output: order_draft_id, payable amount, snapshot.
POST	/api/v1/payments/create-order	Customer	Razorpay payment	Creates Razorpay order for a prepared LNDRY order.	Input: order_draft_id. Output: razorpay_order_id, amount, currency, key.
POST	/api/v1/payments/verify	Customer	Payment result	Verifies Razorpay signature and confirms payment.	Input: payment_id, order_id, signature, order_draft_id.
GET	/api/v1/payments/:paymentId	Customer	Payment status	Loads payment/refund status.	Returns captured, failed, refunded or pending.
GET	/api/v1/payments/history	Customer	Payment history	Lists customer payment records.	Paginated payment list.
POST	/api/v1/orders	Customer	Post-payment order submission	Creates marketplace order from paid draft and sends it to selected vendor.	Input: order_draft_id/payment_id. Output: order and WAITING_VENDOR_CONFIRMATION.

E. Customer order lifecycle, OTP, history and review APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/orders	Customer	Order history	Lists current and past orders.	Query: status,page,date range.
GET	/api/v1/orders/active	Customer	Home/active order	Loads latest active order and timeline.	Returns customer status, detailed activity and OTP visibility flags.
GET	/api/v1/orders/:orderId	Customer	Order detail	Loads full order snapshot.	Garment lines, quantities/weight, service rates, vendor, slot, address, payment and assignments.
GET	/api/v1/orders/:orderId/timeline	Customer	Tracking screen	Returns immutable status events.	Customer label, internal detail, timestamp and actor.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/orders/:orderId/pickup-otp	Customer	Pickup handover	Shows active pickup OTP only at permitted stage.	Returns masked purpose, OTP and expiry.
GET	/api/v1/orders/:orderId/delivery-otp	Customer	Delivery handover	Shows active delivery OTP only at permitted stage.	Returns OTP and expiry.
POST	/api/v1/orders/:orderId/cancel	Customer	Order detail	Cancels within allowed status and triggers refund rules.	Input: reason_code, comment.
POST	/api/v1/orders/:orderId/select-another-vendor	Customer	Rejected order recovery	Creates a new quote/order attempt without auto-assigning vendor.	Input: new_vendor_id and slot.
GET	/api/v1/orders/:orderId/invoice	Customer	Completed order	Downloads final invoice/receipt.	Returns PDF or signed URL.
GET	/api/v1/reviews/vendors/:vendorId	Public/Customer	Vendor profile	Lists verified vendor reviews.	Paginated ratings and comments.
GET	/api/v1/reviews/eligibility/:orderId	Customer	Delivered order	Checks whether delivered order can be rated.	Returns eligible and reason.
POST	/api/v1/reviews	Customer	Rating screen	Creates rating for delivered order.	Input: order_id, vendor_rating, optional rider_rating, comment.
PATCH	/api/v1/reviews/:reviewId	Customer	My reviews	Updates review within permitted period.	Input: rating/comment.
DELETE	/api/v1/reviews/:reviewId	Customer	My reviews	Removes own review subject to policy.	Output: deleted=true.
GET	/api/v1/notifications	Customer	Notification centre	Lists user notifications.	Query: unread,page,type.
PATCH	/api/v1/notifications/:id/read	Customer	Notification centre	Marks one notification read.	Output: notification.
PATCH	/api/v1/notifications/read-all	Customer	Notification centre	Marks all notifications read.	Output: updated_count.
GET	/api/v1/notification-preferences	Customer	Settings	Loads communication preferences.	Push, SMS and email categories.
PUT	/api/v1/notification-preferences	Customer	Settings	Updates notification preferences.	Input: preference matrix.

F. Vendor onboarding, application and public profile APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
POST	/api/v1/vendor/applications	Vendor applicant	Vendor onboarding	Creates temporary vendor application.	Input: owner and business basics. Output: application_id, DRAFT.
GET	/api/v1/vendor/applications/me	Vendor applicant	Onboarding resume	Loads current application and missing steps.	Returns status, sections and correction notes.
PATCH	/api/v1/vendor/applications/:id/owner	Vendor applicant	Owner details step	Updates owner identity and contacts.	Input: owner name, alternate phone, email, identity metadata.
PATCH	/api/v1/vendor/applications/:id/	Vendor applicant	Business details step	Updates laundry name, description,	Input: business fields and

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
	business			hours and working days.	availability.
PATCH	/api/v1/vendor/applications/:id/location	Vendor applicant	Location step	Stores exact business pin and address.	Input: address, lat, lng, place_id.
PATCH	/api/v1/vendor/applications/:id/radius	Vendor applicant	Radius request step	Stores requested service radius.	Input: requested_radius_km.
POST	/api/v1/vendor/applications/:id/documents	Vendor applicant	Document step	Uploads and classifies owner/business documents.	Multipart: document_type, file. Output: secure document reference.
DELETE	/api/v1/vendor/applications/:id/documents:documentId	Vendor applicant	Document correction	Removes a draft/resubmittable document.	Output: removed=true.
POST	/api/v1/vendor/applications/:id/submit	Vendor applicant	Final review	Validates and submits application.	Output: WAITING_FOR_APPROVAL and submitted_at.
POST	/api/v1/vendor/applications/:id/resubmit	Vendor applicant	Correction workflow	Resubmits after admin-requested correction.	Input: correction acknowledgement.
GET	/api/v1/vendor/profile	Vendor owner/staff	Vendor home/profile	Loads approved vendor profile and operational flags.	Returns approved radius, activation, publication and completion status.
PATCH	/api/v1/vendor/profile	Vendor owner	Edit vendor profile	Updates public profile fields.	Input: public name, description, contact, logo, hours.
PATCH	/api/v1/vendor/profile/location	Vendor owner + admin reapproval	Business location	Requests location change.	Input: address, lat,lng; may set PENDING_REVIEW.
GET	/api/v1/vendor/profile/public-preview	Vendor owner	Preview	Shows customer-facing representation before publish.	Returns public profile preview.
POST	/api/v1/vendor/profile/publish	Vendor owner	Publish control	Publishes profile only when approved and at least one active service exists.	Output: published=true or validation errors.

G. Vendor service catalogue, pricing and capacity APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/vendor/categories	Vendor owner/staff	Service setup	Lists admin-created categories available to vendor.	Returns active categories.
GET	/api/v1/vendor/services	Vendor owner/staff	Services screen	Lists vendor services with publication state.	Query: status,category,page.
POST	/api/v1/vendor/services	Vendor owner/staff with permission	Create service	Creates draft laundry service.	Input: category_id,name,description,inclusions,exclusions,completion_time.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/vendor/services/:serviceId	Vendor owner/staff	Service editor	Loads service, garment types and rates and capacity link.	Returns complete editable service.
PATCH	/api/v1/vendor/services/:serviceId	Vendor owner/staff with permission	Service editor	Updates service details.	Input: editable service fields.
DELETE	/api/v1/vendor/services/:serviceId	Vendor owner	Services screen	Soft-deletes unused service or deactivates active one.	Output: state.
POST	/api/v1/vendor/services/:serviceId/garment-rates	Vendor owner/staff	Pricing setup	Adds a customer garment type and its applicable laundry service rate.	Input: garment_type_name, rate_unit PIECE/KG/PAIR, rate_paise, min, max.
PATCH	/api/v1/vendor/services/:serviceId/garment-rates/:garmentRateId	Vendor owner/staff	Pricing setup	Updates garment service rate and quantity/weight rules.	Input: price/unit/min/max/active.
DELETE	/api/v1/vendor/services/:serviceId/garment-rates/:garmentRateId	Vendor owner/staff	Pricing setup	Deactivates garment type for this service.	Output: inactive=true.
POST	/api/v1/vendor/services/:serviceId/garment-rates/bulk	Vendor owner/staff	Bulk pricing	Creates or updates multiple garment-rate lines efficiently.	Input: garment_rates[].
POST	/api/v1/vendor/services/:serviceId/publish	Vendor owner	Publish service	Publishes valid service.	Validates category, garment rates, capacity and profile.
POST	/api/v1/vendor/services/:serviceId/unpublish	Vendor owner	Publish service	Temporarily removes service from discovery.	Input: reason.
GET	/api/v1/vendor/capacity	Vendor owner/staff	Capacity screen	Loads daily limit and weekly availability.	Returns days, slots and booked counts.
PUT	/api/v1/vendor/capacity/daily-limit	Vendor owner	Capacity screen	Sets daily maximum order count.	Input: max_orders_per_day.
GET	/api/v1/vendor/pickup-slots	Vendor owner/staff	Slot screen	Lists recurring 60-minute slots.	Returns enabled, capacity and exceptions.
POST	/api/v1/vendor/pickup-slots	Vendor owner	Slot screen	Creates recurring slot.	Input: day_of_week,start,end,max_orders .
PATCH	/api/v1/vendor/pickup-slots/:slotId	Vendor owner	Slot screen	Updates or enables/disables slot.	Input: times, capacity, active.
DELETE	/api/v1/vendor/pickup-slots/:slotId	Vendor owner	Slot screen	Removes future slot when safe.	Output: deleted/deactivated.
POST	/api/v1/vendor/capacity/exceptions	Vendor owner	Holiday/full-day controls	Adds date-specific closure or capacity override.	Input: date, type, limit, reason.
DELETE	/api/v1/vendor/capacity/exceptions/:id	Vendor owner	Capacity exceptions	Removes exception.	Output: removed=true.

H. Vendor delivery-employee and order-operation APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/vendor/employees	Vendor owner	Employee management	Lists vendor employees and current availability.	Returns role, phone, status, assignments.
POST	/api/v1/vendor/employees	Vendor owner	Add employee	Creates rider/employee account invitation.	Input: name, phone, employee_ref, role.
GET	/api/v1/vendor/employees/:employeeId	Vendor owner	Employee details	Loads employee, documents and metrics.	Returns assignment summary.
PATCH	/api/v1/vendor/employees/:employeeId	Vendor owner	Employee details	Updates name/reference/permissions.	Input: editable fields.
PATCH	/api/v1/vendor/employees/:employeeId/status	Vendor owner	Employee management	Activates or deactivates employee.	Input: active, reason.
POST	/api/v1/vendor/employees/:employeeId/reset-session	Vendor owner	Security	Revokes employee sessions after device loss.	Output: revoked count.
GET	/api/v1/vendor/orders	Vendor owner/staff	Orders board	Lists vendor orders by operational status.	Query: status,date,slot,employee,page.
GET	/api/v1/vendor/orders/:orderId	Vendor owner/staff	Order details	Loads paid order, customer, garment lines, slot and assignment.	Returns permitted customer contact and address.
POST	/api/v1/vendor/orders/:orderId/accept	Vendor owner/staff with permission	Incoming order	Accepts order before deadline.	Input: optional employee_id. Output: accepted order and assignment.
POST	/api/v1/vendor/orders/:orderId/reject	Vendor owner/staff with permission	Incoming order	Rejects with reason and triggers refund/release.	Input: reason_code, comment.
POST	/api/v1/vendor/orders/:orderId/assign-pickup	Vendor owner/staff	Assignment	Assigns/reassigns pickup employee.	Input: employee_id.
POST	/api/v1/vendor/orders/:orderId/received	Vendor owner/staff	Received at partner	Confirms laundry reached vendor.	Input: received_at, notes.
PATCH	/api/v1/vendor/orders/:orderId/actuals	Vendor owner/staff	Verification	Stores actual garment count or measured weight and final amount.	Input: actual_garment_lines or actual_weight_kg, adjustment_reason.
POST	/api/v1/vendor/orders/:orderId/request-balance	Vendor owner/staff	Price adjustment	Creates additional payable amount where policy permits.	Input: final_amount, breakdown. Output: payment request.
POST	/api/v1/vendor/orders/:orderId/status	Vendor owner/staff	Processing board	Moves order only through allowed state transition.	Input: next_status, note. Output: event.
POST	/api/v1/vendor/orders/:orderId/pack	Vendor owner/staff	Processing board	Marks packed and ready for delivery.	Output: packed timestamp.
POST	/api/v1/vendor/orders/:orderId/	Vendor owner/staff	Assignment	Assigns/reassigns delivery	Input: employee_id.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
	assign-delivery			employee.	
GET	/api/v1/vendor/orders/:orderId/audit	Vendor owner/admin	Order audit	Returns status, assignment and price-change history.	Immutable events.
GET	/api/v1/vendor/performance	Vendor owner	Performance dashboard	Returns acceptance, completion, delivery time and rating metrics.	Query: date range.
GET	/api/v1/vendor/revenue/summary	Vendor owner	Revenue dashboard	Returns daily, weekly and monthly totals.	Query: date range.
GET	/api/v1/vendor/revenue/orders	Vendor owner	Revenue details	Lists per-order earnings and payment state.	Paginated records.

I. Rider/Delivery Partner APIs inside the Vendor Partner application

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/rider/profile	Rider	Rider profile	Loads employee identity, vendor and status.	Returns permitted profile fields.
PATCH	/api/v1/rider/profile	Rider	Rider profile	Updates permitted personal fields.	Input: name, photo, emergency contact.
PATCH	/api/v1/rider/availability	Rider	Rider home	Sets AVAILABLE or OFFLINE for assignment.	Input: availability.
GET	/api/v1/rider/assignments	Rider	Assignment list	Lists only rider-assigned pickup/delivery jobs.	Query: type,status,date.
GET	/api/v1/rider/assignments/:assignmentId	Rider assigned only	Assignment detail	Loads customer address, instructions, contact and time slot.	Returns map coordinates and Google Maps deep link.
POST	/api/v1/rider/assignments/:assignmentId/acknowledge	Rider	Assignment detail	Acknowledges assignment notification.	Output: acknowledged_at.
POST	/api/v1/rider/assignments/:assignmentId/going-to-pickup	Rider	Pickup action	Sets customer-facing Pickup Partner Coming.	Output: timeline event.
POST	/api/v1/rider/assignments/:assignmentId/verify-pickup-otp	Rider	Pickup OTP screen	Verifies purpose-bound pickup OTP.	Input: otp. Output: verified or retry state.
POST	/api/v1/rider/assignments/:assignmentId/pickup-complete	Rider	Pickup action	Completes pickup only after OTP verification.	Input: optional proof/notes.
POST	/api/v1/rider/assignments/:assignmentId/arrived-at-vendor	Rider	Vendor handover	Records laundry return to vendor.	Output: handover timestamp.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
POST	/api/v1/rider/assignments/:assignmentId/out-for-delivery	Rider	Delivery action	Sets Out for Delivery.	Output: timeline event.
POST	/api/v1/rider/assignments/:assignmentId/verify-delivery-otp	Rider	Delivery OTP screen	Verifies delivery OTP.	Input: otp. Output: verified or retry state.
POST	/api/v1/rider/assignments/:assignmentId/delivery-complete	Rider	Delivery action	Completes order after OTP.	Input: optional proof/notes.
POST	/api/v1/rider/assignments/:assignmentId/report-issue	Rider	Exception action	Reports customer unavailable, wrong address or other issue.	Input: issue_type, note, optional photo.
GET	/api/v1/rider/history	Rider	History	Lists completed pickup/delivery jobs.	Paginated records.
GET	/api/v1/rider/stats	Rider	Rider home	Shows assigned/completed/pending counts.	Date range summary.
GET	/api/v1/rider/navigation-link	Rider	Open in Google Maps	Builds external Google Maps navigation URL.	Query: assignment_id, target=customer vendor.

J. Admin dashboard authentication, two-factor OTP and team APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
POST	/api/v1/admin/auth/login	Public	Dashboard login	Validates email and password, then requires second factor.	Output: 2FA_REQUIRED, login_challenge_id.
POST	/api/v1/admin/auth/2fa/send	Login challenge	Dashboard login	Sends direct email/SMS OTP fallback where TOTP is not configured.	Input: challenge_id, channel.
POST	/api/v1/admin/auth/2fa/verify	Login challenge	Dashboard login	Verifies TOTP/direct OTP and issues admin session.	Input: challenge_id, otp, trust_device.
POST	/api/v1/admin/auth/2fa/setup	Admin + recent password	Security settings	Creates authenticator TOTP secret and QR.	Returns provisioning URI and masked secret.
POST	/api/v1/admin/auth/2fa/confirm	Admin	Security settings	Confirms authenticator code and generates recovery codes.	Input: otp.
POST	/api/v1/admin/auth/2fa/disable	Admin + step-up OTP	Security settings	Disables TOTP with explicit confirmation.	Input: password, otp.
POST	/api/v1/admin/auth/recovery-code	Login challenge	Dashboard login	Uses one-time recovery code.	Input: challenge_id, recovery_code.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/admin/auth/me	Admin	Dashboard shell	Loads admin identity, role, permissions and 2FA status.	Returns HQ/shop scope.
POST	/api/v1/admin/auth/change-password	Admin	Security settings	Changes password and rotates sessions.	Input: current_password,new_password.
POST	/api/v1/admin/auth/logout	Admin	Dashboard shell	Clears/revokes dashboard session.	Output: success.
GET	/api/v1/admin/team	Admin with permission	Team management	Lists dashboard users.	Returns roles, scope, 2FA and status.
POST	/api/v1/admin/team	Super admin	Team management	Creates admin/team member.	Input: name,email,role,scope,force_password_change.
PATCH	/api/v1/admin/team/:id	Super admin	Team management	Updates role, scope or state.	Input: role/permissions/status.
POST	/api/v1/admin/team/:id/reset-2fa	Super admin	Team security	Resets compromised 2FA after audit.	Input: reason.
GET	/api/v1/admin/roles	Admin	Role management	Lists roles and permission strings.	Returns permission matrix.
PUT	/api/v1/admin/roles/:id	Super admin	Role management	Updates custom role permissions.	Input: permissions[].

K. Admin operations: vendors, categories, customers and riders

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/admin/dashboard/summary	Admin	Dashboard home	Returns KPI cards and exception counts.	Vendors, orders, GMV, pending applications and stuck orders.
GET	/api/v1/admin/vendor-applications	Admin reviewer	Vendor applications	Lists applications by status.	Query: status,search,date,page.
GET	/api/v1/admin/vendor-applications/:id	Admin reviewer	Application detail	Loads owner, business, documents, map and radius request.	Includes secure signed document links.
POST	/api/v1/admin/vendor-applications/:id/approve	Admin reviewer	Application detail	Approves vendor and final service radius.	Input: approved_radius_km, notes.
POST	/api/v1/admin/vendor-applications/:id/reject	Admin reviewer	Application detail	Rejects with customer-readable reason.	Input: reason_code, message.
POST	/api/v1/admin/vendor-applications/:id/request-correction	Admin reviewer	Application detail	Requests section-level corrections.	Input: fields[], message.
GET	/api/v1/admin/vendors	Admin	Vendor management	Lists vendors with status, service/radius/capacity summary.	Query: active,city,search,page.
GET	/api/v1/admin/vendors/:vendorId	Admin	Vendor detail	Loads complete vendor operations profile.	Includes services, employees, metrics and documents.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
PATCH	/api/v1/admin/vendors/:vendorId/status	Admin	Vendor detail	Activates, suspends or deactivates vendor.	Input: status,reason.
PATCH	/api/v1/admin/vendors/:vendorId/radius	Admin	Vendor detail	Changes approved radius.	Input: approved_radius_km, reason.
GET	/api/v1/admin/vendors/:vendorId/services	Admin	Vendor detail	Reviews vendor service listings.	Returns active/draft services and prices.
GET	/api/v1/admin/vendors/:vendorId/capacity	Admin	Vendor detail	Reviews daily and slot capacity.	Returns upcoming utilisation.
PUT	/api/v1/admin/vendors/:vendorId/capacity-override	Admin	Vendor detail	Applies temporary capacity override.	Input: date/slot/limit/reason.
GET	/api/v1/admin/laundry-categories	Admin	Category management	Lists categories including inactive.	Paginated list.
POST	/api/v1/admin/laundry-categories	Admin	Category management	Creates category.	Input: name,description,image,display_order.
PATCH	/api/v1/admin/laundry-categories/:id	Admin	Category management	Updates category.	Input: editable fields.
PATCH	/api/v1/admin/laundry-categories/:id/status	Admin	Category management	Activates/deactivates category.	Input: active.
DELETE	/api/v1/admin/laundry-categories/:id	Admin	Category management	Soft-deletes unused category.	Output: state.
GET	/api/v1/admin/customers	Admin	Customer management	Lists customers and order summary.	Query: status,search,page.
GET	/api/v1/admin/customers/:customerId	Admin	Customer detail	Loads profile, addresses and orders.	Returns permitted PII under audit.
PATCH	/api/v1/admin/customers/:customerId/status	Admin	Customer detail	Suspends or reactivates customer.	Input: status, reason.
GET	/api/v1/admin/riders	Admin	Rider oversight	Lists vendor employees/riders.	Query: vendor,status,search,page.
GET	/api/v1/admin/riders/:riderId	Admin	Rider detail	Loads assignments, documents and metrics.	Returns vendor link and status.
PATCH	/api/v1/admin/riders/:riderId/status	Admin	Rider detail	Suspends/reactivates rider.	Input: status, reason.

L. Admin orders, payments, reports, exceptions and settings

Method	Endpoint	Access	Used by	Purpose	Key input / output
GET	/api/v1/admin/orders	Admin	Order management	Lists all orders with filters.	Query: status,vendor,rider,date,payment,e

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
					exception,page.
GET	/api/v1/admin/orders/:orderId	Admin	Order detail	Loads complete order, timeline, assignments, payments and OTP audit.	Sensitive values remain masked.
POST	/api/v1/admin/orders/:orderId/override-status	Authorised admin + 2FA step-up	Exception handling	Moves stuck order through controlled administrative transition.	Input: target_status, reason; creates audit event.
POST	/api/v1/admin/orders/:orderId/cancel	Authorised admin	Order detail	Cancels with reason and refund handling.	Input: reason, refund_action.
POST	/api/v1/admin/orders/:orderId/reassign	Authorised admin	Order detail	Reassigns vendor employee where operationally valid.	Input: assignment_type, employee_id.
GET	/api/v1/admin/exceptions	Admin	Exception queue	Lists payment, status, capacity, OTP and assignment exceptions.	Query: type,severity,status.
POST	/api/v1/admin/exceptions/:id/resolve	Admin	Exception queue	Resolves exception with action note.	Input: resolution_code, note.
GET	/api/v1/admin/payments	Finance admin	Payments	Lists payments and refunds.	Query: status,date,vendor,order,page.
GET	/api/v1/admin/payments/:id	Finance admin	Payment detail	Loads Razorpay references and ledger events.	Returns payment/refund audit.
POST	/api/v1/admin/payments/:id/refund	Finance admin + 2FA step-up	Payment detail	Initiates full/partial Razorpay refund.	Input: amount, reason, idempotency_key.
GET	/api/v1/admin/reports/orders	Admin	Reports	Order volume, status and trend report.	Query: from,to,group_by.
GET	/api/v1/admin/reports/gmv	Finance admin	Reports	GMV and refund report.	Query: from,to,vendor.
GET	/api/v1/admin/reports/vendors	Admin	Reports	Vendor acceptance, completion, rating and time report.	Query: from,to,sort.
GET	/api/v1/admin/reports/customers	Admin	Reports	Customer activity and repeat usage report.	Query: from,to.
GET	/api/v1/admin/reports/export	Admin	Reports	Exports authorised report to CSV/XLSX.	Query: report_type, filters.
GET	/api/v1/admin/settings	Super admin	Platform settings	Loads operational configuration.	Auto-reject minutes, OTP limits, rating threshold, defaults.
PUT	/api/v1/admin/settings	Super admin + 2FA step-up	Platform settings	Updates validated platform settings.	Input: changed settings and reason.
GET	/api/v1/admin/audit-logs	Admin auditor	Audit logs	Lists security and operational audit events.	Query: actor,action,entity,date,page.
GET	/api/v1/admin/notifications/templates	Admin	Notification templates	Lists SMS/email/push templates.	Returns variables and active versions.

SHOTLIN DIGITAL PRODUCT STUDIO

Method	Endpoint	Access	Used by	Purpose	Key input / output
PUT	/api/v1/admin/notifications/templates/:id	Admin	Notification templates	Updates template content with preview validation.	Input: title/body/channel/variables.
POST	/api/v1/admin/notifications/test	Admin	Notification templates	Sends test push/SMS/email.	Input: channel,target,template_id.

M. Watermark, secure document and upload APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
POST	/api/v1/uploads/image	Authenticated	Customer/Vendor/Admin	Uploads one allowed image to Cloudinary.	Multipart file, context. Returns URL/public_id/dimensions.
POST	/api/v1/uploads/document	Vendor/Admin	Vendor KYC	Uploads private document to restricted storage.	Multipart file,type. Returns document_id; not public URL.
GET	/api/v1/secure-documents/:documentId	Authorised signed access	Admin/vendor document screen	Streams short-lived protected document.	Audits viewer and denies cross-tenant access.
DELETE	/api/v1/uploads/:assetId	Owner/admin	Asset management	Deletes unused asset.	Input: reason.
GET	/api/v1/admin/watermark-settings	Admin	Watermark settings	Loads logo/text/position/opacity/modes.	Returns marketing and KYC watermark profiles.
PUT	/api/v1/admin/watermark-settings	Super admin	Watermark settings	Updates watermark configuration.	Input: logo, text template, opacity, position, apply_to.
POST	/api/v1/admin/watermark-settings/preview	Admin	Watermark settings	Creates non-persistent preview.	Input: sample asset/profile. Output: preview URL.
POST	/api/v1/admin/assets/:assetId/apply-watermark	Admin	Media library	Generates watermarked derivative.	Output: original_url and watermarked_url.
GET	/api/v1/admin/watermark-jobs	Admin	Watermark processing	Lists queued/completed watermark jobs.	Query: status,type,page.
POST	/api/v1/admin/watermark-jobs/:id/retry	Admin	Watermark processing	Retries failed background job.	Output: queued=true.

N. Webhooks, real-time events and operational APIs

Method	Endpoint	Access	Used by	Purpose	Key input / output
POST	/api/webhook/razorpay	Razorpay signature	System	Receives payment/refund events.	Raw body signature verification; idempotent processing.
POST	/api/webhook/cloudinary	Cloudinary signature	System	Receives asynchronous asset processing events where enabled.	Validates signature and updates asset state.
POST	/api/webhook/sms-delivery	SMS provider signature	System	Receives OTP/SMS delivery	Updates message delivery state.

Method	Endpoint	Access	Used by	Purpose	Key input / output
				receipts.	
GET	/api/v1/realtime/token	Authenticated	Apps/dashboard	Issues short-lived Socket.IO subscription token.	Returns allowed rooms and expiry.
WS	order.updated	Scoped subscription	Customer/Vendor/Rider/Admin	Pushes order status/timeline update.	Payload: order_id,status,event_version.
WS	assignment.updated	Vendor/Rider	Vendor app	Pushes new/reassigned pickup or delivery assignment.	Payload: assignment summary.
WS	notification.created	User-scoped	All apps	Pushes in-app notification.	Payload: notification summary.
POST	/api/v1/internal/jobs/auto-reject	Worker secret/internal only	BullMQ worker	Rejects expired vendor-confirmation orders.	Not exposed publicly; idempotent worker action.
POST	/api/v1/internal/jobs/expire-slot-holds	Worker secret/internal only	BullMQ worker	Releases expired booking capacity holds.	Internal only.

5. Key request examples

Create vendor search request

```
GET /api/v1/discovery/vendors?lat=22.5726&lng=88.3639&category_id=cat_dry_cleaning&date=2026-06-22&slot_id=slot_10_11&sort=nearest&page=1
```

Create quotation

```
POST /api/v1/quotes
Authorization: Bearer <customer-token>
{
  "vendor_id": "vendor_uuid",
  "service_id": "service_uuid",
  "garment_lines": [
    {"garment_type_id": "shirt_uuid", "quantity": 3},
    {"garment_type_id": "trouser_uuid", "quantity": 1}
  ]
}
```

Vendor accepts order

```
POST /api/v1/vendor/orders/{orderId}/accept
Authorization: Bearer <vendor-token>
Idempotency-Key: <uuid>
{ "pickup_employee_id": "employee_uuid" }
```

Verify pickup OTP

```
POST /api/v1/rider/assignments/{assignmentId}/verify-pickup-otp
Authorization: Bearer <rider-token>
{ "otp": "482193" }
```

Admin approval

```
POST /api/v1/admin/vendor-applications/{applicationId}/approve
Authorization: Bearer <admin-token>
X-Step-Up-Token: <recent-2fa-token>
{ "approved_radius_km": 6, "notes": "Documents verified" }
```

6. Access-control matrix

Role	Allowed	Explicit restriction
Customer	Own profile, addresses, discovery, quote, payment, own orders, own OTP display, own reviews.	Cannot access vendor private settings, rider data, other customers or admin operations.
Vendor applicant	Own application and resubmission.	Cannot publish services or receive orders until approval.
Vendor owner	Own profile, services, prices, capacity, employees, vendor orders, revenue and performance.	Cannot approve applications or access other vendors.
Vendor staff	Permission-limited service/order operations.	Cannot change ownership, documents, approved radius or high-risk settings unless granted.
Rider	Only own assigned pickup/delivery jobs and permitted customer address/contact.	Cannot change price, service, vendor profile, documents or arbitrary order status.
Platform admin	Vendor approvals, customers, orders, exceptions, reports and configuration under permission model.	High-risk actions require recent 2FA step-up and audit reason.

7. Backend implementation rules

- Reuse the existing Fastify route -> controller -> service -> repository architecture.
- Generate and maintain Swagger/OpenAPI documentation from route schemas.
- Use PostgreSQL transactions and row-level or advisory locking for slot holds, order creation and final capacity decrement.
- Hash login, pickup, delivery and direct 2FA OTP values; never store plaintext OTPs after verification.
- Use Redis for OTP challenges, rate limits, short-lived slot holds, idempotency keys and job coordination.
- Use BullMQ for vendor auto-reject, notification fan-out, watermark processing, payment expiry and retryable background work.
- Use server-side Razorpay signature validation and idempotent webhook processing as payment source of truth.
- Use Cloudinary restricted assets or equivalent signed delivery for sensitive documents; KYC originals must never be public URLs.

- Create immutable order-event and security-audit records for all critical operations.

8. Definition of API completion

1. Every endpoint has validation schema, role/permission guard, service logic, repository query and documented response.
2. Swagger accurately reflects production request/response contracts.
3. Critical endpoints have positive, negative, permission, idempotency and concurrency tests.
4. Flutter and dashboard consume only documented endpoints; no direct database access or undocumented status mutation exists.
5. All high-risk operations produce an audit entry and a stable error code on rejection.