

RVFP

PROCEDIMIENTO DE VUELO VISUAL RNP

RNP VISUAL FLIGHT PROCEDURE (RVFP)

ELEV AD: 8358, THR 32L: 8351

BOGOTÁ
ELDORADO
CAT: A/B/C/D
RNP D RWY 32L

APP: Bogotá North Terminal 121.3 MHz / Alternate 120.3 MHz, Bogotá South Terminal 119.65 MHz / Alternate 120.65 MHz,
Bogotá West Terminal 119.95 MHz / Alternate 120.95 MHz, Bogotá Arrivals 119.5 MHz / Alternate 119.05 MHz, ATIS: 127.8 MHz.
TWR: ELDORADO North Tower 118.1 MHz / Alternate 118.35 MHz, ELDORADO South Tower 118.25 MHz / Alternate 118.35 MHz.

VAR/ARP/BOG
8°W/22

APROXIMACIÓN FRUSTRADA:

Si sobre BO483 no hay contacto visual, mantener trayectoria RVFP, ascender a 13000, después espere instrucciones del ATC. PDG MNM 3.7% hasta 12000 FT.

MISSED APPROACH:

If on BO483 not visual contact, Maintain on RVFP track, climbing to 13000, then expect ATC instructions. PDG MNM 3.7% until 12000 FT.

CAUTION: MOUNTAINOUS AREA AT E/SE 9800' OR ABOVE, 20 NM FROM VOR BOG

RNP APCH REQUIRED

AJUSTE VELOCIDAD:
A: JET (AT) 230 KIAS / TURBO (AT) 215 KIAS
B: (AT) 215 KIAS
C: (AT) 180 KIAS
D: MAX 160 KIAS

BOGOTÁ LLEGADAS CANCELARÁ LA APROXIMACIÓN A AERONAVES QUE INCUMPLAN LAS RESTRICCIONES DE VELOCIDAD ESTABLECIDAS EN LOS AP Y STAR, O LAS REQUERIDAS POR EL ATC.
BOGOTÁ ARRIVALS WILL CANCEL THE APPROACH TO THOSE AIRCRAFT THAT DO NOT COMPLY WITH THE SPEEDS ESTABLISHED IN THE STAR AND AP PROCEDURES, OR REQUIRED BY THE ATC.

IN CASE OF GO AROUND: EXPECT ATC INSTRUCTIONS, OTHERWISE MAINTAIN MISSED APPROACH TRACK

Altitud de Transición 18000

**Visual track:
Missed Approach track: - - - - -**

ESCALA
0 10 NM
0 10 20 Km

OPERATING MINIMA

OCA (H) (FT)	VISIBILITY (M)
9851 (1500)	5000