

Data Manipulation Language(DML)

- Data Manipulation Language statements are used for manipulating data in database
- DML commands are not auto-committed like DDL Statements
Changes done by DML commands can be rolled back
- Under DML Commands we perform:
 - **INSERT Statement**
 - **UPDATE Statement**
 - **DELETE Statement**
 - **SELECT Statement**

Insert Statement

- INSERT Statement used to add records to existing table
- To insert data into table, SQL INSERT INTO command can be used
- To insert few values in table as per columns names we can use following
- **Syntax:**

```
INSERT INTO table_name (column1, column2, column3, ...)
VALUES (value1, value2, value3, ...);
```

Insert Statement

- If all values for all the columns of the table are to be added then **no need to specify** the column names in SQL Query
- However, make sure the order of the values is in the same order as the columns in the table.
- Here, **syntax** would be as follows:

```
INSERT INTO table_name  
VALUES (value1, value2, value3, ...);
```

Insert Statement

Table: Customers

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK

`INSERT INTO Customers(customer_id, first_name,
last_name, age, country)
VALUES (5, 'Harry', 'Potter', 31, 'USA');`

customer_id	first_name	last_name	age	country
1	John	Doe	31	USA
2	Robert	Luna	22	USA
3	David	Robinson	22	UK
4	John	Reinhardt	25	UK
5	Harry	Potter	31	USA

Insert Statement

Insert Row Providing Value Explicitly

- It's possible to provide default values to a column (for example, auto incrementing a column). In a database table, the **ID** field is usually unique auto incremented.
- In such cases, we can omit the value for that column during row insertion
- For example,

```
1 CREATE TABLE Customers(  
2     ID int AUTO_INCREMENT,  
3     FirstName varchar(25) NOT NULL,  
4     LastName varchar(25),  
5     Age int,  
6     Country varchar(25)  
7 );
```

```
INSERT INTO Customers(first_name, last_name, age, country)  
VALUES  
( 'James', 'Bond', 48, 'USA');
```

Insert Statement

Insert Multiple Rows at Once in SQL

- It's also possible to insert multiple rows to a database table at once.
- For example,

```
INSERT INTO Customers(first_name, last_name, age, country)
VALUES
('Harry', 'Potter', 31, 'USA'),
('Chris', 'Hemsworth', 43, 'USA'),
('Tom', 'Holland', 26, 'UK');
```

Insert Statement

Insert rows Without Specifying Column Names

- It is also possible to insert values in a row without specifying column names.
- For example

```
INSERT INTO Customers  
VALUES  
(5, 'Chris', 'Evans', 42, 'USA');
```

Insert Statement

Not Including All Columns During Insertion

- If we skip column names during row insertion, the values of those columns will be NULL

```
INSERT INTO Customers(first_name, last_name, age)
VALUES
('Brad', 'Pitt', 58);
```


Update Statement

- Update statement is used to modify the existing data present in the table
- To update data in table, SQL UPDATE command can be used
- To update all rows in table we can use following
- Syntax:

UPDATE <Table_name>

SET column1=new_value

- For example,

```
UPDATE Customers  
SET country = 'NP';
```

Update Statement

- The SQL UPDATE statement is used to edit existing rows in a database table. For example,

```
UPDATE Customers  
SET first_name = 'Johnny'  
WHERE customer_id = 1;
```

Update Multiple Values in a Row

- We can also update multiple values in a row at once. For example,

```
UPDATE Customers  
SET first_name = 'Johnny', last_name = 'Depp'  
WHERE customer_id = 1;
```

Update Statement

Update Multiple Rows

- The UPDATE statement can update multiple rows at once.
- For example,

```
UPDATE Customers  
SET country = 'NP'  
WHERE age = 22;
```

Delete Statement

- DELETE Statement is used to delete some or all records from existing table
- To delete data into a table, SQL DELETE command can be used

Delete all Rows in a Table

- The WHERE clause determines which rows to delete. However, we can delete all rows at once if we omit the WHERE clause.
- Syntax: DELETE FROM <TABLE_NAME>
- For example,

```
DELETE FROM Customers;
```

Delete Statement

- In SQL, we use the DELETE statement to delete specific row(s) from a database table.
- **Syntax:**

DELETE FROM <TABLE_NAME> WHERE<Condition>

- For example,

```
DELETE FROM Customers  
WHERE customer_id = 5;
```

SELECT Statement

- Select statement is used to retrieve data from database.
- SELECT query can never make any change in the database.
- The data returned by the SELECT query is in the form of result sets
- **Syntax:**

```
SELECT column1, column2, columnN FROM table_name;
```

- The SQL SELECT statement is used to select (retrieve) data from a database table. For example,

```
SELECT first_name, last_name  
FROM Customers;
```

SELECT Statement

- To select all columns from a database table, we use the * character. For example,

```
SELECT *  
FROM Customers;
```

- A SELECT statement can have an optional WHERE clause. The WHERE clause allows us to fetch records from a database table that matches specified condition(s). For example,

```
SELECT *  
FROM Customers  
WHERE last_name = 'Doe';
```