

Basic Tags

<code><html></code> <code></html></code>
Creates an HTML document
<code><head></code> <code></head></code>
Sets off the title & other info that isn't displayed
<code><body></code> <code></body></code>
Sets off the visible portion of the document
<code><title></code> <code></title></code>
Puts name of the document in the title bar; when bookmarking pages, this is what is bookmarked

Body attributes (only used in email newsletters)

<code><body bgcolor=?></code>
Sets background color, using name or hex value
<code><body text=?></code>
Sets text color, using name or hex value
<code><body link=?></code>
Sets color of links, using name or hex value
<code><body vlink=?></code>
Sets color of visited links, using name or hex value
<code><body alink=?></code>
Sets color of active links (while mouse-clicking)

Text Tags

<code><pre></code> <code></pre></code>
Creates preformatted text
<code><h1></code> <code></h1></code> -- <code><h6></code> <code></h6></code>
Creates headlines -- H1=largest, H6=smallest
<code></code> <code></code>
Creates bold text (should use <code></code> instead)
<code><i></code> <code></i></code>
Creates italicized text (should use <code></code> instead)
<code><tt></code> <code></tt></code>
Creates typewriter-style text
<code><code></code> <code></code></code>
Used to define source code, usually monospace
<code><cite></code> <code></cite></code>
Creates a citation, usually processed in italics
<code><address></code> <code></address></code>
Creates address section, usually processed in italics
<code></code> <code></code>
Emphasizes a word (usually processed in italics)
<code></code> <code></code>
Emphasizes a word (usually processed in bold)
<code></code> <code></code>
Sets size of font - 1 to 7 (should use CSS instead)
<code></code> <code></code>
Sets font color (should use CSS instead)
<code></code> <code></code>
Defines the font used (should use CSS instead)

HTML5 input tag attributes

(not all browsers support; visit <http://caniuse.com> for details)

<code><input type="email" name=?></code>
Sets a single-line textbox for email addresses
<code><input type="url" name=?></code>
Sets a single-line textbox for URLs
<code><input type="number" name=?></code>
Sets a single-line textbox for a number
<code><input type="range" name=?></code>
Sets a single-line text box for a range of numbers
<code><input type="date/month/week/time" name=?></code>
Sets a single-line text box with a calendar showing the date/month/week/time
<code><input type="search" name=?></code>
Sets a single-line text box for searching
<code><input type="color" name=?></code>
Sets a single-line text box for picking a color

Links

<code>clickable text</code>
Creates a hyperlink to a Uniform Resource Locator
<code>clickable text</code>
Creates a hyperlink to an email address
<code></code>
Creates a target location within a document
<code>clickable text</code>
Creates a link to that target location

Forms

<code><form></code> <code></form></code>
Defines a form
<code><select multiple name=? size=?></code> <code></select></code>
Creates a scrolling menu. Size sets the number of menu items visible before user needs to scroll.
<code><select name=?></code> <code></select></code>
Creates a pulldown menu
<code><option></code>
Sets off each menu item
<code><textarea name=? cols="x" rows="y"></code> <code></textarea></code>
Creates a text box area. Columns set the width; rows set the height.
<code><input type="checkbox" name=? value=?></code>
Creates a checkbox.
<code><input type="checkbox" name=? value=? checked></code>
Creates a checkbox which is pre-checked.
<code><input type="radio" name=? value=?></code>
Creates a radio button.
<code><input type="radio" name=? value=? checked></code>
Creates a radio button which is pre-checked.
<code><input type="text" name=? size=?></code>
Creates a one-line text area. Size sets length, in characters.
<code><input type="submit" value=?></code>
Creates a submit button. Value sets the text in the submit button.
<code><input type="image" name=? src=? border=? alt=?></code>
Creates a submit button using an image.
<code><input type="reset"></code>
Creates a reset button

Tables (use only for data layout - use CSS for page layout)

<code><table></code> <code></table></code>
Creates a table
<code><tr></code> <code></tr></code>
Sets off each row in a table
<code><td></code> <code></td></code>
Sets off each cell in a row
<code><th></code> <code></th></code>
Sets off the table header (a normal cell with bold, centered text)

Formatting

<code><p></code> <code></p></code>
Creates a new paragraph
<code>
</code>
Inserts a line break (carriage return)
<code><blockquote></code> <code></blockquote></code>
Puts content in a quote - indents text from both sides
<code><div></code> <code></div></code>
Used to format block content with CSS
<code></code> <code></code>
Used to format inline content with CSS

Lists

<code></code> <code></code>
Creates an unordered list
<code><ol start=?></code> <code></code>
Creates an ordered list (start=xx, where xx is a counting number)
<code></code> <code></code>
Encompasses each list item
<code><dl></code> <code></dl></code>
Creates a definition list
<code><dt></code>
Precedes each definition term
<code><dd></code>
Precedes each definition

Graphical elements

<code><hr></code>
Inserts a horizontal rule
<code><hr size=?></code>
Sets size (height) of horizontal rule
<code><hr width=?></code>
Sets width of rule (as a % or absolute pixel length)
<code><hr noshade></code>
Creates a horizontal rule without a shadow
<code></code>
Adds image; it is a separate file located at the URL
<code></code>
Aligns image left/right/center/bottom/top/middle (use <code></code>)
<code></code>
Sets size of border surrounding image (use CSS)
<code></code>
Sets height of image, in pixels
<code></code>
Sets width of image, in pixels
<code></code>
Sets the alternate text for browsers that can't process images (required by the ADA)

Table attributes (only use for email newsletters)

<code><table border=?></code>
Sets the width of the border around table cells
<code><table cellspacing=?></code>
Sets amount of space between table cells
<code><table cellpadding=?></code>
Sets amount of space between a cell's border and its contents
<code><table width=?></code>
Sets width of the table in pixels or as a percentage
<code><tr align=?></code>
Sets alignment for cells within the row (left/center/right)
<code><td align=?></code>
Sets alignment for cells (left/center/right)
<code><tr valign=?></code>
Sets vertical alignment for cells within the row (top/middle/bottom)
<code><td valign=?></code>
Sets vertical alignment for cell (top/middle/bottom)
<code><td rowspan=?></code>
Sets number of rows a cell should span (default=1)
<code><td colspan=?></code>
Sets number of columns a cell should span
<code><td nowrap></code>
Prevents lines within a cell from being broken to fit