





Power name	output voltage(V)	output current(mA)	Default	Sleep	Field	Note
V_PAD	1.8/2.8	60/120	ON	ON	GPIO/SPI/UART/HOST/I2C	
V_ANA	2.5	120	ON	OFF		
VSPI_MEM	1.8/2.8	170	ON	ON	SPI_MEM	
V_MEM	1.8	120	ON	ON	_	Internal memory
V_CAM	1.8/2.8	100/120	ON	OFF	CAM	
V_MMC	2.7/3.0	100	ON	OFF	MMC	SD card
V_LCD	1.8/2.8	140/140	ON	OFF	LCM	
V_MIC	1.8	/	OFF	OFF		
V_VIB	3.2	150	OFF	OFF		Viberator
V_ASW	1.8/2.8	170/190	ON	OFF		
V_USB	3.3	240	ON	ON		USB
VRF28	1.8/2.8	130/130	ON	ON		RF
VTT_DDR	0.6	/	OFF	OFF		
BL_LED_OUT	3.2	190	OFF	OFF		DDR ref
VSIM1	1.8/2.8	100	OFF		SIM1	LED
VSIM2	1.8/2.8	100	OFF		SIM2	
VSIM3	1.8/2.8	100	OFF		SIM3	
V_RTC	2.8	/	ON	ON		

Battery Connector

RDA Microelectronics Inc.								
Title	RDA8810 AB 8	& SIM Card						
Size C	Document Number RDA8810 Schemaitc							
Date:	Saturday, August 29, 2015	Sheet	3	of	9			











