

C Programming: Deck 5

Operator Precedence & Associativity

Prof. Jyotiprakash Mishra
mail@jyotiprakash.org

Topics Covered

- 1 Introduction
- 2 Complete Precedence Table
- 3 Arithmetic Operators
- 4 Unary Operators
- 5 Relational and Logical Operators
- 6 Assignment Operators
- 7 Mixed Operators
- 8 Bitwise Operators
- 9 Parentheses
- 10 Common Pitfalls
- 11 Summary
- 12 Practice Exercises

Why Precedence & Associativity Matter

- Determine order of evaluation in expressions
- Critical for correct program behavior
- Avoid unexpected results
- Write clear, unambiguous code

Example:

- What is $2 + 3 * 4$?
- Is it $(2 + 3) * 4 = 20$? or
- Is it $2 + (3 * 4) = 14$?

Answer: 14 (multiplication has higher precedence than addition)

Key Concepts

Precedence:

- Determines which operator is evaluated first
- Higher precedence = evaluated earlier
- Similar to BODMAS/PEMDAS in mathematics

Associativity:

- Determines order when operators have same precedence
- Left-to-right: $a - b - c = (a - b) - c$
- Right-to-left: $a = b = c$ means $a = (b = c)$

Parentheses:

- Override all precedence and associativity rules
- Always evaluated first

Operator Precedence Table (Part 1)

Level	Operators	Description	Assoc
1	() [] -> .	Parentheses, array, member	L to R
2	++ -- (postfix) ++ -- (prefix) + - (unary) ! ~ * & sizeof	Postfix inc/dec Prefix inc/dec Unary plus, minus Logical NOT, bitwise NOT Dereference, address-of Size of	R to L
3	* / %	Multiply, divide, modulus	L to R
4	+ - (binary)	Addition, subtraction	L to R
5	<< >>	Left shift, right shift	L to R

Operator Precedence Table (Part 2)

Level	Operators	Description	Assoc
6	< <= > >=	Relational operators	L to R
7	== !=	Equality operators	L to R
8	&	Bitwise AND	L to R
9	^	Bitwise XOR	L to R
10		Bitwise OR	L to R
11	&&	Logical AND	L to R
12		Logical OR	L to R
13	?:	Ternary conditional	R to L
14	= += -= *= /= %= &= ^= = <<= >>=	Assignment operators	R to L
15	,	Comma operator	L to R

Precedence Hierarchy - Quick Reference

Remember: High to Low

- 1 Parentheses ()
- 2 Unary: ++ -- ! ~ + - * &
- 3 Arithmetic: * / % then + -
- 4 Shift: << >>
- 5 Relational: < <= > >= then == !=
- 6 Bitwise: & then ^ then |
- 7 Logical: && then ||
- 8 Ternary: ?:
- 9 Assignment: = += -= ...
- 10 Comma: ,

Program 1: Arithmetic Precedence

```
1 #include <stdio.h>
2 int main() {
3     int result;
4     result = 10 + 5 * 2;
5     printf("10 + 5 * 2 = %d\n",
6           result);
7     printf("Evaluation: 10+(5*2)\n");
8     printf(" 5*2 = 10\n");
9     printf(" 10+10 = 20\n\n");
10    result = 20 - 10 / 2;
11    printf("20 - 10 / 2 = %d\n",
12          result);
13    printf("Evaluation: 20-(10/2)\n");
14    printf(" 10/2 = 5\n");
15    printf(" 20-5 = 15\n");
16    return 0;
17 }
```

Output:

```
10 + 5 * 2 = 20
Evaluation: 10+(5*2)
 5*2 = 10
10+10 = 20
20 - 10 / 2 = 15
Evaluation: 20-(10/2)
 10/2 = 5
20-5 = 15
```

Rule:

- *, /, % before +, -

Program 2: Multiple Operations Same Level

```
1 #include <stdio.h>
2 int main() {
3     int result;
4     result = 20 / 4 * 2;
5     printf("20 / 4 * 2 = %d\n",
6           result);
7     printf("Left to right:\n");
8     printf("  20/4 = 5\n");
9     printf("  5*2 = 10\n\n");
10    result = 100 - 50 + 25;
11    printf("100 - 50 + 25 = %d\n",
12          result);
13    printf("Left to right:\n");
14    printf("  100-50 = 50\n");
15    printf("  50+25 = 75\n");
16    return 0;
17 }
```

Output:

```
20 / 4 * 2 = 10
Left to right:
  20/4 = 5
  5*2 = 10
100 - 50 + 25 = 75
Left to right:
  100-50 = 50
  50+25 = 75
```

Associativity:

- Same precedence
- Evaluate left-to-right

Program 3: Complex Arithmetic Expression

```
1 #include <stdio.h>
2 int main() {
3     int result;
4     result = 2+3*4-10/2+6%4;
5     printf("Expression:\n");
6     printf("2+3*4-10/2+6%%4\n\n");
7     printf("Step 1 (*, /, %%):\n");
8     printf("  3*4 = 12\n");
9     printf("  10/2 = 5\n");
10    printf("  6%%4 = 2\n");
11    printf("=> 2+12-5+2\n\n");
12    printf("Step 2 (+, -):\n");
13    printf("  2+12 = 14\n");
14    printf("  14-5 = 9\n");
15    printf("  9+2 = 11\n\n");
16    printf("Result: %d\n", result);
17    return 0;
18 }
```

Output:

```
Expression:
2+3*4-10/2+6%4
Step 1 (*, /, %):
  3*4 = 12
  10/2 = 5
  6%4 = 2
=> 2+12-5+2
Step 2 (+, -):
  2+12 = 14
  14-5 = 9
  9+2 = 11
Result: 11
```

Program 4: Unary vs Binary Operators

```
1 #include <stdio.h>
2 int main() {
3     int a = 5, b = 3;
4     int result;
5     result = -a + b;
6     printf("a=%d, b=%d\n", a, b);
7     printf("\n-a + b:\n");
8     printf("  -a = %d\n", -a);
9     printf("  -5 + 3 = %d\n\n",
10         result);
11     result = a * -b;
12     printf("a * -b:\n");
13     printf("  -b = %d\n", -b);
14     printf("  5 * -3 = %d\n\n",
15         result);
16     result = -a * -b;
17     printf("-a * -b = %d\n", result);
18     return 0;
19 }
```

Output:

```
a=5, b=3
-a + b:
  -a = -5
  -5 + 3 = -2
a * -b:
  -b = -3
  5 * -3 = -15
-a * -b = 15
```

Note:

- Unary - has higher precedence
- Evaluated before binary operators

Program 5: Increment with Other Operators

```
1 #include <stdio.h>
2 int main() {
3     int x = 5, y = 5;
4     int result;
5     result = ++x * 2;
6     printf("++x * 2:\n");
7     printf("  x becomes 6\n");
8     printf(" 6 * 2 = %d\n", result);
9     printf("  x = %d\n\n", x);
10    result = y++ * 2;
11    printf("y++ * 2:\n");
12    printf("  uses y=5\n");
13    printf(" 5 * 2 = %d\n", result);
14    printf(" then y becomes %d\n", y);
15    return 0;
16 }
```

Output:

```
++x * 2:
  x becomes 6
  6 * 2 = 12
  x = 6
y++ * 2:
  uses y=5
  5 * 2 = 10
  then y becomes 6
```

Key:

- Prefix: increment first
- Postfix: use then increment

Program 6: NOT Operator Precedence

```
1 #include <stdio.h>
2 int main() {
3     int a = 5, b = 0;
4     int result;
5     result = !a + b;
6     printf("a=%d, b=%d\n", a, b);
7     printf("\n!a + b:\n");
8     printf("    !a = %d\n", !a);
9     printf("    0 + 0 = %d\n\n",
10            result);
11    result = !(a + b);
12    printf("!(a + b):\n");
13    printf("    a+b = %d\n", a+b);
14    printf("    !5 = %d\n\n", result);
15    result = !a && b;
16    printf("!a && b = %d\n", result);
17    return 0;
18 }
```

Output:

```
a=5, b=0
!a + b:
    !a = 0
    0 + 0 = 0
!(a + b):
    a+b = 5
    !5 = 0
!a && b = 0
```

Precedence:

- ! higher than +
- () highest

Program 7: Relational Precedence

```
1 #include <stdio.h>
2 int main() {
3     int a=5, b=10, c=15;
4     int result;
5     result = a + b < c;
6     printf("a=%d, b=%d, c=%d\n",
7           a, b, c);
8     printf("\na + b < c:\n");
9     printf("  a+b = %d\n", a+b);
10    printf("  15 < 15 = %d\n\n",
11          result);
12    result = a < b + c;
13    printf("a < b + c:\n");
14    printf("  b+c = %d\n", b+c);
15    printf("  5 < 25 = %d\n",
16          result);
17    return 0;
18 }
```

Output:

```
a=5, b=10, c=15
a + b < c:
  a+b = 15
  15 < 15 = 0
a < b + c:
  b+c = 25
  5 < 25 = 1
```

Rule:

- Arithmetic before relational
- +, - before |, &, etc.

Program 8: Multiple Relational Operators

```
1 #include <stdio.h>
2 int main() {
3     int a=5, b=10, c=5;
4     int result;
5     result = a < b == c < b;
6     printf("a=%d, b=%d, c=%d\n",
7           a, b, c);
8     printf("\na < b == c < b:\n");
9     printf("Step 1 (< < same):\n");
10    printf("  a < b = %d\n", a < b);
11    printf("  c < b = %d\n", c < b);
12    printf("  => 1 == 1\n");
13    printf("Step 2 (==):\n");
14    printf("  1 == 1 = %d\n",
15           result);
16    printf("Result: %d\n", result);
17    return 0;
18 }
```

Output:

```
a=5, b=10, c=5
a < b == c < b:
Step 1 (< < same):
  a < b = 1
  c < b = 1
  => 1 == 1
Step 2 (==):
  1 == 1 = 1
Result: 1
```

Note:

- < before ==

Program 9: Logical AND/OR Precedence

```
1 #include <stdio.h>
2 int main() {
3     int a=1, b=0, c=1;
4     int result;
5     result = a || b && c;
6     printf("a=%d, b=%d, c=%d\n",
7           a, b, c);
8     printf("\na || b && c:\n");
9     printf("Step 1 (&& first):\n");
10    printf("  b && c = %d\n", b&& c);
11    printf("  => a || 0\n");
12    printf("Step 2 (||):\n");
13    printf("  1 || 0 = %d\n",
14          result);
15    result = (a || b) && c;
16    printf("(a||b) && c = %d\n",
17          result);
18    return 0;
19 }
```

Output:

```
a=1, b=0, c=1
a || b && c:
Step 1 (&& first):
  b && c = 0
  => a || 0
Step 2 (||):
  1 || 0 = 1
(a||b) && c = 1
```

Rule:

- && before —
- () changes order

Program 10: Complex Logical Expression

```
1 #include <stdio.h>
2 int main() {
3     int a=5, b=10, c=15;
4     int result;
5     result = a<b && b<c || a==c;
6     printf("a=%d, b=%d, c=%d\n",
7           a,b,c);
8     printf("\na<b && b<c || a==c\n");
9     printf("Step 1 (relational):\n");
10    printf("  a<b = %d\n", a<b);
11    printf("  b<c = %d\n", b<c);
12    printf("  a==c = %d\n", a==c);
13    printf("  => 1&&1 || 0\n");
14    printf("Step 2 (&&):\n");
15    printf("  1&&1 = 1\n");
16    printf("  => 1 || 0\n");
17    printf("Step 3 (||): %d\n",
18          result);
19    return 0;
20 }
```

Output:

```
a=5, b=10, c=15
a<b && b<c || a==c
Step 1 (relational):
  a<b = 1
  b<c = 1
  a==c = 0
  => 1&&1 || 0
Step 2 (&&):
  1&&1 = 1
  => 1 || 0
Step 3 (||): 1
```

Order:

- Relational, &&, —

Program 11: Assignment Associativity

```
1 #include <stdio.h>
2 int main() {
3     int a, b, c;
4     a = b = c = 10;
5     printf("a = b = c = 10\n");
6     printf("Right to left:\n");
7     printf("    c = 10\n");
8     printf("    b = c (b=10)\n");
9     printf("    a = b (a=10)\n");
10    printf("Values: a=%d,b=%d,c=%d\n\n",
11           a, b, c);
12    a = (b = 5) + (c = 3);
13    printf("a=(b=5)+(c=3)\n");
14    printf("    b=5, c=3\n");
15    printf("    a = 5+3 = 8\n");
16    printf("Values: a=%d,b=%d,c=%d\n",
17           a, b, c);
18    return 0;
19 }
```

Output:

```
a = b = c = 10
Right to left:
    c = 10
    b = c (b=10)
    a = b (a=10)
Values: a=10,b=10,c=10
a=(b=5)+(c=3)
    b=5, c=3
    a = 5+3 = 8
Values: a=8,b=5,c=3
```

Associativity:

- Assignment: right-to-left

Program 12: Compound Assignment Precedence

```
1 #include <stdio.h>
2 int main() {
3     int x = 10;
4     printf("Initial: x = %d\n", x);
5     x += 5 * 2;
6     printf("\nx += 5 * 2:\n");
7     printf("    5*2 = 10 first\n");
8     printf("    x = x+10\n");
9     printf("    x = %d\n", x);
10    x = 10;
11    x *= 3 + 2;
12    printf("x *= 3 + 2:\n");
13    printf("    3+2 = 5 first\n");
14    printf("    x = x*5\n");
15    printf("    x = %d\n", x);
16    return 0;
17 }
```

Output:

```
Initial: x = 10
x += 5 * 2:
    5*2 = 10 first
    x = x+10
    x = 20
x *= 3 + 2:
    3+2 = 5 first
    x = x*5
    x = 50
```

Note:

- Right side evaluated first
- Then assignment

Program 13: Arithmetic + Relational + Logical

```
1 #include <stdio.h>
2 int main() {
3     int a=5, b=10, c=15;
4     int result;
5     result = a+b>c && c-a<b;
6     printf("a=%d, b=%d, c=%d\n",
7           a,b,c);
8     printf("\na+b>c && c-a<b\n");
9     printf("Step 1 (arithmetic):\n");
10    printf("  a+b = %d\n", a+b);
11    printf("  c-a = %d\n", c-a);
12    printf("  => 15>15 && 10<10\n");
13    printf("Step 2 (relational):\n");
14    printf("  15>15 = 0\n");
15    printf("  10<10 = 0\n");
16    printf("  => 0 && 0\n");
17    printf("Step 3 (&&): %d\n",
18          result);
19    return 0;
20 }
```

Output:

```
a=5, b=10, c=15
a+b>c && c-a<b
Step 1 (arithmetic):
  a+b = 15
  c-a = 10
  => 15>15 && 10<10
Step 2 (relational):
  15>15 = 0
  10<10 = 0
  => 0 && 0
Step 3 (&&): 0
```

Order:

- Arithmetic → Relational → Logical

Program 14: All Operator Types

```
1 #include <stdio.h>
2 int main() {
3     int a=2, b=3, c=4;
4     int result;
5     result = ++a*b+c--<10&&b>a;
6     printf("Initial: a=2,b=3,c=4\n");
7     printf("\n++a*b+c--<10&&b>a\n");
8     printf("Step 1 (++ prefix):\n");
9     printf("    a becomes 3\n");
10    printf("Step 2 (arithmetic):\n");
11    printf("    3*3 = 9\n");
12    printf("    9+4 = 13\n");
13    printf("Step 3 (postfix--):\n");
14    printf("    use 4, then c=3\n");
15    printf("Step 4 (relational):\n");
16    printf("    13<10=0, 3>3=0\n");
17    printf("Step 5 (&&): %d\n",
18           result);
19    printf("Final: a=%d,c=%d\n",
20           a,c);
21    return 0;
22 }
```

Output:

```
Initial: a=2,b=3,c=4
++a*b+c--<10&&b>a
Step 1 (++ prefix):
    a becomes 3
Step 2 (arithmetic):
    3*3 = 9
    9+4 = 13
Step 3 (postfix--):
    use 4, then c=3
Step 4 (relational):
    13<10=0, 3>3=0
Step 5 (&&): 0
Final: a=3,c=3
```

Program 15: Ternary Operator Precedence

```
1 #include <stdio.h>
2 int main() {
3     int a=5, b=10, c=15;
4     int result;
5     result = a<b ? b+c : b-c;
6     printf("a=%d, b=%d, c=%d\n",
7           a,b,c);
8     printf("\na<b ? b+c : b-c\n");
9     printf("Step 1 (relational):\n");
10    printf("    a<b = 1 (true)\n");
11    printf("Step 2 (ternary):\n");
12    printf("    true, so b+c\n");
13    printf("    10+15 = %d\n\n",
14          result);
15    result = a+b<c ? 1 : 0;
16    printf("a+b<c ? 1 : 0\n");
17    printf("    a+b=15, 15<15=0\n");
18    printf("    false, so 0\n");
19    printf("    Result: %d\n",result);
20    return 0;
21 }
```

Output:

```
a=5, b=10, c=15
a<b ? b+c : b-c
Step 1 (relational):
    a<b = 1 (true)
Step 2 (ternary):
    true, so b+c
    10+15 = 25
a+b<c ? 1 : 0
a+b=15, 15<15=0
false, so 0
Result: 0
```

Note:

- Ternary low precedence

Program 16: Bitwise Precedence

```
1 #include <stdio.h>
2 int main() {
3     int a=5, b=3, c=2;
4     int result;
5     result = a & b | c;
6     printf("a=%d, b=%d, c=%d\n",
7           a,b,c);
8     printf("\na & b | c\n");
9     printf("Step 1 (& first):\n");
10    printf("  a&b = 5&3 = %d\n",
11          a&b);
12    printf("  => 1 | 2\n");
13    printf("Step 2 (|):\n");
14    printf("  1|2 = %d\n\n",result);
15    result = a | b & c;
16    printf("a | b & c\n");
17    printf("  b&c = %d\n", b&c);
18    printf("  a|2 = %d\n", result);
19    return 0;
20 }
```

Output:

```
a=5, b=3, c=2
a & b | c
Step 1 (& first):
  a&b = 5&3 = 1
  => 1 | 2
Step 2 (|):
  1|2 = 3
a | b & c
  b&c = 2
  a|2 = 7
```

Order:

- & before ^ before —

Program 17: Shift Operators

```
1 #include <stdio.h>
2 int main() {
3     int a=8, b=2;
4     int result;
5     result = a << 1 + b;
6     printf("a=%d, b=%d\n", a, b);
7     printf("\na << 1 + b\n");
8     printf("Step 1 (+ first):\n");
9     printf("  1+b = %d\n", 1+b);
10    printf("  => a << 3\n");
11    printf("Step 2 (<<):\n");
12    printf("  8<<3 = %d\n", result);
13    result = (a << 1) + b;
14    printf("(a<<1) + b\n");
15    printf("  a<<1 = %d\n", a<<1);
16    printf("  16+2 = %d\n", result);
17    return 0;
18 }
```

Output:

```
a=8, b=2
a << 1 + b
Step 1 (+ first):
  1+b = 3
  => a << 3
Step 2 (<<):
  8<<3 = 64
(a<<1) + b
  a<<1 = 16
  16+2 = 18
```

Note:

- Arithmetic before shift

Program 18: Power of Parentheses

```
1 #include <stdio.h>
2 int main() {
3     int a=2, b=3, c=4;
4     int r1, r2, r3, r4;
5     r1 = a + b * c;
6     r2 = (a + b) * c;
7     r3 = a * b + c;
8     r4 = a * (b + c);
9     printf("a=%d, b=%d, c=%d\n\n",
10         a,b,c);
11     printf("a+b*c = %d\n", r1);
12     printf("(a+b)*c = %d\n", r2);
13     printf("a*b+c = %d\n", r3);
14     printf("a*(b+c) = %d\n", r4);
15     return 0;
16 }
```

Output:

```
a=2, b=3, c=4
a+b*c = 14
(a+b)*c = 20
a*b+c = 10
a*(b+c) = 14
```

Explanation:

- $2+3*4 = 2+12 = 14$
- $(2+3)*4 = 5*4 = 20$
- $2*3+4 = 6+4 = 10$
- $2*(3+4) = 2*7 = 14$

Program 19: Nested Parentheses

```
1 #include <stdio.h>
2 int main() {
3     int a=2, b=3, c=4, d=5;
4     int result;
5     result = ((a+b)*(c+d))/2;
6     printf("a=%d,b=%d,c=%d,d=%d\n",
7           a,b,c,d);
8     printf("\n((a+b)*(c+d))/2\n");
9     printf("Step 1 (innermost):\n");
10    printf("  a+b = %d\n", a+b);
11    printf("  c+d = %d\n", c+d);
12    printf("Step 2 (multiply):\n");
13    printf("  5*9 = %d\n", 5*9);
14    printf("Step 3 (divide):\n");
15    printf("  45/2 = %d\n\n", result);
16    printf("Result: %d\n", result);
17    return 0;
18 }
```

Output:

```
a=2,b=3,c=4,d=5
((a+b)*(c+d))/2
Step 1 (innermost):
  a+b = 5
  c+d = 9
Step 2 (multiply):
  5*9 = 45
Step 3 (divide):
  45/2 = 22
Result: 22
```

Rule:

- Innermost () first

Program 20: Common Mistake - Assignment in Condition

```
1 #include <stdio.h>
2 int main() {
3     int x = 5;
4     printf("x = %d\n\n", x);
5     printf("Wrong: if (x = 0)\n");
6     if (x = 0) {
7         printf("  This won't print\n");
8     } else {
9         printf("  x assigned 0\n");
10    }
11    printf("  x is now: %d\n\n", x);
12    x = 5;
13    printf("Correct: if (x == 0)\n");
14    if (x == 0) {
15        printf("  Won't print\n");
16    } else {
17        printf("  x still: %d\n", x);
18    }
19    return 0;
20 }
```

Output:

```
x = 5
Wrong: if (x = 0)
  x assigned 0
  x is now: 0
Correct: if (x == 0)
  x still: 5
```

Warning:

- = assigns (returns 0)
- == compares
- Big difference!

Program 21: Mistake - Logical vs Bitwise

```
1 #include <stdio.h>
2 int main() {
3     int a = 5, b = 3;
4     printf("a=%d, b=%d\n\n", a, b);
5     printf("Bitwise & (wrong):\n");
6     if (a>0 & b>0) {
7         printf("  Works but wrong!\n");
8     }
9     printf("  a>0 & b>0 = %d\n\n",
10           a>0 & b>0);
11     printf("Logical && (correct):\n");
12     if (a>0 && b>0) {
13         printf("  Both positive\n");
14     }
15     printf("  a>0 && b>0 = %d\n",
16           a>0 && b>0);
17     return 0;
18 }
```

Output:

```
a=5, b=3
Bitwise & (wrong):
  Works but wrong!
  a>0 & b>0 = 1
Logical && (correct):
  Both positive
  a>0 && b>0 = 1
```

Note:

- & is bitwise
- && is logical
- Always use && for conditions

Quick Reference - Precedence Order

High to Low:

- | | |
|--------------------------------------|--|
| 1 <code>() [] -> .</code> | 9 <code>^</code> (bitwise XOR) |
| 2 <code>! ~ ++ --</code> (unary) | 10 <code> </code> (bitwise OR) |
| 3 <code>* / %</code> | 11 <code>&&</code> (logical AND) |
| 4 <code>+ -</code> (binary) | 12 <code> </code> (logical OR) |
| 5 <code><< >></code> | 13 <code>?:</code> (ternary) |
| 6 <code>< <= > >=</code> | 14 <code>= += -=</code> etc. |
| 7 <code>== !=</code> | 15 <code>,</code> (comma) |
| 8 <code>&</code> (bitwise AND) | |

Associativity Rules

Left to Right:

- Most operators: `+` `-` `*` `/` `%` `<` `>` `==` `!=` `&&` `||`
- Evaluated from left side first

Right to Left:

- Unary operators: `!` `~` `++` `--` `+` `-` `*` `&`
- Assignment: `=` `+=` `-=` `*=` `/=`
- Ternary: `?:`
- Evaluated from right side first

Best Practices

- 1 **Use parentheses** for clarity
- 2 **Don't rely on precedence** for complex expressions
- 3 **One operation per line** for readability
- 4 **Use `==` not `=`** in conditions
- 5 **Use `&&` not `&`** for logical operations
- 6 **Avoid side effects** in complex expressions
- 7 **Comment** non-obvious precedence
- 8 **Break down** complex expressions

Common Mistakes to Avoid

- 1 Using `=` instead of `==` in conditions
- 2 Mixing `&` and `&&` (bitwise vs logical)
- 3 Forgetting integer division truncates
- 4 Not using parentheses in complex expressions
- 5 Assuming left-to-right for all operators
- 6 Using multiple `++` `--` in same expression
- 7 Relying on precedence instead of clarity

Try These!

- 1 Evaluate: $5 + 3 * 2 - 4 / 2$
- 2 Evaluate: $10 > 5 \ \&\& \ 3 < 7 \ || \ 2 == 2$
- 3 What's wrong: `if (x = 10)`
- 4 Trace: `int x=5; y = ++x * 2 + x++;`
- 5 Rewrite with `()`: $a + b * c / d - e$
- 6 Evaluate: $2 \ll 3 + 1$

Questions? Next: Deck 6 - Conditional Statements