

C Programming: Structures

Prof. Jyotiprakash Mishra
mail@jyotiprakash.org

January 16, 2026

Topics Covered

- 1 Introduction to Structures
- 2 Basic Structures
- 3 Array of Structures
- 4 Nested Structures
- 5 Structures and Functions
- 6 Typedef
- 7 Structure Operations
- 8 Practical Examples
- 9 Summary

What are Structures?

- User-defined data type
- Groups related variables together
- Variables can be of different types
- Members accessed using dot operator
- Also called "struct" or "record"

Why Use Structures?

- Organize related data
- Represent real-world entities
- Better than separate variables
- Pass multiple values to functions
- Create complex data types

Example Use Cases:

- Student (name, roll, marks)
- Book (title, author, price)
- Point (x, y coordinates)

Structure Declaration and Definition

Declaration:

```
1 struct structure_name {  
2     data_type member1;  
3     data_type member2;  
4     ...  
5 };
```

Creating Variables:

```
1 struct structure_name variable_name;
```

Accessing Members:

```
1 variable_name.member1 = value;
```

Note: Structure declaration ends with semicolon

Program 1: Simple Structure

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int main() {
7     struct Point p1;
8     p1.x = 10;
9     p1.y = 20;
10    printf("Point p1:\n");
11    printf("x = %d\n", p1.x);
12    printf("y = %d\n", p1.y);
13    printf("\nCoordinates: (%d, %d)\n",
14          p1.x, p1.y);
15    return 0;
16 }
```

Output:

```
Point p1:
x = 10
y = 20

Coordinates: (10, 20)
```

Explanation:

- struct Point has 2 members
- p1 is variable of type Point
- Dot operator accesses members
- Each member is separate

Program 2: Structure with Different Types

```
1 #include <stdio.h>
2 #include <string.h>
3 struct Student {
4     int roll;
5     char name[50];
6     float marks;
7 };
8 int main() {
9     struct Student s1;
10    s1.roll = 101;
11    strcpy(s1.name, "Alice");
12    s1.marks = 85.5;
13    printf("Student Details:\n");
14    printf("Roll: %d\n", s1.roll);
15    printf("Name: %s\n", s1.name);
16    printf("Marks: %.2f\n", s1.marks);
17    return 0;
18 }
```

Output:

```
Student Details:
Roll: 101
Name: Alice
Marks: 85.50
```

Note:

- int, char array, float members
- Different data types
- String needs strcpy
- All related to one student

Program 3: Structure Initialization

```
1 #include <stdio.h>
2 struct Book {
3     char title[30];
4     char author[30];
5     float price;
6 };
7 int main() {
8     struct Book b1 = {"C Programming",
9                       "Dennis Ritchie",
10                      45.50};
11     printf("Book Details:\n");
12     printf("Title: %s\n", b1.title);
13     printf("Author: %s\n", b1.author);
14     printf("Price: $%.2f\n", b1.price);
15     return 0;
16 }
```

Output:

```
Book Details:
Title: C Programming
Author: Dennis Ritchie
Price: $45.50
```

Note:

- Initialize at declaration
- Values in curly braces
- Order matches members
- Cleaner than separate assignments

Program 4: Multiple Structure Variables

```
1 #include <stdio.h>
2 struct Rectangle {
3     int length;
4     int width;
5 };
6 int main() {
7     struct Rectangle r1 = {10, 5};
8     struct Rectangle r2 = {8, 6};
9     printf("Rectangle 1:\n");
10    printf("Length: %d, Width: %d\n",
11           r1.length, r1.width);
12    printf("Area: %d\n",
13           r1.length * r1.width);
14    printf("\nRectangle 2:\n");
15    printf("Length: %d, Width: %d\n",
16           r2.length, r2.width);
17    printf("Area: %d\n",
18           r2.length * r2.width);
19    return 0;
20 }
```

Output:

```
Rectangle 1:
Length: 10, Width: 5
Area: 50

Rectangle 2:
Length: 8, Width: 6
Area: 48
```

Note:

- Two variables of same type
- Independent instances
- Each has own members

Program 5: Array of Structures

```
1 #include <stdio.h>
2 struct Student {
3     int roll;
4     float marks;
5 };
6 int main() {
7     struct Student students[3] = {
8         {101, 85.5},
9         {102, 90.0},
10        {103, 78.5}
11    };
12    int i;
13    printf("Student Records:\n");
14    for (i = 0; i < 3; i++) {
15        printf("Roll: %d, Marks: %.1f\n",
16              students[i].roll,
17              students[i].marks);
18    }
19    return 0;
20 }
```

Output:

```
Student Records:
Roll: 101, Marks: 85.5
Roll: 102, Marks: 90.0
Roll: 103, Marks: 78.5
```

Note:

- Array of 3 students
- Each element is struct
- Access: array[i].member
- Nested initialization

Program 6: Find Highest Marks

```
1 #include <stdio.h>
2 struct Student {
3     int roll;
4     char name[20];
5     float marks;
6 };
7 int main() {
8     struct Student s[3] = {
9         {101, "Alice", 85.5},
10        {102, "Bob", 92.0},
11        {103, "Charlie", 78.5}
12    };
13    int i, maxIndex = 0;
14    for (i = 1; i < 3; i++) {
15        if (s[i].marks > s[maxIndex].marks) {
16            maxIndex = i;
17        }
18    }
19    printf("Highest marks:\n");
20    printf("Name: %s\n", s[maxIndex].name);
21    printf("Marks: %.1f\n",
22           s[maxIndex].marks);
23    return 0;
24 }
```

Output:

```
Highest marks:
Name: Bob
Marks: 92.0
```

Logic:

- Array of 3 students
- Compare marks
- Track index of max
- Display winner

Program 7: Calculate Average Marks

```
1 #include <stdio.h>
2 struct Student {
3     int roll;
4     float marks;
5 };
6 int main() {
7     struct Student s[4] = {
8         {101, 85.0},
9         {102, 90.0},
10        {103, 78.0},
11        {104, 88.0}
12    };
13    float sum = 0;
14    int i;
15    for (i = 0; i < 4; i++) {
16        sum += s[i].marks;
17    }
18    printf("Total students: 4\n");
19    printf("Average marks: %.2f\n",
20        sum / 4);
21    return 0;
22 }
```

Output:

```
Total students: 4
Average marks: 85.25
```

Logic:

- Sum all marks
- Divide by count
- Loop through array
- Access marks member

Program 8: Nested Structures

```
1 #include <stdio.h>
2 struct Date {
3     int day;
4     int month;
5     int year;
6 };
7 struct Employee {
8     int id;
9     char name[30];
10    struct Date joinDate;
11 };
12 int main() {
13     struct Employee emp = {
14         101,
15         "John Doe",
16         {15, 6, 2020}
17     };
18     printf("Employee Details:\n");
19     printf("ID: %d\n", emp.id);
20     printf("Name: %s\n", emp.name);
21     printf("Join Date: %d/%d/%d\n",
22           emp.joinDate.day,
23           emp.joinDate.month,
24           emp.joinDate.year);
25     return 0;
26 }
```

Output:

```
Employee Details:
ID: 101
Name: John Doe
Join Date: 15/6/2020
```

Note:

- Date struct inside Employee
- Access: var.nested.member
- Two levels deep
- Initialization nested too

Program 9: Complex Nested Structure

```
1 #include <stdio.h>
2 struct Address {
3     int houseNo;
4     char city[30];
5 };
6 struct Person {
7     char name[30];
8     int age;
9     struct Address addr;
10 };
11 int main() {
12     struct Person p = {
13         "Alice",
14         25,
15         {123, "New York"}
16     };
17     printf("Person Details:\n");
18     printf("Name: %s\n", p.name);
19     printf("Age: %d\n", p.age);
20     printf("Address: House %d, %s\n",
21           p.addr.houseNo,
22           p.addr.city);
23     return 0;
24 }
```

Output:

```
Person Details:
Name: Alice
Age: 25
Address: House 123, New York
```

Note:

- Person contains Address
- Logical grouping
- Represents real-world relation
- Clean organization

Program 10: Pass Structure to Function

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 void printPoint(struct Point p) {
7     printf("Point: (%d, %d)\n",
8         p.x, p.y);
9 }
10 int main() {
11     struct Point p1 = {10, 20};
12     struct Point p2 = {30, 40};
13     printf("Printing points:\n");
14     printPoint(p1);
15     printPoint(p2);
16     return 0;
17 }
```

Output:

```
Printing points:
Point: (10, 20)
Point: (30, 40)
```

Note:

- Structure passed by value
- Copy passed to function
- Original unchanged
- Reusable function

Program 11: Return Structure from Function

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 struct Point createPoint(int x, int y) {
7     struct Point p;
8     p.x = x;
9     p.y = y;
10    return p;
11 }
12 int main() {
13     struct Point p1, p2;
14     p1 = createPoint(5, 10);
15     p2 = createPoint(15, 20);
16     printf("p1: (%d, %d)\n", p1.x, p1.y);
17     printf("p2: (%d, %d)\n", p2.x, p2.y);
18     return 0;
19 }
```

Output:

```
p1: (5, 10)
p2: (15, 20)
```

Note:

- Function returns struct
- Creates and returns Point
- Constructor-like function
- Convenient initialization

Program 12: Calculate Distance

```
1 #include <stdio.h>
2 #include <math.h>
3 struct Point {
4     int x;
5     int y;
6 };
7 float distance(struct Point p1,
8               struct Point p2) {
9     int dx = p2.x - p1.x;
10    int dy = p2.y - p1.y;
11    return sqrt(dx*dx + dy*dy);
12 }
13 int main() {
14     struct Point a = {0, 0};
15     struct Point b = {3, 4};
16     printf("Point A: (%d, %d)\n",
17           a.x, a.y);
18     printf("Point B: (%d, %d)\n",
19           b.x, b.y);
20     printf("Distance: %.2f\n",
21           distance(a, b));
22     return 0;
23 }
```

Output:

```
Point A: (0, 0)
Point B: (3, 4)
Distance: 5.00
```

Logic:

- Two Point parameters
- Calculate dx, dy
- Pythagorean theorem
- $\text{sqrt}(3*3 + 4*4) = 5$

Program 13: Using typedef

```
1 #include <stdio.h>
2 typedef struct {
3     int x;
4     int y;
5 } Point;
6 int main() {
7     Point p1 = {10, 20};
8     Point p2 = {30, 40};
9     printf("p1: (%d, %d)\n", p1.x, p1.y);
10    printf("p2: (%d, %d)\n", p2.x, p2.y);
11    printf("\nNo 'struct' keyword needed\n");
12    return 0;
13 }
```

Output:

p1: (10, 20)
p2: (30, 40)

No 'struct' keyword needed

Note:

- typedef creates alias
- Point instead of struct Point
- Shorter, cleaner
- Common practice

Program 14: typedef with Named Struct

```
1 #include <stdio.h>
2 #include <string.h>
3 typedef struct Student {
4     int roll;
5     char name[30];
6     float marks;
7 } Student;
8
9 int main() {
10     Student s1;
11     s1.roll = 101;
12     strcpy(s1.name, "Alice");
13     s1.marks = 85.5;
14     printf("Student Details:\n");
15     printf("Roll: %d\n", s1.roll);
16     printf("Name: %s\n", s1.name);
17     printf("Marks: %.1f\n", s1.marks);
18     return 0;
19 }
```

Output:

```
Student Details:
Roll: 101
Name: Alice
Marks: 85.5
```

Note:

- struct Student and Student both work
- Typedef after struct definition
- More flexible
- Both names available

Program 15: Structure Assignment

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int main() {
7     struct Point p1 = {10, 20};
8     struct Point p2;
9     printf("Before assignment:\n");
10    printf("p1: (%d, %d)\n", p1.x, p1.y);
11    p2 = p1;
12    printf("\nAfter p2 = p1:\n");
13    printf("p2: (%d, %d)\n", p2.x, p2.y);
14    p1.x = 100;
15    printf("\nAfter p1.x = 100:\n");
16    printf("p1: (%d, %d)\n", p1.x, p1.y);
17    printf("p2: (%d, %d)\n", p2.x, p2.y);
18    return 0;
19 }
```

Output:

Before assignment:
p1: (10, 20)

After p2 = p1:
p2: (10, 20)

After p1.x = 100:
p1: (100, 20)
p2: (10, 20)

Note:

- Can assign one struct to another
- All members copied
- Independent copies

Program 16: Structure Comparison

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int areEqual(struct Point p1,
7             struct Point p2) {
8     return (p1.x == p2.x) &&
9           (p1.y == p2.y);
10 }
11 int main() {
12     struct Point a = {10, 20};
13     struct Point b = {10, 20};
14     struct Point c = {30, 40};
15     printf("a and b: %s\n",
16           areEqual(a,b) ? "Equal" :
17                       "Not equal");
18     printf("a and c: %s\n",
19           areEqual(a,c) ? "Equal" :
20                       "Not equal");
21     return 0;
22 }
```

Output:

```
a and b: Equal
a and c: Not equal
```

Note:

- Cannot use == on structs
- Must compare member by member
- Function for comparison
- Returns 1 if equal, 0 if not

Program 17: Time Structure

```
1 #include <stdio.h>
2 struct Time {
3     int hours;
4     int minutes;
5     int seconds;
6 };
7 void printTime(struct Time t) {
8     printf("%02d:%02d:%02d\n",
9         t.hours, t.minutes, t.seconds);
10 }
11 int main() {
12     struct Time t1 = {9, 30, 45};
13     struct Time t2 = {14, 5, 30};
14     printf("Time 1: ");
15     printTime(t1);
16     printf("Time 2: ");
17     printTime(t2);
18     return 0;
19 }
```

Output:

```
Time 1: 09:30:45
Time 2: 14:05:30
```

Note:

- Time representation
- Format: HH:MM:SS
- %02d for leading zeros
- Clean display function

Program 18: Complex Number Operations

```
1 #include <stdio.h>
2 typedef struct {
3     float real;
4     float imag;
5 } Complex;
6
7 Complex add(Complex c1, Complex c2) {
8     Complex result;
9     result.real = c1.real + c2.real;
10    result.imag = c1.imag + c2.imag;
11    return result;
12 }
13
14 void print(Complex c) {
15     printf("%.1f + %.1fi\n",
16           c.real, c.imag);
17 }
18
19 int main() {
20     Complex c1 = {3.0, 4.0};
21     Complex c2 = {1.5, 2.5};
22     Complex sum = add(c1, c2);
23     printf("c1 = ");
24     print(c1);
25     printf("c2 = ");
26     print(c2);
27     printf("Sum = ");
28     print(sum);
29     return 0;
30 }
```

Output:

```
c1 = 3.0 + 4.0i
c2 = 1.5 + 2.5i
Sum = 4.5 + 6.5i
```

Note:

- Complex number arithmetic
- Add real and imaginary parts
- typedef for convenience
- Functions for operations

Program 19: Student Grade System

```
1 #include <stdio.h>
2 #include <string.h>
3 typedef struct {
4     int roll;
5     char name[30];
6     float marks;
7     char grade;
8 } Student;
9 void assignGrade(Student *s) {
10     if (s->marks >= 90) s->grade = 'A';
11     else if (s->marks >= 80) s->grade = 'B';
12     else if (s->marks >= 70) s->grade = 'C';
13     else if (s->marks >= 60) s->grade = 'D';
14     else s->grade = 'F';
15 }
16 int main() {
17     Student s = {101, "Alice", 85.5, '-'};
18     assignGrade(&s);
19     printf("Name: %s\n", s.name);
20     printf("Marks: %.1f\n", s.marks);
21     printf("Grade: %c\n", s.grade);
22     return 0;
23 }
```

Output:

```
Name: Alice
Marks: 85.5
Grade: B
```

Note:

- Pointer to struct
- Arrow operator: `->`
- Modifies original struct
- Grade based on marks

Program 20: Library Book System

```
1 #include <stdio.h>
2 #include <string.h>
3 typedef struct {
4     int id;
5     char title[40];
6     char author[30];
7     int available;
8 } Book;
9 void displayBook(Book b) {
10     printf("\nID: %d\n", b.id);
11     printf("Title: %s\n", b.title);
12     printf("Author: %s\n", b.author);
13     printf("Status: %s\n",
14           b.available ? "Available" :
15                       "Issued");
16 }
17 int main() {
18     Book books[2] = {
19         {1, "C Programming", "K&R", 1},
20         {2, "Data Structures", "Tanenbaum", 0}
21     };
22     int i;
23     for (i = 0; i < 2; i++) {
24         displayBook(books[i]);
25     }
26     return 0;
27 }
```

Output:

```
ID: 1
Title: C Programming
Author: K&R
Status: Available

ID: 2
Title: Data Structures
Author: Tanenbaum
Status: Issued
```

Note:

- Array of Book structs
- Boolean-like field
- Display function
- Real-world application

Structures - Summary

Key Points:

- Structure = user-defined data type
- Groups related variables together
- Dot operator (.) for member access
- Arrow operator (->) for pointer to struct
- Can be passed to functions
- Can be returned from functions
- Array of structures possible
- Nested structures allowed
- typedef creates alias
- Assignment copies all members
- Cannot use == for comparison

Structure Syntax Reference

Operation	Syntax
Declaration	<code>struct Name { members; };</code>
Variable	<code>struct Name var;</code>
Access member	<code>var.member</code>
Pointer access	<code>ptr->member</code>
Initialize	<code>struct Name v = {val1, val2};</code>
Assignment	<code>var2 = var1;</code>
Array	<code>struct Name arr[10];</code>
typedef	<code>typedef struct {...} Name;</code>

- 1 **Use meaningful names** for structs and members
- 2 **Group related data** logically
- 3 **Use typedef** for convenience
- 4 **Initialize all members** at declaration
- 5 **Pass by pointer** for large structs
- 6 **Use const** for read-only struct parameters
- 7 **Keep structs simple** - not too many members
- 8 **Document member meanings** with comments
- 9 **Use structs for** related data, not random grouping
- 10 **Consider alignment** for memory efficiency

Common Mistakes

- ❶ **Forgetting semicolon** after struct declaration
- ❷ **Using == for comparison** - compare members instead
- ❸ **Missing struct keyword** - use typedef to avoid
- ❹ **Wrong member access** - dot vs arrow operator
- ❺ **Uninitialized members** - always initialize
- ❻ **Not passing size** with array of structs
- ❼ **Modifying in function** - pass pointer if needed
- ❽ **Forgetting to copy strings** - use strcpy
- ❾ **Wrong initialization order** - must match members
- ❿ **Returning local struct address** - return value, not pointer

Try these programs:

- 1 Create Date structure with validation
- 2 Student database with sorting
- 3 Employee payroll system
- 4 Contact list management
- 5 Bank account operations
- 6 Inventory management system
- 7 Circle structure with area/circumference
- 8 Fraction arithmetic (add, subtract, multiply)
- 9 Playing card deck representation
- 10 Polynomial representation and addition