

C Programming - Deck 17

Pointers and Structures

Prof. Jyotiprakash Mishra
`mail@jyotiprakash.org`

Pointers to Structures

- Pointer can point to a structure variable
- Syntax: `struct Point *ptr;`
- Access members using arrow operator: `ptr->x`
- Arrow operator `->` is shorthand for `(*ptr).x`
- Dot operator `.` for structure variable
- Arrow operator `->` for structure pointer
- Passing pointers to functions is more efficient
- Avoids copying entire structure

Program 1: Basic Pointer to Structure

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int main() {
7     struct Point p1 = {10, 20};
8     struct Point *ptr = &p1;
9     printf("Using dot: (%d, %d)\n", p1.x, p1.y);
10    printf("Using arrow: (%d, %d)\n",
11        ptr->x, ptr->y);
12    printf("Using *: (%d, %d)\n",
13        (*ptr).x, (*ptr).y);
14    return 0;
15 }
```

Output:

```
Using dot: (10, 20)
Using arrow: (10, 20)
Using *: (10, 20)
```

Three ways to access: . -> and (*).

Program 2: Modifying Structure Through Pointer

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int main() {
7     struct Point p1 = {5, 10};
8     struct Point *ptr = &p1;
9     printf("Before: (%d, %d)\n", p1.x, p1.y);
10    ptr->x = 15;
11    ptr->y = 25;
12    printf("After: (%d, %d)\n", p1.x, p1.y);
13    return 0;
14 }
```

Output:

```
Before: (5, 10)
After: (15, 25)
```

Modifying structure members via pointer

Program 3: Array of Structure Pointers

```
1 #include <stdio.h>
2 struct Student {
3     int roll;
4     int marks;
5 };
6 int main() {
7     struct Student s1 = {1, 85};
8     struct Student s2 = {2, 90};
9     struct Student s3 = {3, 78};
10    struct Student *arr[3] = {&s1, &s2, &s3};
11    int i;
12    for (i = 0; i < 3; i++) {
13        printf("Roll: %d, Marks: %d\n",
14            arr[i]->roll, arr[i]->marks);
15    }
16    return 0;
17 }
```

Output:

```
Roll: 1, Marks: 85
Roll: 2, Marks: 90
Roll: 3, Marks: 78
```

Array of pointers to structures

Program 4: Passing Structure Pointer to Function

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 void display(struct Point *p) {
7     printf("Point: (%d, %d)\n", p->x, p->y);
8 }
9 int main() {
10     struct Point p1 = {10, 20};
11     display(&p1);
12     return 0;
13 }
```

Output:

Point: (10, 20)

Efficient: passes address, not copy

Program 5: Modifying Structure in Function

Output:

Before: (10, 20)

After: (15, 30)

```
1  #include <stdio.h>
2  struct Point {
3      int x;
4      int y;
5  };
6  void shift(struct Point *p, int dx, int dy) Function modifies original structure
7      p->x += dx;
8      p->y += dy;
9  }
10 int main() {
11     struct Point p1 = {10, 20};
12     printf("Before: (%d, %d)\n", p1.x, p1.y);
13     shift(&p1, 5, 10);
14     printf("After: (%d, %d)\n", p1.x, p1.y);
15     return 0;
16 }
```

Program 6: Returning Structure Pointer

```
1  #include <stdio.h>
2  struct Point {
3      int x;
4      int y;
5  };
6  struct Point p1 = {10, 20};
7  struct Point p2 = {30, 40};
8  struct Point* getMax(struct Point *a,
9      struct Point *b) {
10     if (a->x + a->y > b->x + b->y)
11         return a;
12     return b;
13 }
14 int main() {
15     struct Point *max = getMax(&p1, &p2);
16     printf("Max: (%d, %d)\n", max->x, max->y);
17     return 0;
18 }
```

Output:

Max: (30, 40)

Returning pointer to existing structure

Program 7: Structure with Nested Pointer Members

```
1 #include <stdio.h>
2 struct Person {
3     char *name;
4     int age;
5 };
6 int main() {
7     struct Person p1 = {"Alice", 25};
8     struct Person *ptr = &p1;
9     printf("Name: %s\n", ptr->name);
10    printf("Age: %d\n", ptr->age);
11    ptr->name = "Bob";
12    ptr->age = 30;
13    printf("Updated: %s, %d\n",
14           ptr->name, ptr->age);
15    return 0;
16 }
```

Output:

```
Name: Alice
Age: 25
Updated: Bob, 30
```

Structure containing pointer member

Program 8: Pointer to Array of Structures

Output:

```
Point 0: (1, 2)
Point 1: (3, 4)
Point 2: (5, 6)
```

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int main() {
7     struct Point arr[3] = {{1,2}, {3,4}, {5,6}};
8     struct Point *ptr = arr;
9     int i;
10    for (i = 0; i < 3; i++) {
11        printf("Point %d: (%d, %d)\n",
12            i, (ptr+i)->x, (ptr+i)->y);
13    }
14    return 0;
15 }
```

Pointer arithmetic with structures

Program 9: Compare Structures Using Pointers

Output:

Points are equal

Comparing structure members

```
1 #include <stdio.h>
2 struct Point {
3     int x;
4     int y;
5 };
6 int equal(struct Point *p1,
7     struct Point *p2) {
8     return (p1->x == p2->x && p1->y == p2->y);
9 }
10 int main() {
11     struct Point a = {10, 20};
12     struct Point b = {10, 20};
13     if (equal(&a, &b)) {
14         printf("Points are equal\n");
15     } else {
16         printf("Points are not equal\n");
17     }
18     return 0;
19 }
```

Program 10: Distance Between Two Points

```
1  #include <stdio.h>
2  #include <math.h>
3  struct Point {
4      int x;
5      int y;
6  };
7  double distance(struct Point *p1,
8      struct Point *p2) {
9      int dx = p2->x - p1->x;
10     int dy = p2->y - p1->y;
11     return sqrt(dx*dx + dy*dy);
12 }
13 int main() {
14     struct Point a = {0, 0};
15     struct Point b = {3, 4};
16     printf("Distance: %.2f\n", distance(&a, &b));
17     return 0;
18 }
```

Output:

Distance: 5.00

Computing distance using pointers

Program 11: Self-Referential Structure

```
1 #include <stdio.h>
2 struct Node {
3     int data;
4     struct Node *next;
5 };
6 int main() {
7     struct Node n1 = {10, NULL};
8     struct Node n2 = {20, NULL};
9     struct Node n3 = {30, NULL};
10    n1.next = &n2;
11    n2.next = &n3;
12    struct Node *ptr = &n1;
13    while (ptr != NULL) {
14        printf("%d -> ", ptr->data);
15        ptr = ptr->next;
16    }
17    printf("NULL\n");
18    return 0;
19 }
```

Output:

```
10 -> 20 -> 30 -> NULL
```

Linked list concept with pointers

Program 12: Finding Student with Highest Marks

```
1 #include <stdio.h>
2 struct Student {
3     char name[20];
4     int marks;
5 };
6 int main() {
7     struct Student s[3] = {
8         {"Alice", 85},
9         {"Bob", 92},
10        {"Charlie", 78}
11    };
12    struct Student *max = &s[0];
13    int i;
14    for (i = 1; i < 3; i++) {
15        if (s[i].marks > max->marks) {
16            max = &s[i];
17        }
18    }
19    printf("Highest: %s (%d)\n",
20        max->name, max->marks);
21    return 0;
22 }
```

Output:

Highest: Bob (92)

Pointer to max element in array

Program 13: Swap Two Structures Using Pointers

```
1  #include <stdio.h>
2  struct Point {
3      int x;
4      int y;
5  };
6  void swap(struct Point *p1,
7           struct Point *p2) {
8      struct Point temp = *p1;
9      *p1 = *p2;
10     *p2 = temp;
11 }
12 int main() {
13     struct Point a = {10, 20};
14     struct Point b = {30, 40};
15     printf("Before: (%d,%d) (%d,%d)\n",
16           a.x, a.y, b.x, b.y);
17     swap(&a, &b);
18     printf("After: (%d,%d) (%d,%d)\n",
19           a.x, a.y, b.x, b.y);
20     return 0;
21 }
```

Output:

```
Before: (10,20) (30,40)
After: (30,40) (10,20)
```

Swapping entire structures

Program 14: Nested Structure with Pointers

```
1  #include <stdio.h>
2  struct Date {
3      int day;
4      int month;
5      int year;
6  };
7  struct Employee {
8      char name[20];
9      struct Date dob;
10 };
11 int main() {
12     struct Employee e = {"John", {15, 8, 1990}};
13     struct Employee *ptr = &e;
14     printf("Name: %s\n", ptr->name);
15     printf("DOB: %d/%d/%d\n",
16           ptr->dob.day, ptr->dob.month, ptr->dob.year);
17     return 0;
18 }
```

Output:

```
Name: John
DOB: 15/8/1990
```

Accessing nested structure members

Program 15: Calculate Average Marks Using Pointers

Output:

Average: 84.33

Processing array of structures

```
1  #include <stdio.h>
2  struct Student {
3      int roll;
4      int marks;
5  };
6  float average(struct Student *arr, int n) {
7      int sum = 0;
8      int i;
9      for (i = 0; i < n; i++) {
10         sum += (arr + i)->marks;
11     }
12     return (float)sum / n;
13 }
14 int main() {
15     struct Student s[3] = {{1,85},{2,90},{3,78}};
16     printf("Average: %.2f\n", average(s, 3));
17     return 0;
18 }
```

Program 16: Pointer to Structure with Array Member

Output:

```
Name: Alice
Marks: 85 90 78
```

```
1 #include <stdio.h>
2 struct Student {
3     char name[20];
4     int marks[3];
5 };
6 int main() {
7     struct Student s = {"Alice", {85, 90, 78}};
8     struct Student *ptr = &s;
9     int i;
10    printf("Name: %s\n", ptr->name);
11    printf("Marks: ");
12    for (i = 0; i < 3; i++) {
13        printf("%d ", ptr->marks[i]);
14    }
15    printf("\n");
16    return 0;
17 }
```

Structure with array accessed via pointer

Program 17: Update Structure Array Using Pointer

```
1  #include <stdio.h>
2  struct Point {
3      int x;
4      int y;
5  };
6  void translate(struct Point *arr, int n,
7               int dx, int dy) {
8      int i;
9      for (i = 0; i < n; i++) {
10         (arr + i)->x += dx;
11         (arr + i)->y += dy;
12     }
13 }
14 int main() {
15     struct Point p[2] = {{1,2}, {3,4}};
16     translate(p, 2, 10, 20);
17     printf("( %d,%d) ( %d,%d)\n",
18           p[0].x, p[0].y, p[1].x, p[1].y);
19     return 0;
20 }
```

Output:

(11,22) (13,24)

Modifying all structures in array

Program 18: Size of Structure and Pointer

```
1 #include <stdio.h>
2 struct Student {
3     int roll;
4     char name[20];
5     float marks;
6 };
7 int main() {
8     struct Student s;
9     struct Student *ptr;
10    printf("Size of structure: %lu\n",
11        sizeof(s));
12    printf("Size of pointer: %lu\n",
13        sizeof(ptr));
14    printf("Advantage of pointer: less copy\n");
15    return 0;
16 }
```

Output:

```
Size of structure: 28
Size of pointer: 8
Advantage of pointer: less copy
```

Pointer is much smaller than structure

Program 19: Sort Structures Using Pointers

Output:

```
Roll:1 Marks:85
Roll:2 Marks:90
Roll:3 Marks:78
```

```
1  #include <stdio.h>
2  struct Student {
3      int roll;
4      int marks;
5  };
6  int main() {
7      struct Student s[3] = {{3,78},{1,85},{2,90}};
8      struct Student *p[3] = {&s[0],&s[1],&s[2]};
9      struct Student *temp;
10     int i, j;
11     for (i = 0; i < 2; i++) {
12         for (j = i+1; j < 3; j++) {
13             if (p[i]->roll > p[j]->roll) {
14                 temp = p[i];
15                 p[i] = p[j];
16                 p[j] = temp;
17             }
18         }
19     }
20     for (i=0; i<3; i++)
21         printf("Roll:%d Marks:%d\n",
22             p[i]->roll, p[i]->marks);
23     return 0;
24 }
```

Sorting pointers, not structures

Program 20: Complex Structure with Multiple Pointers

```
1 #include <stdio.h>
2 struct Node {
3     int data;
4     struct Node *prev;
5     struct Node *next;
6 };
7 int main() {
8     struct Node n1 = {10, NULL, NULL};
9     struct Node n2 = {20, NULL, NULL};
10    n1.next = &n2;
11    n2.prev = &n1;
12    struct Node *ptr = &n1;
13    printf("Forward: %d -> %d\n",
14          ptr->data, ptr->next->data);
15    ptr = &n2;
16    printf("Backward: %d -> %d\n",
17          ptr->data, ptr->prev->data);
18    return 0;
19 }
```

Output:

```
Forward: 10 -> 20
Backward: 20 -> 10
```

Doubly linked list concept

Key Takeaways

- Pointer to structure: `struct Type *ptr;`
- Arrow operator `->` for pointer: `ptr->member`
- Dot operator `.` for variable: `var.member`
- `ptr->member` equivalent to `(*ptr).member`
- Passing pointers avoids copying entire structure
- Array of structure pointers for flexible data
- Self-referential structures enable linked lists
- Pointer arithmetic works with structure arrays
- Understanding this is crucial for data structures