



REGIONWIDE INTEGRATED KNOWLEDGE MANAGEMENT SYSTEM

RIKMS Super Admin User Manual

Super Administrator

Platform governance, moderation, access control, security, recovery, and system configuration

Version 1.0 | 5 August 2026

Prepared from the implemented RIKMS v2 workflows and controls.

Use only with an authorized RIKMS account. Protect credentials, restricted records, exports, and recovery codes according to organizational policy.

Contents

Select a heading in Word to jump to that section. Update the table if pagination changes after editing.

1. About this manual.....	4
Your responsibilities	4
2. Sign in and complete MFA.....	5
3. Navigate the administration workspace.....	6
4. Use the System Dashboard	7
Daily triage.....	7
5. Manage agencies	8
Create an agency.....	8
Available row actions	8
6. Manage Agency Admin users.....	9
7. Browse System Research.....	10
8. Moderate research integrity	11
Duplicate review	11
9. Monitor access requests	12
10. Use System Analytics	13
11. Review notifications and activity logs	14
12. Manage RBAC.....	15
Roles and permissions	15
User assignments.....	15
13. Operate the Security Center	16
14. Restore or delete archived records	17
15. Configure Platform Settings	18
16. Active and non-active settings	19
17. Enable and disable maintenance mode	20
18. Operating checklists.....	21
Daily.....	21
Weekly	21

Monthly or release-based 21

19. Troubleshooting and escalation 22

Escalation record..... 22

Appendix A. Super Admin quick paths 23

1. About this manual

This manual is for authorized Super Administrators responsible for regionwide RIKMS governance and operations.

Your responsibilities

- Manage participating agencies and Agency Administrator accounts.
- Review research integrity, decide moderation actions, and publish approved records.
- Monitor access-request decisions without replacing the responsible agency's routine review.
- Manage roles and permissions while preserving last-Super-Admin protection.
- Monitor security events, sessions, queue health, notifications, and audit activity.
- Restore archived records and tightly control permanent deletion.
- Configure platform settings, including access requests, MFA, session timeout, maintenance mode, and AI processing.

Privileged role: Super Admin actions affect multiple agencies and are audited. Use a named account, enable MFA, verify the target before every write action, and never use this role for routine agency data entry.

2. Sign in and complete MFA

Super Administrators enter through the separate System Administration Portal.

1. Open the RIKMS base address supplied by the deployment owner, then go to /admin/login.
2. Enter the Admin Email and password. Select Remember this device only on a managed, private device.
3. Select Access System Portal.
4. If challenged, enter the current authenticator code or an unused recovery code.
5. If MFA setup is required, enable two-factor authentication, scan the QR code, confirm a code, and store recovery codes securely before opening protected admin pages.

MFA enforcement: The database setting and deployment security floor can require Super Admin MFA. A deployment-level requirement cannot be bypassed from Platform Settings.

- All login activity is monitored and logged.
- Use Forgot Password? only through the approved recovery process.
- Sign out after privileged work and revoke unfamiliar sessions in Security Center.

3. Navigate the administration workspace

The navy top bar provides global search, notification access, the Super Admin menu, and sign-out. The left sidebar provides governance modules.

Menu	Primary use
Dashboard	Platform metrics, moderation queue, activity, security status, and quick actions.
Agency Management	Create, edit, activate, deactivate, assign administrators, and archive agencies.
Agency Admin Users	Create and maintain agency-level administrator accounts.
System Research	Browse, filter, view, open, and export records across agencies.
Research Integrity & Moderation	Review records, duplicates, flags, decisions, publication, and moderation activity.
Access Request Monitoring	Audit agency decisions, inspect trends, export, and override an approval to denial when justified.
System Analytics	Analyze repository, access, agency, project report, usage, and security data.
System Notifications & Activity Logs	Review notifications, logs, timeline, filters, export, and clear eligible notices.
RBAC Management	Manage roles, permission sets, user role assignments, and change history.
Security Center	Review alerts, events, sessions, queue health, and security report export.
Archive	Restore or permanently delete eligible archived research, agencies, users, and files.
Platform Settings	Configure supported global controls and view informational or deployment-managed settings.

4. Use the System Dashboard

The System Dashboard is the operating overview for all participating agencies.

- Metric cards for agencies, users, research, moderation, access, or other current platform totals.
- Research upload trends and research-by-agency charts.
- Pending Moderation panel for work requiring review.
- System Activity feed and Security Status panel.
- Quick Management Actions for creating an agency, managing users, viewing research, opening logs, managing RBAC, and opening Security Center.

Pilot limitation: The System Report button on the dashboard is intentionally unavailable during the pilot. Use module-specific CSV/export actions where they are enabled.

Daily triage

1. Review critical or high security alerts.
2. Review pending and flagged research records.
3. Check access-request anomalies and failed operational events.
4. Confirm queue health when AI/PDF processing is enabled.
5. Review recent privileged actions before making configuration changes.

5. Manage agencies

Agency Management controls participating institutions and their relationship to research and Agency Administrator accounts.

Create an agency

1. Open Agency Management and select Create New Agency.
2. Enter the full name, short name, type, initial status, description, website, contact email, and office address.
3. Optionally assign an available Agency Administrator.
4. Review the values and create the agency.

Available row actions

- View Details and Edit Agency.
- Deactivate or Activate.
- Assign / Change Agency Admin.
- View Research Records scoped to the agency.
- Archive Agency.

Dependency check: Before deactivation or archive, confirm who will own ongoing moderation, access requests, and records. Archiving preserves history; it is not the same as permanent deletion.

6. Manage Agency Admin users

Agency Admin Users maintains accounts assigned to participating agencies.

1. Select Create Agency Admin and enter the user's identity, email, agency, role, status, and required credential fields.
2. Use filters and search to locate an account.
3. Use View Details to verify agency, role, status, and last login.
4. Use Edit User to correct approved profile or assignment data.
5. Use Activate or Deactivate to control sign-in without erasing history.
6. Use Reset Password only after verifying the requester and follow the displayed secure handoff process.
7. Use Remove User only when the account should be soft-deleted/archived and institutional ownership has been transferred.

Retention: Normal account removal preserves the user row, ownership history, decisions, audit logs, sessions, and related records through archive and soft deletion. Do not treat Remove User as anonymous cleanup.

7. Browse System Research

System Research Repository provides a cross-agency view without replacing the moderation controls on the dedicated moderation page.

1. Search titles or authors.
 2. Filter by agency, status, year, category, SDG, and document type.
 3. Select View for a summary or Open for the full record page.
 4. Use Export Records, choose CSV and the required date range, then verify the downloaded file.
- Summary items show status, agency, year, title, authors, category, downloads, views, and SDG context.
 - Record detail can include official relational metadata plus PDF parsing, AI metadata, and SDG classification results when available.
 - Use the moderation module for approve, reject, return, publish, flag, and archive decisions.

8. Moderate research integrity

Research Integrity & Moderation controls the official workflow from submitted records to approval and publication.

1. Filter or search the moderation queue and open View Details.
2. Select Review Record and examine required metadata, public fields, files, AI review state, SDG alignment, access classification, and any duplicate indicators.
3. Enter a concise moderation note documenting the decision or required follow-up.
4. Choose only an action allowed for the record's current status.
5. Confirm the action and verify the new status and activity entry.

Current status	Typical allowed actions
Submitted	View, approve, approve and publish, reject, or flag for review.
Under review	View, approve, approve and publish, reject, return to draft, or keep/flag for review.
Approved	View, publish, or archive.
Published	View or archive.
Rejected	View, return to draft, archive, or keep flagged as presented.
Archived / Superseded / Draft	Primarily view; recovery or agency revision flows handle later changes.

Separate approval and publication: Approve validates the record for the workflow; Publish exposes the eligible record. Approve and Publish combines both and should be used only when the review is fully complete.

Duplicate review

- Use the duplicate panel to compare titles, agencies, identifiers, and metadata.
- Dismiss a false-positive pair only after documenting why the records are distinct.
- Do not delete or merge records solely on similarity scoring.

9. Monitor access requests

Access Request Monitoring provides regionwide oversight of requests and agency decisions.

1. Search or filter by status, agency, research, requester email, access level, and date range.
2. Open View Request Details and inspect the request, research, agency, decision, and audit context.
3. Use Audit Decision to record that the agency decision has been reviewed.
4. Use Override - Deny only on an approved request when policy, privacy, legal, or security grounds require revocation. Enter a complete rationale.
5. Use Export Access Report for authorized reporting and protect the exported requester data.

Override authority: Override - Deny is an exceptional governance action, not a substitute for routine agency review. Confirm the exact request and preserve the rationale in the audit trail.

10. Use System Analytics

System Analytics combines platform-level repository, agency, access, usage, security, and project report analysis.

- Select This Year, Last 30 days, or All Time where presented.
- Use charts for research by agency/category, upload trends, SDG contribution, platform usage, most-accessed research, and access-request status.
- Use Project Report Analytics to filter by agency, report type, period, status, completeness, budget class, accomplishment, funding source, and date range.
- Open report details for completeness sections, workflow status, accomplishment source, financial metrics, and performance rows.
- Export only the required report and retain it according to data-handling policy.

Data quality: Analytics reflect persisted source records. Investigate missing fields, incomplete reports, and filter choices before interpreting a metric as an operational failure.

11. Review notifications and activity logs

System Notifications & Activity Logs provides both actionable notices and an auditable view of administrative and system activity.

1. Review notification tabs and mark eligible notices read when addressed.
2. Filter activity logs by search, status, role, agency, and action.
3. Use the timeline to reconstruct a sequence of related events.
4. Export Activity Log for an authorized audit or investigation.
5. Use Clear Notifications only after verifying that the selected notices can be cleared without disrupting an active response.

Audit preservation: Clearing notifications does not authorize deletion of audit evidence. Audit logs are separate records and should be retained under the applicable policy.

12. Manage RBAC

Role-Based Access Control (RBAC) defines what authenticated users can view or manage.

Roles and permissions

1. Open RBAC Management and review Roles, Permissions, User Role Assignments, and Change History.
2. Select Create New Role for a justified custom role. Give it a clear name and limited purpose.
3. Assign only the permissions needed for that purpose and save.
4. Use View Role before editing. System roles are protected from edits or deletion where indicated.
5. Use Duplicate Role as a starting point only when the copied permissions are reviewed one by one.
6. Delete a custom role only after removing or replacing all active assignments and reviewing the impact.

User assignments

1. Locate the user in User Role Assignments.
2. Review current roles and effective permissions.
3. Assign, replace, or remove the role as required, then confirm the change summary.
4. Review Change History to verify the recorded actor and result.

Last Super Admin: RIKMS protects against removing the final Super Admin assignment. Maintain at least one verified recovery-capable Super Admin account at all times.

Least privilege: Avoid broad custom roles when a smaller permission set will work. Periodically remove roles that are no longer needed.

13. Operate the Security Center

Security Center brings together security summary data, alerts, events, active sessions, and queue health.

1. Review Critical and High alerts first, then inspect event details, actor, IP/context, time, and related metadata.
2. Acknowledge an alert when ownership of the investigation is clear.
3. Resolve only after the issue has been contained and the resolution is documented. Reopen if new evidence shows the issue remains active.
4. Review Active Admin Sessions and revoke a session that is unauthorized, lost, or no longer required.
5. Review Queue Health when PDF/AI work is delayed; use operational logs and the queue runbook for service-level recovery.
6. Export Security Report only for authorized incident, audit, or compliance work.

Session revocation: Confirm the session identifier and user before revoking. Revocation interrupts the selected session but does not reset the user's password or resolve the underlying cause.

14. Restore or delete archived records

Archive & Data Recovery covers archived research, agencies, users, and files, plus archive activity and exports.

1. Select the correct archive tab and locate the record by search, agency, type, status, or date filter.
2. Use View Details to verify the record type, agency, archive actor, date, reason, and dependencies.
3. Use Restore and confirm. Verify the restored record in its primary module.
4. Use Delete Permanently only under an approved destruction process and only when backend safeguards permit it.
5. Use Export Archive Report for authorized retention or recovery reporting.

Permanent deletion: Permanent deletion cannot be undone and may damage historical or legal evidence. Restoration is the normal action. Confirm backups, retention authority, dependencies, and exact target before deletion.

User restoration: Restoring an archived user clears deletion/archive state, reactivates the account, and restores valid agency/role associations where supported. Revalidate access before notifying the user.

15. Configure Platform Settings

Platform Settings mixes active controls with informational, deferred, and deployment-managed settings. Read the status shown in the UI before assuming a value changes runtime behavior.

Section	Examples
General	System name, short name, language label, timezone label, and platform logo.
Research Repository	Maximum PDF upload size, allowed file types, and planned metadata/default-status policies.
Access Control	Public access-request enablement and planned default/embargo policies.
Security Policies	Super Admin MFA, session timeout, and deployment-managed login thresholds.
Notifications	Global preferences, including settings that remain deferred or deployment-managed.
Maintenance	Application-level maintenance mode and the public notice.
AI Processing	Enable or disable new PDF parsing, metadata extraction, SDG classification, and manual reruns.
Backup & Recovery	Informational backup frequency/status; backup execution is not configured in the pilot.

1. Review the current values and status labels.
2. Change only the settings included in the approved change request.
3. Review validation errors and high-impact effects.
4. Select Save Changes. Use Discard Changes to abandon unsaved edits.
5. Verify the affected workflow and review the audit log.

Infrastructure floors: Environment configuration can disable public access requests, force Super Admin MFA, cap uploads, and control mail or backup services. A database setting cannot override a stricter deployment security control.

16. Active and non-active settings

Use this reference to distinguish runtime controls from labels or planned behavior.

Status	Setting examples	Meaning
Active	Upload size, allowed PDF type, access requests enabled, Super Admin MFA, session timeout, maintenance mode, AI processing	Changes affect current application behavior, subject to deployment floors.
Informational	Site labels, timezone label, maintenance notice text, backup last-run/frequency/status	Displayed or stored information; may not control the underlying service.
Deferred	Default research status, metadata requirements, default access policy, embargo defaults, several notification toggles	Planned control; do not describe it as enforced.
Deployment-managed	Failed-login threshold, lockout duration, email transport, actual backup execution	Configured in infrastructure or environment, not by this page alone.

Backup limitation: The pilot Backup and Data Recovery panel does not execute database, file, or MongoDB backups. The execution button is disabled. Backups must be configured and performed by the deployment/system administrator.

17. Enable and disable maintenance mode

RIKMS maintenance mode is an application-level gate that blocks normal traffic while preserving Super Admin recovery access.

1. Prepare an approved maintenance window and a clear public notice.
2. Open Platform Settings > System Maintenance.
3. Enable Maintenance Mode, review the warning modal, enter or confirm the maintenance message, and save.
4. Verify that normal public and agency routes receive the maintenance response while admin recovery routes remain available.
5. Perform the approved work and monitor logs.
6. Return to Platform Settings, disable Maintenance Mode, save, and verify public, agency, and API recovery.

Do not lock out recovery: Do not use infrastructure changes that remove the only Super Admin recovery path unless a tested out-of-band rollback exists.

18. Operating checklists

Use these checks as a starting point and adapt them to the organization's approved operating procedures.

Daily

- Review critical/high security alerts and queue health.
- Review pending moderation and access-monitoring anomalies.
- Review failed system activity and recent privileged writes.
- Confirm no unexpected maintenance or AI-processing state change.

Weekly

- Review inactive or unassigned agency administrator accounts.
- Review RBAC changes and custom roles for least privilege.
- Review archived records awaiting recovery or approved disposition.
- Review analytics for unusual download, request, or agency activity.

Monthly or release-based

- Verify backup evidence with the deployment administrator; do not rely on the informational panel.
- Test password recovery, MFA recovery, maintenance recovery, and session revocation in an approved non-production environment.
- Review platform-setting status labels and document any environment-managed values.
- Export and retain authorized audit/security reports according to policy.
- Reconcile active agencies, users, roles, and assigned responsibilities.

19. Troubleshooting and escalation

Privileged troubleshooting should preserve evidence and avoid unreviewed destructive changes.

Problem	Response
Admin page blocked after login	Complete MFA setup/challenge and confirm the account is active with Super Admin authorization.
Setting saves but behavior does not change	Check whether the setting is active, informational, deferred, or deployment-managed; check environment floors and cache invalidation.
Upload limit differs from the page	Compare the configured value with PHP, web-server, and proxy limits; the effective limit is the strictest.
AI jobs remain queued or skipped	Check AI Processing, queue health, worker status, MongoDB/OpenAI configuration, and job logs.
Cannot remove a role	Check system-role protection, active assignments, and last-Super-Admin protection.
Cannot permanently delete	The record may have protected relationships or lack an authorized deletion path. Restore or retain it and escalate.
Email or digest does not run	Mail transport and scheduled delivery may be deployment-managed or not implemented. Check the setting status and infrastructure.
Maintenance recovery fails	Use the preserved admin recovery route or the deployment rollback procedure; do not repeatedly change unrelated settings.

Escalation record

- Record the page, target identifier, user, agency, time, action, result, and exact error code/message.
- Preserve relevant audit, security, queue, and application log references.
- State whether data changed and whether rollback or restoration was attempted.
- Never include passwords, MFA codes, recovery codes, API keys, session secrets, or unrestricted data exports.

Appendix A. Super Admin quick paths

Paths are relative to the RIKMS base address provided by the deployment owner.

Task	Path
Super Admin sign-in	/admin/login
System Dashboard	/admin/dashboard
Agency Management	/admin/agencies
Agency Admin Users	/admin/users
System Research	/admin/research
Research Moderation	/admin/moderation
Access Monitoring	/admin/access-requests
System Analytics	/admin/analytics
Notifications & Activity	/admin/audit-logs
RBAC	/admin/rbac
Security Center	/admin/security
Archive & Recovery	/admin/archive
Platform Settings	/admin/settings

Change record: For every high-impact change, retain the authorization, before/after values, verification result, rollback method, and linked audit event.