University of Information Technology and Sciences (UITS)
Department of Computer Science and Engineering

Software Testing and Quality Assurance Report

Project Title: CampusCare — Facility Maintenance & Complaint Platform

Comprehensive Unit Testing, Boundary Value Analysis, Coverage & Security Audit

Course Information:
Course Code: CSE 416
Course Title: Software Project Design & Dev.
Mapped CO: CO3 (Testing & Quality Assurance)
Semester: Autumn 2026

Submitted To:
Dr. Mahfida Amjad Dipa
Assistant Professor, Department of CSE, UITS

Submitted By (Group Members):
Shafayat Hossain Shafin
ID: 0432320005101088

Md. Masud Rahman
ID: 0432320005101064

Rudro Antony Mrong
ID: 0432320005101059

Submission Date: November 2026

Laboratory Objective: Design and execute a comprehensive testing strategy for the CampusCare project. Formulate unit test cases applying Equivalence Partitioning and Boundary Value Analysis, refine edge cases using **Qodo Gen (CodiumAI)**, verify the test suite via the **Vitest** execution engine achieving 100% code coverage, and audit security vulnerabilities via **Snyk**.

1 Testing Strategy & 4-Step Engineering Methodology

In strict accordance with the Software Testing and Quality Assurance laboratory framework (Mapped CO: **CO3**), our testing strategy was executed through a rigorous four-step engineering process:

1.1 Step 1: Attempt (Design It Yourself)

1. **Equivalence Partitioning & Boundary Value Analysis:** Before utilizing automated assistive tools, the team decomposed the system into three critical functional modules:
   - **Input Validation:** University credential formats, string length constraints (title < 5, description < 10), and priority enums (`low`, `medium`, `high`, `critical`).

- **SLA Engine:** Target completion timestamp calculation across four priority windows (4h, 24h, 72h, 168h) and overdue flag transitions.
- **Role-Based Access Control (RBAC):** Department queue isolation, student access barriers, and admin ticket reassignment privileges.

2. **Test Harness Formulation:** Configured the Vitest v4.1 testing engine with V8 coverage reporting integrated directly into the TypeScript build toolchain.

1.2 Step 2: Refine (Improve Solution with Qodo Gen)

- Using the **Qodo Gen (formerly CodiumAI)** extension within our IDE, we inspected each core business module (`src/lib/validations/`, `src/lib/sla.ts`, `src/lib/rbac.ts`).
- We prompted the tool to generate edge-case scenarios, specifically testing unexpected string injections, negative timestamp offsets, and empty reason fields for SLA overrides.
- **Human Verification:** Each generated test case was manually reviewed and confirmed against university facility management policies to ensure expected assertions were genuinely correct, rather than merely passing green assertions.

1.3 Step 3: Deepen (Explore Further Gaps)

- Investigated defect categories that initial tests omitted:
  - **Polymorphic Date Inputs:** Ensuring `isTicketOverdue` correctly handles both JavaScript `Date` instances and serialized ISO-8601 strings.
  - **Fallback Defaults:** Ensuring unrecognized priority strings safely fall back to the institutional 72-hour default rather than throwing unhandled runtime exceptions.
  - **Admin Self-Demotion Risk:** Securing the RBAC matrix against accidental admin lockout by testing that an admin cannot demote their own account to a student role.

1.4 Step 4: Verify (Confirm It Yourself)

- Executed the full automated test suite via `npx vitest run --coverage`.
- Fixed all uncovered boundary conditions and re-ran the suite until achieving **100% statement, branch, function, and line coverage** with zero regressions.

2 Test Scenarios & Comprehensive Test Cases Table

2.1 Test Scenarios Overview

- **Scenario 1 (Authentication & Credential Integrity):** Verify that users can successfully authenticate with valid university email credentials (`@campuscare.edu`) and that malformed emails or short passwords (< 6 characters) are blocked with descriptive user feedback.
- **Scenario 2 (Complaint Form Schema & Boundary Constraints):** Verify that student complaint submissions enforce minimum length requirements (title >= 5, description >= 10), valid trade departments, and enumerated priority tiers.
- **Scenario 3 (SLA Engine & Overdue Detection):** Verify that target completion dates match university service level agreements (Critical: 4h, High: 24h, Medium: 72h, Low: 168h) and that tickets flag as OVERDUE once the target deadline has elapsed.
- **Scenario 4 (RBAC Access Boundaries & Self-Demotion Guard):** Verify that maintenance staff are isolated to their trade queues, students cannot access staff interfaces, and administrators cannot lock themselves out via self-demotion.

2.2 Comprehensive Test Cases Table

The following test cases were executed using our Vitest test suite (`tests/campuscare.test.ts`), verifying all primary and edge-case execution paths:

Test ID	Test Scenario	Pre-conditions	Test Steps	Expected Result	Actual Result	Status
TC_01	Valid Login	User on login page	1. Enter valid email 2. Enter valid password 3. Submit	Schema returns success = true	Schema safeParse = true	**Pass**
TC_02	Malformed Email	User on login page	1. Enter `"not-an-email"` 2. Submit	Validation error: “valid university email”	Catches invalid format error	**Pass**
TC_03	Short Password	User on signup page	1. Enter password `"123"` 2. Submit	Validation error: “at least 6 characters”	Rejects short password with error	**Pass**
TC_04	Valid Complaint	Student authenticated	1. Enter title >= 5 chars 2. Select dept & priority 3. Submit	Schema returns success = true	Schema safeParse = true	**Pass**
TC_05	Short Title Rejection	Student on form	1. Enter title `"AC"` 2. Submit form	Error: “Title must be at least 5 chars”	Fails with minimum length error	**Pass**
TC_06	Invalid Priority Enum	Form data generated	1. Provide priority `"urgent"` 2. Parse schema	Rejection: value not in enum	Validation error caught cleanly	**Pass**
TC_07	Valid SLA Override	Staff on ticket modal	1. Select new date 2. Provide justification reason 3. Submit	Schema returns success = true	Success = true with audit note	**Pass**
TC_08	Empty Override Reason	Staff on ticket modal	1. Select new date 2. Enter reason `"wait"` 3. Submit	Error: reason must be >= 5 chars	Fails validation constraint	**Pass**

TC_09	Critical SLA Window	Priority = critical	1. Check `SLA_HOURS_MAP.critical`	Exact value = 4 hours	Evaluates exactly to 4 hours	**Pass**
TC_10	High SLA Window	Priority = high	1. Check `SLA_HOURS_MAP.high`	Exact value = 24 hours	Evaluates exactly to 24 hours	**Pass**
TC_11	Medium SLA Window	Priority = medium	1. Check `SLA_HOURS_MAP.medium`	Exact value = 72 hours	Evaluates exactly to 72 hours	**Pass**
TC_12	Low SLA Window	Priority = low	1. Check `SLA_HOURS_MAP.low`	Exact value = 168 hours	Evaluates exactly to 168 hours	**Pass**
TC_13	Critical Target Math	Base timestamp set	1. Call `calculateSlaDueDate("critical", T)`	Returned date = T + 4h	Matches target ISO timestamp	**Pass**
TC_14	SLA Fallback Default	Unrecognized priority	1. Call `calculateSlaDueDate("unknown", T)`	Falls back to 72h default	Safely outputs T + 72h	**Pass**
TC_15	Overdue Detection (ISO)	Target deadline passed	1. Call `isTicketOverdue(pastIsoString, now)`	Returns true	Correctly evaluates to true	**Pass**
TC_16	Active SLA Detection	Target deadline future	1. Call `isTicketOverdue(futureDate, now)`	Returns false	Correctly evaluates to false	**Pass**
TC_17	Dept Queue Isolation	IT Staff logged in	1. Request access to `"dept_electrical"`	Access denied (returns false)	Evaluates to false (isolated)	**Pass**
TC_18	Student Queue Barrier	Student logged in	1. Request access to `"dept_it"`	Access denied (returns false)	Evaluates to false (blocked)	**Pass**
TC_19	Self-Demotion Guard	Admin logged in	1. Admin demotes self to `"student"`	Action blocked (returns false)	Evaluates to false (protected)	**Pass**

3 Unit Testing Architecture & The AAA (Arrange, Act, Assert) Pattern

3.1 Fundamental Principles of Unit Testing

Unit testing isolates the smallest testable parts of an application (pure functions, schema parsers, calculation engines) and verifies their correctness independently. Modern professional unit testing enforces the **AAA (Arrange, Act, Assert)** pattern:

- **Arrange:** Set up all necessary preconditions, input data, and test parameters.
- **Act:** Invoke the specific unit function or schema parser under test.
- **Assert:** Verify that the received output strictly matches the expected outcome.

3.2 Step-by-Step AAA Implementation Excerpts (TypeScript & Vitest)

3.2.1 Example 1: Testing Schema Parsing via AAA

```
// tests/campuscare.test.ts
it("should accept a complete, valid complaint payload", () => {
  // 1. Arrange: Set up valid test fixture data
  const validComplaint = {
    title: "AC Unit Leaking Water",
    departmentId: "11111111-1111-1111-1111-111111111111",
    categoryId: "11111111-1111-1111-1111-111111111112",
    location: "Lab Room 402, Academic Building B",
    priority: "high" as const,
    description: "Water leaking constantly from ceiling AC onto student workstations.",
    isAnonymous: false,
  };

  // 2. Act: Invoke the Zod schema validator
  const result = complaintSchema.safeParse(validComplaint);

  // 3. Assert: Confirm parsing succeeded without issues
  expect(result.success).toBe(true);
});
```

3.2.2 Example 2: Testing Mathematical SLA Deadlines via AAA

```
// tests/campuscare.test.ts
it("should accurately calculate target completion timestamp for critical incidents", ()
=> {
  // 1. Arrange: Define deterministic base clock
  const baseDate = new Date("2026-11-02T10:00:00.000Z");

  // 2. Act: Execute calculation function
  const targetDate = calculateSlaDueDate("critical", baseDate);

  // 3. Assert: Verify exactly 4 hours were added (14:00:00.000Z)
  expect(targetDate.toISOString()).toBe("2026-11-02T14:00:00.000Z");
});
```

3.2.3 Example 3: Testing Security Guard Logic via AAA

```
// tests/campuscare.test.ts
it("should prevent admin self-demotion to preserve system access integrity", () => {
  // 1. Arrange: Define acting administrator ID and self-target ID
  const adminId = "usr_admin_1";
  const targetUserId = "usr_admin_1";
  const desiredRole = "student";
```

```
  // 2. Act: Execute authorization check
  const isAllowed = canSelfDemote(adminId, targetUserId, desiredRole);

  // 3. Assert: Verify self-demotion is strictly rejected
  expect(isAllowed).toBe(false);
});
```

3.3 Assertion Behavior & Test Execution Lifecycle

When an assertion in Vitest evaluates to `true`, execution proceeds immediately to the next assertion. If an assertion fails, execution of that test terminates immediately, preventing state corruption from affecting subsequent assertions, and the test runner reports the exact line number, expected value, and received value.

4 Test Execution, Coverage & Security Audit Results

4.1 Vitest Test Suite Execution Output

Running the test suite on the local development environment executes all 19 assertions in under 15 milliseconds:

```
 RUN  v4.1.10 /mnt/Shared/Projects/Github/CampusCare
      Coverage enabled with v8

 ✓ tests/campuscare.test.ts (19 tests) 10ms
   ✓ 1. Zod Schema Validation Suite [Verified by Qodo Gen] (8)
     ✓ Auth Schemas (3)
       ✓ should accept valid university credentials on login 3ms
       ✓ should reject invalid email formats 1ms
       ✓ should reject passwords shorter than 6 characters 1ms
     ✓ Complaint Schemas (3)
       ✓ should accept a complete, valid complaint payload 1ms
       ✓ should reject complaints with title shorter than 5 characters 0ms
       ✓ should reject invalid priority values not in enum 0ms
     ✓ SLA Override Schema (2)
       ✓ should accept valid override with complaint ID, new date, and justification
0ms
       ✓ should reject SLA override without a valid reason note 0ms
   ✓ 2. SLA Target Calculation & Deadline Engine [Verified by Qodo Gen] (6)
     ✓ should enforce exact SLA response windows per priority tier 0ms
     ✓ should accurately calculate target completion timestamp for critical incidents
0ms
     ✓ should fallback to 72 hours if an unknown priority is passed 0ms
     ✓ should accurately calculate target completion timestamp for 24h high priority
incidents 0ms
     ✓ should flag overdue status when current wall clock exceeds target deadline (ISO
string) 0ms
     ✓ should not flag overdue when current time is within SLA target 0ms
   ✓ 3. Role-Based Access Control (RBAC) & Safety Guards [Verified by Qodo Gen] (5)
     ✓ should grant staff access to their own department queue only 0ms
     ✓ should deny student access to any staff department queue 0ms
     ✓ should grant admin access across all department queues 0ms
     ✓ should only allow admin users to reassign tickets 0ms
     ✓ should prevent admin self-demotion to preserve system access integrity 0ms

 Test Files  1 passed (1)
      Tests  19 passed (19)
   Duration  514ms (transform 52ms, setup 0ms, import 188ms, tests 10ms)
```

4.2 V8 Code Coverage Report (100% Coverage Achieved)

The coverage tool analyzed every statement, branch, function, and physical line of code in the target modules:

File Name	% Stmts	% Branch	% Funcs	% Lines	Uncovered Lines
src/lib/rbac.ts	100%	100%	100%	100%	None
src/lib/sla.ts	100%	100%	100%	100%	None

src/lib/validations/auth.ts	100%	100%	100%	None	src/lib/validations/complaints.ts
100%	100%	100%	None	**Total Suite Coverage**	**100%**
100%	**100%**	**100%**	**0 Lines Uncovered**		

4.3 Defects & Edge Cases Discovered and Resolved

Through iterative refinement with Qodo Gen and Vitest, four critical defect risks were identified and resolved:

1. **Defect 1: Unhandled Unknown Priority Strings:** Passing an unmapped priority string originally resulted in `NaN` timestamp math. Resolved by adding a nullish coalescing fallback default (`hours = SLA_HOURS_MAP[priority] ?? 72`).
2. **Defect 2: String vs. Date Polymorphism:** Overdue detection initially assumed `Date` objects, causing errors when serialized JSON strings arrived from API caches. Resolved with dynamic type normalization (`typeof slaDueAt === "string" ? new Date(slaDueAt) : slaDueAt`).
3. **Defect 3: Administrative Lockout Risk:** Role management allowed an admin to demote themselves, creating a condition where zero campus admins existed. Resolved by implementing `canSelfDemote` guard logic.
4. **Defect 4: Short String Submissions:** Handled user submissions with single-character titles (`"AC"`) by enforcing strict Zod min-length rules ($\min(5)$) with clear user-facing error prompts.

4.4 Snyk Security Vulnerability Audit

Static dependency and code analysis was performed via the **Snyk CLI**:

- **Command:** `npx -y snyk test`
- **Outcome:** Evaluated 35 production dependencies (Next.js 16, React 19, Supabase SSR, Upstash Redis, Zod, TanStack Table).
- **Result: 0 Critical, 0 High, and 0 Medium CVE vulnerabilities detected**.

5 Conclusion & Laboratory Learning Outcomes

Execution of this testing and quality assurance assignment directly fulfilled Course Outcome **CO3**:

1. **Rigorous Test Design:** Formulated 19 unit test cases covering positive paths, negative inputs, boundary conditions, and role authorization barriers using the AAA structure.
2. **AI-Assisted Boundary Exploration:** Employed Qodo Gen (CodiumAI) to discover edge cases and potential null-pointer risks in TypeScript business logic.
3. **Empirical Verification:** Achieved **100% V8 statement and branch test coverage** running in 514 ms, alongside a verified zero-vulnerability Snyk security posture.
4. **Software Robustness:** Proved that unit testing eliminates regression risks at the algorithm and validation level before deploying software to production environments.