SafeLane HN - Cycling safety priority list Heilbronn

Generated 2026-10-28

Data: ATRAI senseBox:bike, Heilbronn. Data generated 2026-10-28. 6,638 street segments with measurements, 5,109 with enough data to rank, 602 with recorded overtakes.

Top 20 priority streets

Rank	Street	Score	Measure-ments	Overtakes < 150 cm	Main reason
1	Austraße	68.0	234	100% of 65	100% of 65 overtakes were closer than 150 cm
2	Service road off Weipertstraße	62.9	503	97% of 62	40.0 close-overtake danger points per 100 m
3	Brückenstraße	55.5	576	92% of 26	35.6 close-overtake danger points per 100 m
4	Weipertstraße	50.9	378	100% of 21	100% of 21 overtakes were closer than 150 cm
5	Haller Straße	45.6	57	100% of 23	100% of 23 overtakes were closer than 150 cm
6	Salzstraße	44.8	1,467	91% of 35	91% of 35 overtakes were closer than 150 cm
7	Service road off Wilhelmstraße	44.7	59	45% of 22	30.0 close-overtake danger points per 100 m
8	Service road off Max-Planck-Straße	44.4	179	86% of 22	86% of 22 overtakes were closer than 150 cm
9	Rampachertal	43.0	26	100% of 26	100% of 26 overtakes were closer than 150 cm
10	Horkheimer Straße	41.0	70	70% of 23	25.3 close-overtake danger points per 100 m
11	Biberacher Straße	38.4	617	76% of 21	76% of 21 overtakes were closer than 150 cm
12	Path along Weidenbäumle	38.4	144	100% of 20	100% of 20 overtakes were closer than 150 cm
13	Schäfergasse	36.4	23	100% of 22	100% of 22 overtakes were closer than 150 cm
14	Schmollerstraße	35.7	24	88% of 24	28.0 close-overtake danger points per 100 m
15	Max-von-Laue-Straße	34.5	586	100% of 20	100% of 20 overtakes were closer than 150 cm
16	Spemannstraße	33.2	1,679	38% of 26	38% of 26 overtakes were closer than 150 cm
17	Charlottenstraße	32.6	297	61% of 31	61% of 31 overtakes were closer than 150 cm
18	Spemannstraße	32.4	240	45% of 42	15.7 close-overtake danger points per 100 m
19	Saarlandstraße	32.3	248	95% of 22	95% of 22 overtakes were closer than 150 cm
20	Feurerstraße	32.3	189	38% of 24	38% of 24 overtakes were closer than 150 cm

Method

Each street segment gets five factors from 0 to 1: share of close passes under 150 cm, danger points per 100 m, surface roughness, fine-dust risk and stop-and-go traffic.

Default weights: Close passes 35%, Danger spots 25%, Rough surface 15%, Fine dust 15%, Stop-and-go 10%.

Score = 100 x confidence x weighted sum of the factors, from 0 to 100; confidence = min(1, measurements / 30).

Only segments with at least 5 measurements are ranked; ties go to the segment with more measurements.

The main reason is the factor that adds the most to the score at the default weights.

Data limits

- Riders chose their own routes, so popular streets have more data. A street with no data is not safe, just unmeasured.
- Passing cars are detected by AI. It misses some and miscounts others, so a single value can be off.
- Some streets have only a few measurements. Their scores are less certain and are scaled down by the confidence factor.