

Hadoop MapReduce

INF 551 & 553

Wensheng Wu


Hadoop

- A large-scale distributed batch-processing infrastructure
- Large-scale:
 - Handle a large amount of data and computation
- Distributed:
 - Distribute data & work across a number of machines
- Batch processing
 - Process a series of jobs without human intervention

Cluster Architecture

2-10 Gbps backbone between racks

1 Gbps between
any pair of nodes
in a rack




Each rack contains 16-64 nodes

In 2011 it was guestimated that Google had 1M machines, <http://bit.ly/Shh0RO>



Roadmap

- Hadoop architecture 
 - HDFS
 - MapReduce
- MapReduce implementation
- Compile & run MapReduce programs

Key components

- HDFS (Hadoop distributed file system)
 - Distributed data storage with **high reliability**
- MapReduce
 - A parallel, distributed computational paradigm
 - With a **simplified** programming model

HDFS

- Data are distributed among multiple data nodes
 - Data nodes may be added on demand for more storage space
- Data are replicated to cope with node failure
 - Typically replication factor = 2/3
- Requests can go to any replica
 - Removing the bottleneck (in single file server)

HDFS architecture

NameNode:


Stores metadata only

METADATA:

/user/aaron/foo → 1, 2, 4

/user/aaron/bar → 3, 5

DataNodes: Store blocks from files



HDFS has ...

- A single NameNode, storing meta data:
 - A hierarchy of directories and files
 - Attributes of directories and files
 - Mapping of files to blocks on data nodes
- A number of DataNodes:
 - Storing contents/blocks of files

Compute nodes

- Data nodes are compute nodes too
- Advantage:
 - Allow schedule computation close to data

HDFS also has ...

- A SecondaryNameNode
 - Maintaining checkpoints of NameNode
 - For recovery
- In a single-machine setup
 - all nodes correspond to the same machine

Metadata in NameNode

- NameNode has an inode for each file and dir
- Record attributes of file/dir such as
 - Permission
 - Access time
 - Modification time
- Also record mapping of files to blocks


Mapping information in NameNode

- E.g., file /user/aaron/foo consists of blocks 1, 2, and 4
- Block 1 is stored on data nodes 1 and 3
- Block 2 is stored on data nodes 1 and 2
- ...

Block size

- HDFS: 64MB
 - Much larger than disk block size (4KB)
- Why larger size in HDFS?
 - Reduce metadata required per file
 - Fast streaming read of data (since larger amount of data are sequentially laid out on disk)
 - Good for workload with largely sequential read of large file

Roadmap

- Hadoop architecture
 - HDFS
 - MapReduce 
- MapReduce implementation
- Compile & run MapReduce programs

MapReduce job


- A MapReduce job consists of a number of
 - Map tasks
 - Reduce tasks
 - (Internally) shuffle tasks

Map, reduce, and shuffle tasks

- Map task performs data transformation
- Reduce task combines results of map tasks
- Shuffle task sends output of map tasks to right reduce tasks

Hadoop cluster

Each may be run on
a separate machine



Job tracker

- Takes requests from clients (MapReduce programs)
- Ask name node for location of data
- Assign tasks to task trackers near the data
- Reassign tasks if failed

Task tracker

- Accept (map, reduce, shuffle) tasks from job trackers
- Send heart beats to job trackers: I am alive
- Monitor status of tasks and notify job tracker

Roadmap

- Hadoop architecture
 - HDFS
 - MapReduce
- MapReduce implementation
 - Map & reduce functions and tasks
 - Shuffling & group by
 - Input and output format
 - Combiner
- Compile & run MapReduce programs



Roots in functional programming

- Functional programming languages:
 - Python, Lisp (list processor), Scheme, Erlang, Haskell
- Two functions:
 - Map: mapping a list => list
 - Reduce: reducing a list => value
- map() and reduce() in Python
 - <https://docs.python.org/2/library/functions.html#map>

map() and reduce() in Python

- `list = [1, 2, 3]`
- `def sqr(x): return x ** 2`
- `list1 = map(sqr, list)`

What are the value of list1 and z?

- `def add(x, y): return x + y`
- `z = reduce(add, list)`


Lambda function

- Anonymous function (not bound to a name)
- `list = [1, 2, 3]`
- `list1 = map(lambda x: x ** 2, list)`
- `z = reduce(lambda x, y: x + y, list)`

How is reduce() in Python evaluated?

- $z = \text{reduce}(f, \text{list})$ where f is add function
- Initially, z (an accumulator) is set to $\text{list}[0]$
- Next, repeat $z = \text{add}(z, \text{list}[i])$ for each $i > 0$
- Return final z
- Example: $z = \text{reduce}(\text{add}, [1, 2, 3])$
 - $i = 0, z = 1; i = 1, z = 3; i = 2, z = 6$


MapReduce

- Map function:
 - Input: $\langle k, v \rangle$ pair
 - Output: a list of $\langle k', v' \rangle$ pairs
 - Reduce function:
 - Input: $\langle k', \text{list of } v' \text{'s} \rangle$ (note k' 's are output by map)
 - Output: a list of $\langle k'', v'' \rangle$ pairs
- 

MapReduce: The Map Step

Input: key-value pairs

Output: (intermediate) key-value pairs






MapReduce: The Reduce Step

**Output
key-value
pairs**


Group by

Intermediate
key-value pairs


Key-value groups




...



Group
by key





...




reduce

reduce



...



Map-Reduce: A diagram

MAP:

Read input and produces a set of key-value pairs


Intermediate

Group by key:

Collect all pairs with the same key


Reduce:

Reduce all values belonging to the key and output



Single map & reduce task

Map-Reduce: In Parallel



Multiple map & reduce tasks

Example: WordCount

- Counting the number of occurrences of words in a collection of documents
- helloworld.txt (stored under an input directory, among possible other documents)
 - hello world
 - hello this world
 - hello hello world

Example: WordCount

- Map function:
 - Input: `<offset of line, line>` // line = a line of text in a document
 - Output: for each word in line, output `<word, 1>`
- Reduce function:
 - Input: `<word, list of 1's>`
 - Output: `<word, count>` where count is the number of 1's in the input list

Word Count Using MapReduce

Pseudocode

map(key, value):

```
// key: line offset; value: line content
for each word w in value:
    output (w, 1)
```

reduce(key, values):

```
// key: a word; values: an iterator over counts
result = 0
for each count v in values:
    result += v
output (key, result)
```

Group by

- System groups the intermediate key-value pairs from map tasks **by key**
- E.g., $\langle \text{hello}, 1 \rangle \langle \text{hello}, 1 \rangle \langle \text{hello}, 1 \rangle \langle \text{this}, 1 \rangle$
 $\Rightarrow \langle \text{hello}, [1, 1, 1] \rangle, \langle \text{this}, [1] \rangle$

Example: WordCount

- `hadoop jar wc.jar WordCount input output`
- Output:
 - hello 4
 - this 1
 - world 3

WordCount: Mapper

Object can be replaced with LongWritable

```
public class WordCount {  
    public static class TokenizerMapper  
        extends Mapper<Object, Text, Text, IntWritable>{  
  
        private final static IntWritable one = new IntWritable(1);  
        private Text word = new Text();  
  
        public void map(Object key, Text value, Context context  
                        ) throws IOException, InterruptedException {  
            StringTokenizer itr = new StringTokenizer(value.toString());  
            while (itr.hasMoreTokens()) {  
                word.set(itr.nextToken());  
                context.write(word, one);  
            }  
        }  
    }  
}
```

Data types of input key-value

Data types of output key-value

Key-value pairs with specified data types

WordCount: Reducer

Data types of input key-value

Should be the same as output data types of mapper

Data types of output key-value

```
public static class IntSumReducer
    extends Reducer<Text,IntWritable,Text,IntWritable> {
    private IntWritable result = new IntWritable();

    public void reduce(Text key, Iterable<IntWritable> values,
        Context context
        ) throws IOException, InterruptedException {

        int sum = 0;
        for (IntWritable val : values) {
            sum += val.get();
        }
        result.set(sum);
        context.write(key, result);
    }
}
```

Checking map input

```
public void map(Object key, Text value, Context context
                ) throws IOException, InterruptedException {
    System.out.println("map input: key=" + key + ", value=" + value);

    StringTokenizer itr = new StringTokenizer(value.toString());
    while (itr.hasMoreTokens()) {
        word.set(itr.nextToken());
        context.write(word, one);
    }
}
```

- map input: key=0, value=hello world
- map input: key=12, value=hello this world
- map input: key=29, value=hello hello world

Checking reduce input

```
public void reduce(Text key, Iterable<IntWritable> values,  
                  Context context  
                  ) throws IOException, InterruptedException {  
    System.out.print("reduce input: key=" + key + ", values=");  
  
    int sum = 0;  
    for (IntWritable val : values) {  
        System.out.print(val + " ");  
        sum += val.get();  
    }  
  
    System.out.println();  
}
```

- reduce input: key=hello, values=1 1 1 1
- reduce input: key=this, values=1
- reduce input: key=world, values=1 1 1

Map and reduce tasks in Hadoop

- A node may run multiple map/reduce tasks
- Typically, **one map task per input split** (chunk of data)
- One reduce task per partition of map output
 - E.g., partition by key range or hashing


Mapper and Reducer

- Each map task runs an instance of **Mapper**
 - Mapper has a **map function**
 - Map task invokes the map function of the Mapper once for each input key-value pair
- Each reduce task runs an instance of **Reducer**
 - Reducer has a **reduce function**
 - Reduce task invokes the reduce function of the Reducer once for every different intermediate key

Reduce function

- Input: a key and an iterator over the values for the key
- Values are NOT in any particular order
- Reduce function is called once for every different key (received by the reduce task)

Roadmap

- Hadoop architecture
 - HDFS
 - MapReduce
- MapReduce implementation
 - Map & reduce functions and tasks
 - **Shuffling & group by** 
 - Input and output format
 - Combiner
- Compile & run MapReduce programs

Shuffling

- Process of distributing intermediate key-values to the right reduce tasks
- It is **the only communication** among map and reduce tasks
 - Individual map tasks do not exchange data directly with other map tasks
 - They are not even aware of existence of their peers

Shuffling

- Begins when a map task completed on a node
- All intermediate key-value pairs with the same key are sent to the same reducer task
- Partitioning method defined in Partitioner class
 - Default rule: partition by hashing the key

Sorting


- Key-value pairs from the same map task are sorted first (by key)
 - before they are sent to the reduce task
- Each reduce task receives up to M # of sorted files (by key)
 - $M = \#$ of map tasks

Merging

- System merges the sorted files (details: [here](#))
 - Recall merge-sort in external sorting
 - Difference: now sorting/merging done in parallel
- Shuffling and merging happen simultaneously
 - Merging a new file once it is fetched
 - without waiting for other files to be fetched

Partitioning, shuffling & merging


Keys in the same partition are sorted (keys from different partitions may not be)




Merging by partition
(& then by key)

Merging by key


Roadmap

- Hadoop architecture
 - HDFS
 - MapReduce
- MapReduce implementation
 - Map & reduce functions and tasks
 - Shuffling & group by
 - **Input and output format** 
 - Combiner
- Compile & run MapReduce programs

Node 1



Node 2



"Shuffling" process

Intermediate (k, v) pairs exchanged by all nodes

InputFormat

- Determine how input files are split and read
- Defined in the Java interface InputFormat
- Job:
 - Split input file into chunks called InputSplits
 - Implement RecordReader to read data from splits

InputFormat implementations

- FileInputFormat (input from files in given dirs)
- DBInputFormat (input data from a database)
- CombineFileInputFormat (input data by combining multiple files)
- ...

FileInputFormat

- Job:
 - Takes paths to files
 - Read all files in the paths
 - Divide each file into one or more InputSplits
- Subclasses:
 - TextInputFormat
 - KeyValueTextInputFormat
 - SequenceFileInputFormat

Subclasses of FileInputFormat

InputFormat:	Description:	Key:	Value:
TextInputFormat	Default format; reads lines of text files	The byte offset of the line	The line content
KeyValueTextInputFormat	Parses lines into key, value pairs	Everything up to the first tab character	The remainder of the line
SequenceFileInputFormat	A Hadoop-specific high-performance binary format	user-defined	user-defined

Use non-default input format

- If input file contains tab-separated key-value pairs, e.g.,
 - John 5
 - David 6
 - ...
- `job.setInputFormatClass(KeyValueTextInputFormat.class);`
 - Both key and value are of type "Text"

InputSplits

- If a file is big, multiple splits may be created
 - Typical split size = 64MB
- A map task is created for each split
 - i.e., a chunk of some input file

RecordReader (RR)

- InputFormat defines an instance of RR
 - E.g., TextInputFormat provides LineRecordReader
- LineRecordReader
 - Form a key-value pair for every line of file
 - Data type for key: LongWritable; value: Text
- Reader is repeatedly called
 - Until all data in the split are processed

OutputFormat

- Define the format of output from Reducers
 - Output stored in a file
- Defined in the Java interface OutputFormat
- Implementation: FileOutputFormat
 - Subclasses: TextOutputFormat, SequenceFileOutputFormat

OutputFormat

OutputFormat:	Description
TextOutputFormat	Default ; writes lines in "key \t value" form
SequenceFileOutputFormat	Writes binary files suitable for reading into subsequent MapReduce jobs

Outputs

- All Reducers write to the same directory
 - Each writes a separate file, named part-r-nnnnn
 - r: output from Reducers
 - nnnnn: partition id associated with reduce task
- Output directory
 - Set by `FileOutputFormat.setOutputPath()` method
- `OutputFormat` defines a `RecordWriter`
 - which handles the write

WordCount: setting up job

```
public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    String[] otherArgs = new GenericOptionsParser(conf, args).getRemainingArgs();
    if (otherArgs.length < 2) {
        System.err.println("Usage: wordcount <in> [<in>...] <out>");
        System.exit(2);
    }
    Job job = Job.getInstance(conf, "word count");
    job.setJarByClass(WordCount.class);
    job.setMapperClass(TokenMapper.class);
    job.setCombinerClass(IntSumReducer.class);
    job.setReducerClass(IntSumReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);
    for (int i = 0; i < otherArgs.length - 1; ++i) {
        FileInputFormat.addInputPath(job, new Path(otherArgs[i]));
    }
    FileOutputFormat.setOutputPath(job,
        new Path(otherArgs[otherArgs.length - 1]));
    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
```



Take multiple directories as input


Set output key and value types for both map and reduce tasks.

If Mapper has different types, use `setMapOutputKeyClass` and `setMapOutputValueClass`


setJarByClass

- Mapper and reducer code may be in a different jar
 - E.g., a jar in Hadoop class search path
 - (wc.jar contains only the job submission code)
- setJarByClass tells Hadoop where to find jar containing mapper and reducer code
 - By specifying its class name (e.g., WordCount)

Roadmap

- Hadoop architecture
 - HDFS
 - MapReduce
- MapReduce implementation
 - Map & reduce functions and tasks
 - Shuffling & group by
 - Input and output format
 - **Combiner** 
- Compile & run MapReduce programs

Combiner



Combiner

- Run on the node running the Mapper
 - Perform local (or mini-) reduction
- Combine Mapper results
 - Before they are sent to the Reducers
 - Reduce communication costs
- E.g., may use a combiner in WordCount
 - (cat, 1), (cat, 1), (cat, 1) => (cat, 3)
 - One key-value pair per unique word

Without combiner

- Mapper 1 outputs:
 - (cat, 1), (cat, 1), (cat, 1), (dog, 1)
- Mapper 2 outputs:
 - (dog, 1), (dog, 1), (cat, 1)
- Suppose there is only one Reducer
 - It will receive: (cat, [1, 1, 1, 1]), (dog, [1, 1, 1])

Implementing combiner

- May directly use the reduce function
 - If it is **commutative and associative**
 - Meaning operations can be grouped & performed in any order
- Operation 'op' is commutative if:
 - $A \text{ op } B = B \text{ op } A$
- Op is associative if:
 - $A \text{ op } (B \text{ op } C) = (A \text{ op } B) \text{ op } C$

Example: without combiner

- Consider two map tasks
 - M1 \Rightarrow 1, 2, 3 for some key x
 - M2 \Rightarrow 4, 5 for the same key
- Reducer adds all values for x
 - Result = $((1 + 2) + 3) + 4 + 5$

Example: with combiner

- $M1 \Rightarrow 1, 2, 3 \Rightarrow \text{combiner: } (1 + 2) + 3 \Rightarrow 6$
- $M2 \Rightarrow 4, 5 \Rightarrow \text{combiner: } 4 + 5 \Rightarrow 9$
- Reducer now $6 + 9$,
 - I.e., $((1 + 2) + 3) + (4 + 5)$
 - Question: is it the same as $((1 + 2) + 3) + 4 + 5$?
- Yes, since '+' is **associative**

Example: with combiner

- $M1 \Rightarrow 1, 2, 3 \Rightarrow \text{combiner: } (1 + 2) + 3 \Rightarrow 6$
- $M2 \Rightarrow 4, 5 \Rightarrow \text{combiner: } 4 + 5 \Rightarrow 9$
- Reducer may also compute $9 + 6$,
 - I.e., $(4 + 5) + ((1 + 2) + 3)$
 - Since values may arrive at reducer in any order
 - Question: is it the same as $((1 + 2) + 3) + 4 + 5$?
- Yes, since '+' is also commutative

General requirements

- To use reduce function 'f' for a combiner
 - Consider a set of values S and its subsets S_1, \dots, S_k
 - It must be that: $f(S) = f(f(S_1), \dots, f(S_k))$
- E.g., in WordCount:
 - $f = \text{sum}$
 - $S = \text{a list of integers}$

Commutative and associative

- Examples
 - Sum
 - Max
 - Min
- Non-examples
 - Count
 - Average
 - Median


Custom combiner

- Key & value data type of both input & output
 - Should be same as that of the output of Mapper
 - (Also the same as that for input to Reducer)
- So if Mapper outputs (Text, IntWritable), then:
 - public static class MyCombiner
 - extends Reducer<Text, IntWritable,
 - Text, IntWritable> {
 - ...
 - }

Enabling combiner

- `job.setCombinerClass(IntSumReducer.class)`
 - To use reduce function for combiner

```
Job job = Job.getInstance(conf, "word count");
job.setJarByClass(WordCount.class);
job.setMapperClass(TokenizeMapper.class);
job.setCombinerClass(IntSumReducer.class);
job.setReducerClass(IntSumReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
```



Roadmap

- Hadoop architecture
- MapReduce framework
- **Compile & run MapReduce programs**
 - On Amazon EC2



Hadoop installation

- Install the Hadoop package
 - Log into your EC2 instance and then execute:
 - `wget`
<http://apache.cs.utah.edu/hadoop/common/hadoop-2.7.5/hadoop-2.7.5.tar.gz>
 - `tar xvf hadoop-2.7.5.tar.gz`
- Might want to remove installation package (~400MB) to save space

Install java sdk

- `sudo yum install java-devel`

Setup environment variables

- Add HADOOP_HOME variable
- Add \${HADOOP_HOME}/bin to path
- Your ~/.bashrc now should have:

```
export JAVA_HOME=/usr/lib/jvm/java
export PATH=${JAVA_HOME}/bin:${PATH}
export HADOOP_CLASSPATH=${JAVA_HOME}/lib/tools.jar

export HADOOP_HOME=/home/ec2-user/hadoop-2.7.4
export PATH=${PATH}:${HADOOP_HOME}/bin
```

Run Hadoop in standalone mode

- Comment out `<property>` element in `etc/hadoop/core-site.xml` as shown below
 - If you have one...

```
<configuration>
<!--property>
    <name>fs.defaultFS</name>
    <value>hdfs://localhost:9000</value>
</property-->
</configuration>
```

Examples

- Find example source codes here:
 - `/home/ec2-user/hadoop-2.7.5/src/hadoop-mapreduce-project/hadoop-mapreduce-examples/src/main/java/org/apache/hadoop/examples`

WordCount.java

- Copy WordCount.java to a working directory of your choice
 - E.g., ~/inf551
- Comment out first line:
 - `// package org.apache.hadoop.examples;`

Compile & run

- Go to the directory that has WordCount.java
- `hadoop com.sun.tools.javac.Main WordCount.java`
- `jar cf wc.jar WordCount*.class`
- `hadoop jar wc.jar WordCount input-hello output-hello`

More examples

- Two input splits
- Multiple reducers

Two-split example

- Now input directory has two files
=> Two splits (hence two map tasks) generated, one for each file

```
[ec2-user@ip-172-31-52-194 inf551]$ ls input-hello2/  
helloworld1.txt helloworld2.txt  
[ec2-user@ip-172-31-52-194 inf551]$ cat input-hello2/helloworld1.txt  
hello world  
hello this world  
hello hello world  
[ec2-user@ip-172-31-52-194 inf551]$ cat input-hello2/helloworld2.txt  
hello that world  
hello this world  
hello hello that world
```

```
16/11/14 22:26:32 INFO input.FileInputFormat: Total input paths to process : 2  
16/11/14 22:26:32 INFO mapreduce.JobSubmitter: number of splits:2  
16/11/14 22:26:32 INFO mapreduce.JobSubmitter: Submitting tokens for job  
: job_local462978203_0001
```

Processing one split (Mapper)

- Split for "helloworld2.txt"
 - This shows map function is called 3 times
 - One for each line of text

```
16/11/14 22:26:33 INFO mapred.MapTask: Processing split: file:/home/ec2-  
user/hadoop-2.7.3/inf551/input-hello2/helloworld2.txt:0+57  
16/11/14 22:26:33 INFO mapred.MapTask: (EQUATOR) 0 kvi 26214396(10485758  
4)  
16/11/14 22:26:33 INFO mapred.MapTask: mapreduce.task.io.sort.mb: 100  
16/11/14 22:26:33 INFO mapred.MapTask: soft limit at 83886080  
16/11/14 22:26:33 INFO mapred.MapTask: bufstart = 0; bufvoid = 104857600  
16/11/14 22:26:33 INFO mapred.MapTask: kvstart = 26214396; length = 6553  
600  
16/11/14 22:26:33 INFO mapred.MapTask: Map output collector class = org.  
apache.hadoop.mapred.MapTask$MapOutputBuffer  
map input: key=0, value=hello that world  
map input: key=17, value=hello this world  
map input: key=34, value=hello hello that world
```

Processing one split (combiner)

- This shows input key-values for combiner
 - Note combiner uses the same reduce function

```
16/11/14 22:26:33 INFO mapred.MapTask: kvstart = 26214396(104857584); kv
end = 26214360(104857440); length = 37/6553600
reduce input: key=hello, values=1 1 1 1
reduce input: key=that, values=1 1
reduce input: key=this, values=1
reduce input: key=world, values=1 1 1
16/11/14 22:26:33 INFO mapred.MapTask: Finished spill 0
```

Process the other split (Mapper)

- helloworld1.txt

```
16/11/14 22:26:33 INFO mapred.MapTask: Processing split: file:/home/ec2-user/hadoop-2.7.3/in551/input-hello2/helloworld1.txt:0+47
16/11/14 22:26:33 INFO mapred.MapTask: (EQUATOR) 0 kvi 26214396(104857584)
16/11/14 22:26:33 INFO mapred.MapTask: mapreduce.task.io.sort.mb: 100
16/11/14 22:26:33 INFO mapred.MapTask: soft limit at 83886080
16/11/14 22:26:33 INFO mapred.MapTask: bufstart = 0; bufvoid = 104857600
16/11/14 22:26:33 INFO mapred.MapTask: kvstart = 26214396; length = 6553600
16/11/14 22:26:33 INFO mapred.MapTask: Map output collector class = org.apache.hadoop.mapred.MapTask$MapOutputBuffer
map input: key=0, value=hello world
map input: key=12, value=hello this world
map input: key=29, value=hello hello world
16/11/14 22:26:33 INFO mapred.MapTask: mapreduce.task.io.sort.mb: 100
```

Process the other split (combiner)


- This shows the input to the combiner for the 2nd Map task

```
16/11/14 22:26:33 INFO mapred.MapTask: kvstart = 26214396(104857584); kv  
end = 26214368(104857472); length = 29/6553600  
reduce input: key=hello, values=1 1 1 1  
reduce input: key=this, values=1  
reduce input: key=world, values=1 1 1
```


Reducer input (one Reducer)

- Assume only one Reducer is used
 - Note the input values now contain local counts


```
16/11/14 22:26:33 INFO Configuration.deprecation: mapred.skip.on is deprecated. Instead, use mapreduce.job.skiprecords  
reduce input: key=hello, values=4 4  
reduce input: key=that, values=2  
reduce input: key=this, values=1 1  
reduce input: key=world, values=3 3  
16/11/14 22:26:33 INFO mapred.Task: Task:attempt_local1462978203_0001_r_000000 0 is done. And is in the process of committing
```



Setting number of Reducers

- `job.setNumReduceTasks(2);`
 - Two reduce tasks

```
Job job = Job.getInstance(conf, "word count");
job.setJarByClass(WordCount.class);
job.setMapperClass(TokenMapper.class);
job.setCombinerClass(IntSumReducer.class);
job.setReducerClass(IntSumReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
job.setNumReduceTasks(2);
```



Two-Reducer case

- Note "that" is in one partition
- "hello", "this", "world" in the other

```
16/11/14 22:44:31 INFO Configuration.deprecation: mapred.skiprecords is deprecated. Instead, use mapreduce.job.skiprecords
reduce input: key=that, values=2
16/11/14 22:44:31 INFO mapred.Task: Task:attempt_local1764839547_0001_r_000000_0 is done. And is in the process of committing
16/11/14 22:44:31 INFO mapred.LocalJobRunner: 2 / 2 copied.
```

```
reduce input: key=hello, values=4 4
reduce input: key=this, values=1 1
reduce input: key=world, values=3 3
16/11/14 22:44:31 INFO mapred.Task: Tas
```

Two output files

- Part-r-00000 for partition 00000
- Part-r-00001 for partition 00001

```
[ec2-user@ip-172-31-52-194 output-hello2-r2]$ ls
part-r-00000  part-r-00001  _SUCCESS
[ec2-user@ip-172-31-52-194 output-hello2-r2]$ cat part-r-00000
that      2
[ec2-user@ip-172-31-52-194 output-hello2-r2]$ cat part-r-00001
hello     8
this      2
world     6
```

Resources & readings

- MapReduce tutorial from Apache:
 - <https://hadoop.apache.org/docs/stable/hadoop-mapreduce-client/hadoop-mapreduce-client-core/MapReduceTutorial.html>
- MapReduce tutorial from Yahoo! – module 4
 - <https://developer.yahoo.com/hadoop/tutorial/module4.html>

Readings

- J. Dean and S. Ghemawat, [MapReduce: simplified data processing on large clusters](#)," Communications of the ACM, vol. 51, pp. 107-113, 2008.