

Ex. No.: 5

Date: 12/02/2025

System Calls Programming

Aim: To experiment system calls using fork(), execlp() and pid() functions.

Algorithm:

1. **Start**
 - o Include the required header files (stdio.h and stdlib.h).
2. **Variable Declaration**
 - o Declare an integer variable pid to hold the process ID.
3. **Create a Process**
 - o Call the fork() function to create a new process. Store the return value in the pid variable:
 - If fork() returns:
 - -1: Forking failed (child process not created).
 - 0: Process is the child process.
 - Positive integer: Process is the parent process.
4. **Print Statement Executed Twice**
 - o Print the statement:

```
scss
Copy code
THIS LINE EXECUTED TWICE
```

(This line is executed by both parent and child processes after fork()).

5. **Check for Process Creation Failure**

- o If pid == -1:
 - Print:

```
Copy code
CHILD PROCESS NOT CREATED
```

- Exit the program using exit(0).

6. **Child Process Execution**

- o If pid == 0 (child process):
 - Print:
 - Process ID of the child process using getpid().
 - Parent process ID of the child process using getppid().

7. **Parent Process Execution**

- o If pid > 0 (parent process):
 - Print:
 - Process ID of the parent process using getpid().
 - Parent's parent process ID using getppid().

8. **Final Print Statement**

- o Print the statement:

```
objectivec
```

Copy code
IT CAN BE EXECUTED TWICE

(This line is executed by both parent and child processes).

9. End

Program:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
int main()
{
    int pid;
    pid = fork();
    printf("\n THIS LINE EXECUTED TWICE");
    if (pid == -1)
    {
        printf("\n CHILD PROCESS NOT CREATED\n");
        exit(0);
    }
    if (pid == 0)
    {
        printf("\n I AM CHILD PROCESS AND MY ID IS %d\n", getpid());
        printf("\n THE CHILD PARENT PROCESS ID IS : %d\n", getppid());
    }
    else
    {
        printf("\n I AM PARENT PROCESS AND MY ID IS: %d\n", getpid());
        printf("\n THE PARENTS PARENT PROCESS ID IS: %d\n", getppid());
    }
    printf("\n IT CAN BE EXECUTED TWICE");
    printf("\n");
}
```

Output:

This line executed twice
I am parent process and my id is 1644
The parents parent process ID is 1509
It can be executed twice
This line executed twice
This line executed twice.
I am child process and my id is 1645
The child parent process ID is 1644.
It can be executed twice

Result:

Thus the program is executed using
~~fork()~~, ~~exec()~~ and ~~pid()~~ functions

8/11